




Thundercomm Turbox™ T55M SOM **mmWave Test Report**

Revision History

Revision	Date	Description
1.0	June 20, 2021	Initial release

Thundercomm Confidential

Table List

[Table 2-1. Test environment](#)

[Table 2-2. Equipment information](#)

[Table 3-1. Basic test information](#)

[Table 3-2. Test condition 1](#)

[Table 3-3. Result of testing condition 1](#)

[Table 3-4. Test condition 2](#)

[Table 3-5. Result of testing condition 2](#)

[Table 3-6. Test condition 3](#)

[Table 3-7. Result of testing condition 3](#)

[Table 3-8. Test condition 4](#)

[Table 3-9. Result of test condition 4 \(DL Power: -67dBm\)](#)

[Table 3-10. Test condition 5-1](#)

[Table 3-11. Result of test condition 5-1](#)

[Table 3-12. Test condition 5-2](#)

[Table 3-13. Result of test condition 5-2](#)

[Table 3-14. Test condition 5-3](#)

[Table 3-15. Result of test condition 5-3](#)

[Table 3-16. Test condition 5-4](#)

[Table 3-17. Result of test condition 5-4](#)

[Table 3-18. Test condition 5-5](#)

[Table 3-19. Result of test condition 5-5](#)

[Table 3-20. Test condition 5-6](#)

[Table 3-21. Result of test condition 5-6](#)

[Table 3-22. Test condition 5-7](#)

[Table 3-23. Result of test condition 5-7](#)

[Table 3-24. Test condition 5-8](#)

[Table 3-25. Result of test condition 5-8](#)

[Table 3-26. Test condition 5-9](#)

[Table 3-27. Result of test condition 5-9](#)

[Table 3-28. Test condition 5-10](#)

[Table 3-29. Result of test condition 5-10](#)

[Table 3-30. Test condition 5-11](#)

[Table 3-31. Result of test condition 5-11](#)

[Table 3-32. Test condition 5-12](#)

[Table 3-33. Result of test condition 5-12](#)

[Table 3-34. Test condition 5-13](#)

[Table 3-35. Result of test condition 5-13](#)

[Table 3-36. Test condition 5-14](#)

[Table 3-37. Result of test condition 5-14](#)

[Table 3-38. Test condition 6-1](#)

[Table 3-39. Result of test condition 6-1](#)

[Table 3-40. Test condition 6-1](#)

[Table 3-41. Result of test condition 6-1](#)

[Table 3-42. Test condition 7-1](#)

[Table 3-43. Result of test condition 7-1](#)

[Table 3-44. Test condition 7-2](#)

[Table 3-45. Result of test condition 7-2](#)

[Table 3-46. Test condition 7-3](#)

[Table 3-47. Result of test condition 7-3](#)

[Table 3-48. Test condition 7-4](#)

[Table 3-49. Result of test condition 7-4](#)

[Table 3-50. Test condition 7-5](#)

[Table 3-51. Result of test condition 7-5](#)

[Table 3-52. Test condition 7-6](#)

[Table 3-53. Result of test condition 7-6](#)

[Table 3-54. Test condition 7-7](#)

[Table 3-55. Result of test condition 7-7](#)

[Table 3-56. Test condition 8-1](#)

[Table 3-57. Result of test condition 8-1](#)

[Table 3-58. Test condition 8-2](#)

[Table 3-59. Result of test condition 8-2](#)

[Table 3-60. Test condition 9-1](#)

[Table 3-61. Result of test condition 9-1](#)

[Table 3-62. Test condition 9-2](#)

[Table 3-63. Result of test condition 9-2](#)

[Table 3-64. Test condition 9-3](#)

[Table 3-65. Result of test condition 9-3](#)

[Table 3-66. Test condition 9-4](#)

[Table 3-67. Result of test condition 9-4](#)

[Table 3-68. Test condition 9-5](#)

[Table 3-69. Result of test condition 9-5](#)

[Table 3-70. Test condition 9-6](#)

[Table 3-71. Result of test condition 9-6](#)

[Table 3-72. Test condition 9-7](#)

[Table 3-73. Result of test condition 9-7](#)

[Table 3-74. Test condition 9-8](#)

[Table 3-75. Result of test condition 9-8](#)

[Table 3-76. Test condition 9-9](#)

[Table 3-77. Result of test condition 9-9](#)

[Table 3-78. Test condition 9-10](#)

[Table 3-79. Result of test condition 9-10](#)

[Table 3-80. Test condition 9-11](#)

[Table 3-81. Result of test condition 9-11](#)

[Table 3-82. Test condition 9-12](#)

[Table 3-83. Result of test condition 9-12](#)

[Table 3-84. Test condition 9-13](#)

[Table 3-85. Result of test condition 9-13](#)

[Table 3-86. Test condition 9-14](#)

[Table 3-87. Result of test condition 9-14](#)

[Table 3-88. Test condition 9-15](#)

[Table 3-89. Result of test condition 9-15](#)

[Table 3-90. Test condition 9-16](#)

[Table 3-91. Result of test condition 9-16](#)

[Table 3-92. Test condition 9-17](#)

[Table 3-93. Result of test condition 9-17](#)

[Table 3-94. Test condition 9-18](#)

[Table 3-95. Result of test condition 9-18](#)

[Table 3-96. Test condition 9-19](#)

[Table 3-97. Result of test condition 9-19](#)

[Table 3-98. Test condition 9-20](#)

[Table 3-99. Result of test condition 9-20](#)

[Table 3-100. Test condition 9-21](#)

[Table 3-101. Result of test condition 9-21](#)

[Table 3-102. Test condition 9-22](#)

[Table 3-103. Result of test condition 9-22](#)

[Table 3-104. Test condition 9-23](#)

[Table 3-105. Result of test condition 9-23](#)

[Table 3-106. Test condition 9-24](#)

[Table 3-107. Result of test condition 9-24](#)

[Table 3-108. Test condition 9-25](#)

[Table 3-109. Result of test condition 9-25](#)

[Table 3-110. Test condition 9-26](#)

[Table 3-111. Result of test condition 9-26](#)

[Table 3-112. Test condition 9-27](#)

[Table 3-113. Result of test condition 9-27](#)

[Table 3-114. Test condition 9-28](#)

[Table 3-115. Result of test condition 9-28](#)

[Table 3-116. Test condition 9-29](#)

[Table 3-117. Result of test condition 9-29 \(DL Power -82.96dBm/BW\)](#)

Thundercomm Confidential

About This Document

- Illustrations in this documentation might look different from your product.
- Depending on the model, some optional accessories, features, and software programs might not be available on your device.
- Depending on the version of operating systems and programs, some user interface instructions might not be applicable to your device.
- Documentation content is subject to change without notice. Thundercomm makes constant improvements on the documentation of your computer, including this guidebook.
- Function declarations, function names, type declarations, attributes, and code samples appear in a different format, for example, `cp armcc armcpp`.
- Code variables appear in angle brackets, for example, `<number>`.
- Button, tool, and key names appear in bold font, for example, click **Save** or press **Enter**.
- Commands to be entered appear in a different font, on the host computer use \$ as shell prompt, while on the target device use # as shell prompt, for example,

```
$ adb devices
# logcat
```

- Part of the code that does not contain instructions appear in a different format, for example,

```
SUBSYSTEM=="usb", ATTR{idVendor}=="18d1", MODE="0777", GROUP="adm"
```

- Folders and files are formatted in italic, for example, *turbox_flash_flat.sh*.

Table of Contents

Chapter 1.	Overview	- 2 -
Chapter 2.	Test Environment	- 3 -
2.1.	Test environment	- 3 -
2.2.	Test equipment.....	- 3 -
2.3.	DUT (Device Under Test)	- 3 -
Chapter 3.	Test Items	- 4 -
3.1.	Purpose.....	- 4 -
3.2.	Measurement	- 4 -
3.3.	Test procedure.....	- 5 -
3.4.	Test results	- 5 -
Appendix 1.	Notices.....	- 48 -
Appendix 2.	Trademarks	- 50 -

Chapter 1. Overview

According to the guideline defined by 3GPP, only OTA test is supported for mmW (mmWave) RF (Radio Frequency) test. This is a pretest of *Chapter 6 Transmitter Characteristics* and *Chapter 7 Receiver characteristics* of 3GPP 38.521-3 and is required to be performed in a test chamber. Limited by test environment and test time, only partial use cases can be tested; however, these use cases can reflect the basic RF performance of the device and most transmitter use cases have been tested.

Thundercomm Confidential

Chapter 2. Test Environment

2.1. Test environment

Table 2-1. Test environment

Operating temperature	15°C - 35°C
Relative humidity	30-60%

2.2. Test equipment

Table 2-2. Equipment information

Equipment	Model	Manufacturer
UXM 5G Wireless Test Platform	E7515B UXM	Keysight
Compact Antenna Test Range	CATR 330	Keysight
CIU (Common Interfacing Unit)	E7770A	Keysight
28/39GHz RRH (Remote Radio Head)	M1740A	Keysight
5G NR PAvT	C87350R3A	Keysight

2.3. DUT (Device Under Test)




Figure 2-1. Device Under Test

Chapter 3. Test Items

3.1. Purpose

This test is aimed to measure if the M.2 mmWave sample can meet 3GPP RF requirements.

3.2. Measurement

3.2.1. Basic test information

Table 3-1. Basic test information

Device under test	Thundercomm mmW sample device
Test station (PC Name)	K-E7515B-92714
IMEI	869751050003571

3.2.2. UE capability

- LTE access stratum: rel15
- LTE UE category: 12, UL13, DL20
- LTE band: 1, 3, 5, 8, 2, 4, 7, 12, 13, 14, 17, 18, 19, 20, 21, 25, 26, 28, 30, 32, 34, 38, 39, 40, 41, 42, 43, 46, 48, 64, 64
- LTE TM: TM3, TM4, TM9
- LTE UL comb: CA_1A, CA_3A, CA_5A, CA_8A, CA_2A, CA_4A, CA_7A, CA_12A, CA_13A, CA_14A, CA_17A, CA_18A, CA_19A, CA_20A, CA_21A, CA_25A, CA_26A, CA_28A, CA_30A, CA_34A, CA_38A, CA_39A, CA_40A, CA_41A, CA_42A, CA_43A, CA_48A, CA_64A, CA_64A, CA_1A, CA_1A, CA_1C
- LTE DL comb: CA_1A(4x4), CA_3A(4x4), CA_5A(2x2), CA_8A(2x2), CA_2A(2x2), CA_4A(2x2), CA_7A(4x4), CA_12A(2x2), CA_13A(2x2), CA_14A(2x2), CA_17A(2x2), CA_18A(2x2), CA_19A(2x2), CA_20A(2x2), CA_21A(2x2), CA_25A(2x2), CA_26A(2x2), CA_28A(2x2), CA_30A(2x2), CA_32A(2x2), CA_34A(2x2), CA_38A(4x4), CA_39A(4x4), CA_40A(4x4), CA_41A(4x4), CA_42A(4x4), CA_43A(2x2), CA_46A(2x2), CA_48A(2x2), CA_64A(4x4), CA_64A(2x2), CA_1A(4x4)_1A(4x4), CA_1C(4x4), CA_1C(4x4)
- LTE max modulation: DL_QAM256, UL_QAM64
- ENDC band: 1, 2, 3, 5, 7, 8, 12, 20, 25, 28, 38, 40, 41, 66, 71, 77, 78, 79, 257, 258, 260, 261
- SA band: 1, 2, 3, 5, 7, 8, 12, 20, 25, 28, 38, 40, 41, 66, 71, 77, 78, 79
- NR access stratum: rel15
- Modulation mode: NR Pdsch-256QAM-FR1
- NR band details: 79_pc2_QAM256, 78_pc2_QAM256, 77_pc3_QAM256, 66_pc3_QAM256, 41_pc2_QAM256, 28_pc3_QAM256, 25_pc3_QAM256, 12_pc3_QAM256, 5_pc3_QAM256, 3_pc3_QAM256, 2_pc3_QAM256, 1_pc3_QAM256, 261_pc3, 260_pc3, 258_pc3, 257_pc3
- Nr FeatureSet DL PerCC: 30KHz_100MHz_4x4_QAM256, 30KHz_100MHz_4x4_QAM256_BW90MHz-supported, 15KHz_20MHz_4x4_QAM256, 30KHz_40MHz_4x4_QAM256, 15KHz_30MHz_2x2_QAM256, 15KHz_15MHz_2x2_QAM256, 15KHz_20MHz_2x2_QAM256, 15KHz_40MHz_4x4_QAM256, 120KHz_100MHz_2x2_QAM64
- Nr FeatureSet UL PerCC: 30KHz_100MHz_QAM256, 30KHz_100MHz_QAM256_BW90MHz-supported, 15KHz_20MHz_QAM256, 30KHz_40MHz_QAM256, 15KHz_30MHz_QAM256, 15KHz_15MHz_QAM256,

15KHz_40MHz_AM256, 120KHz_100MHz_2x2_QAM64

- LTE/NR Band Comb DL: DC_1A(4x4)_n261M(2x2)|(2x2)|(2x2)|(2x2)|(2x2)|(2x2)|(2x2)|(2x2)
- LTE/NR Band Comb UL: DC_1A_n261G(2x2)|(2x2)
- Manufacturer: Keysight Technologies
- Model: C8700200A Test Application Framework
- UXM SN: MY60192714
- TA version: 15.26.4.54151
- License information: C8700A_D26, N7699A-D26
- Measurement engine: XApps
- 3GPP protocol version: EG50
- RFA version: 6.0.7808.34161
- Start time: 2021-06-11_15-50-14
- End time: 2021-06-11_15-59-46
- Test duration: 00h09m32s

3.3. Test procedure

Step 1. Open the CATR.

Step 2. Insert a SIM card to the DUT.

Step 3. Place the DUT on the positioner, make sure that the maximum power (EIRP) beam faces the reflector directly.

Step 4. Keep the sub6 antenna (Flexible Printed Circuit antenna) away from the QTM module and boot up the DUT.

Step 5. Close the CATR.

Step 6. Run the **RF Auto test** app.

3.4. Test results

3.4.1. 6.2B.1.4.1 UE maximum output power (PC3)

Table 3-2. Test condition 1

Time	2021-06-11T15:51:51
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.2B.1.4.1 UE maximum output power (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Freq [MHz]	27924.96MHz

LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 0_50
Expected power [dBm]	23
Others	-
OFDM	DFT
Modulation	QPSK_2
RB allocation	20@22: InnerFull

Table 3-3. Result of testing condition 1

Item	Lower limit	Value	Upper limit	Unit	Status
EIRP	19.53	20.08	43	dBm	Pass
EIRP (Phi)	19.53	17.1	43	dBm	Not set
EIRP (Theta)	19.53	17.03	43	dBm	Not set

3.4.2. 6.3B.1.4 Minimum output power (PC3)

Table 3-4. Test condition 2

Time	2021-06-11T15:51:56
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.3B.1.4 minimum output power (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Freq [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 0_50
Expected power [dBm]	-13
Others	-
OFDM	DFT
Modulation	QPSK_2
RB allocation	64@0: OuterFull

Table 3-5. Result of testing condition 2

Item	Lower limit	Value	Upper limit	Unit	Status
Min power	-999	-28.15	-10.6	dBm	Pass
Min power (Phi)	-999	-31.45	-10.6	dBm	Not set
Min power (Theta)	-999	-30.89	-10.6	dBm	Not set

3.4.3. 6.3B.2.4 Transmit OFF power (PC3)

Table 3-6. Test condition 3

Time	2021-06-11T15:52:04
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.3B.2.4 transmit OFF power (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	0
Others	
OFDM	
Modulation	
RB allocation	0@0

Table 3-7. Result of testing condition 3

Item	Lower limit	Value	Upper limit	Unit	Status
Transmit Off Power	NaN	-42.08	-10.6	dBm	Pass
Transmit off power (Phi)	NaN	-44.53	-10.6	dBm	Not set
Transmit off power (Theta)	NaN	-45.73	-10.6	dBm	Not set

3.4.4. 6.4B.1.4 Frequency error (PC3)

Table 3-8. Test condition 4

Time	2021-06-11T15:52:12
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.4B.1.4 frequency error (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE: 10MHz@NR: 100MHz
SCS	120kHz
ARFCN	2077915
Freq [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	23
Others	-

OFDM	DFT
Modulation	QPSK_2
RB allocation	64@0: OuterFull

Table 3-9. Result of test condition 4 (DL Power: -67dBm)

Item	Lower limit	Value	Upper limit	Unit	Status
Frequency error	-2806.46	NaN	2806.46	Hz	Pass
Frequency error (Phi)	-2806.46	167.26	2806.46	Hz	Not set
Frequency error (Theta)	-2806.46	145.2	2806.46	Hz	Not set

3.4.5. 6.4B.2.4.1 PUSCH error vector magnitude (PC3)

Table 3-10. Test condition 5-1

Time	2021-06-11T15:52:19
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.4B.2.4.1 PUSCH error vector magnitude (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 0_50
Expected power [dBm]	23
Others	-
OFDM	DFT
Modulation	PI2BPSK_0
RB allocation	20@22: InnerFull

Table 3-11. Result of test condition 5-1

Item	Lower limit	Value	Upper limit	Unit	Status
PUSCH EVM & DMRS EVM	0	NaN	30	%	Pass
PUSCH EVM (Phi)	0	4.45	30	%	Not set
PUSCH EVM (Theta)	0	4.43	30	%	Not set
PUSCH DMRS EVM (Phi)	0	2.87	30	%	Not set
PUSCH DMRS EVM (Theta)	0	2.79	30	%	Not set

Table 3-12. Test condition 5-2

Time	2021-06-11T15:52:16
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.4B.2.4.1 PUSCH error vector magnitude (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	23
Others	-
OFDM	DFT
Modulation	PI2BPSK_0
RB allocation	64@0: OuterFull

Table 3-13. Result of test condition 5-2

Item	Lower limit	Value	Upper limit	Unit	Status
PUSCH EVM & DMRS EVM	0	NaN	30	%	Pass
PUSCH EVM (Phi)	0	4.45	30	%	Not set
PUSCH EVM (Theta)	0	4.35	30	%	Not set
PUSCH DMRS EVM (Phi)	0	2.89	30	%	Not set
PUSCH DMRS EVM (Theta)	0	2.87	30	%	Not set

Table 3-14. Test condition 5-3

Time	2021-06-11T15:52:33
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.4B.2.4.1 PUSCH error vector magnitude (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	23
Others	-
OFDM	DFT

Modulation	QPSK_2
RB allocation	20@22: InnerFull

Table 3-15. Result of test condition 5-3

Item	Lower limit	Value	Upper limit	Unit	Status
PUSCH EVM & DMRS EVM	0	NaN	17.5	%	Pass
PUSCH EVM (Phi)	0	4.48	17.5	%	Not set
PUSCH EVM (Theta)	0	4.52	17.5	%	Not set
PUSCH DMRS EVM (Phi)	0	3.04	17.5	%	Not set
PUSCH DMRS EVM (Theta)	0	2.95	17.5	%	Not set

Table 3-16. Test condition 5-4

Time	2021-06-11T15:52:39
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.4B.2.4.1 PUSCH error vector magnitude (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 0_50
Expected power [dBm]	23
Others	-
OFDM	DFT
Modulation	QPSK_2
RB allocation	64@0: OuterFull

Table 3-17. Result of test condition 5-4

Item	Lower limit	Value	Upper limit	Unit	Status
PUSCH EVM & DMRS EVM	0	NaN	17.5	%	Pass
PUSCH EVM (Phi)	0	4.39	17.5	%	Not set
PUSCH EVM (Theta)	0	4.6	17.5	%	Not set
PUSCH DMRS EVM (Phi)	0	2.65	17.5	%	Not set
PUSCH DMRS EVM (Theta)	0	2.62	17.5	%	Not set

Table 3-18. Test condition 5-5

Time	2021-06-11T15:52:46
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.4B.2.4.1 PUSCH error vector magnitude (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	21
Others	-
OFDM	DFT
Modulation	QAM16_10
RB allocation	20@22: InnerFull

Table 3-19. Result of test condition 5-5

Item	Lower limit	Value	Upper limit	Unit	Status
PUSCH EVM & DMRS EVM	0	NaN	12.5	%	Pass
PUSCH EVM (Phi)	0	4.67	12.5	%	Not set
PUSCH EVM (Theta)	0	4.27	12.5	%	Not set
PUSCH DMRS EVM (Phi)	0	3.23	12.5	%	Not set
PUSCH DMRS EVM (Theta)	0	2.69	12.5	%	Not set

Table 3-20. Test condition 5-6

Time	2021-06-11T15:52:53
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.4B.2.4.1 PUSCH error vector magnitude (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	21
Others	-

OFDM	DFT
Modulation	QAM16_10
RB allocation	64@0: OuterFull

Table 3-21. Result of test condition 5-6

Item	Lower limit	Value	Upper limit	Unit	Status
PUSCH EVM & DMRS EVM	0	NaN	12.5	%	Pass
PUSCH EVM (Phi)	0	4.32	12.5	%	Not set
PUSCH EVM (Theta)	0	4.49	12.5	%	Not set
PUSCH DMRS EVM (Phi)	0	2.92	12.5	%	Not set
PUSCH DMRS EVM (Theta)	0	2.96	12.5	%	Not set

Table 3-22. Test condition 5-7

Time	2021-06-11T15:52:59
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.4B.2.4.1 PUSCH error vector magnitude (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 0_50
Expected power [dBm]	20
Others	-
OFDM	DFT
Modulation	QAM64_18
RB allocation	20@22: InnerFull

Table 3-23. Result of test condition 5-7

Item	Lower limit	Value	Upper limit	Unit	Status
PUSCH EVM & DMRS EVM	0	NaN	8	%	Pass
PUSCH EVM (Phi)	0	4.19	8	%	Not set
PUSCH EVM (Theta)	0	4.14	8	%	Not set
PUSCH DMRS EVM (Phi)	0	2.82	8	%	Not set
PUSCH DMRS EVM (Theta)	0	2.74	8	%	Not set

Table 3-24. Test condition 5-8

Time	2021-06-11T15:53:06
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.4B.2.4.1 PUSCH error vector magnitude (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	20
Others	-
OFDM	DFT
Modulation	QAM64_18
RB allocation	64@0: OuterFull

Table 3-25. Result of test condition 5-8

Item	Lower limit	Value	Upper limit	Unit	Status
PUSCH EVM & DMRS EVM	0	NaN	8	%	Pass
PUSCH EVM (Phi)	0	4.35	8	%	Not set
PUSCH EVM (Theta)	0	4.27	8	%	Not set
PUSCH DMRS EVM (Phi)	0	2.88	8	%	Not set
PUSCH DMRS EVM (Theta)	0	3.01	8	%	Not set

Table 3-26. Test condition 5-9

Time	2021-06-11T15:53:17
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.4B.2.4.1 PUSCH error vector magnitude (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	23
Others	-
OFDM	DFT

Modulation	QPSK_2
RB allocation	22@22: InnerFull

Table 3-27. Result of test condition 5-9

Item	Lower limit	Value	Upper limit	Unit	Status
PUSCH EVM & DMRS EVM	0	NaN	17.5	%	Pass
PUSCH EVM (Phi)	0	4.58	17.5	%	Not set
PUSCH EVM (Theta)	0	4.43	17.5	%	Not set
PUSCH DMRS EVM (Phi)	0	4.47	17.5	%	Not set
PUSCH DMRS EVM (Theta)	0	4.25	17.5	%	Not set

Table 3-28. Test condition 5-10

Time	2021-06-11T15:53:24
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.4B.2.4.1 PUSCH error vector magnitude (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	23
Others	-
OFDM	CP
Modulation	QPSK_2
RB allocation	66@0: OuterFull

Table 3-29. Result of test condition 5-10

Item	Lower limit	Value	Upper limit	Unit	Status
PUSCH EVM & DMRS EVM	0	NaN	17.5	%	Pass
PUSCH EVM (Phi)	0	4.91	17.5	%	Not set
PUSCH EVM (Theta)	0	4.78	17.5	%	Not set
PUSCH DMRS EVM (Phi)	0	4.65	17.5	%	Not set
PUSCH DMRS EVM (Theta)	0	4.62	17.5	%	Not set

Table 3-30. Test condition 5-11

Time	2021-06-11T15:53:30
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.4B.2.4.1 PUSCH error vector magnitude (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	21
Others	-
OFDM	CP
Modulation	QAM16_10
RB allocation	22@22: InnerFull

Table 3-31. Result of test condition 5-11

Item	Lower limit	Value	Upper limit	Unit	Status
PUSCH EVM & DMRS EVM	0	NaN	12.5	%	Pass
PUSCH EVM (Phi)	0	4.48	12.5	%	Not set
PUSCH EVM (Theta)	0	4.3	12.5	%	Not set
PUSCH DMRS EVM (Phi)	0	4.17	12.5	%	Not set
PUSCH DMRS EVM (Theta)	0	4.36	12.5	%	Not set

Table 3-32. Test condition 5-12

Time	2021-06-11T15:53:37
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.4B.2.4.1 PUSCH error vector magnitude (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	21
Others	-
OFDM	CP

Modulation	QAM16_10
RB allocation	66@0: OuterFull

Table 3-33. Result of test condition 5-12

Item	Lower limit	Value	Upper limit	Unit	Status
PUSCH EVM & DMRS EVM	0	NaN	12.5	%	Pass
PUSCH EVM (Phi)	0	4.69	12.5	%	Not set
PUSCH EVM (Theta)	0	4.47	12.5	%	Not set
PUSCH DMRS EVM (Phi)	0	4.5	12.5	%	Not set
PUSCH DMRS EVM (Theta)	0	4.49	12.5	%	Not set

Table 3-34. Test condition 5-13

Time	2021-06-11T15:53:44
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.4B.2.4.1 PUSCH error vector magnitude (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	20
Others	-
OFDM	CP
Modulation	QAM64_18
RB allocation	22@22: InnerFull

Table 3-35. Result of test condition 5-13

Item	Lower limit	Value	Upper limit	Unit	Status
PUSCH EVM & DMRS EVM	0	NaN	8	%	Pass
PUSCH EVM (Phi)	0	4.35	8	%	Not set
PUSCH EVM (Theta)	0	4.32	8	%	Not set
PUSCH DMRS EVM (Phi)	0	4.13	8	%	Not set
PUSCH DMRS EVM (Theta)	0	4.38	8	%	Not set

Table 3-36. Test condition 5-14

Time	2021-06-11T15:53:50
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.4B.2.4.1 PUSCH error vector magnitude (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	20
Others	-
OFDM	CP
Modulation	QAM64_18
RB allocation	66@0: OuterFull

Table 3-37. Result of test condition 5-14

Item	Lower limit	Value	Upper limit	Unit	Status
PUSCH EVM & DMRS EVM	0	NaN	8	%	Pass
PUSCH EVM (Phi)	0	4.52	8	%	Not set
PUSCH EVM (Theta)	0	4.5	8	%	Not set
PUSCH DMRS EVM (Phi)	0	4.39	8	%	Not set
PUSCH DMRS EVM (Theta)	0	4.52	8	%	Not set

3.4.6. 6.4B.2.4.2 Carrier leakage (PC3)

Table 3-38. Test condition 6-1

Time	2021-06-11T15:54:01
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.4B.2.4.2 carrier leakage (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	0

Others	-
OFDM	DFT
Modulation	QPSK_2
RB allocation	16@43: Inner16RBRight

Table 3-39. Result of test condition 6-1

Item	Lower limit	Value	Upper limit	Unit	Status
Carrier leakage	-999	-55.12	-25	dBc	Pass
Carrier leakage (Phi)	-999	-57.7	-25	dBc	Not set
Carrier leakage (Theta)	-999	-58.6	-25	dBc	Not set

Table 3-40. Test condition 6-1

Time	2021-06-11T15:54:09
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.4B.2.4.2 carrier leakage (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	-13
Others	-
OFDM	DFT
Modulation	QPSK_2
RB allocation	16@43: Inner16RBRight

Table 3-41. Result of test condition 6-1

Item	Lower limit	Value	Upper limit	Unit	Status
Carrier leakage	-999	-46.36	-20	dBc	Pass
Carrier leakage (Phi)	-999	-49.9	-20	dBc	Not set
Carrier leakage (Theta)	-999	-48.91	-20	dBc	Not set

3.4.7.6.4B.2.4.3 PUSCH in-band emissions (PC3)

Table 3-42. Test condition 7-1

Time	2021-06-11T15:54:18
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.4B.2.4.3 PUSCH in-band emissions (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	10
Others	-
OFDM	DFT
Modulation	PI2BPSK_0
RB allocation	16@22: Inner16RBLeft

Table 3-43. Result of test condition 7-1

Item	Lower limit	Value	Upper limit	Unit	Status
In-band emissions	0	-46.36	0	dB	Pass
All worst margin (Phi)	NaN	-49.9	0	dB	Not set
General worst margin (Phi)	NaN	-48.91	0	dB	Not set
IQ image worst margin (Phi)	NaN	-6.05	0	dB	Not set
Carrier leakage worst margin (Phi)	NaN	9.910000E+037	0	dB	Not set
All worst margin (Theta)	NaN	-16.61	0	dB	Not set
General worst margin (Theta)	NaN	-16.61	0	dB	Not set
IQ image worst margin (Theta)	NaN	-10.58	0	dB	Not set
Carrier leakage worst margin (Theta)	NaN	9.910000E+037	0	dB	Not set

Table 3-44. Test condition 7-2

Time	2021-06-11T15:54:38
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.4B.2.4.3 PUSCH in-band emissions (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915

Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 0_50
Expected power [dBm]	10
Others	-
OFDM	CP
Modulation	QPSK_2
RB allocation	16@22: Inner16RBLeft

Table 3-45. Result of test condition 7-2

Item	Lower limit	Value	Upper limit	Unit	Status
In-band emissions	0	NaN	0	dB	Pass
All worst margin (Phi)	NaN	-16.04	0	dB	Not set
General worst margin (Phi)	NaN	-16.04	0	dB	Not set
IQ image worst margin (Phi)	NaN	-10.61	0	dB	Not set
Carrier leakage worst margin (Phi)	NaN	9.910000E+037	0	dB	Not set
All worst margin (Theta)	NaN	-16.5	0	dB	Not set
General worst margin (Theta)	NaN	-16.61	0	dB	Not set
IQ image worst margin (Theta)	NaN	-10.41	0	dB	Not set
Carrier leakage worst margin (Theta)	NaN	9.910000E+037	0	dB	Not set

Table 3-46. Test condition 7-3

Time	2021-06-11T15:54:45
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.4B.2.4.3 PUSCH in-band emissions (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 0_50
Expected power [dBm]	10
Others	-
OFDM	CP
Modulation	QPSK_2
RB allocation	16@43: Inner16RBLeft

Table 3-47. Result of test condition 7-3

Item	Lower limit	Value	Upper limit	Unit	Status
In-band emissions	0	NaN	0	dB	Pass
All worst margin (Phi)	NaN	-16.01	0	dB	Not set
General worst margin (Phi)	NaN	-16.01	0	dB	Not set
IQ image worst margin (Phi)	NaN	-19.69	0	dB	Not set
Carrier leakage worst margin (Phi)	NaN	-26.2	0	dB	Not set
All worst margin (Theta)	NaN	-16.42	0	dB	Not set
General worst margin (Theta)	NaN	-16.42	0	dB	Not set
IQ image worst margin (Theta)	NaN	-20.17	0	dB	Not set
Carrier leakage worst margin (Theta)	NaN	-25.08	0	dB	Not set

Table 3-48. Test condition 7-4

Time	2021-06-11T15:54:57
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.4B.2.4.3 PUSCH in-band emissions (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	10
Others	-
OFDM	DFT
Modulation	PI2BPSK_0
RB allocation	16@22: Inner16RBLeft

Table 3-49. Result of test condition 7-4

Item	Lower limit	Value	Upper limit	Unit	Status
In-band emissions	0	NaN	0	dB	Pass
All worst margin (Phi)	NaN	-20.57	0	dB	Not set
General worst margin (Phi)	NaN	-20.57	0	dB	Not set
IQ image worst margin (Phi)	NaN	-12.38	0	dB	Not set
Carrier leakage worst margin (Phi)	NaN	9.910000E+037	0	dB	Not set
All worst margin (Theta)	NaN	-21.37	0	dB	Not set
General worst margin (Theta)	NaN	-21.37	0	dB	Not set
IQ image worst margin (Theta)	NaN	-11.58	0	dB	Not set
Carrier leakage worst margin (Theta)	NaN	9.910000E+037	0	dB	Not set

Table 3-50. Test condition 7-5

Time	2021-06-11T15:55:05
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.4B.2.4.3 PUSCH in-band emissions (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	10
Others	-
OFDM	DFT
Modulation	PI2BPSK_0
RB allocation	16@43: Inner16RBLeft

Table 3-51. Result of test condition 7-5

Item	Lower limit	Value	Upper limit	Unit	Status
In-band emissions	0	NaN	0	dB	Pass
All worst margin (Phi)	NaN	-15.59	0	dB	Not set
General worst margin (Phi)	NaN	-15.59	0	dB	Not set
IQ image worst margin (Phi)	NaN	-16.65	0	dB	Not set
Carrier leakage worst margin (Phi)	NaN	-31.07	0	dB	Not set
All worst margin (Theta)	NaN	-15.76	0	dB	Not set
General worst margin (Theta)	NaN	-15.76	0	dB	Not set
IQ image worst margin (Theta)	NaN	-16.78	0	dB	Not set
Carrier leakage worst margin (Theta)	NaN	-30.4	0	dB	Not set

Table 3-52. Test condition 7-6

Time	2021-06-11T15:55:17
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.4B.2.4.3 PUSCH in-band emissions (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz

LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 0_50
Expected power [dBm]	10
Others	-
OFDM	CP
Modulation	QPSK_2
RB allocation	16@22: Inner16RBLeft

Table 3-53. Result of test condition 7-6

Item	Lower limit	Value	Upper limit	Unit	Status
In-band emissions	0	NaN	0	dB	Pass
All worst margin (Phi)	NaN	-15.49	0	dB	Not set
General worst margin (Phi)	NaN	-15.49	0	dB	Not set
IQ image worst margin (Phi)	NaN	-11.46	0	dB	Not set
Carrier leakage worst margin (Phi)	NaN	9.910000E+037	0	dB	Not set
All worst margin (Theta)	NaN	-16.2	0	dB	Not set
General worst margin (Theta)	NaN	-16.2	0	dB	Not set
IQ image worst margin (Theta)	NaN	-11.59	0	dB	Not set
Carrier leakage worst margin (Theta)	NaN	9.910000E+037	0	dB	Not set

Table 3-54. Test condition 7-7

Time	2021-06-11T15:55:25
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.4B.2.4.3 PUSCH in-band emissions (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 0_50
Expected power [dBm]	10
Others	-
OFDM	CP
Modulation	QPSK_2
RB allocation	16@43: Inner16RBLeft

Table 3-55. Result of test condition 7-7

Item	Lower limit	Value	Upper limit	Unit	Status
In-band emissions	0	NaN	0	dB	Pass
All worst margin (Phi)	NaN	-14.03	0	dB	Not set
General worst margin (Phi)	NaN	-11.12	0	dB	Not set
IQ image worst margin (Phi)	NaN	-16.54	0	dB	Not set
Carrier leakage worst margin (Phi)	NaN	-29.61	0	dB	Not set
All worst margin (Theta)	NaN	-14.85	0	dB	Not set
General worst margin (Theta)	NaN	-11.9	0	dB	Not set
IQ image worst margin (Theta)	NaN	-17.39	0	dB	Not set
Carrier leakage worst margin (Theta)	NaN	-30.24	0	dB	Not set

3.4.8.6.4B.2.4.4 EVM equalizer flatness (PC3)

Table 3-56. Test condition 8-1

Time	2021-06-11T15:55:36
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.4B.2.4.4 EVM equalizer flatness (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 0_50
Expected power [dBm]	23
Others	-
OFDM	DFT
Modulation	QPSK_2
RB allocation	64@0: OuterFull

Table 3-57. Result of test condition 8-1

Item	Lower limit	Value	Upper limit	Unit	Status
Ripple	0	NaN	6	dB	Pass
Ripple1 (Phi)	0	0.59	6	dB	Not set
Ripple1 (Theta)	0	1.44	6	dB	Not set
Ripple2 (Phi)	0	0.89	9	dB	Not set
Ripple2 (Theta)	0	1.35	9	dB	Not set

Table 3-58. Test condition 8-2

Time	2021-06-11T15:55:47
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.4B.2.4.4 EVM equalizer flatness (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	23
Others	-
OFDM	CP
Modulation	QPSK_2
RB allocation	64@0: OuterFull

Table 3-59. Result of test condition 8-2

Item	Lower limit	Value	Upper limit	Unit	Status
Ripple	0	NaN	6	dB	Pass
Ripple1 (Phi)	0	0.59	6	dB	Not set
Ripple1 (Theta)	0	1.37	6	dB	Not set
Ripple2 (Phi)	0	1.05	9	dB	Not set
Ripple2 (Theta)	0	1.37	9	dB	Not set

3.4.9.6.5B.2.4.1 Spectrum emissions mask (PC3)

Table 3-60. Test condition 9-1

Time	2021-06-11T15:56:00
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.5B.2.4.1 Spectrum emissions mask (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	23

Others	-
OFDM	DFT
Modulation	PI2BPSK_0
RB allocation	1@0: Outer1RBLeft

Table 3-61. Result of test condition 9-1

Item	Lower limit	Value	Upper limit	Unit	Status
SEM	0	NaN	0	dB	Pass
Offset1 L margin	-999	-19.83	0	dB	Not set
Offset1 H margin	-999	-40.47	0	dB	Not set
Offset2 L margin	-999	-27.38	0	dB	Not set
Offset2 H margin	-999	-30.42	0	dB	Not set
Offset1 L margin (Phi)	-999	-22.09	0	dB	Not set
Offset1 H margin (Phi)	-999	-42.46	0	dB	Not set
Offset2 L margin (Phi)	-999	-29.7	0	dB	Not set
Offset2 H margin (Phi)	-999	-32.7	0	dB	Not set
Offset1 L margin (Theta)	-999	-23.75	0	dB	Not set
Offset1 H margin (Theta)	-999	-44.13	0	dB	Not set
Offset2 L margin (Theta)	-999	-31.21	0	dB	Not set
Offset2 H margin (Theta)	-999	-33.91	0	dB	Not set

Table 3-62. Test condition 9-2

Time	2021-06-11T15:56:09
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.5B.2.4.1 Spectrum emissions mask (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 0_50
Expected power [dBm]	23
Others	-
OFDM	DFT
Modulation	PI2BPSK_0
RB allocation	1@65: Outer1RBRight

Table 3-63. Result of test condition 9-2

Item	Lower limit	Value	Upper limit	Unit	Status
SEM	0	NaN	0	dB	Pass
Offset1 L margin	-999	-39.69	0	dB	Not set
Offset1 H margin	-999	-19.96	0	dB	Not set
Offset2 L margin	-999	-28.68	0	dB	Not set
Offset2 H margin	-999	-27.37	0	dB	Not set
Offset1 L margin (Phi)	-999	-41.93	0	dB	Not set
Offset1 H margin (Phi)	-999	-22.19	0	dB	Not set
Offset2 L margin (Phi)	-999	-31.73	0	dB	Not set
Offset2 H margin (Phi)	-999	-29.4	0	dB	Not set
Offset1 L margin (Theta)	-999	-43.22	0	dB	Not set
Offset1 H margin (Theta)	-999	-23.92	0	dB	Not set
Offset2 L margin (Theta)	-999	-31.65	0	dB	Not set
Offset2 H margin (Theta)	-999	-31.65	0	dB	Not set

Table 3-64. Test condition 9-3

Time	2021-06-11T15:56:18
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.5B.2.4.1 Spectrum emissions mask (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	23
Others	-
OFDM	DFT
Modulation	PI2BPSK_0
RB allocation	64@0: OuterFull

Table 3-65. Result of test condition 9-3

Item	Lower limit	Value	Upper limit	Unit	Status
SEM	0	NaN	0	dB	Pass
Offset1 L margin	-999	-29.94	0	dB	Not set
Offset1 H margin	-999	-32.53	0	dB	Not set
Offset2 L margin	-999	-26.49	0	dB	Not set
Offset2 H margin	-999	-27.89	0	dB	Not set
Offset1 L margin (Phi)	-999	-32	0	dB	Not set
Offset1 H margin (Phi)	-999	-34.76	0	dB	Not set
Offset2 L margin (Phi)	-999	-28.7	0	dB	Not set
Offset2 H margin (Phi)	-999	-29.97	0	dB	Not set
Offset1 L margin (Theta)	-999	-34.17	0	dB	Not set
Offset1 H margin (Theta)	-999	-36.47	0	dB	Not set
Offset2 L margin (Theta)	-999	-30.34	0	dB	Not set
Offset2 H margin (Theta)	-999	-31.65	0	dB	Not set

Table 3-66. Test condition 9-4

Time	2021-06-11T15:56:27
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.5B.2.4.1 Spectrum emissions mask (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	23
Others	-
OFDM	DFT
Modulation	QPSK_2
RB allocation	1@0: Outer1RBLeft

Table 3-67. Result of test condition 9-4

Item	Lower limit	Value	Upper limit	Unit	Status
SEM	0	NaN	0	dB	Pass
Offset1 L margin	-999	-19.29	0	dB	Not set
Offset1 H margin	-999	-40.54	0	dB	Not set
Offset2 L margin	-999	-26.59	0	dB	Not set
Offset2 H margin	-999	-30.15	0	dB	Not set

Item	Lower limit	Value	Upper limit	Unit	Status
Offset1 L margin (Phi)	-999	-21.41	0	dB	Not set
Offset1 H margin (Phi)	-999	-42.98	0	dB	Not set
Offset2 L margin (Phi)	-999	-28.55	0	dB	Not set
Offset2 H margin (Phi)	-999	-32.39	0	dB	Not set
Offset1 L margin (Theta)	-999	-23.43	0	dB	Not set
Offset1 H margin (Theta)	-999	-43.94	0	dB	Not set
Offset2 L margin (Theta)	-999	-30.51	0	dB	Not set
Offset2 H margin (Theta)	-999	-33.93	0	dB	Not set

Table 3-68. Test condition 9-5

Time	2021-06-11T15:56:36
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.5B.2.4.1 Spectrum emissions mask (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	23
Others	-
OFDM	DFT
Modulation	QPSK_2
RB allocation	1@65: Outer1RBRight

Table 3-69. Result of test condition 9-5

Item	Lower limit	Value	Upper limit	Unit	Status
SEM	0	NaN	0	dB	Pass
Offset1 L margin	-999	-39.57	0	dB	Not set
Offset1 H margin	-999	-19.26	0	dB	Not set
Offset2 L margin	-999	-28.35	0	dB	Not set
Offset2 H margin	-999	-26.98	0	dB	Not set
Offset1 L margin (Phi)	-999	-42.39	0	dB	Not set
Offset1 H margin (Phi)	-999	-21.39	0	dB	Not set
Offset2 L margin (Phi)	-999	-31.11	0	dB	Not set
Offset2 H margin (Phi)	-999	-29.48	0	dB	Not set
Offset1 L margin (Theta)	-999	-42.78	0	dB	Not set
Offset1 H margin (Theta)	-999	-23.37	0	dB	Not set

Item	Lower limit	Value	Upper limit	Unit	Status
Offset2 L margin (Theta)	-999	-31.6	0	dB	Not set
Offset2 H margin (Theta)	-999	-30.32	0	dB	Not set

Table 3-70. Test condition 9-6

Time	2021-06-11T15:56:45
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.5B.2.4.1 Spectrum emissions mask (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 0_50
Expected power [dBm]	23
Others	-
OFDM	DFT
Modulation	QPSK_2
RB allocation	64@0: OuterFull

Table 3-71. Result of test condition 9-6

Item	Lower limit	Value	Upper limit	Unit	Status
SEM	0	NaN	0	dB	Pass
Offset1 L margin	-999	-30.66	0	dB	Not set
Offset1 H margin	-999	-31.1	0	dB	Not set
Offset2 L margin	-999	-25.12	0	dB	Not set
Offset2 H margin	-999	-25.72	0	dB	Not set
Offset1 L margin (Phi)	-999	-32.73	0	dB	Not set
Offset1 H margin (Phi)	-999	-33.08	0	dB	Not set
Offset2 L margin (Phi)	-999	-27.42	0	dB	Not set
Offset2 H margin (Phi)	-999	-27.94	0	dB	Not set
Offset1 L margin (Theta)	-999	-34.86	0	dB	Not set
Offset1 H margin (Theta)	-999	-35.45	0	dB	Not set
Offset2 L margin (Theta)	-999	-28.97	0	dB	Not set
Offset2 H margin (Theta)	-999	-29.71	0	dB	Not set

Table 3-72. Test condition 9-7

Time	2021-06-11T15:56:54
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.5B.2.4.1 Spectrum emissions mask (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	21
Others	-
OFDM	DFT
Modulation	QAM16_10
RB allocation	1@0: Outer1RBLeft

Table 3-73. Result of test condition 9-7

Item	Lower limit	Value	Upper limit	Unit	Status
SEM	0	NaN	0	dB	Pass
Offset1 L margin	-999	-21.19	0	dB	Not set
Offset1 H margin	-999	-40.66	0	dB	Not set
Offset2 L margin	-999	-29.48	0	dB	Not set
Offset2 H margin	-999	-30.83	0	dB	Not set
Offset1 L margin (Phi)	-999	-23.29	0	dB	Not set
Offset1 H margin (Phi)	-999	-42.9	0	dB	Not set
Offset2 L margin (Phi)	-999	-31.88	0	dB	Not set
Offset2 H margin (Phi)	-999	-33.34	0	dB	Not set
Offset1 L margin (Theta)	-999	-25.35	0	dB	Not set
Offset1 H margin (Theta)	-999	-44.51	0	dB	Not set
Offset2 L margin (Theta)	-999	-32.98	0	dB	Not set
Offset2 H margin (Theta)	-999	-34.41	0	dB	Not set

Table 3-74. Test condition 9-8

Time	2021-06-11T15:57:03
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.5B.2.4.1 Spectrum emissions mask (PC3)
Description	-
Band	n261 B1

Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 0_50
Expected power [dBm]	21
Others	-
OFDM	DFT
Modulation	QAM16_10
RB allocation	1@65: Outer1RBRight

Table 3-75. Result of test condition 9-8

Item	Lower limit	Value	Upper limit	Unit	Status
SEM	0	NaN	0	dB	Pass
Offset1 L margin	-999	-40.13	0	dB	Not set
Offset1 H margin	-999	-22.61	0	dB	Not set
Offset2 L margin	-999	-30.55	0	dB	Not set
Offset2 H margin	-999	-30.49	0	dB	Not set
Offset1 L margin (Phi)	-999	-42.54	0	dB	Not set
Offset1 H margin (Phi)	-999	-24.83	0	dB	Not set
Offset2 L margin (Phi)	-999	-32.73	0	dB	Not set
Offset2 H margin (Phi)	-999	-32.51	0	dB	Not set
Offset1 L margin (Theta)	-999	-43.23	0	dB	Not set
Offset1 H margin (Theta)	-999	-26.59	0	dB	Not set
Offset2 L margin (Theta)	-999	-33.51	0	dB	Not set
Offset2 H margin (Theta)	-999	-34.17	0	dB	Not set

Table 3-76. Test condition 9-9

Time	2021-06-11T15:57:12
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.5B.2.4.1 Spectrum emissions mask (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 0_50
Expected power [dBm]	21
Others	-

OFDM	DFT
Modulation	QAM16_10
RB allocation	64@0: OuterFull

Table 3-77. Result of test condition 9-9

Item	Lower limit	Value	Upper limit	Unit	Status
SEM	0	NaN	0	dB	Pass
Offset1 L margin	-999	-32.75	0	dB	Not set
Offset1 H margin	-999	-34.29	0	dB	Not set
Offset2 L margin	-999	-26.77	0	dB	Not set
Offset2 H margin	-999	-27.63	0	dB	Not set
Offset1 L margin (Phi)	-999	-34.94	0	dB	Not set
Offset1 H margin (Phi)	-999	-36.52	0	dB	Not set
Offset2 L margin (Phi)	-999	-28.91	0	dB	Not set
Offset2 H margin (Phi)	-999	-29.67	0	dB	Not set
Offset1 L margin (Theta)	-999	-36.76	0	dB	Not set
Offset1 H margin (Theta)	-999	-38.25	0	dB	Not set
Offset2 L margin (Theta)	-999	-30.5	0	dB	Not set
Offset2 H margin (Theta)	-999	-31.85	0	dB	Not set

Table 3-78. Test condition 9-10

Time	2021-06-11T15:57:20
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.5B.2.4.1 Spectrum emissions mask (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	20
Others	-
OFDM	DFT
Modulation	QAM64_18
RB allocation	1@0: Outer1RBLeft

Table 3-79. Result of test condition 9-10

Item	Lower limit	Value	Upper limit	Unit	Status
SEM	0	NaN	0	dB	Pass
Offset1 L margin	-999	-21.92	0	dB	Not set
Offset1 H margin	-999	-40.71	0	dB	Not set
Offset2 L margin	-999	-29.44	0	dB	Not set
Offset2 H margin	-999	-31.75	0	dB	Not set
Offset1 L margin (Phi)	-999	-24.3	0	dB	Not set
Offset1 H margin (Phi)	-999	-43.26	0	dB	Not set
Offset2 L margin (Phi)	-999	-31.65	0	dB	Not set
Offset2 H margin (Phi)	-999	-34.12	0	dB	Not set
Offset1 L margin (Theta)	-999	-25.67	0	dB	Not set
Offset1 H margin (Theta)	-999	-44.22	0	dB	Not set
Offset2 L margin (Theta)	-999	-32.96	0	dB	Not set
Offset2 H margin (Theta)	-999	-35.46	0	dB	Not set

Table 3-80. Test condition 9-11

Time	2021-06-11T15:57:29
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.5B.2.4.1 Spectrum emissions mask (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	20
Others	-
OFDM	DFT
Modulation	QAM64_18
RB allocation	1@65: Outer1RBRight

Table 3-81. Result of test condition 9-11

Item	Lower limit	Value	Upper limit	Unit	Status
SEM	0	NaN	0	dB	Pass
Offset1 L margin	-999	-40.12	0	dB	Not set
Offset1 H margin	-999	-22.2	0	dB	Not set
Offset2 L margin	-999	-30.62	0	dB	Not set
Offset2 H margin	-999	-29.76	0	dB	Not set
Offset1 L margin (Phi)	-999	-42.48	0	dB	Not set
Offset1 H margin (Phi)	-999	-24.34	0	dB	Not set
Offset2 L margin (Phi)	-999	-33.55	0	dB	Not set
Offset2 H margin (Phi)	-999	-32.47	0	dB	Not set
Offset1 L margin (Theta)	-999	-43.43	0	dB	Not set
Offset1 H margin (Theta)	-999	-26.29	0	dB	Not set
Offset2 L margin (Theta)	-999	-33.53	0	dB	Not set
Offset2 H margin (Theta)	-999	-33.08	0	dB	Not set

Table 3-82. Test condition 9-12

Time	2021-06-11T15:57:38
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.5B.2.4.1 Spectrum emissions mask (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	20
Others	-
OFDM	DFT
Modulation	QAM64_18
RB allocation	64@0: OuterFull

Table 3-83. Result of test condition 9-12

Item	Lower limit	Value	Upper limit	Unit	Status
SEM	0	NaN	0	dB	Pass
Offset1 L margin	-999	-33.87	0	dB	Not set
Offset1 H margin	-999	-36.93	0	dB	Not set
Offset2 L margin	-999	-29.08	0	dB	Not set
Offset2 H margin	-999	-30.53	0	dB	Not set

Item	Lower limit	Value	Upper limit	Unit	Status
Offset1 L margin (Phi)	-999	-36.17	0	dB	Not set
Offset1 H margin (Phi)	-999	-39.37	0	dB	Not set
Offset2 L margin (Phi)	-999	-31.31	0	dB	Not set
Offset2 H margin (Phi)	-999	-32.71	0	dB	Not set
Offset1 L margin (Theta)	-999	-37.74	0	dB	Not set
Offset1 H margin (Theta)	-999	-40.59	0	dB	Not set
Offset2 L margin (Theta)	-999	-32.7	0	dB	Not set
Offset2 H margin (Theta)	-999	-34.32	0	dB	Not set

Table 3-84. Test condition 9-13

Time	2021-06-11T15:57:51
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.5B.2.4.1 Spectrum emissions mask (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	20
Others	-
OFDM	CP
Modulation	QPSK_2
RB allocation	1@0: Outer1RBLeft

Table 3-85. Result of test condition 9-13

Item	Lower limit	Value	Upper limit	Unit	Status
SEM	0	NaN	0	dB	Pass
Offset1 L margin	-999	-21.19	0	dB	Not set
Offset1 H margin	-999	-40.75	0	dB	Not set
Offset2 L margin	-999	-27.96	0	dB	Not set
Offset2 H margin	-999	-31.77	0	dB	Not set
Offset1 L margin (Phi)	-999	-23.44	0	dB	Not set
Offset1 H margin (Phi)	-999	-43.27	0	dB	Not set
Offset2 L margin (Phi)	-999	-30.17	0	dB	Not set
Offset2 H margin (Phi)	-999	-34.11	0	dB	Not set
Offset1 L margin (Theta)	-999	-25.13	0	dB	Not set
Offset1 H margin (Theta)	-999	-44.16	0	dB	Not set

Item	Lower limit	Value	Upper limit	Unit	Status
Offset2 L margin (Theta)	-999	-31.81	0	dB	Not set
Offset2 H margin (Theta)	-999	-35.27	0	dB	Not set

Table 3-86. Test condition 9-14

Time	2021-06-11T15:58:00
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.5B.2.4.1 Spectrum emissions mask (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 0_50
Expected power [dBm]	23
Others	-
OFDM	CP
Modulation	QPSK_2
RB allocation	1@65: Outer1RBRight

Table 3-87. Result of test condition 9-14

Item	Lower limit	Value	Upper limit	Unit	Status
SEM	0	NaN	0	dB	Pass
Offset1 L margin	-999	-39.83	0	dB	Not set
Offset1 H margin	-999	-21.22	0	dB	Not set
Offset2 L margin	-999	-29.46	0	dB	Not set
Offset2 H margin	-999	-28.64	0	dB	Not set
Offset1 L margin (Phi)	-999	-41.98	0	dB	Not set
Offset1 H margin (Phi)	-999	-23.68	0	dB	Not set
Offset2 L margin (Phi)	-999	-32.43	0	dB	Not set
Offset2 H margin (Phi)	-999	-31.08	0	dB	Not set
Offset1 L margin (Theta)	-999	-43.32	0	dB	Not set
Offset1 H margin (Theta)	-999	-24.87	0	dB	Not set
Offset2 L margin (Theta)	-999	-32.49	0	dB	Not set
Offset2 H margin (Theta)	-999	-32.11	0	dB	Not set

Table 3-88. Test condition 9-15

Time	2021-06-11T15:58:09
System	ENDC FR2
Band combo info	DC_1A_n261A

Test case	6.5B.2.4.1 Spectrum emissions mask (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 0_50
Expected power [dBm]	23
Others	-
OFDM	CP
Modulation	QPSK_2
RB allocation	66@0: OuterFull

Table 3-89. Result of test condition 9-15

Item	Lower limit	Value	Upper limit	Unit	Status
SEM	0	NaN	0	dB	Pass
Offset1 L margin	-999	-32.19	0	dB	Not set
Offset1 H margin	-999	-31.9	0	dB	Not set
Offset2 L margin	-999	-25.46	0	dB	Not set
Offset2 H margin	-999	-26.09	0	dB	Not set
Offset1 L margin (Phi)	-999	-34.35	0	dB	Not set
Offset1 H margin (Phi)	-999	-33.89	0	dB	Not set
Offset2 L margin (Phi)	-999	-27.67	0	dB	Not set
Offset2 H margin (Phi)	-999	-28.26	0	dB	Not set
Offset1 L margin (Theta)	-999	-36.26	0	dB	Not set
Offset1 H margin (Theta)	-999	-36.26	0	dB	Not set
Offset2 L margin (Theta)	-999	-29.15	0	dB	Not set
Offset2 H margin (Theta)	-999	-30.14	0	dB	Not set

3.4.10. 6.5B.2.4.3 NR ACLR (PC3)

Table 3-90. Test condition 9-16

Time	2021-06-11T15:58:17
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.5B.2.4.3 NR ACLR (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz

ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 0_50
Expected power [dBm]	23
Others	-
OFDM	DFT
Modulation	PI2BPSK_0
RB allocation	1@0: Outer1RBLeft

Table 3-91. Result of test condition 9-16

Item	Lower limit	Value	Upper limit	Unit	Status
ACLR	-999	NaN	-12.04	dB	Pass
OffsetA L	-999	-37.95	-12.04	dB	Not set
OffsetA U	-999	-40.74	-12.04	dB	Not set
Reference carrier power	NaN	17.3	NaN	dB	Not set

Table 3-92. Test condition 9-17

Time	2021-06-11T15:58:22
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.5B.2.4.3 NR ACLR (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 0_50
Expected power [dBm]	23
Others	-
OFDM	DFT
Modulation	PI2BPSK_0
RB allocation	1@65: Outer1RBRight

Table 3-93. Result of test condition 9-17

Item	Lower limit	Value	Upper limit	Unit	Status
ACLR	-999	NaN	-12.04	dB	Pass
OffsetA L	-999	-40	-12.04	dB	Not set
OffsetA U	-999	-39.53	-12.04	dB	Not set
Reference carrier power	NaN	17.98	NaN	dB	Not set

Table 3-94. Test condition 9-18

Time	2021-06-11T15:58:26
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.5B.2.4.3 NR ACLR (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	23
Others	-
OFDM	DFT
Modulation	PI2BPSK_0
RB allocation	64@0: OuterFull

Table 3-95. Result of test condition 9-18

Item	Lower limit	Value	Upper limit	Unit	Status
ACLR	-999	NaN	-12.04	dB	Pass
OffsetA L	-999	-36.9	-12.04	dB	Not set
OffsetA U	-999	-38.25	-12.04	dB	Not set
Reference carrier power	NaN	17.77	NaN	dB	Not set

Table 3-96. Test condition 9-19

Time	2021-06-11T15:58:30
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.5B.2.4.3 NR ACLR (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	23
Others	-
OFDM	DFT
Modulation	QPSK_2

RB allocation	1@0: Outer1RBLeft
----------------------	-------------------

Table 3-97. Result of test condition 9-19

Item	Lower limit	Value	Upper limit	Unit	Status
ACLR	-999	NaN	-12.04	dB	Pass
OffsetA L	-999	-38.17	-12.04	dB	Not set
OffsetA U	-999	-41.14	-12.04	dB	Not set
Reference carrier power	NaN	17.68	NaN	dB	Not set

Table 3-98. Test condition 9-20

Time	2021-06-11T15:58:34
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.5B.2.4.3 NR ACLR (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	23
Others	-
OFDM	DFT
Modulation	QPSK_2
RB allocation	1@65: Outer1RBRight

Table 3-99. Result of test condition 9-20

Item	Lower limit	Value	Upper limit	Unit	Status
ACLR	-999	NaN	-12.04	dB	Pass
OffsetA L	-999	-40.19	-12.04	dB	Not set
OffsetA U	-999	-39.62	-12.04	dB	Not set
Reference carrier power	NaN	18.23	NaN	dB	Not set

Table 3-100. Test condition 9-21

Time	2021-06-11T15:58:39
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.5B.2.4.3 NR ACLR (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz

SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 0_50
Expected power [dBm]	23
Others	-
OFDM	DFT
Modulation	QPSK_2
RB allocation	64@0: OuterFull

Table 3-101. Result of test condition 9-21

Item	Lower limit	Value	Upper limit	Unit	Status
ACLR	-999	NaN	-12.04	dB	Pass
OffsetA L	-999	-35.79	-12.04	dB	Not set
OffsetA U	-999	-36.48	-12.04	dB	Not set
Reference carrier power	NaN	17.95	NaN	dBm	Not set

Table 3-102. Test condition 9-22

Time	2021-06-11T15:58:43
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.5B.2.4.3 NR ACLR (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 0_50
Expected power [dBm]	21
Others	-
OFDM	DFT
Modulation	QAM16_10
RB allocation	1@0: Outer1RBLeft

Table 3-103. Result of test condition 9-22

Item	Lower limit	Value	Upper limit	Unit	Status
ACLR	-999	NaN	-12.04	dB	Pass
OffsetA L	-999	-36.58	-12.04	dB	Not set
OffsetA U	-999	-39.06	-12.04	dB	Not set
Reference carrier power	NaN	15.47	NaN	dBm	Not set

Table 3-104. Test condition 9-23

Time	2021-06-11T15:58:47
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.5B.2.4.3 NR ACLR (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	21
Others	-
OFDM	DFT
Modulation	QAM16_10
RB allocation	1@65: Outer1RBRight

Table 3-105. Result of test condition 9-23

Item	Lower limit	Value	Upper limit	Unit	Status
ACLR	-999	NaN	-12.04	dB	Pass
OffsetA L	-999	-38.39	-12.04	dB	Not set
OffsetA U	-999	-38.33	-12.04	dB	Not set
Reference carrier power	NaN	16.15	NaN	dBm	Not set

Table 3-106. Test condition 9-24

Time	2021-06-11T15:58:51
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.5B.2.4.3 NR ACLR (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	21
Others	-
OFDM	DFT
Modulation	QAM16_10

RB allocation	64@0: OuterFull
----------------------	-----------------

Table 3-107. Result of test condition 9-24

Item	Lower limit	Value	Upper limit	Unit	Status
ACLR	-999	NaN	-12.04	dB	Pass
OffsetA L	-999	-35.72	-12.04	dB	Not set
OffsetA U	-999	-36.79	-12.04	dB	Not set
Reference carrier power	NaN	16.25	NaN	dBm	Not set

Table 3-108. Test condition 9-25

Time	2021-06-11T15:58:56
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.5B.2.4.3 NR ACLR (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	21
Others	-
OFDM	DFT
Modulation	QAM64_18
RB allocation	64@0: OuterFull

Table 3-109. Result of test condition 9-25

Item	Lower limit	Value	Upper limit	Unit	Status
ACLR	-999	NaN	-12.04	dB	Pass
OffsetA L	-999	-34.96	-12.04	dB	Not set
OffsetA U	-999	-36.32	-12.04	dB	Not set
Reference carrier power	NaN	14.07	NaN	dBm	Not set

Table 3-110. Test condition 9-26

Time	2021-06-11T15:59:04
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.5B.2.4.3 NR ACLR (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz

SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 0_50
Expected power [dBm]	23
Others	-
OFDM	CP
Modulation	QPSK_2
RB allocation	1@0: Outer1RBLeft

Table 3-111. Result of test condition 9-26

Item	Lower limit	Value	Upper limit	Unit	Status
ACLR	-999	NaN	-12.04	dB	Pass
OffsetA L	-999	-36.21	-12.04	dB	Not set
OffsetA U	-999	-38.5	-12.04	dB	Not set
Reference carrier power	NaN	14.87	NaN	dBm	Not set

Table 3-112. Test condition 9-27

Time	2021-06-11T15:59:08
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.5B.2.4.3 NR ACLR (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 0_50
Expected power [dBm]	23
Others	-
OFDM	CP
Modulation	QPSK_2
RB allocation	1@65: Outer1RBRight

Table 3-113. Result of test condition 9-27

Item	Lower limit	Value	Upper limit	Unit	Status
ACLR	-999	NaN	-12.04	dB	Pass
OffsetA L	-999	-37.7	-12.04	dB	Not set
OffsetA U	-999	-37.87	-12.04	dB	Not set
Reference carrier power	NaN	15.47	NaN	dBm	Not set

Table 3-114. Test condition 9-28

Time	2021-06-11T15:59:12
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	6.5B.2.4.3 NR ACLR (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	23
Others	-
OFDM	CP
Modulation	QPSK_2
RB allocation	66@0: OuterFull

Table 3-115. Result of test condition 9-28

Item	Lower limit	Value	Upper limit	Unit	Status
ACLR	-999	NaN	-12.04	dB	Pass
OffsetA L	-999	-34.3	-12.04	dB	Not set
OffsetA U	-999	-35.03	-12.04	dB	Not set
Reference carrier power	NaN	15.77	NaN	dBm	Not set

3.4.11. 7.3B.2.4 Reference sensitivity power level (PC3)

Table 3-116. Test condition 9-29

Time	2021-06-11T15:59:27
System	ENDC FR2
Band combo info	DC_1A_n261A
Test case	7.3B.2.4 Reference sensitivity power level (PC3)
Description	-
Band	n261 B1
Bandwidth	LTE:10MHz@NR:100MHz
SCS	120kHz
ARFCN	2077915
Frequency [MHz]	27924.96MHz
LTESCC info	LTE: DLARFCN_300 EIP_15 QPSK_2 O_50
Expected power [dBm]	23
Others	-

OFDM	DFT
Modulation	DL QPSK_4: UL QPSK_2
RB allocation	UL 64@0: OuterFull DL 66@0: FullRB

Table 3-117. Result of test condition 9-29 (DL Power -82.96dBm/BW)

Item	Lower limit	Value	Upper limit	Unit	Status
Throughput @ -82.96dBm	0	100	95	%	Pass

Appendix 1. Notices

Thundercomm may have patents or pending patent programs covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries to service@thundercomm.com.

THUNDERCOMM PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions; therefore, this statement may not apply to you.

Changes are made periodically to the information herein; these changes will be incorporated in new editions of the publication. To provide better service, Thundercomm reserves the right to improve and/or modify the products and software programs described in the manuals, and the content of the manual, at any time without additional notice.

The software interface and function and hardware configuration described in the manuals included with your development board or system on module might not match exactly the actual configuration of that you have purchased. For the configuration of the product, refer to the related contract (if any) or product packing list, or consult the distributor for the product sales. Thundercomm may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Thundercomm product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Thundercomm or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary.

The information of this document should not be as any invitation for offer or any advice to the visitors. Please consult the professional comments from the sales consultant prior to do any actions of invest or purchase.

Thundercomm may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Thundercomm Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Thundercomm product, and use of those Web sites is at your own risk. Thundercomm shall not be responsible for the content of the third party.

Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

This document is copyrighted by Thundercomm and the property right of the date mentioned in this document, including but not limited trademarks, patents, copyrights, trade name etc. are not covered by any open-source license. Thundercomm may update this document at any time without notice.

Anyone doesn't have the right to amend, reprint, republication, reproduce, transmit, distribute or any other way to use this document in business or public purpose without the prior written consent by Thundercomm.

E-mail messages sent to Thundercomm via the Internet are not guaranteed to be completely secure. Thundercomm shall not be liable for any loss incurred by the surfer when transmitting any information over the Internet or for any loss incurred by Thundercomm when sending any information over the Internet at your request.

Thundercomm has all rights under other relevant exemptions provided by laws and regulations, and Thundercomm's failure to claim or delay in claiming such rights shall not be deemed to be a waiver of such rights by Thundercomm.

Thundercomm reserves the right of final interpretation of this document.

Thundercomm Confidential

Appendix 2. Trademarks

Thundercomm and Thundercomm Turbox are trademarks of Thundercomm Corporation or its associate companies in China and/or other countries. Intel, Intel SpeedStep, Optane, and Thunderbolt are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries. Microsoft, Windows, Direct3D, BitLocker, and Cortana are trademarks of the Microsoft group of companies. MDP (Mini DisplayPort), DisplayPort, and VESA are trademarks of the Video Electronics Standards Association. The terms HDMI and HDMI High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Wi-Fi, Wi-Fi Alliance, WiGig, and Miracast are registered trademarks of Wi-Fi Alliance. USB-C is a registered trademark of USB Implementers Forum. All other trademarks are the property of their respective owners.