



REPORT No.: SZ26020168W02

TEST REPORT

APPLICANT : ZHONGSHAN EvoAria
TECHNOLOGY CO.,LTD.
PRODUCT NAME : HIGH RESOLUTION DIGITAL
MUSIC PLAYER
MODEL NAME : EA-P001
BRAND NAME : EvoAria
STANDARD(S) : MIC Notice No.88 Annex 43
RECEIPT DATE : 2026-03-02
TEST DATE : 2026-03-12 to 2026-04-09
ISSUE DATE : 2026-04-17



Edited by:

Peng Mi

Peng Mi (Rapporteur)

Approved by:

Shen Junsheng

Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, Guangdong Province, P. R. China

Tel: 86-755-36698555
Http://www.morlab.cn

Fax: 86-755-36698525
E-mail: service@morlab.cn





DIRECTORY

1. Summary of Test Results	4
1.1. Testing Applied Methods	4
1.2. Test Equipment List	5
1.3. Measurement Uncertainty	6
1.4. Testing Laboratory	6
2. General Description	7
2.1. Information of Applicant and Manufacturer	7
2.2. Information of EUT	7
2.3. Information of Antenna	8
2.4. Channel List of EUT	8
2.5. Test Configuration of EUT	9
2.6. Test Conditions	11
2.7. Test Setup Layout Diagram	12
3. Description of Test Items	14
3.1. Frequency Error	14
3.2. Occupied Bandwidth	15
3.3. Unwanted Emission Intensity	16
3.4. Antenna Power Error	17
3.5. Limitation of Collateral Emission of Receiver	18
3.6. E.I.R.P.	19
3.7. Radiation Angle of Antenna	20
3.8. Radio Interference Prevention Capability	21
3.9. Carrier Sense Function	22
3.10. Construction Protection Confirmation Method	23
Annex A Test Data and Results	24
Notes	39



REPORT No.: SZ26020168W02

Change History		
Version	Date	Reason for change
1.0	2026-04-17	First edition

1. Summary of Test Results

No.	Description of Test	Test Engineer	Result	Remark
1	Frequency Error	Zhu Peihong	PASS	/
2	Occupied Bandwidth	Zhu Peihong	PASS	/
3	Unwanted Emission Intensity	Zhu Peihong	PASS	/
4	Antenna Power Error	Zhu Peihong	PASS	/
5	Limitation of Collateral Emission of Receiver	Zhu Peihong	PASS	/
6	E.I.R.P.	Zhu Peihong	PASS	/
7	Radiation Angle of Antenna	Zhu Peihong	PASS	/
8	Radio Interference Prevention Capability	Zhu Peihong	PASS	/
9	Carrier Sense Function	Zhu Peihong	PASS	/
10	Construction Protection Confirmation	N/A	PASS	/

Note 1: Any additions, deviation, or exclusions from the method shall be noted in the "Remark".

1.1. Testing Applied Methods

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- MIC Notice No.88 Annex 43
- Certification of technical standard conformity for specified radio equipment, etc. Article 2 Paragraph 1 of Item 19
- Radio Equipment Regulations Article 49-20



1.2. Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Due Date	Cal. Body	Cal. Method
EXA Signal Analyzer	Agilent	N9010A	MY53470836	2025.12.23	2026.12.22	SMQ	c
DC Power Supply	IVYTECH	IV3610	1709D361010	2025.09.03	2026.09.02	CCIC	c
Power Sensor	Agilent	U2021XA	MY54180008	2025.09.03	2026.09.02	CCIC	c
Radio Communication Tester	R&S	CMW500	108950	2025.12.23	2026.12.22	CCIC	c

Note 1: The equipment were calibrated by CCIC (Shenzhen) Metrology&Testing Service Co.,Ltd and Shenzhen Academy of Metrology and Quality Inspection.

Note 2: Calibration Method:

- Calibration conducted by the National Institute of Information and Communications Technology (NICT) (hereinafter referred to as "NICT") or a designated calibration agency under Article 102-18 paragraph (1);
- Correction conducted pursuant to the provisions of Article 135 or Article 144 of the Measurement Law (Law No. 51 of 1992);
- Calibration conducted in foreign countries, which shall be equivalent to the calibration conducted by the NICT or a designated calibration agency under Article 102-18 paragraph (1);
- Calibration conducted by using measuring instruments and other equipment listed in the right column of Table No. 3 attached hereto, which shall have been given any of calibration, etc. listed above from a) to c).



1.3. Measurement Uncertainty

No.	Test Items	Uncertainty	Remark
1	Frequency Error / 99% Bandwidth	$\pm 1.75 \times 10^{-6}$	Confidence levels of 95%
2	Antenna Power	$\pm 1.14\text{dB}$	Confidence levels of 95%
3	Spurious Emissions(<1GHz)	$\pm 2.23\text{dB}$	Confidence levels of 95%
4	Spurious Emissions(>1GHz)	$\pm 1.72\text{dB}$	Confidence levels of 95%
5	Transmission Antenna Gain	$\pm 2.49\text{dB}$	Confidence levels of 95%

1.4. Testing Laboratory

Laboratory Name	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address	FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone	+86 755 36698555
Facsimile	+86 755 36698525

2. General Description

2.1. Information of Applicant and Manufacturer

Applicant	ZHONGSHAN EvoAria TECHNOLOGY CO.,LTD.
Applicant Address	No. 420, 4th Floor, Building 3, No. 9, Boai 3rd Road, Shiqi District, Zhongshan City, Guangdong Province, China
Manufacturer	TempoTec Corp
Manufacturer Address	Room 201, Building 1, No.37, Zhushan Datangtuo West Street, Dongcheng Street, Dongguan City, Guangdong Province, China

2.2. Information of EUT

Product Name	HIGH RESOLUTION DIGITAL MUSIC PLAYER		
Sample No.	1#		
Hardware Version	1.0		
Software Version	1.10		
Modulation Technology	DSSS, OFDM		
Modulation Type and Data Rate	Refer to 2.5.2		
Wireless Technology	802.11b, 802.11g, 802.11n(HT20), 802.11n(HT40)		
Operating Frequency Range	2412MHz–2472MHz		
Channel List	Please refer as chapter 2.4 in this report.		
Power Supply	Type		Battery
	Voltage (V)	Low	3.55
		Rated	3.87
		High	4.45

Note 1: The black bold voltage values were selected for test, about the voltage fluctuation evaluation, please refer as chapter 2.6.2 in this report.

Note 2: The EUT supports a MIMO function. Physically, the EUT provides two completed transmitters and two receivers for 802.11n modulation mode. For the test item Antenna Power Error, we recorded the test result of two antennas separately, for other test items both of the two antennas were tested separately, we only recorded the worst test result(ANT2) in this report.

Note 3: The EUT description presented in the report are provided by applicant and/or manufacturer, and the test laboratory is not responsible for the accuracy of the information. For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



2.3. Information of Antenna

Antenna Manufacturer	N/A
Brand Name	N/A
Model Name	N/A
Antenna Type	ANT 1: FPC Antenna; ANT 2: MET Antenna
Antenna Gain	ANT 1: 1.5dBi; ANT 2: 2.0dBi

2.4. Channel List of EUT

Nominal Channel Bandwidth	Channel	Frequency (MHz)	Channel	Frequency (MHz)
20MHz	1	2412	8	2447
	2	2417	9	2452
	3	2422	10	2457
	4	2427	11	2462
	5	2432	12	2467
	6	2437	13	2472
	7	2442		
Nominal Channel Bandwidth	Channel	Frequency (MHz)	Channel	Frequency (MHz)
40MHz	3	2422	8	2447
	4	2427	9	2452
	5	2432	10	2457
	6	2437	11	2462
	7	2442		

Note 1: The black bold channels were selected for test.



2.5. Test Configuration of EUT

2.5.1. Evaluation of The Worst Case

Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Channel
Frequency Error	Unmodulated Single Carrier	1/7/13
Occupied Bandwidth	CCK	1/7/13
Unwanted Emission Intensity	CCK	1/7/13
Antenna Power and Antenna Power Error	CCK	1/7/13
Limitation of Collateral Emission of Receiver	CCK	1/7/13
Transmission Radiation Angle Width	CCK	1/7/13
Carrier Sense Function	OFDM	Normal Use
Radio Interference Prevention Capability	CCK	Normal Use



2.5.2.Operation and Transmitter Power Setting

The EUT was tested while in a continues transmitter/receiver mode under the control of tool which is provided by manufacturer, all the items of transmitter were tested under the power setting as below:

Modulation Technology	Modulation Type	Data Rate (Mbps)	Power Setting
DSSS (802.11b)	DBPSK	1	ANT1: 14 ANT2: 14
	DQPSK	2	
	CCK	5.5/ 11	
OFDM (802.11g)	BPSK	6 / 9	ANT1: 17 ANT2: 17
	QPSK	12 / 18	
	16QAM	24 / 36	
	64QAM	48 / 54	
OFDM (802.11n (HT20))	BPSK	6.5	ANT1: 17 ANT2: 17 ANT1+2: 14
	QPSK	13/19.5	
	16QAM	26/39	
	64QAM	52/58.5/65	
OFDM (802.11n (HT40))	BPSK	13.5	ANT1: 17 ANT2: 17 ANT1+2: 14
	QPSK	27/40.5	
	16QAM	54/81	
	64QAM	108/121.5/135	

Note 1: The black bold modes were selected for test.



2.6. Test Conditions

2.6.1. Environment Condition

Temperature (°C)	23.8
Relative Humidity (%)	45

2.6.2. Power Supply Voltage Fluctuation

During the input supply voltage to the EUT from the external power source is varied by +/- 10%, the output voltage had been confirmed that the fluctuation of power supply to the RF unit of EUT is equal to or less +/- 1%.

Power Supply		External Voltage $V_E(V)$			Internal Voltage V_I		
		V_{EN}	V_{EL}/V_{EH}		$V_{IN}(V)$	$V_{IE}(V)$	Variation of V_I
Type1	Battery	3.87	V_{EL}	3.550	3.3	3.290	0.30%
			V_{EH}	4.257		3.310	0.30%

V_{EN} : Normal Voltage


V_{EL} : V_{EL} is the declared low voltage provided that $V_{EN} \times 90\%$ is less than the declared low voltage, otherwise it is $V_{EN} \times 90\%$

V_{EH} : V_{EH} is the declared high voltage provided that $V_{EN} \times 110\%$ is larger than the declared high voltage, otherwise it is $V_{EN} \times 110\%$


V_{IN} : The voltage supply to the radio unit.

2.7. Test Setup Layout Diagram


2.7.1. General Measurement




2.7.2. Antenna Power Measurement




2.7.3. Radiation Angle of Antenna



2.7.4. Radio Interference Prevention Capability Measurement



2.7.5.Carrier Sense Function





3. Description of Test Items

3.1. Frequency Error

3.1.1. Limits

Within ± 50 ppm.

3.1.2. Test Procedures

According to MIC Notice No.88 Annex 43.

3.1.3. Test Setup Layout

Refer to chapter 2.7.1 in this report.

3.1.4. Test Deviation

There is no deviation with the original standard.

3.1.5. Test Results

Refer to Annex A.1 in this report.



3.2. Occupied Bandwidth

3.2.1. Limits

Item	Type	Limits
Occupied Bandwidth	FHSS	≤83.5MHz
	DSSS	≤26MHz
	OFDM	
	Other	

3.2.2. Test Procedures

According to MIC Notice No.88 Annex 43.

3.2.3. Test Setup Layout

Refer to chapter 2.7.1 in this report.

3.2.4. Test Deviation

There is no deviation with the original standard.

3.2.5. Test Results

Refer to Annex A.2 in this report.

3.3. Unwanted Emission Intensity

3.3.1. Limits

Frequency Range	Limits
30MHz-1000MHz	$\leq 0.25 \mu\text{W}/100\text{kHz}$
1000MHz-2387MHz	$\leq 2.5 \mu\text{W}/\text{MHz}$
2387MHz-2400MHz	$\leq 25 \mu\text{W}/\text{MHz}$
2483.5MHz-2496.5MHz	$\leq 25 \mu\text{W}/\text{MHz}$
2496.5MHz-12500MHz	$\leq 2.5 \mu\text{W}/\text{MHz}$

3.3.2. Test Procedures

According to MIC Notice No.88 Annex 43.

3.3.3. Test Setup Layout

Refer to chapter 2.7.1 in this report.

3.3.4. Test Deviation

There is no deviation with the original standard.

3.3.5. Test Results

Refer to Annex A.3 in this report.

Note1: The spurious emissions mask that displayed on the plots is composed of several frequency ranges below:

Range	Start Freq. (MHz)	Stop Freq. (MHz)	RBW	VBW	Detector Type	Trace Mode	Limit (μW)
1	30	1000	100kHz	100kHz	Peak	Max Hold	0.25
2	1000	2387	1MHz	1MHz	Peak	Max Hold	2.5
3	2387	2400	1MHz	1MHz	Peak	Max Hold	25
4	2400	2483.5	1MHz	1MHz	Peak	Max Hold	20000
5	2483.5	2496.5	1MHz	1MHz	Peak	Max Hold	25
6	2496.5	12500	1MHz	1MHz	Peak	Max Hold	2.5

Note 2: Only the spurious with the minimum margin from the limit line will be displayed in the mark table (The lower window on the test plots).



3.4. Antenna Power Error

3.4.1. Limits

Type	Frequency Range	Limits	
		Antenna Power Density	Antenna Power Error
FHSS	2427-2470.75 MHz	≤ 3 mW/MHz	$\leq +20\%$
	2400-2483.5 MHz (except 2427-2470.75 MHz)	≤ 10 mW/MHz	
DSSS	2400-2483.5 MHz	≤ 10 mW/MHz	
OFDM	2400-2483.5 MHz	≤ 10 mW/MHz (20MHz System) ≤ 5 mW/MHz (40MHz System)	
Other	2400-2483.5 MHz	≤ 10 mW	

3.4.1. Test Procedures

According to MIC Notice No.88 Annex 43..

3.4.2. Test Setup Layout

Refer to chapter 2.7.2 in this report.

3.4.3. Test Deviation

There is no deviation with the original standard.

3.4.4. Test Results

Refer to Annex A.4 in this report.



3.5. Limitation of Collateral Emission of Receiver

3.5.1. Limits

Frequency Range	Limits
30MHz-1000MHz	$\leq 4\text{nW}/100\text{kHz}$
1000MHz-12500MHz	$\leq 20\text{nW}/\text{MHz}$

3.5.2. Test Procedures

According to MIC Notice No.88 Annex 43.

3.5.3. Test Setup Layout

Refer to chapter 2.7.1 in this report.

3.5.4. Test Deviation

There is no deviation with the original standard.

3.5.5. Test Results

Refer to Annex A.5 in this report.

Note 1: The spurious emissions mask that displayed on the plots is composed of several frequency ranges below:

Range	Start Freq. (MHz)	Stop Freq. (MHz)	RBW	VBW	Detector Type	Trace Mode	Limit (nW)
1	30	1000	100kHz	100kHz	Peak	Max Hold	4
2	1000	12500	1MHz	1MHz	Peak	Max Hold	20

Note 2: Only the spurious with the minimum margin from the limit line will be displayed in the mark table (The lower window on the test plots).



3.6.E.I.R.P.

3.6.1.Limits

Type	Frequency Range	Limits
FHSS	2427-2470.75 MHz	6.91-16.91dBm/MHz
	2400-2483.5 MHz (except 2427-2470.75 MHz)	12.14-22.14dBm/MHz
DSSS	2400-2483.5 MHz	12.14-22.14dBm/MHz
OFDM	2400-2483.5 MHz	12.14-22.14dBm/MHz (20MHz System) 9.13-19.13dBm/MHz (40MHz System)
Other	2400-2483.5 MHz	12.14-22.14dBm (GFSK) 10dBm (except GFSK)

Note: This item not be applied to the transmission antenna which has a gain of 2.14dBi or less

3.6.2.Test Procedures

Add antenna gain to the value P which got in chapter 3.4.1 to calculate E.I.R.P. value.

3.6.3.Test Setup Layout

Refer to chapter 2.7.2 in this report.

3.6.4.Test Deviation

There is no deviation with the original standard.

3.6.5.Test Results

Refer to Annex A.6 in this report.



3.7. Radiation Angle of Antenna

3.7.1. Limits

Type	Limits
FHSS	360° /A; (A= E.I.R.P./ 6.91, if A<1; then A=1)
DSSS	360° /A; (A= E.I.R.P./ 12.14, if A<1; then A=1)
OFDM	
Other	

Note: This item not be applied to the transmission antenna which has a gain of 2.14dBi or less

3.7.2. Test Procedures

According to MIC Notice No.88 Annex 43.

3.7.3. Test Setup Layout

Refer to chapter 2.7.3 in this report.

3.7.4. Test Deviation

There is no deviation with the original standard.

3.7.5. Test Results

Refer to Annex A.7 in this report.

Note: Each of these EUT operation modes mentioned in clause 2.2 has been evaluated respectively in pre-scanning, only the data of worst case was included in this report.



3.8. Radio Interference Prevention Capability

3.8.1. Limits

The one automatically to transmit and to receive identification code with the wireless equipment of the wireless station used in the same premises.

3.8.2. Test Procedures

According to MIC Notice No.88 Annex 43.

3.8.3. Test Setup Layout

Refer to chapter 2.7.4 in this report.

3.8.4. Test Deviation

There is no deviation with the original standard.

3.8.5. Test Results

Refer to Annex A.8 in this report.



3.9. Carrier Sense Function

3.9.1. Limits

Type	Requirements		
	BW	Required?	Note
FHSS	-	-	
OFDM	40MHz	Y	
	20MHz	-	When the E.I.R.P. shortage is compensated by the antenna power, the transmitter shall have a carrier sensing function. (Excluding "Other method" transmitters that switch frequencies within 4 seconds from the start of transmission)
DSSS	-	-	
Other	-	-	
Good – EUT stop RF transmission signal after carrier inject to EUT. (On 22.79 +AG-20*log(f) dBm) (AG: dBi; f:MHz) or 100mV/m)			

3.9.2. Test Procedures

According to MIC Notice No.88 Annex 43.

3.9.3. Test Setup Layout

Refer to chapter 2.7.5 in this report.

3.9.4. Test Deviation

There is no deviation with the original standard.

3.9.5. Test Results

Refer to Annex A.9 in this report.

3.10. Construction Protection Confirmation Method

3.10.1.Limits


The high-frequency section and modulation section of the radio equipment except for the antenna system shall not be capable of being opened easily.

3.10.2.Confirmation Method

The RF and modulation portions are protected against illegal modification as following method:

Protected Method	Description
Shield	The RF module use a shield to protect the RF and modulation portions, if the shield is removed, the module will be damaged to the point that it will not work properly.

3.10.3.Reference Documents


Reference Documents	Item
Photo	



Annex A Test Data and Results

A.1. Frequency Error

Channel	Frequency f_c (MHz)	Test Frequency f (MHz)	Frequency Error(ppm)	Verdict
1	2412	2412.0235	9.74	PASS
7	2442	2442.0237	9.71	PASS
13	2472	2472.0236	9.55	PASS






A.2. Occupied Bandwidth

Mode	Channel	Frequency (MHz)	99% OBW(MHz)	Verdict
802.11b	1	2412	13.285	PASS
	7	2442	13.241	PASS
	13	2472	13.231	PASS
802.11g	1	2412	15.109	PASS
	7	2442	14.925	PASS
	13	2472	14.881	PASS
802.11n(HT20)	1	2412	16.199	PASS
	7	2442	15.936	PASS
	13	2472	15.989	PASS
802.11n(HT40)	3	2422	32.848	PASS
	7	2442	33.017	PASS
	11	2462	32.483	PASS




99% Occupied Bandwidth:





REPORT No.: SZ26020168W02



MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL 1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , Guangdong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn


Fax: 86-755-36698525


E-mail: service@morlab.cn



A.3. Unwanted Emission Intensity

Mode	Frequency Range (MHz)	Test Result Value	Limit	Verdict
802.11b/g/n	30~1000	Refer to below plot	0.25μW/100kHz	PASS
	1000~2387		2.5μW/MHz	PASS
	2387~2400		25μW/MHz	PASS
	2483.5~2496.5		25μW/MHz	PASS
	2496.5~12500		2.5μW/MHz	PASS







A.4. Antenna Power Error

ANT1(SISO):

Mode	Channel	Test Value P _t (dBm/ MHz)	Duty Factor	Antenna Power P(dBm/ MHz)	Antenna Power P (mW/ MHz)	Declare Power (mW/ MHz)	Antenna Power Error	Verdict
802.11b	2412	5.90	0.11	6.01	3.99	4.00	-0.25%	PASS
	2442	6.23		6.34	4.31		7.75%	PASS
	2472	6.00		6.11	4.08		2.00%	PASS
802.11g	2412	4.75	0.05	4.80	3.02	3.00	-13.71%	PASS
	2442	5.14		5.19	3.30		-5.71%	PASS
	2472	4.97		5.02	3.18		-9.14%	PASS
802.11n (HT20)	2412	4.23	0.01	4.24	2.65	3.00	-11.67%	PASS
	2442	4.51		4.52	2.83		-5.67%	PASS
	2472	4.57		4.58	2.87		-4.33%	PASS
802.11n (HT40)	2422	1.83	0.02	1.85	1.53	1.50	2.00%	PASS
	2442	1.74		1.76	1.50		0.00%	PASS
	2462	1.83		1.85	1.53		2.00%	PASS

ANT2(SISO):

Mode	Channel	Test Value P _t (dBm/ MHz)	Duty Factor	Antenna Power P(dBm/ MHz)	Antenna Power P (mW/ MHz)	Declare Power (mW/ MHz)	Antenna Power Error	Verdict
802.11b	2412	5.33	0.11	5.44	3.50	4.00	-12.50%	PASS
	2442	5.86		5.97	3.95		-1.25%	PASS
	2472	6.08		6.19	4.16		4.00%	PASS
802.11g	2412	4.77	0.05	4.82	3.03	3.00	-13.43%	PASS
	2442	5.23		5.28	3.37		-3.71%	PASS
	2472	5.64		5.69	3.71		6.00%	PASS
802.11n (HT20)	2412	4.57	0.01	4.58	2.87	3.00	-4.33%	PASS
	2442	5.18		5.19	3.30		10.00%	PASS
	2472	5.27		5.28	3.37		12.33%	PASS
802.11n (HT40)	2422	2.24	0.02	2.26	1.68	1.50	12.00%	PASS
	2442	2.16		2.18	1.65		10.00%	PASS
	2462	2.40		2.42	1.75		16.67%	PASS



REPORT No.: SZ26020168W02

ANT1+ANT2 (MIMO):


Mode	Channel	Antenna Power P (mW/MHz)	Declare Power (mW/MHz)	Antenna Power Error	Verdict
802.11n (HT20)	2412	5.52	6.00	-8.00%	PASS
	2442	6.13		2.17%	PASS
	2472	6.24		4.00%	PASS
802.11n (HT40)	2422	3.21	3.00	7.00%	PASS
	2442	3.15		5.00%	PASS
	2462	3.28		9.33%	PASS




REPORT No.: SZ26020168W02

Duty Cycle


802.11b




802.11g



802.11n(HT20)



802.11n(HT40)



MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL 1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, Guangdong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn


Fax: 86-755-36698525

E-mail: service@morlab.cn



A.5. Limitation of Collateral Emission of Receiver

Mode	Frequency Range (MHz)	Test Result Value	Limit	Verdict
Receive	30~1000	Refer to below plot	4nW/100kHz	PASS
	1000~12500		20nW/MHz	PASS





A.6. E.I.R.P.

ANT1

Mode	Channel	Frequency (MHz)	Measured E.I.R.P. (dBm/MHz)	Limit (dBm/MHz)	Verdict
802.11b	1	2412	7.51	12.14	PASS
	7	2442	7.84		PASS
	13	2472	7.61		PASS
802.11g	1	2412	6.30	12.14	PASS
	7	2442	6.69		PASS
	13	2472	6.52		PASS
802.11n(HT20)	1	2412	5.74	12.14	PASS
	7	2442	6.02		PASS
	13	2472	6.08		PASS
802.11n(HT40)	3	2422	3.35	12.14	PASS
	7	2442	3.26		PASS
	11	2462	3.35		PASS

ANT2

Mode	Channel	Frequency (MHz)	Measured E.I.R.P. (dBm/MHz)	Limit (dBm/MHz)	Verdict
802.11b	1	2412	7.44	13.00	PASS
	7	2442	7.97		PASS
	13	2472	8.19		PASS
802.11g	1	2412	6.82	13.00	PASS
	7	2442	7.28		PASS
	13	2472	7.69		PASS
802.11n(HT20)	1	2412	6.58	13.00	PASS
	7	2442	7.19		PASS
	13	2472	7.28		PASS
802.11n(HT40)	3	2422	4.26	9.99	PASS
	7	2442	4.18		PASS
	11	2462	4.42		PASS



REPORT No.: SZ26020168W02

ANT1+2(MIMO)

Mode	Channel	Frequency (MHz)	Measured E.I.R.P. (dBm/MHz)	Limit (dBm/MHz)	Verdict
802.11n(HT20)	1	2412	9.19	15.01	PASS
	7	2442	9.65		PASS
	13	2472	9.73		PASS
802.11n(HT40)	3	2422	6.84	12.00	PASS
	7	2442	6.75		PASS
	11	2462	6.93		PASS

**A.7. Radiation Angle of Antenna**

Mode	Channel	Frequency (MHz)	3dB Beamwidth (Degree)	Limit (Degree)	Verdict
802.11b	1	2412	94	360	PASS
	7	2442	96		PASS
	13	2472	93		PASS

A.8. Radio Interference Prevention Capability


The identification code of the EUT is: 6e:57:9f:98:79:7c






A.9. Carrier Sense Function

The carrier sense function is good.



(2422MHz)



(2462MHz)



REPORT No.: SZ26020168W02

Notes

1. The report shall have report stamp or our company stamp.
2. The report shall be invalid without all the signatures of the editor and approver.
3. The report shall not be changed.
4. Any objections must be raised to Morlab within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.
5. Conformity declaration:
 - ☒ Morlab issues a statement of conformity based on the corresponding standards (default)
 - ☐ Morlab issues a statement of conformity based on the applicant requirement
6. Use of uncertainty of measurement for decisions on conformity (decision rule):

No decision rule is specified by the testing standard, when comparing the measurement result with the applicable limit according to the specification in that standard. The decisions on conformity are made without applying the measurement uncertainty ("simple acceptance" decision rule).

_____ END OF REPORT _____