


























NTNV-DH5-Ant1-2480-30~1000-PASS




















































































































7.7 INTERFACE PREVENTION FUNCTION

7.7.1 Standard Applicable

According to Item 19 of Article 2 Paragraph 1. The device shall have the function of automatic transmission or reception of identification code.

7.7.2 Test Setup Block Diagram



7.7.3 Test Procedure

1. Set the EUT in the usual operation condition
2. The radio equipment with automatic transmitting function of identification code
 - A. Transmit the assigned identification code from the radio equipment.
 - B. Confirm the identification code received by the demodulator.
3. The radio equipment with automatic receiving function of identification code
 - A. Transmit the assigned identification code from the opposite equipment.
 - B. Confirm that the usual communication is available.
 - C. Transmit the identification code distinct from the assigned one from the opposite equipment.
 - D. Confirm that the radio equipment is stopped or an indication is displayed as the identification code is different.

The identification function shall be recorded.

7.7.4 Summary of Test Results/Plots

All the modes were tested and recorded, the results of the test item are good.

Test Item	Test Result
Transmitting Function of Identification Code	>48 bits
Receiving Function of Identification Code	>48 bits
Mark Address	00:1A:7D:5E:3B:9C
Test Results	Pass

8 APPENDIX PHOTOGRAPHS OF TEST SETUP



--- End of Report ---