

Test Report

Report No. : MTi251222036-0404E2

Date of issue : 2026-02-06

Applicant : Shenzhen Zero Zero Infinity Technology Co.,
Ltd.

Product : AQUA Lighthouse

Model(s) : ZZ-H-2-002

Shenzhen Microtest Co., Ltd.

TEST REPORT

Report No.: MTi251222036-0404E2

Table of contents

1	General Description	4
1.1	Description of the EUT	4
1.2	Description of test modes	4
1.3	Environmental Conditions	6
1.4	Description of support units	6
1.5	Measurement uncertainty	6
2	Summary of Test Result	7
3	Test Facilities and accreditations	8
3.1	Test laboratory	8
4	List of test equipment	9
5	Evaluation Results (Evaluation)	10
5.1	Interference Prevention Function	10
6	Radio Spectrum Matter Test Results (RF)	11
6.1	Tolerance of Frequency	11
6.2	Occupied Bandwidth (99%)	12
6.3	Spread Factor	14
6.4	Antenna Power and Tolerance	15
6.5	Spurious Emission Intensity	16
6.6	Secondary Radiated Emissions	19
6.7	Carrier Sensing 1	21
6.8	Carrier Sensing 2	23
	Photographs of the test setup	25
	Photographs of the EUT	26
7	Appendix A: Frequency Error	27
8	Appendix B: Antenna Power	31
9	Appendix C: Occupied Bandwidth	41
10	Appendix D: Spread Bandwidth	48
11	Appendix E: Spurious Emission of TX	54
12	Appendix F: Spurious Emission of RX	86

TEST REPORT

Report No.: MTi251222036-0404E2

Test Result Certification		
Applicant	Shenzhen Zero Zero Infinity Technology Co., Ltd.	
Applicant Address	4th Floor,Qianhai E-metro Tower,Shenzhen-Hong Kong Cooperation Zone, Shenzhen,China	
Manufacturer	Shenzhen Zero Zero Infinity Technology Co., Ltd.	
Manufacturer Address	4th Floor,Qianhai E-metro Tower,Shenzhen-Hong Kong Cooperation Zone, Shenzhen,China	
Product description		
Product name	AQUA Lighthouse	
Trademark	HOVERAir	
Model name	ZZ-H-2-002	
Series Model(s)	N/A	
Standards	Article 2-1, Item 19-MIC Notice No. 88 Appendix No. 43	
Testing Information		
Date of test	2026-01-14 to 2026-01-27	
Test result	Pass	
Prepared by:	Letter Lan	<i>Letter Lan.</i>
Reviewed by:	David Lee	<i>David. Lee</i>
Approved by:	Lewis Lian	<i>Lewis Lian</i>

TEST REPORT

Report No.: MTi251222036-0404E2

1 General Description

1.1 Description of the EUT

Product name:	AQUA Lighthouse
Model name:	ZZ-H-2-002
Series Model(s):	N/A
Model difference:	N/A
Electrical rating:	Input: Type C DC 5V 1.5A Battery: 3.85VDC 1550mAh
Accessories:	N/A
Hardware version:	RC102_MB_V30
Software version:	0.5.x
Test sample(s) number:	MTi251222036-04-R001
RF specification	
Bluetooth version:	2.35dBi
Operating frequency range:	2412-2472MHz
Channel number:	13 channels for 20MHz bandwidth; 9 channels for 40MHz bandwidth
Modulation type:	802.11b: DSSS(CCK, DQPSK, DBPSK); 802.11g: OFDM(BPSK, QPSK, 16QAM, 64QAM); 802.11n(HT20 and HT40): OFDM (BPSK, QPSK, 16QAM, 64QAM)
Antenna(s) type:	IFA
Antenna(s) gain:	2.35dBi

1.2 Description of test modes

No.	Emission test modes
Mode1	802.11b TX mode
Mode2	802.11g TX mode
Mode3	802.11n20 TX mode
Mode4	802.11n40 TX mode
Mode5	RX mode

1.2.1 Operation channel list

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	6	2437	11	2462
2	2417	7	2442	12	2467
3	2422	8	2447	13	2472

TEST REPORT

Report No.: MTi251222036-0404E2

4	2427	9	2452	/	/
5	2432	10	2457	/	/

Test Channel List Operation Band: 1

Bandwidth (MHz)	Lowest Channel (LCH) (MHz)	Middle Channel (MCH) (MHz)	Highest Channel (HCH) (MHz)
20	2412	2442	2472
40	2422	2442	2462

Note: The test software provided by manufacturer is used to control EUT for working in engineering mode, that enables selectable channel, and capable of continuous transmitting mode.

Test Software: EspRFTTestTool

For power setting, refer to below table.

Mode	LCH	MCH	HCH
802.11b	54	54	54
802.11g	54	54	54
802.11n20	48	48	48
802.11n40	48	48	48

TEST REPORT

Report No.: MTi251222036-0404E2

1.3 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15°C ~ 35°C
Humidity:	20% RH ~ 75% RH
Atmospheric pressure:	98 kPa ~ 101 kPa

Test Conditions		Power Supply (VDC)	Input Voltage to the circuit of RF unit (VDC)
NTNV (V_{normal})	/	3.85	3.3
NTHV ($V_{\text{max.}}$)	+10%	4.235	3.3
NTLV ($V_{\text{min.}}$)	-10%	3.465	3.3

Note: If the fluctuation of input voltage to the circuit of RF unit (except power supply) of test equipment is under $\pm 1\%$, when input voltage from external power supply to the test equipment is fluctuated by $\pm 10\%$: conduct the test with the rated voltage only

1.4 Description of support units

Support equipment list

Description	Model	Serial No.	Manufacturer
/	/	/	/

Support cable list

Description	Length (m)	From	To
/	/	/	/

1.5 Measurement uncertainty

Parameter	Measurement uncertainty
Frequency tolerance	± 10 ppm
Occupied channel bandwidth	± 3 %
RF output power, conducted	± 1 dB
Power Spectral Density, conducted	± 1 dB
Unwanted Emissions, conducted	± 1 dB
All emissions, radiated	± 4.7 dB
Temperature	± 1 °C
Supply voltages	± 1 %
Time	± 1 %

Note: the measurement uncertainty is calculated and correspond to a factor $k=2$ (which provide confidence levels of 95.45%)

TEST REPORT

Report No.: MTi251222036-0404E2

2 Summary of Test Result

No.	Item	Standard	Requirement	Result
1	Tolerance of Frequency	Article 2-1, Item 19-MIC Notice No. 88 Appendix No. 43	Article 2-1, Item 19	Pass
2	Occupied Bandwidth (99%)	Article 2-1, Item 19-MIC Notice No. 88 Appendix No. 43	Article 2-1, Item 19	Pass
3	Spread Factor	Article 2-1, Item 19-MIC Notice No. 88 Appendix No. 43	Article 2-1, Item 19	Pass
4	Antenna Power and Tolerance	Article 2-1, Item 19-MIC Notice No. 88 Appendix No. 43	Article 2-1, Item 19	Pass
5	Spurious Emission Intensity	Article 2-1, Item 19-MIC Notice No. 88 Appendix No. 43	Article 2-1, Item 19	Pass
6	Secondary Radiated Emissions	Article 2-1, Item 19-MIC Notice No. 88 Appendix No. 43	Article 2-1, Item 19	Pass
7	Carrier Sensing 1	Article 2-1, Item 19-MIC Notice No. 88 Appendix No. 43	Article 2-1, Item 19	Pass
8	Carrier Sensing 2	Article 2-1, Item 19-MIC Notice No. 88 Appendix No. 43	Article 2-1, Item 19	Pass

Notes:

N/A means not applicable

TEST REPORT

Report No.: MTi251222036-0404E2

3 Test Facilities and accreditations

3.1 Test laboratory

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No.7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573
IC Registration No.:	21760
CABID:	CN0093

TEST REPORT

Report No.: MTi251222036-0404E2

4 List of test equipment

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due	Calibration method
Tolerance of Frequency Occupied Bandwidth (99%) Spread Factor Antenna Power and Tolerance Spurious Emission Intensity Secondary Radiated Emissions Carrier Sensing 1 Carrier Sensing 2							
1	Wideband Radio Communication Tester	Rohde&schwarz	CMW500	149155	2025-03-18	2026-03-17	C
2	ESG Series Analog Ssignal Generator	Agilent	E4421B	GB40051240	2025-03-14	2026-03-13	C
3	PXA Signal Analyzer	Agilent	N9030A	MY51350296	2025-03-14	2026-03-13	C
4	Synthesized Sweeper	Agilent	83752A	3610A01957	2025-03-14	2026-03-13	C
5	MXA Signal Analyzer	Agilent	N9020A	MY50143483	2025-03-14	2026-03-13	C
6	RF Control Unit	Tonscend	JS0806-1	19D8060152	2025-03-18	2026-03-17	C
7	Band Reject Filter Group	Tonscend	JS0806-F	19D8060160	2025-03-14	2026-03-13	C
8	ESG Vector Signal Generator	Agilent	N5182A	MY50143762	2025-03-14	2026-03-13	C
9	DC Power Supply	Agilent	E3632A	MY40027695	2025-03-18	2026-03-17	C
10	RF Test System	Tonscend	JS1120-3 Test System Ver. V3.5.39	/	/	/	/

Remark:

(a) Calibration conducted by the National institute of information and Communications Technology (NICT) in Japan (hereinafter referred to as "NICT") or a designated calibration agency under Article 102-18 paragraph (1) in JRL.

(b) Correction conducted pursuant to the provisions of Article 135 or Article 144 of the Measurement Act (Act No. 51 of 1992).

(c) Calibration conducted in countries except Japan, which shall be equivalent to the calibration conducted by the NICT or a designated calibration agency under Article 102-18 paragraph (1).

(d) Calibration, etc, conducted by using measuring instruments and other equipment listed in the right column of appended table No. 3, which shall have been given any type of calibration, etc. listed above from (a) to (c)

From JRL Article 24-2, paragraph 4, Item 2

TEST REPORT

Report No.: MTi251222036-0404E2

5 Evaluation Results (Evaluation)

5.1 Interference Prevention Function

Test Requirement:	The EUT shall support one of the following functions: - Automatic identification transmission - Automatic identification reception
Test Method:	Notification No.88 of MIC, 2004
Procedure:	(1) For EUTs capable of automatically transmitting identification data a. Transmit identification data from EUT to Demodulator b. Confirm identification data is correctly received by Demodulator (2) For EUTs capable of automatically receiving identification data a. Transmit identification data from Link Partner to EUT b. Confirm communication link is established c. Link Partner shall respond by transmitting different identification data back to the EUT d. Confirm EUT stops transmitting, or confirm EUT recognizes that the two identification data are different

5.1.1 Conclusion:

The detected ID of the device is below: 3C:84:27:27:4E:B4

Test result: The device meet the requirements
PASS

TEST REPORT

Report No.: MTi251222036-0404E2

6 Radio Spectrum Matter Test Results (RF)


6.1 Tolerance of Frequency

Test Requirement:	Article 2-1, Item 19	
Test Limit:	±50ppm or less.	
Test Method:	Notification No.88 of MIC, 2004	
Procedure:	Center frequency:	Test frequency
	Span:	2 times channel bandwidth
	RBW:	100 kHz (Modulation ON)
	VBW:	100 kHz (Modulation ON)
	Sweep data points:	1001 or greater
	Sweep time:	Auto
	Detector mode:	Positive peak
	Indication mode:	Max hold
If the EUT cannot transmit in un-modulated mode then modulated mode measurements can be made, as follows: If the spectrum observed using the spectrum analyzer has a characteristic dip at the center, then the center frequency of the dip shall be regarded as the center frequency of the carrier.		

6.1.1 E.U.T. Operation:

Operating Environment:					
Temperature:	24.3 °C	Humidity:	49.7 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4				
Final test mode:	Mode1, Mode2, Mode3, Mode4				

6.1.2 Test Setup Diagram:



6.1.3 Test Data:

Please Refer to Appendix for Details.

TEST REPORT


Report No.: MTi251222036-0404E2

6.2 Occupied Bandwidth (99%)

Test Requirement:	Article 2-1, Item 19																		
Test Limit:	For OFDM Modulation: The measured bandwidth at the low and high channels shall meet the following requirements: - The lowest frequency of the measured bandwidth shall not be less than 2400 MHz - The highest frequency of the measured bandwidth shall not be greater than 2483.5 MHz [Occupied Bandwidth] 40 MHz or less For DSSS or other modulation: The measured bandwidth at the low and high channels shall meet the following requirements: - The lowest frequency of the measured bandwidth shall not be less than 2400 MHz - The highest frequency of the measured bandwidth shall not be greater than 2483.5 MHz [Occupied Bandwidth] 26 MHz or less																		
Test Method:	Notification No.88 of MIC, 2004																		
Procedure:	<table border="1"> <tr> <td>Center Frequency:</td><td>Test frequency</td></tr> <tr> <td>Span:</td><td>2 - 3.5 times the technical standard</td></tr> <tr> <td>RBW:</td><td>Within 3% of the technical standard</td></tr> <tr> <td>VBW:</td><td>Same as RBW</td></tr> <tr> <td>Sweep time:</td><td>Auto</td></tr> <tr> <td>Sweep data points:</td><td>1001 or greater</td></tr> <tr> <td>Detector mode:</td><td>Positive peak</td></tr> <tr> <td>Indication mode:</td><td>Max hold</td></tr> <tr> <td>BW setting:</td><td>99%</td></tr> </table> (1) Measure the signal bandwidth using a spectrum analyzer (2) For multiple antenna systems: a) Each antenna shall be individually measured b) If the measured occupied bandwidth for any antenna exceeds [(Occupied Bandwidth Limit) – 100kHz] then, in addition, the occupied bandwidth shall be measured with all antennas combined – see diagram below:	Center Frequency:	Test frequency	Span:	2 - 3.5 times the technical standard	RBW:	Within 3% of the technical standard	VBW:	Same as RBW	Sweep time:	Auto	Sweep data points:	1001 or greater	Detector mode:	Positive peak	Indication mode:	Max hold	BW setting:	99%
Center Frequency:	Test frequency																		
Span:	2 - 3.5 times the technical standard																		
RBW:	Within 3% of the technical standard																		
VBW:	Same as RBW																		
Sweep time:	Auto																		
Sweep data points:	1001 or greater																		
Detector mode:	Positive peak																		
Indication mode:	Max hold																		
BW setting:	99%																		

TEST REPORT

Report No.: MTi251222036-0404E2



6.2.1 E.U.T. Operation:


Operating Environment:

Temperature:	24.3 °C	Humidity:	49.7 %	Atmospheric Pressure:	101 kPa
--------------	---------	-----------	--------	-----------------------	---------

Pre test mode:	Mode1, Mode2, Mode3, Mode4
----------------	----------------------------

Final test mode:	Mode1, Mode2, Mode3, Mode4
------------------	----------------------------

6.2.2 Test Setup Diagram:



6.2.3 Test Data:

Please Refer to Appendix for Details.

TEST REPORT

Report No.: MTi251222036-0404E2


6.3 Spread Factor

Test Requirement:	Article 2-1, Item 19
Test Limit:	The spread factor should be more than 5.
Test Method:	The test method is the same as spread bandwidth.
Procedure:	The test procedure is the same as spread bandwidth.

6.3.1 E.U.T. Operation:

Operating Environment:					
Temperature:	24.3 °C	Humidity:	49.7 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1				
Final test mode:	Mode1				

6.3.2 Test Setup Diagram:



6.3.3 Test Data:

Please Refer to Appendix for Details.

TEST REPORT

Report No.: MTi251222036-0404E2

6.4 Antenna Power and Tolerance


Test Requirement:	Article 2-1, Item 19
Test Limit:	Antenna Power: $26\text{MHz} < \text{OBW} \leq 40\text{MHz}$: 5 mW/MHz or less Tolerance: +20% or less EIRP: 19.13dBm/MHz Antenna Power: $\text{OBW} \leq 26\text{MHz}$: 10mW/MHz or less Tolerance: +20% or less EIRP: 12.14dBm/MHz
Test Method:	Notification No.88 of MIC, 2004
Procedure:	Connect high frequency power meter to the RF output of the EUT with a suitable attenuator and measure the total electric power.



6.4.1 E.U.T. Operation:

Operating Environment:					
Temperature:	24.3 °C	Humidity:	49.7 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4				
Final test mode:	Mode1, Mode2, Mode3, Mode4				

6.4.2 Test Setup Diagram:



6.4.3 Test Data:

Please Refer to Appendix for Details.

TEST REPORT

Report No.: MTi251222036-0404E2

6.5 Spurious Emission Intensity

Test Requirement:	Article 2-1, Item 19																																															
Test Limit:	(1) Below 2387 MHz: 2.5 μ W (-26 dBm)/MHz or less (2) 2387 to 2400 MHz: 25.0 μ W (-16 dBm)/MHz or less (3) 2483.5 to 2496.5 MHz: 25.0 μ W (-16 dBm)/MHz or less (4) Over 2496.5 MHz: 2.5 μ W (-26 dBm)/MHz or less																																															
Test Method:	Notification No.88 of MIC, 2004																																															
Procedure:	<table><tr><td colspan="2">[Setting 1]</td></tr><tr><td>Frequency range:</td><td>(see Note 1)</td></tr><tr><td>RBW:</td><td>1 MHz</td></tr><tr><td>VBW:</td><td>1 MHz</td></tr><tr><td>Sweep time:</td><td>Minimum time required to make an accurate measurement</td></tr><tr><td>Sweep Data Points:</td><td>1001 or greater</td></tr><tr><td>Detector mode:</td><td>Positive peak</td></tr><tr><td>Indication mode:</td><td>Max hold (see Note 2)</td></tr><tr><td>Note 1:</td><td>Measurement range shall be 30 MHz to 12.5 GHz, except for the following cases: -FHSS, FHSS+DSSS, FHSS+OFDM:2374 MHz to 2509.5 MHz -Other than FHSS, FHSS+DSSS, FHSS+OFDM: 2400 MHz to 2483.5 MHz</td></tr><tr><td>Note 2:</td><td>Sweep shall be repeated until the max hold waveform is stable.</td></tr><tr><td colspan="2">[Setting 2]</td></tr><tr><td>Center frequency:</td><td>Frequency of spurious emission found using [Setting 1]</td></tr><tr><td>Span:</td><td>0 Hz</td></tr><tr><td>RBW:</td><td>1 MHz</td></tr><tr><td>VBW:</td><td>1 MHz</td></tr><tr><td>Sweep time:</td><td>Minimum time required to make an accurate measurement. For burst type (intermittent) spurious emissions, sweep time shall be greater than one burst interval</td></tr><tr><td>Sweep Data Points:</td><td>1001 or greater</td></tr><tr><td>Detector mode:</td><td>Sample</td></tr><tr><td colspan="2">[Setting 3]</td></tr><tr><td>Frequency range:</td><td>2374 MHz to 2400 MHz 2483.5 MHz to 2509.5 MHz</td></tr><tr><td>RBW:</td><td>30 kHz</td></tr><tr><td>VBW:</td><td>30 kHz</td></tr><tr><td>Sweep time:</td><td>Minimum time required to make an accurate measurement.</td></tr></table>		[Setting 1]		Frequency range:	(see Note 1)	RBW:	1 MHz	VBW:	1 MHz	Sweep time:	Minimum time required to make an accurate measurement	Sweep Data Points:	1001 or greater	Detector mode:	Positive peak	Indication mode:	Max hold (see Note 2)	Note 1:	Measurement range shall be 30 MHz to 12.5 GHz, except for the following cases: -FHSS, FHSS+DSSS, FHSS+OFDM:2374 MHz to 2509.5 MHz -Other than FHSS, FHSS+DSSS, FHSS+OFDM: 2400 MHz to 2483.5 MHz	Note 2:	Sweep shall be repeated until the max hold waveform is stable.	[Setting 2]		Center frequency:	Frequency of spurious emission found using [Setting 1]	Span:	0 Hz	RBW:	1 MHz	VBW:	1 MHz	Sweep time:	Minimum time required to make an accurate measurement. For burst type (intermittent) spurious emissions, sweep time shall be greater than one burst interval	Sweep Data Points:	1001 or greater	Detector mode:	Sample	[Setting 3]		Frequency range:	2374 MHz to 2400 MHz 2483.5 MHz to 2509.5 MHz	RBW:	30 kHz	VBW:	30 kHz	Sweep time:	Minimum time required to make an accurate measurement.
[Setting 1]																																																
Frequency range:	(see Note 1)																																															
RBW:	1 MHz																																															
VBW:	1 MHz																																															
Sweep time:	Minimum time required to make an accurate measurement																																															
Sweep Data Points:	1001 or greater																																															
Detector mode:	Positive peak																																															
Indication mode:	Max hold (see Note 2)																																															
Note 1:	Measurement range shall be 30 MHz to 12.5 GHz, except for the following cases: -FHSS, FHSS+DSSS, FHSS+OFDM:2374 MHz to 2509.5 MHz -Other than FHSS, FHSS+DSSS, FHSS+OFDM: 2400 MHz to 2483.5 MHz																																															
Note 2:	Sweep shall be repeated until the max hold waveform is stable.																																															
[Setting 2]																																																
Center frequency:	Frequency of spurious emission found using [Setting 1]																																															
Span:	0 Hz																																															
RBW:	1 MHz																																															
VBW:	1 MHz																																															
Sweep time:	Minimum time required to make an accurate measurement. For burst type (intermittent) spurious emissions, sweep time shall be greater than one burst interval																																															
Sweep Data Points:	1001 or greater																																															
Detector mode:	Sample																																															
[Setting 3]																																																
Frequency range:	2374 MHz to 2400 MHz 2483.5 MHz to 2509.5 MHz																																															
RBW:	30 kHz																																															
VBW:	30 kHz																																															
Sweep time:	Minimum time required to make an accurate measurement.																																															

TEST REPORT

Report No.: MTi251222036-0404E2

Sweep data points:	1001 or greater
Detector mode:	Positive peak
Indication mode:	Max hold

(1) After configuring the spectrum analyzer to [Setting 1], search for spurious emissions from 30 MHz to 12.5 GHz. If the sweep range does not cover the required measurement frequency range then the measurement range will need to be divided into sufficient sections of size [RBW x Sweep Data Points]. If spurious emissions greater than [Limit - 3dB] are found, then more detailed measurements are required, go to step (2)

(2) Configure the spectrum analyzer using [Setting 2] and measure the average signal amplitude.
If the spurious emission is burst type (intermittent), then the average value shall not include signal OFF time.
If spurious emissions ranging from 30 MHz to 2374 MHz and from 2509.5MHz to 12.5GHz are over the limit, then the test result is Fail.
If spurious emissions ranging from 2374 MHz to 2400 MHz and from 2483.5 MHz to 2509.5 MHz are over the limit, then further detailed measurements are required, go to step (3)

(3) In the following cases, measure the spurious emissions using [Setting 3]
- Case1: FHSS, FHSS+DSSS, FHSS+OFDM
- Case2: Other than FHSS, FHSS+DSSS, FHSS+OFDM, and the spurious emissions in step (2) are over the limit

(4) Calculate the spurious emission value (Calculated Value) using following the formula below:
Calculated Value = (Measured Value using (3) + 15.2dB)
Note: 15.2dB adjustment is derived from the Conversion Factor of RBW
Conversion Factor of RBW = 10 x Log (Reference Bandwidth / RBW of measurement) = 15.2 [dB] Where: Reference Bandwidth = 1 MHz
RBW of measurement = 30 kHz

(5) If the calculated value using (4) is over the Limit (section 6.7), go to (6)

(6) Configure the spectrum analyzer to [Setting 3] then make the following changes: Frequency: Frequency of spurious emission
Span: 1 MHz

(7) After sweep, send the span data set to the PC

(8) Convert measured data from dBm to Watts

(9) Sum all the data using the formula below. If the sum is within the limit, the test result is Pass, otherwise, Fail

$$P_s = \left(\sum_{i=1}^n E_i \right) \times \frac{S_w}{RBW \times k \times n}$$

Ps: Sum (Watts)

Ei: Measured value at each point in the Span (Watts) Sw: Span (1MHz)

n: Number of measurement points in the Span

k: Correction factor for Equivalent Noise Bandwidth, specific to each spectrum analyzer, check the instrument user guide

RBW: Resolution Bandwidth (MHz).

TEST REPORT

Report No.: MTi251222036-0404E2

	(10) If the EUT has multiple antennas, measure the spurious emission from each individual antenna using steps (1) through (9)
	(11) Convert the individual antenna spurious level measurements (step (10)) from dB to absolute values
	(12) Combine (sum) the absolute values of the spurious measurements at each frequency for each antenna (to create a single composite spectrum of spurious emissions)
	(13) Ensure that the composite spectrum does not exceed the Limit defined in 6.7 (Technical Standard)
	(14) Configuring the spectrum analyzer using [Setting 3] and measure the spurious emissions with all the antennas electrically combined

6.5.1 E.U.T. Operation:


Operating Environment:

Temperature:	24.3 °C	Humidity:	49.7 %	Atmospheric Pressure:	101 kPa
--------------	---------	-----------	--------	-----------------------	---------

Pre test mode:	Mode1, Mode2, Mode3, Mode4
----------------	----------------------------

Final test mode:	Mode1, Mode2, Mode3, Mode4
------------------	----------------------------

6.5.2 Test Setup Diagram:



6.5.3 Test Data:

Please Refer to Appendix for Details.

TEST REPORT

Report No.: MTi251222036-0404E2

6.6 Secondary Radiated Emissions

Test Requirement:	Article 2-1, Item 19		
Test Limit:	(1) Below 1 GHz: 4 nW (-54dBm) or less (2) Above 1 GHz: 20 nW (-47dBm) or less		
Test Method:	Notification No.88 of MIC, 2004		
Procedure:	[Setting 1]		
	Frequency range:	30 MHz ~ 12.5 GHz	
	RBW:	Below 1 GHz:100 kHz	
		Above 1 GHz:1 MHz	
	VBW:	Below 1 GHz:100 kHz	
		Above 1 GHz:1 MHz	
	Sweep time:	Auto	
	Sweep data points:	1001 or greater	
	Detector mode:	Positive peak	
	Indication mode:	Max hold	
	[Setting 2]		
	Center Frequency:	Frequency of spurious emission found using [Setting 1]	
	Span:	0 Hz	
	RBW:	Below 1 GHz:100 kHz	
		Above 1 GHz:1 MHz	
	VBW:	Below 1 GHz:100 kHz	
		Above 1 GHz:1 MHz	
	Sweep time:	Auto	
	Sweep data points:	1001 or greater	
	Detector mode:	Sample	

6.6.1 E.U.T. Operation:


Operating Environment:					
Temperature:	24.3 °C	Humidity:	49.7 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode5				

TEST REPORT

Report No.: MTi251222036-0404E2

Final test mode:	Mode5
------------------	-------

6.6.2 Test Setup Diagram:



6.6.3 Test Data:

Please Refer to Appendix for Details.

TEST REPORT

Report No.: MTi251222036-0404E2

6.7 Carrier Sensing 1

Test Requirement:	Article 2-1, Item 19	
Test Method:	Notification No.88 of MIC, 2004	
Procedure:	Signal Generator Settings	
	[Setting 1]	
	Output frequency:	Center of test frequency
	Modulation:	Un-modulated, see note
	Output level:	The required level at the EUT antenna input, as defined by the applicant
	Note:	
	If the EUT's carrier sensing cannot function with an un-modulated signal at the center of the test frequency, then the un-modulated signal can be moved away from the center.	
	Spectrum Analyzer Settings	
	[Setting 2]	
	Frequency:	Center of test frequency
	Span:	50 MHz
	RBW:	1 MHz
	VBW:	1 MHz
	Trigger:	Free running
	Detector:	Positive peak
	Testing without a Link Partner	
	(1) Set the spectrum analyzer to [Setting 2]	
	(2) With the signal generator OFF, set the EUT to transmit mode and confirm that the transmission meets the following characteristics:	
	a.Modulation:OFDM	
	b.Occupied bandwidth:over 26 MHz	
	(3) Set the EUT to receive mode	
	(4) First, set the signal generator output ON, then set the EUT to transmit mode and confirm that the EUT does NOT transmit a signal with the following characteristics:	
	a.Modulation:OFDM	
	b.Occupied bandwidth:over 26 MHz	
	Testing with a Link Partner	
	(1) Set the spectrum analyzer to [Setting 2]	
	(2) Set the signal generator output to OFF	
	(3) After establishing a connection between the EUT and the Link Partner, set the EUT to transmit mode and confirm that the transmission meets the following characteristics:	
	a.Modulation:OFDM	
	b.Occupied bandwidth:over 26 MHz	
	(4) Set the EUT to receive mode	
	(5) Set the signal generator output ON, then set the EUT to transmit mode and confirm that the EUT does NOT transmit a signal with the following characteristics:	
	a.Modulation:OFDM	
	b.Occupied bandwidth:over 26 MHz	

6.7.1 E.U.T. Operation:


Operating Environment:

TEST REPORT

Report No.: MTi251222036-0404E2

Temperature:	24.3 °C	Humidity:	49.7 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode5				
Final test mode:	Mode5				

6.7.2 Test Setup Diagram:



6.7.3 Test Data:

Please Refer to Appendix for Details.

TEST REPORT

Report No.: MTi251222036-0404E2

6.8 Carrier Sensing 2

Test Requirement:	Article 2-1, Item 19	
Test Method:	Notification No.88 of MIC, 2004	
Procedure:	Signal Generator Settings	
	[Setting 1]	
	Output frequency:	Center of test frequency
	Modulation:	Un-modulated, see note
	Output level:	The required level at the EUT antenna input, as defined by the applicant
	Note:	
	If the EUT's carrier sensing cannot function with an un-modulated signal at the center of the test frequency, then the un-modulated signal can be moved away from the center.	
	Spectrum Analyzer Settings	
	[Setting 2]	
	Frequency:	Center of test frequency
	Span:	50 MHz
	RBW:	1 MHz
	VBW:	1 MHz
	Trigger:	Free running
	Detector:	Positive peak
	Testing without a Link Partner	
	(1) Set the spectrum analyzer to [Setting 2]	
	(2) With the signal generator OFF, set the EUT to transmit mode and confirm that the transmission meets the following characteristics:	
	a.Modulation:OFDM	
	b.Occupied bandwidth:over 26 MHz	
	(3) Set the EUT to receive mode	
	(4) First, set the signal generator output ON, then set the EUT to transmit mode and confirm that the EUT does NOT transmit a signal with the following characteristics:	
	a.Modulation:OFDM	
	b.Occupied bandwidth:over 26 MHz	
	Testing with a Link Partner	
	(1) Set the spectrum analyzer to [Setting 2]	
	(2) Set the signal generator output to OFF	
	(3) After establishing a connection between the EUT and the Link Partner, set the EUT to transmit mode and confirm that the transmission meets the following characteristics:	
	a.Modulation:OFDM	
	b.Occupied bandwidth:over 26 MHz	
	(4) Set the EUT to receive mode	
	(5) Set the signal generator output ON, then set the EUT to transmit mode and confirm that the EUT does NOT transmit a signal with the following characteristics:	
	a.Modulation:OFDM	
	b.Occupied bandwidth:over 26 MHz	

6.8.1 E.U.T. Operation:


Operating Environment:

TEST REPORT

Report No.: MTi251222036-0404E2

Temperature:	24.3 °C	Humidity:	49.7 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4				
Final test mode:	Mode1, Mode2, Mode3, Mode4				

6.8.2 Test Setup Diagram:



6.8.3 Test Data:

Please Refer to Appendix for Details.

TEST REPORT

Report No.: MTi251222036-0404E2

Photographs of the test setup

Refer to Appendix - Test Setup Photos

TEST REPORT

Report No.: MTi251222036-0404E2

Photographs of the EUT

Refer to Appendix - EUT Photos

TEST REPORT

Report No.: MTi251222036-0404E2

Appendix

7 Appendix A: Frequency Error


7.1.1 Test Result

TestCondition	TestMode	Antenna	Frequency[MHz]	CenterFreq [MHz]	Result[ppm]	Limit[ppm]	Verdict
NTNV	11B	Ant1	2412	2412.027	11.19403	±50	PASS
			2442	2442.027	11.05651	±50	PASS
			2472	2472.027	10.92233	±50	PASS
	11N40SI SO	Ant1	2422	2422.026	10.73493	±50	PASS
			2442	2442.026	10.64701	±50	PASS
			2462	2462.027	10.96669	±50	PASS

TEST REPORT

Report No.: MTi251222036-0404E2


7.1.2 Test Graphs




TEST REPORT

Report No.: MTi251222036-0404E2

NTNV_11B_Ant1_2472




NTNV_11N40SISO_Ant1_2422



TEST REPORT

Report No.: MTi251222036-0404E2



TEST REPORT

Report No.: MTi251222036-0404E2

8 Appendix B: Antenna Power

Antenna Power							
Test Condition	Test Mode	Antenna	Frequency[MHz]	Result(dBm/MHz)	Result(mW/MHz)	Limit(mW/MHz)	Verdict
NTNV	11B	Ant1	2412	-3.43	0.4539	≤10	PASS
			2442	-3.53	0.4436	≤10	PASS
			2472	-3.75	0.4217	≤10	PASS
	11G	Ant1	2412	-4.91	0.3228	≤10	PASS
			2442	-5.13	0.3069	≤10	PASS
			2472	-5.66	0.2716	≤10	PASS
	11N20SISO	Ant1	2412	-6.00	0.2512	≤10	PASS
			2442	-5.74	0.2667	≤10	PASS
			2472	-6.09	0.2460	≤10	PASS
	11N40SISO	Ant1	2422	-8.02	0.1578	≤5	PASS
			2442	-8.30	0.1479	≤5	PASS
			2462	-8.41	0.1442	≤5	PASS

Tolerance								
Test Condition	Test Mode	Antenna	Frequency[MHz]	Power (mW/MHz)	RatedPower (mW/MHz)	Result (%)	Limit (%)	Verdict
NTNV	11B	Ant1	2412	0.4539	0.5	-9.21	≤20	PASS
			2442	0.4603	0.5	-11.28	≤20	PASS
			2472	0.4217	0.5	-15.66	≤20	PASS
	11G	Ant1	2412	0.3548	0.5	-35.43	≤20	PASS
			2442	0.3381	0.5	-38.62	≤20	PASS
			2472	0.2992	0.5	-45.67	≤20	PASS
	11N20SISO	Ant1	2412	0.2979	0.5	-49.76	≤20	PASS
			2442	0.3162	0.5	-46.66	≤20	PASS
			2472	0.2911	0.5	-50.79	≤20	PASS
	11N40SISO	Ant1	2422	0.1603	0.5	-68.45	≤20	PASS
			2442	0.1503	0.5	-70.42	≤20	PASS
			2462	0.1466	0.5	-71.16	≤20	PASS

EIRP							
Test Condition	Test Mode	Antenna	Frequency[MHz/MHz]	Result(dBm/MHz)	EIRP(dBm/MHz)	Limit(dBm/MHz)	Verdict
NTNV	11B	Ant1	2412	-3.43	-1.08	≤12.14	PASS
			2442	-3.37	-1.18	≤12.14	PASS
			2472	-3.75	-1.40	≤12.14	PASS
	11G	Ant1	2412	-4.50	-2.56	≤12.14	PASS
			2442	-4.71	-2.78	≤12.14	PASS
			2472	-5.24	-3.31	≤12.14	PASS
	11N20SISO	Ant1	2412	-5.26	-3.65	≤12.14	PASS
			2442	-5.00	-3.39	≤12.14	PASS
			2472	-5.36	-3.74	≤12.14	PASS
	11N40SISO	Ant1	2422	-7.95	-5.67	≤9.13	PASS
			2442	-8.23	-5.95	≤9.13	PASS
			2462	-8.34	-6.06	≤9.13	PASS


Note: 1. Antenna gain is 2.35dBi

2. EIRP= Result + antenna gain

TEST REPORT

Report No.: MTi251222036-0404E2


8.1.1 Test Graphs




TEST REPORT

Report No.: MTi251222036-0404E2

NTNV_11B_Ant1_2442




NTNV_11B_Ant1_2472



TEST REPORT


Report No.: MTi251222036-0404E2




TEST REPORT

Report No.: MTi251222036-0404E2

NTNV_11G_Ant1_2442




NTNV_11G_Ant1_2472




TEST REPORT

Report No.: MTi251222036-0404E2



TEST REPORT

Report No.: MTi251222036-0404E2



TEST REPORT

Report No.: MTi251222036-0404E2




NTNV 11N40SISO Ant1 2422



TEST REPORT

Report No.: MTi251222036-0404E2



TEST REPORT

Report No.: MTi251222036-0404E2



TEST REPORT

Report No.: MTi251222036-0404E2

9 Appendix C: Occupied Bandwidth

9.1.1 Test Result

TestCondition	TestMode	Antenna	Frequency[MHz]	Result [MHz]	Limit [MHz]	Verdict
NTNV	11B	Ant1	2412	12.989	≤26	PASS
			2442	12.921	≤26	PASS
			2472	12.922	≤26	PASS
	11G	Ant1	2412	16.529	≤26	PASS
			2442	16.475	≤26	PASS
			2472	16.478	≤26	PASS
	11N20SISO	Ant1	2412	17.417	≤26	PASS
			2442	17.387	≤26	PASS
			2472	17.372	≤26	PASS
	11N40SISO	Ant1	2422	35.794	26-40	PASS
			2442	35.708	26-40	PASS
			2462	35.847	26-40	PASS

TEST REPORT

Report No.: MTi251222036-0404E2


9.1.2 Test Graphs




TEST REPORT

Report No.: MTi251222036-0404E2

NTNV_11B_Ant1_2472




NTNV_11G_Ant1_2412




TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11G Ant1 2442



NTNV 11G Ant1 2472




TEST REPORT

Report No.: MTI251222036-0404E2



TEST REPORT

Report No.: MTi251222036-0404E2



TEST REPORT

Report No.: MTi251222036-0404E2



TEST REPORT


Report No.: MTi251222036-0404E2

10 Appendix D: Spread Bandwidth

10.1.1 Test Result

TestCondition	TestMode	Antenna	Frequency[MHz]	Result [MHz]
NTNV	11B	Ant1	2412	8.903
			2442	8.916
			2472	8.900
	11G	Ant1	2412	14.471
			2442	14.313
			2472	14.478
	11N20SISO	Ant1	2412	15.240
			2442	15.204
			2472	15.218
	11N40SISO	Ant1	2422	30.787
			2442	30.592
			2462	30.752


10.1.2 Test Graphs




TEST REPORT

Report No.: MTI251222036-0404E2

NTNV_11B_Ant1_2472




NTNV_11G_Ant1_2412




TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11G Ant1 2442



NTNV 11G Ant1 2472



TEST REPORT

Report No.: MTi251222036-0404E2




TEST REPORT

Report No.: MTi251222036-0404E2



TEST REPORT

Report No.: MTI251222036-0404E2



TEST REPORT

Report No.: MTi251222036-0404E2

11 Appendix E: Spurious Emission of TX

11.1.1 Test Result

TestCondition	TestMode	Antenna	Frequency[MHz]	Freq.Range [MHz]	Result [dBm]	Limit [dBm]	Result [μW]	Limit [μW]	Verdict
NTNV	11B	Ant1	2412	30~1000	-51.52	≤-26	0.00705	≤2.5	PASS
				1000~2387	-50.50	≤-26	0.00891	≤2.5	PASS
				2387~2400	-38.36	≤-16	0.14588	≤25	PASS
				2483.5~2496.5	-38.86	≤-16	0.13002	≤25	PASS
				2496.5~13000	-34.14	≤-26	0.38548	≤2.5	PASS
			2442	30~1000	-52.23	≤-26	0.00598	≤2.5	PASS
				1000~2387	-50.02	≤-26	0.00995	≤2.5	PASS
				2387~2400	-39.20	≤-16	0.12023	≤25	PASS
				2483.5~2496.5	-39.70	≤-16	0.10715	≤25	PASS
				2496.5~13000	-32.39	≤-26	0.57677	≤2.5	PASS
			2472	30~1000	-51.36	≤-26	0.00731	≤2.5	PASS
				1000~2387	-50.44	≤-26	0.00904	≤2.5	PASS
				2387~2400	-38.81	≤-16	0.13152	≤25	PASS
				2483.5~2496.5	-38.25	≤-16	0.14962	≤25	PASS
				2496.5~13000	-32.03	≤-26	0.62661	≤2.5	PASS
	11G	Ant1	2412	30~1000	-51.52	≤-26	0.00705	≤2.5	PASS
				1000~2387	-50.20	≤-26	0.00955	≤2.5	PASS
				2387~2400	-30.82	≤-16	0.82794	≤25	PASS
				2483.5~2496.5	-38.75	≤-16	0.13335	≤25	PASS
				2496.5~13000	-37.28	≤-26	0.18707	≤2.5	PASS
			2442	30~1000	-51.86	≤-26	0.00652	≤2.5	PASS
				1000~2387	-51.01	≤-26	0.00793	≤2.5	PASS
				2387~2400	-38.82	≤-16	0.13122	≤25	PASS
				2483.5~2496.5	-40.06	≤-16	0.09863	≤25	PASS
				2496.5~13000	-36.08	≤-26	0.24660	≤2.5	PASS
			2472	30~1000	-51.49	≤-26	0.00710	≤2.5	PASS
				1000~2387	-50.42	≤-26	0.00908	≤2.5	PASS
				2387~2400	-38.60	≤-16	0.13804	≤25	PASS

TEST REPORT


Report No.: MTi251222036-0404E2

				2483.5~2496.5	-28.48	≤-16	1.4190 6	≤25	PASS
				2496.5~13000	-35.13	≤-26	0.3069 0	≤2.5	PASS
	11N20SI SO	Ant1	2412	30~1000	-51.64	≤-26	0.0068 5	≤2.5	PASS
				1000~2387	-50.29	≤-26	0.0093 5	≤2.5	PASS
				2387~2400	-33.59	≤-16	0.4375 2	≤25	PASS
				2483.5~2496.5	-39.03	≤-16	0.1250 3	≤25	PASS
				2496.5~13000	-39.51	≤-26	0.11194	≤2.5	PASS
				30~1000	-52.18	≤-26	0.0060 5	≤2.5	PASS
			2442	1000~2387	-51.47	≤-26	0.0071 3	≤2.5	PASS
				2387~2400	-39.82	≤-16	0.1042 3	≤25	PASS
				2483.5~2496.5	-39.73	≤-16	0.1064 1	≤25	PASS
				2496.5~13000	-37.29	≤-26	0.1866 4	≤2.5	PASS
			2472	30~1000	-51.95	≤-26	0.0063 8	≤2.5	PASS
				1000~2387	-51.28	≤-26	0.0074 5	≤2.5	PASS
				2387~2400	-37.56	≤-16	0.1753 9	≤25	PASS
				2483.5~2496.5	-31.04	≤-16	0.7870 5	≤25	PASS
				2496.5~13000	-36.51	≤-26	0.2233 6	≤2.5	PASS
	11N40SI SO	Ant1	2422	30~1000	-51.32	≤-26	0.0073 8	≤2.5	PASS
				1000~2387	-45.91	≤-26	0.0256 4	≤2.5	PASS
				2387~2400	-30.22	≤-16	0.9506 0	≤25	PASS
				2483.5~2496.5	-37.77	≤-16	0.16711	≤25	PASS
				2496.5~13000	-43.77	≤-26	0.0419 8	≤2.5	PASS
			2442	30~1000	-51.96	≤-26	0.0063 7	≤2.5	PASS
				1000~2387	-50.47	≤-26	0.0089 7	≤2.5	PASS
				2387~2400	-39.04	≤-16	0.1247 4	≤25	PASS
				2483.5~2496.5	-39.54	≤-16	0.11117	≤25	PASS
				2496.5~13000	-40.75	≤-26	0.0841 4	≤2.5	PASS
			2462	30~1000	-52.59	≤-26	0.0055 1	≤2.5	PASS
				1000~2387	-49.72	≤-26	0.0106 7	≤2.5	PASS
				2387~2400	-38.73	≤-16	0.1339 7	≤25	PASS
				2483.5~2496.5	-28.70	≤-16	1.3489 6	≤25	PASS
				2496.5~13000	-39.00	≤-26	0.1258 9	≤2.5	PASS

TEST REPORT

Report No.: MTi251222036-0404E2


11.1.2 Test Graphs




TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11B_Ant1 2412_2387~2400



NTNV 11B_Ant1 2412_2483.5~2496.5



TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11B_Ant1_2412_2496.5~13000




NTNV 11B_Ant1_2442_30~1000




TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11B_Ant1 2442 1000~2387




NTNV 11B_Ant1 2442 2387~2400




TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11B Ant1 2442 2483.5~2496.5




NTNV 11B Ant1 2442 2496.5~13000



TEST REPORT


Report No.: MTi251222036-0404E2




TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11B_Ant1 2472 2387~2400



NTNV 11B_Ant1 2472 2483.5~2496.5



TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11B_Ant1 2472_2496.5~13000



NTNV 11G_Ant1 2412_30~1000




TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11G_Ant1 2412 1000~2387




NTNV 11G_Ant1 2412 2387~2400



TEST REPORT

Report No.: MTi251222036-0404E2

NTNV_11G_Ant1_2412_2483.5~2496.5




NTNV_11G_Ant1_2412_2496.5~13000



TEST REPORT


Report No.: MTi251222036-0404E2



TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11G_Ant1 2442 2387~2400




NTNV 11G_Ant1 2442 2483.5~2496.5



TEST REPORT

Report No.: MTi251222036-0404E2




TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11G_Ant1_2472_1000~2387




NTNV 11G_Ant1_2472_2387~2400




TEST REPORT

Report No.: MTi251222036-0404E2

NTNV_11G_Ant1_2472_2483.5~2496.5



NTNV_11G_Ant1_2472_2496.5~13000



NTNV_11N20SISO_Ant1_2412_30~1000

TEST REPORT


Report No.: MTi251222036-0404E2



TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11N20SISO Ant1 2412 2483.5~2496.5




NTNV 11N20SISO Ant1 2412 2496.5~13000



TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11N20SISO Ant1 2442 30~1000




NTNV 11N20SISO Ant1 2442 1000~2387



TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11N20SISO Ant1 2442 2387~2400



NTNV 11N20SISO Ant1 2442 2483.5~2496.5




TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11N20SISO Ant1 2442 2496.5~13000



NTNV 11N20SISO Ant1 2472 30~1000




TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11N20SISO Ant1 2472 1000~2387




NTNV 11N20SISO Ant1 2472 2387~2400




TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11N20SISO Ant1 2472 2483.5~2496.5




NTNV 11N20SISO Ant1 2472 2496.5~13000




TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11N40SISO Ant1 2422 30~1000




NTNV 11N40SISO Ant1 2422 1000~2387




TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11N40SISO Ant1 2422 2387~2400



NTNV 11N40SISO Ant1 2422 2483.5~2496.5




TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11N40SISO Ant1 2422 2496.5~13000



NTNV 11N40SISO Ant1 2442 30~1000



TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11N40SISO Ant1 2442 1000~2387




NTNV 11N40SISO Ant1 2442 2387~2400




TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11N40SISO Ant1 2442 2483.5~2496.5




NTNV 11N40SISO Ant1 2442 2496.5~13000



TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11N40SISO Ant1 2462 30~1000



NTNV 11N40SISO Ant1 2462 1000~2387



TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11N40SISO Ant1 2462 2387~2400




NTNV 11N40SISO Ant1 2462 2483.5~2496.5



TEST REPORT

Report No.: MTi251222036-0404E2



TEST REPORT


Report No.: MTi251222036-0404E2

12 Appendix F: Spurious Emission of RX

12.1.1 Test Result


TestCondition	TestMode	Antenna	Frequen cy[MHz]	Freq.Range [MHz]	Result [dBm]	Limit [dBm]	Result [nW]	Limit [nW]	Verdict
NTNV	11B	Ant1	2412	30~1000	-78.05	≤-54	0.01567	≤4	PASS
				1000~12500	-58.53	≤-47	1.40281	≤20	PASS
			2442	30~1000	-78.71	≤-54	0.01346	≤4	PASS
				1000~12500	-59.30	≤-47	1.17490	≤20	PASS
			2472	30~1000	-77.85	≤-54	0.01641	≤4	PASS
				1000~12500	-58.98	≤-47	1.26474	≤20	PASS
	11G	Ant1	2412	30~1000	-71.41	≤-54	0.07228	≤4	PASS
				1000~12500	-59.08	≤-47	1.23595	≤20	PASS
			2442	30~1000	-77.72	≤-54	0.01690	≤4	PASS
				1000~12500	-59.79	≤-47	1.04954	≤20	PASS
			2472	30~1000	-72.17	≤-54	0.06067	≤4	PASS
				1000~12500	-58.89	≤-47	1.29122	≤20	PASS
	11N20SI SO	Ant1	2412	30~1000	-69.69	≤-54	0.10740	≤4	PASS
				1000~12500	-58.93	≤-47	1.27938	≤20	PASS
			2442	30~1000	-76.48	≤-54	0.02249	≤4	PASS
				1000~12500	-59.16	≤-47	1.21339	≤20	PASS
			2472	30~1000	-69.37	≤-54	0.11561	≤4	PASS
				1000~12500	-58.63	≤-47	1.37088	≤20	PASS
	11N40SI SO	Ant1	2422	30~1000	-78.10	≤-54	0.01549	≤4	PASS
				1000~12500	-58.75	≤-47	1.33352	≤20	PASS
			2442	30~1000	-78.89	≤-54	0.01291	≤4	PASS
				1000~12500	-59.70	≤-47	1.07152	≤20	PASS
			2462	30~1000	-69.66	≤-54	0.10814	≤4	PASS
				1000~12500	-59.46	≤-47	1.13240	≤20	PASS

12.1.2 Test Graphs




TEST REPORT


Report No.: MTi251222036-0404E2



NTNV_11B_Ant1_2442_30~1000




NTNV_11B_Ant1_2442_1000~12500



TEST REPORT


Report No.: MTi251222036-0404E2




TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11B Ant1 2472 1000~12500




NTNV 11G Ant1 2412 30~1000




TEST REPORT

Report No.: MTi251222036-0404E2

NTNV_11G_Ant1_2412_1000~12500




NTNV_11G_Ant1_2442_30~1000




TEST REPORT

Report No.: MTi251222036-0404E2

NTNV_11G_Ant1_2442_1000~12500




NTNV_11G_Ant1_2472_30~1000





Report No.: MTi251222036-0404E2


NTNV 11G Ant1 2472 1000~12500




TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11N20SISO_Ant1_2412_1000~12500




NTNV 11N20SISO_Ant1_2442_30~1000




TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11N20SISO_Ant1_2442 1000~12500




NTNV 11N20SISO_Ant1_2472 30~1000






NTNV 11N20SISO Ant1 2472 1000~12500




TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11N40SISO_Ant1_2422 1000~12500




NTNV 11N40SISO_Ant1_2442 30~1000




TEST REPORT

Report No.: MTi251222036-0404E2

NTNV 11N40SISO_Ant1_2442 1000~12500




NTNV 11N40SISO_Ant1_2462 30~1000



TEST REPORT

Report No.: MTi251222036-0404E2



TEST REPORT

Report No.: MTi251222036-0404E2

Statement

1. This report is invalid without the seal and signature of the laboratory.
2. The test results of this report are only responsible for the samples submitted. Client shall be responsible for representativeness of the sample and authenticity of the material.
3. The report shall not be partially reproduced without the written consent of the Laboratory.
4. This report is invalid if transferred, altered or tampered with in any form without authorization.
5. The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.
6. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

***** END OF REPORT *****