RADIO TEST REPORT

For

IRIS OHYAMA Inc.

Tablet

Test Model: TM15F1Q74

Prepared for	:	IRIS OHYAMA Inc.
Address	:	2-12-1 Itsutsubashi Aoba-ku, Sendai City, Miyagi, 980-8510, JAPAN
Prepared by	:	Shenzhen LCS Compliance Testing Laboratory Ltd.
Address	:	Room 101/201, Building A, and Room 101/301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China
Tel	:	(+86)755-82591330
Fax	:	(+86)755-82591332
Web	:	www.LCS-cert.com
Mail	:	webmaster@LCS-cert.com
Date of receipt of test sample	:	May 15, 2026
Number of tested samples	:	2
Sample number	:	A260512077-1, A260512077-2
Serial number	:	Prototype
Date of Test	:	May 15, 2026 ~ June 08, 2026
Date of Report	:	June 09, 2026

RADIO TEST REPORT
MIC Notice No.88 Appendix No. 43
Second-Generation Low-Power Data Communication System/Wireless LAN System

Report Reference No.	:	**LCSA05126036EA**
Date of Issue	:	June 09, 2026
Testing Laboratory Name	:	**Shenzhen LCS Compliance Testing Laboratory Ltd.**
Address	:	Room 101/201, Building A, and Room 101/301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China
Testing Location/ Procedure ...	:	Full application of Harmonised standards ■ Partial application of Harmonised standards □ Other standard testing method □
Applicant's Name	:	**IRIS OHYAMA Inc.**
Address	:	2-12-1 Itsutsubashi Aoba-ku, Sendai City, Miyagi, 980-8510, JAPAN
Test Specification		
Standard	:	MIC Notice No.88 Appendix No.43
Test Report Form No.	:	TRF-4-E-111 A/0
TRF Originator	:	Shenzhen LCS Compliance Testing Laboratory Ltd.
Master TRF	:	Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description.....	:	**Tablet**
Trade Mark.....	:	IRIS
Test Model	:	TM15F1Q74
Ratings.....	:	Please Refer to Page 6
Result	:	**PASS**

Compiled by:	**Supervised by:**	**Approved by:**
Vera Deng	Kevin Huang	Gavin Liang
Vera Deng/ Administrator	Kevin Huang/ RF Manager	Gavin Liang/ Manager

RADIO -- TEST REPORT

Test Report No. : LCSA05126036EA	June 09, 2026 Date of issue

Test Model.....	: TM15F1Q74
EUT.....	: Tablet
Applicant.....	**: IRIS OHYAMA Inc.**
Address.....	: 2-12-1 Itsutsubashi Aoba-ku, Sendai City, Miyagi, 980-8510, JAPAN
Telephone.....	: /
Fax.....	: /
Manufacturer.....	**: Shenzhen Luckystar Technology Co., Ltd**
Address.....	: Bldg 1, Yujingtai Industrial Park, Huarong Rd, Shuiwei Village, Dalang, Longhua District, Shenzhen, Guangdong Province, China
Telephone.....	: /
Fax.....	: /
Factory.....	**: Anhui UPin Intelligent Technology Co., Ltd**
Address.....	: Luckystar intelligent terminal industrial park at the intersection of Hanwen West Road and Binhe Road in Anhui Susong Economic Development Zone
Telephone.....	: /
Fax.....	: /

Test Result	**PASS**

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

Report Version	Issue Date	Revision Content	Revised By
000	June 09, 2026	Initial Issue	---

TABLE OF CONTENTS

1. GENERAL INFORMATION 6
1.1. DESCRIPTION OF DEVICE (EUT) 6
1.2. SUPPORT EQUIPMENT LIST 8
1.3. EXTERNAL I/O CABLE 8
1.4. DESCRIPTION OF TEST FACILITY 8
1.5. TEST CONDITIONS 8
1.6. FREQUENCY OF CHANNELS 8
2. TEST METHODOLOGY 9
2.1. EUT EXERCISE 9
2.2. MEASUREMENT UNCERTAINTY 9
2.3. TABLE FOR PARAMETERS OF TEST SOFTWARE SETTING 9
2.4. DESCRIPTION OF TEST MODES 9
2.5. TEST VOLTAGE 10
3. SYSTEM TEST CONFIGURATION 11
3.1. JUSTIFICATION 11
3.2. EUT EXERCISE SOFTWARE 11
3.3. SPECIAL ACCESSORIES 11
3.4. BLOCK DIAGRAM/SCHEMATICS 11
3.5. EQUIPMENT MODIFICATIONS 11
4. SUMMARY OF TEST RESULTS 12
5. TEST RESULT 13
5.1. FREQUENCY TOLERANCE 13
5.2. ANTENNA POWER 14
5.3. OCCUPIED FREQUENCY BANDWIDTH 15
5.4. SPREAD BANDWIDTH 16
5.5. TRANSMITTER SPURIOUS EMISSIONS (CONDUCTED) 17
5.6. SECONDARY RADIATED EMISSIONS 18
5.7. DWELL TIME 19
5.8. CARRIER SENSING FUNCTION 20
5.9. INTERFERENCE PREVENTION FUNCTION 21
6. PHOTOGRAPHS OF TEST SETUP 22
7. EXTERNAL PHOTOGRAPHS OF THE EUT 22
8. INTERNAL PHOTOGRAPHS OF THE EUT 22
9. LIST OF MEASURING EQUIPMENTS 22

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	:	Tablet
Test Model	:	TM15F1Q74
Ratings	:	Input: 5V⎓3A For AC Adapter Input: 100-240V~, 50/60Hz, 0.8A Adapter Output: 5V⎓3A/ 9V⎓2.77A/ 12V⎓2.08A/ 15V⎓1.66A/ 20V⎓1.25A DC 3.8V by Rechargeable Li-ion Battery, 8000mAh
Hardware Version	:	A16-T616(EDP)V2.0-260323-LU
Software Version	:	IRIS_OHYAMA_TM15F1Q74_V1.0_20260508
Bluetooth		
Frequency Range	:	2402-2480MHz for Bluetooth (79 channels for Bluetooth V5.0(BDR/EDR) Channel Frequency=2402+(K-1), K=1, 2, 3 ……79 40 channels for Bluetooth V5.0(BT LE) Channel Frequency=2402+2(K-1), K=1, 2, 3 ……40
Declared Antenna Power	:	Bluetooth V5.0(BDR/EDR): 0.02mW/MHz Bluetooth V5.0(BT LE): 1.0mW
Modulation Technology	:	Bluetooth V5.0(BDR/EDR): GFSK, π/4-DQPSK, 8-DPSK Bluetooth V5.0(BT LE): GFSK
Data Rate	:	Bluetooth V5.0(BDR/EDR): 1/2/3Mbps Bluetooth V5.0(BT LE): 1Mbps
Antenna Description	:	FPC Antenna,2.44dBi(max.)
WIFI (2.4G Band)		
Frequency Range	:	2412-2472MHz for 802.11b/g/n(HT20) 2422-2462MHz for 802.11n(HT40)
Channel Spacing	:	5MHz
Channel Number	:	13 Channel for 802.11b/g/n(HT20)(2412~2472MHz) 9 channels for 802.11n(HT40) (2422~2462MHz)
Modulation Type	:	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Declared Antenna Power	:	802.11b: 4.0mW/MHz 802.11g: 4.0mW/MHz 802.11n(HT20): 2.0mW/MHz 802.11n(HT40): 1.0mW/MHz
Antenna Description	:	FPC Antenna, 2.44dBi(max.)
WIFI (5.2G Band)		
Frequency Range	:	5180-5240MHz
Channel Number	:	4 Channel for 20MHz bandwidth(5180-5240MHz) 2 Channel for 40MHz bandwidth(5190-5230MHz) 1 Channel for 80MHz bandwidth(5210MHz)

Modulation Type	:	802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Declared Antenna Power	:	802.11a: 4.0mW/MHz 802.11n(HT20): 4.0mW/MHz 802.11n(HT40): 2.0mW/MHz 802.11ac(VHT20): 4.0mW/MHz 802.11ac(VHT40): 2.0mW/MHz 802.11ac(VHT80): 0.2mW/MHz
Antenna Description	:	FPC Antenna, 2.78dBi(max.)
WIFI (5.3G Band)		
Frequency Range	:	5260~5320MHz
Channel Number	:	4 channels for 20MHz bandwidth(5260-5320MHz) 2 channels for 40MHz bandwidth(5270-5310MHz) 1 Channel for 80MHz bandwidth(5290MHz)
Modulation Type	:	802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Declared Antenna Power	:	802.11a: 2.0mW/MHz 802.11n(HT20): 2.0mW/MHz 802.11n(HT40): 1.0mW/MHz 802.11ac(VHT20): 2.0mW/MHz 802.11ac(VHT40): 1.0mW/MHz 802.11ac(VHT80): 0.6mW/MHz
Antenna Description	:	FPC Antenna, 2.78dBi(max.)
WIFI (5.6G Band)		
Frequency Range	:	5500~5700MHz
Channel Number	:	11Channels for 20MHz bandwidth(5500-5700MHz) 5 Channels for 40MHz bandwidth(5510-5670MHz) 2 channels for 80MHz bandwidth(5530-5610MHz)
Modulation Type	:	802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Declared Antenna Power	:	802.11a: 4.0mW/MHz 802.11n(HT20): 4.0mW/MHz 802.11n(HT40): 1.0mW/MHz 802.11ac(VHT20): 4.0mW/MHz 802.11ac(VHT40): 1.0mW/MHz 802.11ac(VHT80): 0.2mW/MHz
Antenna Description	:	FPC Antenna, 2.78dBi(max.)
Wireless Charging	:	
Operating Frequency	:	110.0~205.0KHz
Modulation Type	:	ASK
Antenna Type	:	Coil Antenna

Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.

1.2. Support Equipment List

Manufacturer	Description	Model	Serial Number	Certificate
Shenzhen Jihongda Power Co.,Ltd.	AC/DC ADAPTER	JHD-AP045E-1902 10-AF	--	PSE

Note: Auxiliary equipment is provided by the laboratory.

1.3. External I/O Cable

I/O Port Description	Quantity	Cable
Type-C USB Port	1	N/A

1.4. Description of Test Facility

FCC Registration Number is 254912.
NVLAP Accreditation Code is 600167-0.
FCC Designation Number is CN5024.
CAB identifier is CN0071.
CNAS Registration Number is L4595.
Industry Canada Registration Number is 9642A.

1.5. Test Conditions

Temperature Range	:	21-25℃
Humidity Range	:	45-85%
Pressure Range	:	86-106kPa

1.6. Frequency of Channels

Bluetooth V5.0(BDR/EDR)

Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	2402	41	2442
2	2403	42	2443
--	--	--	--
38	2439	78	2479
39	2440	79	2480
40	2441		

2. TEST METHODOLOGY

2.1. EUT Exercise

The EUT was tested while in a continuous transmitter/receiver mode.
The EUT was tuned to a low, middle, and high channel for the purpose of the measurements.
For all test case pre/scans were completed in all Modes to determine worst case levels.
According to its specifications, the EUT must comply with the requirements of MIC Notice No.88 Appendix No. 43.

2.2. Measurement Uncertainty

Test Item		MU	Remark
Bandwidth	:	+/- 0.2 E-6	/
Antenna Power	:	+/-0.33dB	/
Frequency Tolerance	:	+/- 0.3 E-6	/
Conducted spurious emission	:	+/-0.13dB	/
DC Power	:	+/-1%	/

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2.3. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.
Power Parameters:

Test Software Version	Engineering code		
Frequency	2402MHz	2441MHz	2480MHz
Bluetooth V5.0	Default	Default	Default

2.4. Description of Test Modes

Tested channel, Frequency and Modulation Information		
CH1	2402MHz	GFSK(1Mbps), π/4-DQPSK(2Mbps), 8-DPSK(3Mbps)
CH40	2441MHz	GFSK(1Mbps), π/4-DQPSK(2Mbps), 8-DPSK(3Mbps)
CH79	2480MHz	GFSK(1Mbps), π/4-DQPSK(2Mbps), 8-DPSK(3Mbps)
Hopping Mode		GFSK(1Mbps), π/4-DQPSK(2Mbps), 8-DPSK(3Mbps)
Note: According exploratory test, EUT has maximum output power for GFSK modulation, All the test modes were tested, but only the worst case was recorded in this report.		

2.5. Test Voltage

POWER SUPPLY VOLTAGE FLUCTUATION TEST

Voltage Fluctuation Test	Normal Voltage	High Voltage +10% of Normal Voltage	Low Voltage -10% of Normal Voltage
Input To EUT	DC 3.8V	DC 4.2V	DC 3.4V
Output To RF Module	DC 3.3V	DC 3.3V	DC 3.3V
Voltage Variation (%)	--	--	--

Note: As the EUT was powered by DC 3.8V, and with the voltage stabilizing circuit used, the chip voltage received floating not exceed ±1% of nominal condition when working on extreme voltage, so all test performed at nominal voltage only.

3. SYSTEM TEST CONFIGURATION

3.1. Justification

The system was configured for testing in a typical fashion.

3.2. EUT Exercise Software

N/A.

3.3. Special Accessories

N/A.

3.4. Block Diagram/Schematics

Please refer to the report.

3.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

4. SUMMARY OF TEST RESULTS

MIC Notice No.88 Appendix No.43 Article 2 Paragraph 1 Item 19		
Clause	Description of Test (Transmitter Parameters)	Result
3	Frequency Tolerance	PASS
6	Antenna Power	PASS
6	Tolerances for Antenna Power	PASS
4	Transmission Rate	PASS
4	Occupied Frequency Bandwidth	PASS
4	Spread Bandwidth	PASS
13	Dwell Time	PASS
5	Spurious Emissions	PASS
10	Transmission Antenna Gain (EIRP Antenna Power)	N/A
11	Transmission Radiated Angle Width (3dB Beam width)	N/A
12	Interference prevention function	PASS
8	Carrier Sensing function	N/A
Receiver Parameters		
7	Secondary Radiated Emissions	PASS
(1) N/A is an abbreviation for Not Applicable.		

5. TEST RESULT

5.1. Frequency Tolerance

5.1.1. Standard Applicable

Tolerance of frequency shall be ±50ppm.

5.1.2. Test Procedures

a. Set EUT work in test mode as described in clause 2.4.

b. Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, set the Spectrum Analyzer as below:

Centre Frequency: The centre frequency of the channel under test.

Resolution BW: 10 KHz.

Video BW: 10 KHz.

Span: 1MHz.

Detector: Peak.

Trace Mode: Max Hold.

c. When the trace is complete, find the peak value of the power envelope and record.

5.1.3. Test Setup Layout



5.1.4. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.1.5. Test Result

PASS

Please refer to the Appendix A.1 for BT Test Data.

5.2. Antenna Power

5.2.1. Standard Applicable

Type	Limit
Antenna Power	3mW/MHz
Tolerance	+20%

5.2.2. Measuring Instruments

Please refer to section 9 of equipments list in this report.

5.2.2. Test Procedures

a. EUT have transmitted continuous maximum power

b. Antenna Power Error is definition that actual measure antenna power tolerance between +20% power range that base on manufacturer declare the conducted power density.

5.2.3. Test Setup



5.2.4. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.2.5. Test Result

PASS

Please refer to the Appendix A.2 for BT Test Data.

5.3. Occupied Frequency Bandwidth

5.3.1. Standard Applicable

Permissible value for occupied bandwidth using the FH system, a hybrid system combining DS and FH systems, or a hybrid system combining FH and OFDM systems shall be 83.5 MHz or less, while necessary bandwidth (minimum occupied bandwidth sufficient to ensure information transmission of required quality at a required transmission rate for the system used under specified conditions for a given emission type) using a system other than any of the above shall be 26 MHz or less.

5.3.2. Test Procedures

a. Set EUT work in test mode as described in clause 2.4.

b. Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, set the Spectrum Analyzer as below:

Centre Frequency: The centre frequency of the channel under test.

Resolution BW: 30 KHz.

Video BW: 30 KHz.

Span: Wide enough to cover the complete power envelope of the signal of the EUT.

Sweep mode: Continuous sweeping.

Detector: Peak.

Trace Mode: Max Hold.

c. When the trace is complete, measure the occupied bandwidth (99% bandwidth) with spectrum analyzer's bandwidth measure function.

5.3.3. Test Setup Layout



5.3.4. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.3.5. Test Result of Occupied Bandwidth

PASS

Please refer to the Appendix A.3 for BT Test Data.

5.4. Spread Bandwidth

5.4.1. Standard Applicable

In spread spectrum systems, spread bandwidth (which refers to a frequency bandwidth with an upper limit and lower limit such that each of the mean powers radiated above the upper frequency limit and below the lower frequency limit is equal to 5 % of the total mean power radiated; this also applies hereafter) shall be 500 kHz or more.

The OFDM system shall have one or more carriers per 1 MHz bandwidth.

5.4.2. Test Procedures

a. Set EUT work in test mode as described in clause 2.4.

b. Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, set the Spectrum Analyzer as below:

Centre Frequency: The centre frequency of the channel under test.

Resolution BW: 1MHz.

Video BW: 1MHz.

Span: Wide enough to cover the complete power envelope of the signal of the EUT.

Detector: Peak.

Trace Mode: Max Hold.

c. When the trace is complete, measure the spread bandwidth (90% bandwidth) with spectrum analyzer's bandwidth measure function.

5.4.3. Test Setup Layout



5.4.4. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.4.5. Test Result of Spectrum Bandwidth

PASS

Please refer to the Appendix A.4 for BT Test Data.

5.5. Transmitter Spurious Emissions (conducted)

5.5.1. Standard Applicable

Permissible mean power of spurious emission of each frequency supplied to a feeder, that is, mean power of spurious emission in the 1 MHz bandwidth at frequency f other than frequency band used shall be as follows:

a. 30MHz - 1,000MHz	2.5 μW or less
b. 1,000MHz - 2,387MHz	2.5 μW or less
c. 2,387MHz - 2,400MHz and 2,483.5MHz - 2,496.5MHz	25 μW or less
d. 2,496.5MHz - 13GHz	2.5 μW or less

5.5.2. Test Procedures

a. Set EUT work in test mode as described in clause 2.4.

b. Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, set the Spectrum Analyzer as below:

Centre Frequency: The centre frequency of the channel under test.

Below 1GHz: RBW/VBW= 1MHz / 1MHz

Above 1GHz: RBW/VBW= 1MHz / 1MHz

Detector: Peak.

Trace Mode: Max Hold.

c. All the emissions from 30MHz to 13GHz were measured and record.

5.5.3. Test Setup Layout



5.5.4. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.5.5. Test Results

PASS

Please refer to the Appendix A.5 for BT Test Data.

Note:SA set to from 2.4965GHz to 13GHz, plot shows from 2.497GHz to 13GHz as of SA's default format.

5.6. Secondary Radiated Emissions

5.6.1. Standard Applicable

The limit on secondary emissions radiated from the receiving equipment within which the
function of other radio equipment will not be impaired shall be, in terms of the power of a
dummy antenna circuit that has the same electrical constant as the receiving antenna, 4nW or less at a frequency below 1 GHz and 20nW or less at a frequency of 1 GHz or higher as measured using the circuit

5.6.2. Test Procedures

a. Set EUT work in test mode as described in clause 2.4.

b. Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, set the Spectrum Analyzer as below:

Resolution BW: 100 KHz for frequency below 1GHz and

1MHz for frequency above 1GHz

Video BW: 100 KHz for frequency below 1GHz and

1MHz for frequency above 1GHz

Detector: Peak.

Trace Mode: Max Hold.

c. All the emissions from 30MHz to 12.5GHz were measured and record.

5.6.3. Test Setup



5.6.4. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.6.5. Test Results

PASS

Please refer to the Appendix A.6 for BT Test Data.

5.7. Dwell Time

5.7.1. Standard Applicable

Frequency dwell time (time during which radio waves continue to be emitted at a specified

frequency) of a transmitting equipment using the FH system shall be 0.4 seconds or less.

5.7.2. Test Procedures

a. Set EUT work in test mode as described in clause 2.4.

b. Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, set the Spectrum Analyzer as below:

Centre Frequency: The centre frequency of the channel under test.

Resolution BW: 1MHz/510kHz

Video BW: 1MHz/3MHz

Span: Zero MHz

Detector: Peak.

Trace Mode: Max Hold.

c. When the trace is complete, measure the sending time of 1 burst and the duty cycle of 1 burst cycle.

5.7.3. Test Setup Layout



5.7.4. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.7.5. Test Results

PASS

Please refer to the Appendix A.7 for BT Test Data.

5.8. Carrier sensing function

5.8.1. Standard Applicable

Item	Limits
Carrier Sense	Good – EUT stop RF transmission signal after carrier inject to EUT. (On 22.79+Gr-20*log (f)[dBm] (Gr: dBi; f: MHz) or 100mV/m)

5.8.2. Instruments Setting

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
RB / VB	1 MHz
Span	0 MHz
Sweep	Continuous
Detector	Peak
Trigger mode	Video

5.8.3. Test Procedures

1. SSG adjusted the frequency as same as the EUT transmitted signal and emitted the absence of modulation from SSG and power level is (On 22.79+Gr-20*log (f) [dBm] (Gr: dBi; f: MHz). Then turn off the RF signal of SSG.
2. EUT have transmitted the maximum modulation signal and fixed channelize.
3. Setting of SA is following as: RB: 1MHz / VB: 1MHz / SPAN: 50MHz / AT: 10dB /Ref: 0dBm / Sweep time: Auto / Sweep Mode: Continuous sweep / Detect mode: Positive peak.
4. SSG RF Signal On.
5. EUT shall be stop the transmitted any signal and SSG RF Signal Off. Then EUT will be continuous transmitted signal.

5.8.4. Test Setup Layout



5.8.5. EUT Operation during Test

The EUT was programmed to be in normal transmitting mode.

5.8.6. Test Result

Not Applicable.

5.9. Interference prevention function

5.9.1. Standard Applicable

Item	Limits
Identification code	≧ 48 bits

5.9.2. Measuring ID Code Software

PC with NetTool	Setting
MAC IP List	MAC Scan

5.9.3. Test Procedures

1. In the case that the EUT has the function of automatically transmitting the identification code: a. Transmit the predetermined identification codes from EUT. b. Check the transmitted identification codes with the demodulator.

2. In the case of receiving the identification code: a. Transmit the predetermined identification codes from the counterpart. b. Check if communication is normal. c. Transmit the other signals than predetermined ID codes from the counterpart. d. check if the EUT stops the transmission, or if it displays that identification codes are different from the predetermined ones.

5.9.4. Test Setup Layout



5.9.5. EUT Operation during Test

The EUT was programmed to be in normal transmitting mode.

5.9.6. Test Result

EUT ID	Performance index
9A:6F:5E:28:39:D5	Good

6. PHOTOGRAPHS OF TEST SETUP

Please refer to separated files Appendix G for Test Setup Photographs

7. EXTERNAL PHOTOGRAPHS OF THE EUT

Please refer to separated files Appendix H for External Photos of EUT

8. INTERNAL PHOTOGRAPHS OF THE EUT

Please refer to separated files Appendix I for Internal Photos of EUT

9. LIST OF MEASURING EQUIPMENTS

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	Power Meter	R&S	NRVS	100444	2025-05-22	2026-05-21
					2026-05-21	2027-05-20
2	Power Sensor	R&S	NRP-Z81	100458	2025-05-22	2026-05-21
					2026-05-21	2027-05-20
3	Power Sensor	R&S	U2021	10057	2025-05-22	2026-05-21
					2026-05-21	2027-05-20
4	Test Software	Tonscend	JS1120-2	/	N/A	N/A
5	RF Control Unit	Tonscend	JS0806-2	/	2025-11-07	2026-11-06
6	MXA Signal Analyzer	Agilent	N9020A	MY49100699	2026-04-21	2027-04-20
7	DC Power Supply	Agilent	E3642A	N/A	2025-09-27	2026-09-26
8	Oscilloscope	Tektronix	46084A/4609A	140920	2025-05-22	2026-05-21
					2026-05-21	2027-05-20
9	Signal Generator	Agilent	N5182A	MY47071151	2026-04-21	2027-04-20

Note: Calibration by the calibration agencies listed in the table corres pond to paragraph 4 (ii) (c) of Article 24-2 in the Radio Law.
Calibration Agencies: Guangzhou LiSai Metrology & Test Co., Ltd.

☐(a) Calibration conducted by the National Institute of Information and Communications Technology (NICT) or a designated calibration agency under Article 102-18-1 of the Radio Act.

☐(b) Calibration conducted based on the regulations of Article 135 or 144 of the Measurement Act.

☒(c) Calibration conducted in foreign countries, which is equivalent to calibration conducted by the NICT or a designated calibration agency under Article 102-18-1 of the Radio Act.

☐(d) Calibration, etc. conducted by using measuring instruments and other facilities listed at the bottom of appended table 3 of the Radio Act, which is to have been calibrated as described in (a) through (c) above.

----------THE END OF REPORT----------