NCC RADIO TEST REPORT

Equipment	:	**Floodlight Cam Wired Pro**
Brand Name	:	**Ring**
Model Name	:	**5B28S4**
Applicant	:	環安智控股份有限公司 台北市內湖區堤頂大道二段 **179** 號 **4** 樓
Manufacturer	:	**Ring LLC** **1523 26th St Santa Monica, CA 90404 USA**
Standard	:	**NCC LP0002 (2020-07-01)**

The product was received on Feb. 09, 2021 and testing was started from Feb. 25, 2021 and completed on Mar. 22, 2021. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures NCC LP0002 (2020-07-01) and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory
No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)

Table of Contents

History of this test report **3**
Summary of Test Result **4**
1 General Description **5**
1.1 Product Feature of Equipment Under Test 5
1.2 Modification of EUT 5
1.3 Testing Location 6
1.4 Applicable Standards 6
2 Test Configuration of Equipment Under Test **7**
2.1 Carrier Frequency Channel 7
2.2 Test Mode 8
2.3 Connection Diagram of Test System 9
2.4 EUT Operation Test Setup 10
2.5 Measurement Results Explanation Example 10
3 Test Result **11**
3.1 6dB and 99% Bandwidth Measurement 11
3.2 Output Power Measurement 16
3.3 Power Spectral Density Measurement 17
3.4 Conducted Band Edges and Spurious Emission Measurement 22
3.5 Radiated Band Edges and Spurious Emission Measurement 27
3.6 AC Conducted Emission Measurement 31
3.7 Antenna Requirements 33
4 List of Measuring Equipment **34**
5 Uncertainty of Evaluation **36**
Appendix A. Conducted Test Results
Appendix B. AC Conducted Emission Test Result
Appendix C. Radiated Spurious Emission
Appendix D. Radiated Spurious Emission Plots
Annex A. Receiver Radiated Emission
Annex B. Maximum Power Density
Appendix E. Duty Cycle Plots

History of this test report

Report No.	Version	Description	Issued Date
TR120337A	01	Initial issue of report	May 11, 2021
TR120337A	02	Add test data of Receiver Radiated Emission and Maximum Power Density in Annex	Jun. 18, 2021

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	LP0002 4.10.1.6 (2)(A)	6dB Bandwidth	Pass	-
3.1	-	99% Occupied Bandwidth	Reporting only	-
3.2	LP0002 4.10.1.2 (1)(C)	Output Power	Pass	-
3.3	LP0002 4.10.1.6 (2)(B)	Power Spectral Density	Pass	-
3.4	LP0002 4.10.1.5	Conducted Band Edges and Spurious Emission	Pass	-
3.5	LP0002 4.10.1.5	Radiated Band Edges and Spurious Emission	Pass	Under limit 3.57 dB at 43.580 MHz
3.6	LP0002 3.3	AC Conducted Emission	Pass	Under limit 13.23 dB at 0.184 MHz
3.7	LP0002 3.2 4.10.1.3 4.10.1.4	Antenna Requirement	Pass	-
Annex A	LP0002 3.9	Receiver Radiated Emission	Pass	Please refer to Annex A
Annex B	LP0002 3.2 6.20.2	Maximum Power Density	Pass	-

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Tina Chuang

1 General Description

1.1 Product Feature of Equipment Under Test

Bluetooth-LE, Wi-Fi 2.4GHz 802.11b/g/n, Wi-Fi 5GHz 802.11a/n/ac, LoRa and 24G Radar.

Product Specification subjective to this standard	
Tx/Rx Frequency	2400 MHz ~ 2483.5 MHz
Type of Modulation	Bluetooth LE : GFSK

Antenna Information				
Antenna	**Brand Name**	INPAQ TECHNOLOGY CO., LTD	**Peak Gain**	3.21
	Model Name	RFFPA322204IMLB301	**Type**	FPC Antenna

Remark:

1. The detail internal, external and transmit antenna photo please refer to Sporton report no.: EP120337.
2. The above EUT's information was declared by manufacturer. Please refer to Comments and Explanations in report summary.

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	**Sporton Site No.**
	03CH13-HY, CO07-HY, TH05-HY

FCC designation No.: TW3786

1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- NCC LP0002 (2020-07-01)
- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- FCC KDB 414788 D01 Radiated Test Site v01r01
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

2.2 Test Mode

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	**Data Rate / Modulation**
Conducted Test Cases	**Bluetooth – LE / GFSK**
	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
Radiated Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
AC Conducted Emission	Mode 1: WLAN (2.4GHz) Tx + Bluetooth Tx + Lora Tx
Remark: For radiated test cases, after pretest 110Vac and 120Vac, the worst case is 120Vac; therefore, only performed the 120Vac test results in this report.	

2.3 Connection Diagram of Test System

<AC Conducted Emission Mode>



<Bluetooth-LE Tx Mode>



2.4 EUT Operation Test Setup

The WLAN and Bluetooth-LE test items, utility “ComplianceTool V1.0.0.87” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

The Lora test items, utility “CMD V10.40.02” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.5 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :
The spectrum analyzer offset is derived from RF cable loss and attenuator factor.
Offset = RF cable loss + attenuator factor.
Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).
= 4.2 + 10 = 14.2 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) ≥ 3 * RBW.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

<1Mbps>

6 dB Bandwidth Plot on Channel 00	6 dB Bandwidth Plot on Channel 19
	
6 dB Bandwidth Plot on Channel 39	**N/A**
	

<2Mbps>

6 dB Bandwidth Plot on Channel 00	6 dB Bandwidth Plot on Channel 19
	
6 dB Bandwidth Plot on Channel 39	**N/A**
	

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

<1Mbps>

99% Bandwidth Plot on Channel 00	99% Occupied Bandwidth Plot on Channel 19
	
99% Occupied Bandwidth Plot on Channel 39	**N/A**
	

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

<2Mbps>

99% Bandwidth Plot on Channel 00	99% Occupied Bandwidth Plot on Channel 19
	
99% Occupied Bandwidth Plot on Channel 39	**N/A**
	

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna of directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT was connected to the power meter by RF cable and attenuator.
3. The path loss was compensated to the results for each measurement.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz. In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100 kHz is a reference level and is used as 20 dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.3.6 Test Result of Power Spectral Density Plots (100kHz)

<1Mbps>

PSD 100kHz Plot on Channel 00	PSD 100kHz Plot on Channel 19
	
PSD 100kHz Plot on Channel 39	**N/A**
	

<2Mbps>

PSD 100kHz Plot on Channel 00	PSD 100kHz Plot on Channel 19
	
PSD 100kHz Plot on Channel 39	**N/A**
	

3.3.7 Test Result of Power Spectral Density Plots (3kHz)

<1Mbps>

PSD 3kHz Plot on Channel 00	PSD 3kHz Plot on Channel 19
	
PSD 3kHz Plot on Channel 39	**N/A**
	

<2Mbps>

PSD 3kHz Plot on Channel 00	PSD 3kHz Plot on Channel 19
	
PSD 3kHz Plot on Channel 39	**N/A**
	

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.

3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

<1Mbps>

Low Band Edge Plot on Channel 00	High Band Edge Plot on Channel 39
	

<2Mbps>

Low Band Edge Plot on Channel 00	High Band Edge Plot on Channel 39
	

3.4.6 Test Result of Conducted Spurious Emission Plots

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00	Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00
	
Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19	**Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19**
	

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39	Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39
	

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 00	Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 00
	

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 19



Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 19



Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 39



Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 39



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the NCC LP0002 section 3.6 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

3.5.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1 GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and be reported.
7. For testing above 1 GHz, the emission level of the EUT in peak mode was 20 dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and be reported.
8. Use the following spectrum analyzer settings:
   (1) Span shall wide enough to fully capture the emission being measured;
   (2) Set RBW = 100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
   (3) Set RBW = 1 MHz, VBW = 3 MHz for f ≥ 1 GHz for peak measurement.
   For average measurement:
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup

For radiated test below 30MHz



For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per NCC LP0002 section 6.13 was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30 MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



AMN = Artificial mains network (LISN)
AE = Associated equipment
EUT = Equipment under test
ISN = Impedance stabilization network

3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the LP0002 Section 3.2, Section 4.10.1.3, and Section 4.10.1.4.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Amplifier	Sonoma-Instrument	310 N	187282	9KHz~1GHz	Dec. 16, 2020	Feb. 25, 2021~ Mar. 08, 2021	Dec. 15, 2021	Radiation (03CH13-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800N1D01N-06	40103&07	30MHz to 1GHz	Apr. 29, 2020	Feb. 25, 2021~ Mar. 08, 2021	Apr. 28, 2021	Radiation (03CH13-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1212	1GHz ~ 18GHz	May 20, 2020	Feb. 25, 2021~ Mar. 08, 2021	May 19, 2021	Radiation (03CH13-HY)
Preamplifier	MITEQ	AMF-7D-00101800-30-10P	1590074	1GHz~18GHz	May 19, 2020	Feb. 25, 2021~ Mar. 08, 2021	May 18, 2021	Radiation (03CH13-HY)
Preamplifier	Keysight	83017A	MY53270147	1GHz~26.5GHz	Oct. 28, 2020	Feb. 25, 2021~ Mar. 08, 2021	Oct. 27, 2021	Radiation (03CH13-HY)
Signal Generator	Anritsu	MG3694C	163401	0.1Hz~40GHz	Jan. 31, 2021	Feb. 25, 2021~ Mar. 08, 2021	Jan. 30, 2022	Radiation (03CH13-HY)
Spectrum Analyzer	Keysight	N9010A	MY55370526	10Hz~44GHz	Mar. 20, 2020	Feb. 25, 2021~ Mar. 08, 2021	Mar. 19, 2021	Radiation (03CH13-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Feb. 25, 2021~ Mar. 08, 2021	N/A	Radiation (03CH13-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Feb. 25, 2021~ Mar. 08, 2021	N/A	Radiation (03CH13-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Feb. 25, 2021~ Mar. 08, 2021	N/A	Radiation (03CH13-HY)
Software	Audix	E3 6.2009-8-24	RK-000992	N/A	N/A	Feb. 25, 2021~ Mar. 08, 2021	N/A	Radiation (03CH13-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz ~ 40GHz	Dec. 11, 2020	Feb. 25, 2021~ Mar. 08, 2021	Dec. 10, 2021	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0030/126E	30M-18G	Feb. 10, 2021	Feb. 25, 2021~ Mar. 08, 2021	Feb. 09, 2022	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	804793/4	30M-18G	Feb. 10, 2021	Feb. 25, 2021~ Mar. 08, 2021	Feb. 09, 2022	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30M~40GHz	Feb. 22, 2021	Feb. 25, 2021~ Mar. 08, 2021	Feb. 21, 2022	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY4274/2	30M~40GHz	Mar. 12, 2020	Feb. 25, 2021~ Mar. 08, 2021	Mar. 11, 2021	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24961/4	30M-18G	Feb. 10, 2021	Feb. 25, 2021~ Mar. 08, 2021	Feb. 09, 2022	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4 PE	9kHz~30MHz	Mar. 12, 2020	Feb. 25, 2021~ Mar. 08, 2021	Mar. 11, 2021	Radiation (03CH13-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Dec. 11, 2020	Feb. 25, 2021~ Mar. 08, 2021	Dec. 10, 2021	Radiation (03CH13-HY)
Filter	Wainwright	WHKX12-1080-1200-15000-60SS	SN3	1.2GHz High Pass Filter	Jul. 02, 2020	Feb. 25, 2021~ Mar. 08, 2021	Jul. 01, 2021	Radiation (03CH13-HY)
Hygrometer	TECPEL	DTM-303A	TP190075	N/A	Apr. 23, 2020	Feb. 25, 2021~ Mar. 08, 2021	Apr. 22, 2021	Radiation (03CH13-HY)

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ACPOWER	AFC-11003G	F317040033	N/A	N/A	Mar. 22, 2021	N/A	Conduction (CO07-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Mar. 22, 2021	N/A	Conduction (CO07-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	9561-F N00373	9kHz-200MHz	Nov. 02, 2020	Mar. 22, 2021	Nov. 01, 2021	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	N/A	Mar. 22, 2021	N/A	Conduction (CO07-HY)
Two-Line V-Network	TESEQ	NNB 51	45051	N/A	Feb. 01, 2021	Mar. 22, 2021	Jan. 31, 2022	Conduction (CO07-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz~3.6GHz	Sep. 11, 2020	Mar. 22, 2021	Sep. 10, 2021	Conduction (CO07-HY)
Hygrometer	Testo	608-H1	34893241	N/A	Mar. 02, 2020	Mar. 05, 2021~ Mar. 08, 2021	Mar. 01, 2021	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	16I00054SNO12	10MHz~6GHz	Dec. 16, 2020	Mar. 05, 2021~ Mar. 08, 2021	Dec. 15, 2021	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz ~ 40GHz	Jul. 22, 2020	Mar. 05, 2021~ Mar. 08, 2021	Jul. 21, 2021	Conducted (TH05-HY)
Switch Box & RF Cable	EM Electronics	EMSW18SE	SW200302	N/A	Mar. 17, 2020	Mar. 05, 2021~ Mar. 08, 2021	Mar. 16, 2021	Conducted (TH05-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.2

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.8

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.1

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.8

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Eason Huang	Temperature:	21~25	°C
Test Date:	2021/3/5~2021/03/08	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.030	0.682	0.50	Pass
BLE	1Mbps	1	19	2440	1.030	0.682	0.50	Pass
BLE	1Mbps	1	39	2480	1.030	0.684	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail	Ppwer Setting
BLE	1Mbps	1	0	2402	10.50	30.00	3.21	13.71	36.00	Pass	Defult
BLE	1Mbps	1	19	2440	10.30	30.00	3.21	13.51	36.00	Pass	Defult
BLE	1Mbps	1	39	2480	10.30	30.00	3.21	13.51	36.00	Pass	Defult

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	9.26	-5.10	3.21	8.00	Pass
BLE	1Mbps	1	19	2440	9.38	-4.97	3.21	8.00	Pass
BLE	1Mbps	1	39	2480	9.09	-5.22	3.21	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

Report Number : TR120337A

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	2Mbps	1	0	2402	2.057	1.179	0.50	Pass
BLE	2Mbps	1	19	2440	2.053	1.179	0.50	Pass
BLE	2Mbps	1	39	2480	2.053	1.179	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail	Ppwer Setting
BLE	2Mbps	1	0	2402	10.50	30.00	3.21	13.71	36.00	Pass	Defult
BLE	2Mbps	1	19	2440	10.60	30.00	3.21	13.81	36.00	Pass	Defult
BLE	2Mbps	1	39	2480	10.50	30.00	3.21	13.71	36.00	Pass	Defult

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	2Mbps	1	0	2402	9.30	-8.66	3.21	8.00	Pass
BLE	2Mbps	1	19	2440	9.14	-8.75	3.21	8.00	Pass
BLE	2Mbps	1	39	2480	9.28	-8.71	3.21	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

Appendix B. AC Conducted Emission Test Results

Test Engineer :	Eric Jeng	**Temperature :**	23~26℃
		Relative Humidity :	40~50%

EUT Information

Report NO :	120337
Test Mode :	Mode 1
Test Voltage :	110Vac/60Hz
Phase :	Line



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.159000	---	31.28	55.52	24.24	L1	OFF	20.0
0.159000	51.44	---	65.52	14.08	L1	OFF	20.0
0.183750	---	33.29	54.31	21.02	L1	OFF	20.0
0.183750	51.08	---	64.31	13.23	L1	OFF	20.0
0.244590	---	24.24	51.94	27.70	L1	OFF	20.0
0.244590	43.38	---	61.94	18.56	L1	OFF	20.0
0.498300	---	26.23	46.03	19.80	L1	OFF	20.0
0.498300	32.38	---	56.03	23.65	L1	OFF	20.0
0.997260	---	23.79	46.00	22.21	L1	OFF	20.0
0.997260	29.96	---	56.00	26.04	L1	OFF	20.0
12.862500	---	33.30	50.00	16.70	L1	OFF	20.2
12.862500	38.98	---	60.00	21.02	L1	OFF	20.2

EUT Information

Report NO :	120337
Test Mode :	Mode 1
Test Voltage :	110Vac/60Hz
Phase :	Neutral



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.339000	---	18.19	49.23	31.04	N	OFF	20.0
0.339000	28.07	---	59.23	31.16	N	OFF	20.0
0.975750	---	14.63	46.00	31.37	N	OFF	20.0
0.975750	21.22	---	56.00	34.78	N	OFF	20.0
1.768290	---	18.67	46.00	27.33	N	OFF	20.0
1.768290	22.77	---	56.00	33.23	N	OFF	20.0
2.744250	---	20.22	46.00	25.78	N	OFF	20.1
2.744250	23.26	---	56.00	32.74	N	OFF	20.1
8.925270	---	21.11	50.00	28.89	N	OFF	20.1
8.925270	25.41	---	60.00	34.59	N	OFF	20.1
12.963480	---	34.70	50.00	15.30	N	OFF	20.2
12.963480	38.69	---	60.00	21.31	N	OFF	20.2

Appendix C. Radiated Spurious Emission

Test Engineer :	Daniel Lee, Jacky Hong and Wilson Wu	Temperature :	20~25°C
		Relative Humidity :	50~60%

<1Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2343.6	56.09	-17.91	74	42.16	27.71	14.07	27.85	160	190	P	H
		2378.46	45.3	-8.7	54	31.39	27.64	14.11	27.84	160	190	A	H
	*	2402	105.47	-	-	91.58	27.6	14.13	27.84	160	190	P	H
	*	2402	104.86	-	-	90.97	27.6	14.13	27.84	160	190	A	H
													H
		2349.165	54.99	-19.01	74	41.06	27.7	14.08	27.85	283	158	P	V
		2367.225	45.31	-8.69	54	31.39	27.67	14.1	27.85	283	158	A	V
	*	2402	104	-	-	90.11	27.6	14.13	27.84	283	158	P	V
	*	2402	103.26	-	-	89.37	27.6	14.13	27.84	283	158	A	V
													V
BLE CH 19 2440MHz		2377.48	54.79	-19.21	74	40.87	27.65	14.11	27.84	159	189	P	H
		2366.28	45.37	-8.63	54	31.45	27.67	14.1	27.85	159	189	A	H
	*	2440	105.01	-	-	91.16	27.52	14.16	27.83	159	189	P	H
	*	2440	104.55	-	-	90.7	27.52	14.16	27.83	159	189	A	H
		2495.38	54.57	-19.43	74	40.68	27.5	14.21	27.82	159	189	P	H
		2491.46	45.18	-8.82	54	31.3	27.5	14.2	27.82	159	189	A	H
		2374.12	55.14	-18.86	74	41.24	27.65	14.1	27.85	312	169	P	V
		2349.62	45.55	-8.45	54	31.62	27.7	14.08	27.85	312	169	A	V
	*	2440	104.03	-	-	90.18	27.52	14.16	27.83	312	169	P	V
	*	2440	103.49	-	-	89.64	27.52	14.16	27.83	312	169	A	V
		2498.32	54.75	-19.25	74	40.86	27.5	14.21	27.82	312	169	P	V
		2487.4	45.28	-8.72	54	31.4	27.5	14.2	27.82	312	169	A	V

BLE CH 39 2480MHz	*	2480	105.1	-	-	91.23	27.5	14.19	27.82	145	188	P	H
	*	2480	104.39	-	-	90.52	27.5	14.19	27.82	145	188	A	H
		2484.68	56.53	-17.47	74	42.65	27.5	14.2	27.82	145	188	P	H
		2493.24	45.47	-8.53	54	31.59	27.5	14.2	27.82	145	188	A	H
													H
													H
	*	2480	105.05	-	-	91.18	27.5	14.19	27.82	304	171	P	V
	*	2480	104.46	-	-	90.59	27.5	14.19	27.82	304	171	A	V
		2485.2	55.62	-18.38	74	41.74	27.5	14.2	27.82	304	171	P	V
		2484.32	45.4	-8.6	54	31.52	27.5	14.2	27.82	304	171	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	37.11	-36.89	74	56.98	31.11	6.51	57.49	100	0	P	H
		17955	55.96	-18.04	74	52.47	46.84	13.15	56.5	125	209	P	H
		17955	46.9	-7.1	54	43.41	46.84	13.15	56.5	125	209	A	H
													H
		4804	37.21	-36.79	74	57.08	31.11	6.51	57.49	100	0	P	V
		17970	55.58	-18.42	74	51.65	47.26	13.16	56.49	131	236	P	V
		17970	47.18	-6.82	54	43.25	47.26	13.16	56.49	131	236	A	V
													V
BLE CH 19 2440MHz		4880	38.08	-35.92	74	57.38	31.2	6.83	57.33	100	0	P	H
		7320	45.4	-28.6	74	57.01	36.76	8.73	57.1	100	0	P	H
		17940	56.21	-17.79	74	53.17	46.42	13.14	56.52	156	196	P	H
		17940	46.57	-7.43	54	43.53	46.42	13.14	56.52	156	196	A	H
		4880	38.28	-35.72	74	57.58	31.2	6.83	57.33	100	0	P	V
		7320	44.45	-29.55	74	56.06	36.76	8.73	57.1	100	0	P	V
		17970	55.68	-18.32	74	51.75	47.26	13.16	56.49	150	243	P	V
		17970	47.03	-6.97	54	43.1	47.26	13.16	56.49	150	243	A	V
BLE CH 39 2480MHz		4960	39.15	-34.85	74	57.72	31.42	7.17	57.16	100	0	P	H
		7440	45.07	-28.93	74	56.83	36.82	8.7	57.28	100	0	P	H
		17970	55.47	-18.53	74	51.54	47.26	13.16	56.49	126	201	P	H
		17970	47.59	-6.41	54	43.66	47.26	13.16	56.49	126	201	A	H
		4960	39.33	-34.67	74	57.9	31.42	7.17	57.16	100	0	P	V
		7440	44.45	-29.55	74	56.21	36.82	8.7	57.28	100	0	P	V
		17970	56.01	-17.99	74	52.08	47.26	13.16	56.49	163	241	P	V
		17970	47.19	-6.81	54	43.26	47.26	13.16	56.49	163	241	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

<2Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2373	54.97	-19.03	74	41.07	27.65	14.1	27.85	114	189	P	H
		2326.485	44.66	-9.34	54	30.7	27.75	14.06	27.85	114	189	A	H
	*	2402	105.7	-	-	91.81	27.6	14.13	27.84	114	189	P	H
	*	2402	104.11	-	-	90.22	27.6	14.13	27.84	114	189	A	H
													H
													H
		2357.985	55.15	-18.85	74	41.23	27.68	14.09	27.85	283	166	P	V
		2389.905	44.6	-9.4	54	30.7	27.62	14.12	27.84	283	166	A	V
	*	2402	104.55	-	-	90.66	27.6	14.13	27.84	283	166	P	V
	*	2402	103	-	-	89.11	27.6	14.13	27.84	283	166	A	V
													V
													V
BLE CH 19 2440MHz		2317.42	55.22	-18.78	74	41.26	27.77	14.05	27.86	101	184	P	H
		2347.24	44.65	-9.35	54	30.71	27.71	14.08	27.85	101	184	A	H
	*	2440	105.66	-	-	91.81	27.52	14.16	27.83	101	184	P	H
	*	2440	103.9	-	-	90.05	27.52	14.16	27.83	101	184	A	H
		2488.66	54.24	-19.76	74	40.36	27.5	14.2	27.82	101	184	P	H
		2484.88	44.41	-9.59	54	30.53	27.5	14.2	27.82	101	184	A	H
		2367.68	54.42	-19.58	74	40.51	27.66	14.1	27.85	342	167	P	V
		2351.86	44.62	-9.38	54	30.69	27.7	14.08	27.85	342	167	A	V
	*	2440	104.65	-	-	90.8	27.52	14.16	27.83	342	167	P	V
	*	2440	102.01	-	-	88.16	27.52	14.16	27.83	342	167	A	V
		2496.5	54.48	-19.52	74	40.59	27.5	14.21	27.82	342	167	P	V
		2496.71	44.51	-9.49	54	30.62	27.5	14.21	27.82	342	167	A	V

BLE CH 39 2480MHz	*	2480	104.76	-	-	90.89	27.5	14.19	27.82	117	185	P	H
	*	2480	103.16	-	-	89.29	27.5	14.19	27.82	117	185	A	H
		2485.6	57.19	-16.81	74	43.31	27.5	14.2	27.82	117	185	P	H
		2483.52	46.15	-7.85	54	32.27	27.5	14.2	27.82	117	185	A	H
													H
													H
	*	2480	105.23	-	-	91.36	27.5	14.19	27.82	305	171	P	V
	*	2480	103.65	-	-	89.78	27.5	14.19	27.82	305	171	A	V
		2488.36	56.63	-17.37	74	42.75	27.5	14.2	27.82	305	171	P	V
		2483.52	46.41	-7.59	54	32.53	27.5	14.2	27.82	305	171	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	38.16	-35.84	74	58.03	31.11	6.51	57.49	100	0	P	H
		17910	55.81	-18.19	74	53.65	45.58	13.12	56.54	153	288	P	H
		17910	45.57	-8.43	54	43.41	45.58	13.12	56.54	153	288	A	H
													H
		4804	40.15	-33.85	74	60.02	31.11	6.51	57.49	100	0	P	V
		17955	54.95	-19.05	74	51.46	46.84	13.15	56.5	103	231	P	V
		17955	46.96	-7.04	54	43.47	46.84	13.15	56.5	103	231	A	V
													V
BLE CH 19 2440MHz		4880	38.99	-35.01	74	58.29	31.2	6.83	57.33	100	0	P	H
		7320	43.97	-30.03	74	55.58	36.76	8.73	57.1	100	0	P	H
		17970	55.76	-18.24	74	51.83	47.26	13.16	56.49	152	207	P	H
		17970	47.34	-6.66	54	43.41	47.26	13.16	56.49	152	207	A	H
		4880	38.83	-35.17	74	58.13	31.2	6.83	57.33	100	0	P	V
		7320	44.77	-29.23	74	56.38	36.76	8.73	57.1	100	0	P	V
		17970	55.9	-18.1	74	51.97	47.26	13.16	56.49	156	207	P	V
		17970	47.08	-6.92	54	43.15	47.26	13.16	56.49	156	207	A	V
BLE CH 39 2480MHz		4960	38.98	-35.02	74	57.55	31.42	7.17	57.16	100	0	P	H
		7440	43.84	-30.16	74	55.6	36.82	8.7	57.28	100	0	P	H
		17955	56.82	-17.18	74	53.33	46.84	13.15	56.5	174	219	P	H
		17955	47.01	-6.99	54	43.52	46.84	13.15	56.5	174	219	A	H
		4960	39.19	-34.81	74	57.76	31.42	7.17	57.16	100	0	P	V
		7440	44.86	-29.14	74	56.62	36.82	8.7	57.28	100	0	P	V
		17985	56.74	-17.26	74	52.37	47.68	13.17	56.48	125	209	P	V
		17985	47.65	-6.35	54	43.28	47.68	13.17	56.48	125	209	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission above 18GHz

2.4GHz BLE (SHF)

BT	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE SHF		23691	42.07	-31.93	74	42.86	39.97	12.74	53.5	150	0	P	H
													H
													H
													H
													H
													H
													H
		23502	42.11	-31.89	74	43.27	39.7	12.64	53.5	150	0	P	V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE LF		120.21	37.07	-6.43	43.5	50.72	17.56	1.03	32.24	100	0	P	H
		160.95	23.54	-19.96	43.5	38.03	16.56	1.2	32.25	-	-	P	H
		419.94	25.83	-20.17	46	32.89	22.76	1.8	31.62	-	-	P	H
		863.23	31.1	-14.9	46	30.61	28.98	2.66	31.15	-	-	P	H
		916.58	31.96	-14.04	46	31.17	29.01	2.74	30.96	-	-	P	H
		953.44	33.37	-12.63	46	30.69	30.64	2.81	30.77	-	-	P	H
													H
													H
													H
													H
													H
													H
		30.97	32.61	-7.39	40	40.11	24.21	0.52	32.23	-	-	P	V
		43.58	36.43	-3.57	40	50.46	17.61	0.63	32.27	100	171	QP	V
		77.53	29.53	-10.47	40	47.71	13.26	0.82	32.26	-	-	P	V
		118.27	32.58	-10.92	43.5	46.33	17.47	1.02	32.24	-	-	P	V
		480.08	28.53	-17.47	46	34.82	23.64	1.94	31.87	-	-	P	V
		957.32	33.17	-12.83	46	30.47	30.63	2.82	30.75	-	-	P	V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Note symbol

*	**Fundamental Frequency** which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is **over limit** line.
P/A	**P**eak or **A**verage
H/V	**H**orizontal or **V**ertical

A calculation example for radiated spurious emission is shown as below:

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =

Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Daniel Lee, Jacky Hong and Wilson Wu	**Temperature :**	20~25°C
		Relative Humidity :	50~60%

Note symbol

-L	**Low channel location**
-R	**High channel location**

<1Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Fundamental
Peak		
Avg.		

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 1	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 1
Avg	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 1	 Site : 03CH13-HY Condition : AVG_54 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 1

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Horizontal	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 2	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 2
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 2	 Site : 03CH13-HY Condition : AVG_54 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 2

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Horizontal	Fundamental
Peak		Left blank
Avg.		Left blank

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 2	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 2
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 2	 Site : 03CH13-HY Condition : AVG_54 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 2

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Vertical	Fundamental
Peak		Left blank
Avg.		Left blank

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 3	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 3
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 3	 Site : 03CH13-HY Condition : AVG_54 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 3

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 3	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 3
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 3	 Site : 03CH13-HY Condition : AVG_54 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 3

2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_9120D_1241 HORIZONTAL Detector : Peak Project : 120337 Mode : 1	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_9120D_1241 VERTICAL Detector : Peak Project : 120337 Mode : 1

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH19 2440MHz	
	Horizontal	Vertical
Peak Avg.		

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Vertical
Peak		

<2Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Fundamental
Peak		
Avg.		

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 4	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 4
Avg	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 4	 Site : 03CH13-HY Condition : AVG_54 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 4

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Horizontal	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 5	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 5
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 5	 Site : 03CH13-HY Condition : AVG_54 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 5

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Horizontal	Fundamental
Peak		Left blank
Avg.		Left blank

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 5	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 5
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 5	 Site : 03CH13-HY Condition : AVG_54 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 5

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Vertical	Fundamental
Peak		Left blank
Avg.		Left blank

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 6	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 6
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 6	 Site : 03CH13-HY Condition : AVG_54 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 6

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 6	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 6
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 6	 Site : 03CH13-HY Condition : AVG_54 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 6

2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_9120D_1241 HORIZONTAL Detector : Peak Project : 120337 Mode : 4	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_9120D_1241 VERTICAL Detector : Peak Project : 120337 Mode : 4

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH19 2440MHz	
	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 5	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 120337 Mode : 5

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Vertical
Peak		

Emission above 18GHz

2.4GHz BLE (SHF)

BLE	2.4GHz 2400~2483.5MHz	
	BLE SHF	
	Horizontal	Vertical
QP / Peak		

Emission below 1GHz

2.4GHz BLE (LF)

BLE	2.4GHz 2400~2483.5MHz	
	BLE LF	
	Horizontal	Vertical
QP / Peak	 Site : 03CH13-HY Condition : QP 3m BILOG_40103 HORIZONTAL Detector : Peak Project : 120337 Mode : 7	 Site : 03CH13-HY Condition : QP 3m BILOG_40103 VERTICAL Detector : Peak Project : 120337 Mode : 7

Annex. A Receiver Radiated Emission Measurement

A.1 Limit of Receiver Radiated Emission

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

A.2 Measuring Instruments

See list of measuring equipment of this test report.

A.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dBμV/m) = 20 log Emission level (μV/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

A.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



A.5 Test Result of Receiver Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per NCC LP0002 section 6.13 was not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

A.6 Connection Diagram of Test System



A.7 EUT Operation Test Setup

The RF test items, utility “ComplianceTool V1.0.0.87” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, data rate (MCS0) and the application type and for continuous receiving signals.

A.8 Test Result of Receiver Radiated Spurious Emission (30MHz ~ 5th Harmonic)

Test Engineer :	Daniel Lee, Jacky Hong and Wilson Wu	**Temperature :**	20~25°C
		Relative Humidity :	50~60%
Frequency :	117.300 MHz	**Margin :**	Under 6.02 dB
Test Mode :	WLAN (2.4GHz) Rx + Bluetooth-LE RX		

	Idle Mode	
	Horizontal	**Vertical**
Peak **Avg.**	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_9120D_1241 HORIZONTAL Detector : Peak Project : 120337 Mode : 21 1 117.30 37.48 -6.02 43.50 51.27 17.43 0.95 32.24 100 15 QP 2 129.91 32.57 -10.93 43.50 46.14 17.61 0.99 32.24 --- --- Peak 3 161.92 28.52 -14.98 43.50 43.01 16.55 1.11 32.25 --- --- Peak 4 714.82 28.52 -17.48 46.00 31.32 26.77 2.27 31.97 --- --- Peak 5 770.11 30.53 -15.47 46.00 31.55 28.03 2.36 31.55 --- --- Peak 6 951.50 33.57 -12.43 46.00 30.98 30.57 2.59 30.78 --- --- Peak 7 1464.00 34.40 -39.60 74.00 63.07 25.72 3.59 57.98 --- --- Peak 8 2600.00 36.34 -37.66 74.00 61.48 27.50 4.72 57.36 --- --- Peak 9 4245.00 39.87 -34.13 74.00 61.16 30.17 6.80 58.26 --- --- Peak 10 8760.00 46.71 -27.29 74.00 55.85 38.30 8.79 56.23 --- --- Peak 11 13800.00 48.69 -25.31 74.00 54.80 40.10 10.88 57.09 --- --- Peak 12 17670.00 49.75 -24.25 74.00 52.16 42.12 12.19 56.72 100 0 Peak	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_9120D_1241 VERTICAL Detector : Peak Project : 120337 Mode : 21 1 45.52 29.15 -10.85 40.00 44.03 16.76 0.61 32.28 100 0 Peak 2 117.30 31.59 -11.91 43.50 45.38 17.43 0.95 32.24 --- --- Peak 3 155.13 26.29 -17.21 43.50 40.41 16.95 1.08 32.25 --- --- Peak 4 480.08 28.05 -17.95 46.00 34.34 23.64 1.86 31.87 --- --- Peak 5 868.08 32.63 -13.37 46.00 32.15 28.96 2.50 31.14 --- --- Peak 6 960.00 33.97 -12.03 46.00 31.33 30.55 2.61 30.74 --- --- Peak 7 1940.00 34.93 -39.07 74.00 62.69 25.86 4.02 57.64 --- --- Peak 8 2946.00 37.51 -36.49 74.00 61.58 28.39 5.12 57.58 --- --- Peak 9 5820.00 39.83 -34.17 74.00 55.91 32.18 7.05 55.31 --- --- Peak 10 9750.00 47.56 -26.44 74.00 55.54 39.40 9.36 56.74 --- --- Peak 11 13755.00 48.80 -25.20 74.00 54.94 40.06 10.87 57.07 100 0 Peak 12 17445.00 48.77 -25.23 74.00 52.62 40.83 12.06 56.74 --- --- Peak

<Receiver Radiated Emission>

LF



HF



Annex. B Maximum Power Density

B.1 RF Exposure Limit Introduction

According to NCC LP0002, the criteria listed in Table shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §5.20.2.1 and §5.20.2.2.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm^2)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f2)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f2)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:
S = Power Density
P = Output Power at Antenna Terminals
G = Gain of Transmit Antenna (linear gain)
R = Distance from Transmitting Antenna

B.2 Standalone Power Density Calculation

Maximum Power Density				
Max. Power	Gain	EIRP	20 cm PSD	Limit
10.6	3.21	13.81	0.0048	1
dBm	dBi	dBm	mW/cm^2	mW/cm^2

Appendix E. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
Bluetooth –LE for 1Mbps	61.6	385	2.60	3kHz	2.10
Bluetooth –LE for 2Mbps	57.07	1070	0.93	1kHz	2.44

Bluetooth –LE for 1Mbps



Bluetooth –LE for 2Mbps