



SAR TEST REPORT

No. I15Z42998-SEM01

For

TCL Communication Ltd.

GSM Quad-band / UMTS Tril-band / LTE 5-band mobile phone

Model name: 5056O

With

Hardware Version: 04

Software Version: vH55

FCC ID: 2ACCJB043

Issued Date: 2016-1-27



中国认可
国际互认
检测
TESTING
CNAS L0570

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:

CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT
No. 51 Shouxiang Science Building, Xueyuan Road, Haidian District, Beijing, P. R. China100191
Tel:+86(0)10-62304633-2512,Fax:+86(0)10-62304633-2504

Email:cttl_terminals@catr.cn, website:www.chinattl.com

REPORT HISTORY

Report Number	Revision	Issue Date	Description
I15Z42998-SEM01	Rev.0	2016-1-19	Initial creation of test report
I15Z42998-SEM01	Rev.1	2016-1-26	Update the frequency of LTE Band30, and add the data of WCDMA850 body.
I15Z42998-SEM01	Rev.2	2016-1-27	Update the table of page61

TABLE OF CONTENT

1 TEST LABORATORY	5
1.1 TESTING LOCATION	5
1.2 TESTING ENVIRONMENT.....	5
1.3 PROJECT DATA	5
1.4 SIGNATURE.....	5
2 STATEMENT OF COMPLIANCE	6
3 CLIENT INFORMATION	8
3.1 APPLICANT INFORMATION	8
3.2 MANUFACTURER INFORMATION	8
4 EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	9
4.1 ABOUT EUT	9
4.2 INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	9
4.3 INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	9
5 TEST METHODOLOGY	10
5.1 APPLICABLE LIMIT REGULATIONS	10
5.2 APPLICABLE MEASUREMENT STANDARDS.....	10
6 SPECIFIC ABSORPTION RATE (SAR).....	11
6.1 INTRODUCTION.....	11
6.2 SAR DEFINITION	11
7 TISSUE SIMULATING LIQUIDS	12
7.1 TARGETS FOR TISSUE SIMULATING LIQUID	12
7.2 DIELECTRIC PERFORMANCE	12
8 SYSTEM VERIFICATION	19
8.1 SYSTEM SETUP.....	19
8.2 SYSTEM VERIFICATION.....	20
9 MEASUREMENT PROCEDURES	21
9.1 TESTS TO BE PERFORMED	21
9.2 GENERAL MEASUREMENT PROCEDURE.....	23
9.3 WCDMA MEASUREMENT PROCEDURES FOR SAR	24
9.4 SAR MEASUREMENT FOR LTE.....	25
9.5 BLUETOOTH & WI-FI MEASUREMENT PROCEDURES FOR SAR	25
9.6 POWER DRIFT.....	26
10 AREA SCAN BASED 1-G SAR.....	26
10.1 REQUIREMENT OF KDB.....	26
10.2 FAST SAR ALGORITHMS	26
11 CONDUCTED OUTPUT POWER.....	27

11.1 MANUFACTURING TOLERANCE	27
11.2 HOTSPOT	32
11.3 GSM MEASUREMENT RESULT	33
11.4 WCDMA MEASUREMENT RESULT.....	34
11.5 LTE MEASUREMENT RESULT	35
11.6 Wi-Fi AND BT MEASUREMENT RESULT	47
12 SIMULTANEOUS TX SAR CONSIDERATIONS.....	50
12.1 INTRODUCTION.....	50
12.2 TRANSMIT ANTENNA SEPARATION DISTANCES	50
12.3 SAR MEASUREMENT POSITIONS	50
12.4 STANDALONE SAR TEST EXCLUSION CONSIDERATIONS	51
13 EVALUATION OF SIMULTANEOUS.....	51
14 SAR TEST RESULT	53
14.1 SAR RESULTS FOR FAST SAR.....	53
14.2 SAR RESULTS FOR STANDARD PROCEDURE.....	62
14.3 WLAN EVALUATION	67
15 SAR MEASUREMENT VARIABILITY.....	76
16 MEASUREMENT UNCERTAINTY	77
16.1 MEASUREMENT UNCERTAINTY FOR NORMAL SAR TESTS (300MHz~3GHz)	77
16.2 MEASUREMENT UNCERTAINTY FOR NORMAL SAR TESTS (3~6GHz)	78
16.3 MEASUREMENT UNCERTAINTY FOR FAST SAR TESTS (300MHz~3GHz)	79
16.4 MEASUREMENT UNCERTAINTY FOR FAST SAR TESTS (3~6GHz).....	80
17 MAIN TEST INSTRUMENTS.....	81
ANNEX A GRAPH RESULTS.....	82
ANNEX B SYSTEM VERIFICATION RESULTS	140
ANNEX C SAR MEASUREMENT SETUP	159
ANNEX D POSITION OF THE WIRELESS DEVICE IN RELATION TO THE PHANTOM	165
ANNEX E EQUIVALENT MEDIA RECIPES.....	168
ANNEX F SYSTEM VALIDATION	169
ANNEX G PROBE CALIBRATION CERTIFICATE.....	170
ANNEX H DIPOLE CALIBRATION CERTIFICATE	181
ANNEX I ACCREDITATION CERTIFICATE.....	237

1 Test Laboratory

1.1 Testing Location

Company Name:	CTTL(Shouxiang)
Address:	No. 51 Shouxiang Science Building, Xueyuan Road, Haidian District, Beijing, P. R. China100191

1.2 Testing Environment

Temperature:	18°C~25 °C,
Relative humidity:	30%~ 70%
Ground system resistance:	< 0.5 Ω
Ambient noise & Reflection:	< 0.012 W/kg


1.3 Project Data

Project Leader:	Qi Dianyuan
Test Engineer:	Lin Xiaojun
Testing Start Date:	December 25, 2015
Testing End Date:	January 11, 2016

1.4 Signature



Lin Xiaojun
(Prepared this test report)



Qi Dianyuan
(Reviewed this test report)



Xiao Li
Deputy Director of the laboratory
(Approved this test report)

2 Statement of Compliance

The maximum results of SAR found during testing for TCL Communication Ltd. GSM Quad-band / UMTS Tri-band / LTE 5-band mobile phone 5056O are as follows:

Table 2.1: Highest Reported SAR (1g)

Exposure Configuration	Technology Band	Highest Reported SAR 1g (W/Kg)	Equipment Class
Head (Separation Distance 0mm)	GSM 850	0.37	PCE
	PCS 1900	0.12	
	UMTS FDD 2	0.35	
	UMTS FDD 4	0.25	
	UMTS FDD 5	0.17	
	LTE Band 2	0.16	
	LTE Band 4	0.26	
	LTE Band 5	0.39	
	LTE Band 12	0.23	
	LTE Band 30	0.34	
	WLAN 2.4 GHz	0.35	DTS
	WLAN 5 GHz	0.36	UNII
Hotspot (Separation Distance 10mm)	GSM 850	0.96	PCE
	PCS 1900	1.16	
	UMTS FDD 2	0.59	
	UMTS FDD 4	1.40	
	UMTS FDD 5	1.02	
	LTE Band 2	1.07	
	LTE Band 4	1.01	
	LTE Band 5	0.62	
	LTE Band 12	0.47	
	LTE Band 30	0.55	
	WLAN 2.4 GHz	0.12	DTS
	WLAN 5 GHz	0.36	UNII
Body-worn (Data) (Separation Distance 15mm)	LTE Band 30	0.25	PCE

The SAR values found for the Mobile Phone are below the maximum recommended levels of 1.6 W/Kg as averaged over any 1g tissue according to the ANSI C95.1-1992.

For body worn operation, this device has been tested and meets FCC RF exposure guidelines when used with any accessory that contains no metal and which provides a minimum separation distance of 10 mm for hotspot on and 15mm for hotspot off and speech between this device and the body of the user. Use of other accessories may not ensure compliance with FCC RF exposure guidelines.

The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power output.

The measurement together with the test system set-up is described in annex C of this test report. A detailed description of the equipment under test can be found in chapter 4 of this test report.

The highest reported SAR value is obtained at the case of **(Table 2.1)**, and the values are: **1.40 W/kg (1g)**.

Table 2.2: The sum of reported SAR values for main antenna and WLAN

	Position	Main antenna	WLAN	Sum	Distance (mm)	Ratio
Maximum reported SAR value for Head	Left hand, Touch cheek	0.34	0.36	0.70	/	/
	Right hand, Touch cheek	0.39	0.13	0.52	/	/
Maximum reported SAR value for Body	Rear	1.40	0.36	1.76	149.3	0.02
			0.32	1.72	152.6	0.01

According to the KDB 447498 D01, when the sum of SAR is larger than the limit, SAR test exclusion is determined by the SAR to peak location separation ratio. The ratio is determined by $(SAR1 + SAR2)^{1.5}/R_i$, rounded to two decimal digits, and must be ≤ 0.04 for all antenna pairs in the configuration to qualify for 1-g SAR test exclusion.

Table 2.3: The sum of reported SAR values for main antenna and Bluetooth

	Position	Main antenna	BT*	Sum
Highest reported SAR value for Head	Right hand, Touch cheek	0.39	0.21	0.60
Highest reported SAR value for Body	Rear	1.40	0.10	1.50

BT* - Estimated SAR for Bluetooth (see the table 13.3)

According to the above tables, the highest sum of reported SAR values is **1.76 W/kg (1g)**. The detail for simultaneous transmission consideration is described in chapter 13.

3 Client Information

3.1 Applicant Information

Company Name:	TCL Communication Ltd.
Address /Post:	5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai, P.R. China. 201203
City:	Shanghai
Postal Code:	201203
Country:	China
Contact Person:	Gong Zhizhou
Email:	zhizhou.gong@tcl.com
Telephone:	0086-21-51798260
Fax:	0086-21-61460602

3.2 Manufacturer Information

Company Name:	TCL Communication Ltd.
Address /Post:	5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai, P.R. China. 201203
City:	Shanghai
Postal Code:	201203
Country:	China
Contact Person:	Gong Zhizhou
Email:	zhizhou.gong@tcl.com
Telephone:	0086-21-51798260
Fax:	0086-21-61460602

4 Equipment Under Test (EUT) and Ancillary Equipment (AE)

4.1 About EUT

Description:	GSM Quad-band / UMTS Tri-band / LTE 5-band mobile phone
Model name:	5056O
Operating mode(s):	GSM 850/900/1800/1900, WCDMA 850/1700/1900 BT, Wi-Fi, LTE Band 2/4/5/12/30
Tested Tx Frequency:	825 – 848.8 MHz (GSM 850)
	1850.2 – 1910 MHz (GSM 1900)
	826.4–846.6 MHz (WCDMA850 Band V)
	1712.4 – 1752.6 MHz (WCDMA 1700 Band IV)
	1852.4–1907.6 MHz (WCDMA1900 Band II)
	1860 – 1900 MHz (LTE Band 2)
	1720 – 1745 MHz (LTE Band 4)
	824.7 – 848.3 MHz (LTE Band 5)
	699.7 – 715.3 MHz (LTE Band 12)
	2307.5 – 2310 MHz (LTE Band 30)
	2412 – 2462 MHz (Wi-Fi 2.4G)
	5200 – 5600 MHz (Wi-Fi 5G)
GPRS/EGPRS Multislot Class:	33
GPRS capability Class:	B
Test device Production information:	Production unit
Device type:	Portable device
Antenna type:	Integrated antenna
Accessories/Body-worn configurations:	Headset
Hotspot mode:	Support simultaneous transmission of hotspot and voice(or data)

4.2 Internal Identification of EUT used during the test

EUT ID*	IMEI	HW	SW Version
EUT1	014584000004249	04	vH55
EUT2	014584000003548	04	vH55
EUT3	014584000003563	04	vH55
EUT4	014584000003555	04	vH55

*EUT ID: is used to identify the test sample in the lab internally.

Note: It is performed to test SAR with the EUT1&2 and conducted power with the EUT3&4.

4.3 Internal Identification of AE used during the test

AE ID*	Description	Model	SN	Manufacturer
AE1	Battery	CAC2500037C2	/	SCUD

*AE ID: is used to identify the test sample in the lab internally.

5 TEST METHODOLOGY

5.1 Applicable Limit Regulations

ANSI C95.1–1992: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

It specifies the maximum exposure limit of **1.6 W/kg** as averaged over any 1 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.

5.2 Applicable Measurement Standards

IEEE 1528–2013: Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.

KDB447498 D01: General RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

KDB648474 D04 Handset SAR v01r03: SAR Evaluation Considerations for Wireless Handsets.

KDB941225 D01 SAR test for 3G devices v03r01: SAR Measurement Procedures for 3G Devices

KDB941225 D05 SAR for LTE Devices v02r05: SAR Evaluation Considerations for LTE Devices

KDB941225 D06 Hotspot Mode SAR v02r01: SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities

KDB248227 D01 802.11 Wi-Fi SAR v02r02: SAR GUIDANCE FOR IEEE 802.11 (Wi-Fi) TRANSMITTERS

KDB865664 D01 SAR measurement 100 MHz to 6 GHz v01r04: SAR Measurement Requirements for 100 MHz to 6 GHz.

KDB865664 D02 RF Exposure Reporting v01r02: RF Exposure Compliance Reporting and Documentation Considerations

6 Specific Absorption Rate (SAR)

6.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

6.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$SAR = c \left(\frac{\delta T}{\delta t} \right)$$

Where: C is the specific heat capacity, δT is the temperature rise and δt is the exposure duration, or related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

7 Tissue Simulating Liquids

7.1 Targets for tissue simulating liquid

Table 7.1: Targets for tissue simulating liquid


Frequency(MHz)	Liquid Type	Conductivity(σ)	$\pm 5\%$ Range	Permittivity(ϵ)	$\pm 5\%$ Range
750	Head	0.89	0.85~0.93	41.94	39.8~44.0
750	Body	0.96	0.91~1.01	55.5	52.7~58.3
835	Head	0.90	0.86~0.95	41.5	39.4~43.6
835	Body	0.97	0.92~1.02	55.2	52.4~58.0
1750	Head	1.37	1.30~1.44	40.08	38.1~42.1
1750	Body	1.49	1.42~1.56	53.4	50.7~56.1
1900	Head	1.40	1.33~1.47	40.0	38.0~42.0
1900	Body	1.52	1.44~1.60	53.3	50.6~56.0
2450	Head	1.80	1.71~1.89	39.2	37.2~41.2
2450	Body	1.95	1.85~2.05	52.7	50.1~55.3
5200	Head	4.66	4.43~4.89	35.99	34.19~37.79
5200	Body	5.30	5.04~5.56	49.0	46.6~51.4
5300	Head	4.76	4.52~5.00	35.87	34.08~37.66
5300	Body	5.42	5.15~5.69	48.9	46.46~51.34
5600	Head	5.07	4.82~5.32	35.53	33.75~37.31
5600	Body	5.77	5.48~6.06	48.5	46.08~50.92
5800	Head	5.27	5.01~5.53	35.3	33.5~37.1
5800	Body	6.00	5.70~6.30	48.2	45.8~50.6

7.2 Dielectric Performance

Table 7.2: Dielectric Performance of Tissue Simulating Liquid

Measurement Date (yyyy-mm-dd)	Type	Frequency	Permittivity ϵ	Drift (%)	Conductivity σ (S/m)	Drift (%)
2015-12-25	Head	750 MHz	43.08	2.72	0.912	2.47
	Body	750 MHz	56.98	2.67	0.946	-1.46
2015-12-26	Head	835 MHz	41.12	-0.92	0.921	2.33
	Body	835 MHz	56.23	1.87	0.972	0.21
2015-12-27	Head	1750 MHz	39.53	-1.37	1.331	-2.85
	Body	1750 MHz	52.7	-1.31	1.472	-1.21
2015-12-28	Head	1900 MHz	39.78	-0.55	1.427	1.93
	Body	1900 MHz	54.05	1.41	1.55	1.97
2015-12-29	Head	2450 MHz	38.01	-3.04	1.822	1.22
	Body	2450 MHz	51.63	-2.03	1.974	1.23
2016-1-11	Head	5200 MHz	36.7	1.97	4.64	-0.43
	Body	5200 MHz	50.47	3.00	5.107	-3.64
	Head	5300 MHz	36.65	2.17	4.754	-0.13
	Body	5300 MHz	50.17	2.60	5.274	-2.69
	Head	5600 MHz	35.92	1.10	5.061	-0.18
	Body	5600 MHz	49.48	2.02	5.728	-0.73
	Head	5800 MHz	35.54	0.68	5.29	0.38
	Body	5800 MHz	48.99	1.64	6.055	0.92

Note: The liquid temperature is 22.0 °C



Picture 7-1: Liquid depth in the Head Phantom (750 MHz)



Picture 7-2: Liquid depth in the Flat Phantom (750 MHz)




Picture 7-3: Liquid depth in the Head Phantom (835 MHz)




Picture 7-4: Liquid depth in the Flat Phantom (835 MHz)



Picture 7-5: Liquid depth in the Head Phantom (1750 MHz)




Picture 7-6 Liquid depth in the Flat Phantom (1750MHz)



Picture 7-7: Liquid depth in the Head Phantom (1900 MHz)



Picture 7-8 Liquid depth in the Flat Phantom (1900MHz)



Picture 7-9 Liquid depth in the Head Phantom (2450MHz)



Picture 7-10 Liquid depth in the Flat Phantom (2450MHz)



Picture 7-11 Liquid depth in the Head Phantom (5GHz)




Picture 7-12 Liquid depth in the Flat Phantom (5GHz)

8 System verification

8.1 System Setup

In the simplified setup for system evaluation, the DUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



Picture 8.1 System Setup for System Evaluation



Picture 8.2 Photo of Dipole Setup

8.2 System Verification

SAR system verification is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device.

The system verification results are required that the area scan estimated 1-g SAR is within 3% of the zoom scan 1-g SAR. The details are presented in annex B.

Table 8.1: System Verification of Head

Measurement Date (yyyy-mm-dd)	Frequency	Target value (W/kg)		Measured value (W/kg)		Deviation	
		10 g Average	1 g Average	10 g Average	1 g Average	10 g Average	1 g Average
2015-12-25	750 MHz	5.36	8.2	5.4	8.28	0.75%	0.98%
2015-12-26	835 MHz	5.86	9.01	6	9.24	2.39%	2.55%
2015-12-27	1750 MHz	19.9	36.9	19.56	36.44	-1.71%	-1.25%
2015-12-28	1900 MHz	21.5	40.7	21.96	41.64	2.14%	2.31%
2015-12-29	2450 MHz	24.5	52.5	24.48	52.44	-0.08%	-0.11%
2016-1-11	5200 MHz	22.3	77.8	23.2	81.8	4.04%	4.11%
	5300 MHz	23.4	81.6	23.8	82.3	1.71%	0.86%
	5600 MHz	23.5	82.6	24.2	85.1	2.98%	3.03%
	5800 MHz	22.5	79	22.1	78.2	-1.78%	-1.01%

Table 8.2: System Verification of Body

Measurement Date (yyyy-mm-dd)	Frequency	Target value (W/kg)		Measured value (W/kg)		Deviation	
		10 g Average	1 g Average	10 g Average	1 g Average	10 g Average	1 g Average
2015-12-25	750 MHz	5.68	8.64	5.8	8.84	2.11%	2.31%
2015-12-26	835 MHz	6.12	9.29	6.2	9.36	1.31%	0.75%
2015-12-27	1750 MHz	20.3	37.4	20.08	37.4	-1.08%	0.00%
2015-12-28	1900 MHz	21.7	40.4	22.04	41.44	1.57%	2.57%
2015-12-29	2450 MHz	24.4	52.1	23.92	50.76	-1.97%	-2.57%
2016-1-11	5200 MHz	21.2	75.9	21.2	74.8	0.00%	-1.45%
	5300 MHz	21.5	76.8	21.6	76	0.47%	-1.04%
	5600 MHz	22.8	82.2	22.5	81.4	-1.32%	-0.97%
	5800 MHz	21.8	78.5	21.4	76.1	-1.83%	-3.06%

9 Measurement Procedures

9.1 Tests to be performed

In order to determine the highest value of the peak spatial-average SAR of a handset, all device positions, configurations and operational modes shall be tested for each frequency band according to steps 1 to 3 below. A flowchart of the test process is shown in picture 9.1.


Step 1: The tests described in 9.2 shall be performed at the channel that is closest to the centre of the transmit frequency band (f_c) for:

- a) all device positions (cheek and tilt, for both left and right sides of the SAM phantom, as described in annex D),
- b) all configurations for each device position in a), e.g., antenna extended and retracted, and
- c) all operational modes, e.g., analogue and digital, for each device position in a) and configuration in b) in each frequency band.

If more than three frequencies need to be tested according to 11.1 (i.e., $N_c > 3$), then all frequencies, configurations and modes shall be tested for all of the above test conditions.

Step 2: For the condition providing highest peak spatial-average SAR determined in Step 1, perform all tests described in 9.2 at all other test frequencies, i.e., lowest and highest frequencies. In addition, for all other conditions (device position, configuration and operational mode) where the peak spatial-average SAR value determined in Step 1 is within 3 dB of the applicable SAR limit, it is recommended that all other test frequencies shall be tested as well.

Step 3: Examine all data to determine the highest value of the peak spatial-average SAR found in Steps 1 to 2.



Picture 9.1 Block diagram of the tests to be performed

9.2 General Measurement Procedure

The area and zoom scan resolutions specified in the table below must be applied to the SAR measurements and fully documented in SAR reports to qualify for TCB approval. Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1-g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2003. The results should be documented as part of the system validation records and may be requested to support test results when all the measurement parameters in the following table are not satisfied.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <u>reported</u> SAR from the area scan based 1-g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

9.3 WCDMA Measurement Procedures for SAR

The following procedures are applicable to WCDMA handsets operating under 3GPP Release99, Release 5 and Release 6. The default test configuration is to measure SAR with an established radio link between the DUT and a communication test set using a 12.2kbps RMC (reference measurement channel) configured in Test Loop Mode 1. SAR is selectively confirmed for other physical channel configurations (DPCCH & DPDCH_n), HSDPA and HSPA (HSUPA/HSDPA) modes according to output power, exposure conditions and device operating capabilities. Both uplink and downlink should be configured with the same RMC or AMR, when required. SAR for Release 5 HSDPA and Release 6 HSPA are measured using the applicable FRC (fixed reference channel) and E-DCH reference channel configurations. Maximum output power is verified according to applicable versions of 3GPP TS 34.121 and SAR must be measured according to these maximum output conditions. When Maximum Power Reduction (MPR) is not implemented according to Cubic Metric (CM) requirements for Release 6 HSPA, the following procedures do not apply.

For Release 5 HSDPA Data Devices:

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	β_{hs}	CM/dB
1	2/15	15/15	64	2/15	4/15	0.0
2	12/15	15/15	64	12/15	24/25	1.0
3	15/15	8/15	64	15/8	30/15	1.5
4	15/15	4/15	64	15/4	30/15	1.5

For Release 6 HSPA Data Devices

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	β_{hs}	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM (dB)	MPR (dB)	AG Index	E-TFCI
1	11/15	15/15	64	11/15	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	12/15	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}:47/15$ $\beta_{ed2}:47/15$	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	4/15	56/75	4	1	3.0	2.0	17	71
5	15/15	15/15	64	15/15	24/15	30/15	134/15	4	1	1.0	0.0	21	81

9.4 SAR Measurement for LTE

SAR tests for LTE are performed with a base station simulator, Rohde & Schwarz CMW500. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. All powers were measured with the CMW 500.

It is performed for conducted power and SAR based on the KDB941225 D05.

SAR is evaluated separately according to the following procedures for the different test positions in each exposure condition – head, body, body-worn accessories and other use conditions. The procedures in the following subsections are applied separately to test each LTE frequency band.

1) QPSK with 1 RB allocation

Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

2) QPSK with 50% RB allocation

The procedures required for 1 RB allocation in 1) are applied to measure the SAR for QPSK with 50% RB allocation.

3) QPSK with 100% RB allocation

For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation in 1) and 2) are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

9.5 Bluetooth & Wi-Fi Measurement Procedures for SAR

Normal network operating configurations are not suitable for measuring the SAR of 802.11 transmitters in general. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure that the results are consistent and reliable.

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in a test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

9.6 Power Drift

To control the output power stability during the SAR test, DASY4 system calculates the power drift by measuring the E-field at the same location at the beginning and at the end of the measurement for each test position. These drift values can be found in section 14 labeled as: (Power Drift [dB]). This ensures that the power drift during one measurement is within 5%.

10 Area Scan Based 1-g SAR

10.1 Requirement of KDB

According to the KDB447498 D01 v05, when the implementation is based the specific polynomial fit algorithm as presented at the 29th Bioelectromagnetics Society meeting (2007) and the estimated 1-g SAR is ≤ 1.2 W/kg, a zoom scan measurement is not required provided it is also not needed for any other purpose; for example, if the peak SAR location required for simultaneous transmission SAR test exclusion can be determined accurately by the SAR system or manually to discriminate between distinctive peaks and scattered noisy SAR distributions from area scans.

There must not be any warning or alert messages due to various measurement concerns identified by the SAR system; for example, noise in measurements, peaks too close to scan boundary, peaks are too sharp, spatial resolution and uncertainty issues etc. The SAR system verification must also demonstrate that the area scan estimated 1-g SAR is within 3% of the zoom scan 1-g SAR (See Annex B). When all the SAR results for each exposure condition in a frequency band and wireless mode are based on estimated 1-g SAR, the 1-g SAR for the highest SAR configuration must be determined by a zoom scan.

10.2 Fast SAR Algorithms

The approach is based on the area scan measurement applying a frequency dependent attenuation parameter. This attenuation parameter was empirically determined by analyzing a large number of phones. The MOTOROLA FAST SAR was developed and validated by the MOTOROLA Research Group in Ft. Lauderdale.

In the initial study, an approximation algorithm based on Linear fit was developed. The accuracy of the algorithm has been demonstrated across a broad frequency range (136-2450 MHz) and for both 1- and 10-g averaged SAR using a sample of 264 SAR measurements from 55 wireless handsets. For the sample size studied, the root-mean-squared errors of the algorithm are 1.2% and 5.8% for 1- and 10-g averaged SAR, respectively. The paper describing the algorithm in detail is expected to be published in August 2004 within the Special Issue of Transactions on MTT.

In the second step, the same research group optimized the fitting algorithm to an Polynomial fit whereby the frequency validity was extended to cover the range 30-6000MHz. Details of this study can be found in the BEMS 2007 Proceedings.

Both algorithms are implemented in DASY software.

11 Conducted Output Power

When WLAN Hotspot mode is activated (AP ON), the conducted output power will be reduced for LTE band 30. When WLAN Hotspot mode is deactivated (AP OFF), the RF output power level return to their normal RF power level.

11.1 Manufacturing tolerance

When the hotspot mode is ON:

Table 11.1: LTE

Mode	Target (dBm)	Tune-up (dBm)
LTE Band 30	21	22

Note: When the hotspot mode is ON, MPR settings doesn't work.

When the hotspot mode is OFF:

Table 11.2: GSM Speech

GSM 850			
Channel	Channel 251	Channel 190	Channel 128
Target (dBm)	32.5	32.5	32.5
Tune-up (dBm)	33.5	33.5	33.5
GSM 1900			
Channel	Channel 810	Channel 661	Channel 512
Target (dBm)	29	29	29
Tune-up (dBm)	30	30	30

Table 11.3: GPRS and EGPRS

GSM 850 GPRS (GMSK)				
Channel		251	190	128
1 Txslot	Target (dBm)	32.5	32.5	32.5
	Tune-up (dBm)	33.5	33.5	33.5
2 Txslots	Target (dBm)	31	31	31
	Tune-up (dBm)	32	32	32
3 Txslots	Target (dBm)	29	29	29
	Tune-up (dBm)	30	30	30
4 Txslots	Target (dBm)	28	28	28
	Tune-up (dBm)	29	29	29
GSM 850 EGPRS (GMSK)				
Channel		251	190	128
1 Txslot	Target (dBm)	32.5	32.5	32.5
	Tune-up (dBm)	33.5	33.5	33.5
2 Txslots	Target (dBm)	31	31	31
	Tune-up (dBm)	32	32	32
3 Txslots	Target (dBm)	29	29	29
	Tune-up (dBm)	30	30	30

4 Txslots	Target (dBm)	28	28	28
	Tune-up (dBm)	29	29	29
GSM 850 EGPRS (8PSK)				
Channel		251	190	128
1 Txslot	Target (dBm)	26.5	26.5	26.5
	Tune-up (dBm)	27.5	27.5	27.5
2 Txslots	Target (dBm)	25.5	25.5	25.5
	Tune-up (dBm)	26.5	26.5	26.5
3 Txslots	Target (dBm)	24	24	24
	Tune-up (dBm)	25	25	25
4 Txslots	Target (dBm)	22	22	22
	Tune-up (dBm)	23	23	23
GSM 1900 GPRS (GMSK)				
Channel		810	661	512
1 Txslot	Target (dBm)	29	29	29
	Tune-up (dBm)	30	30	30
2 Txslots	Target (dBm)	28	28	28
	Tune-up (dBm)	29	29	29
3 Txslots	Target (dBm)	26.5	26.5	26.5
	Tune-up (dBm)	27.5	27.5	27.5
4 Txslots	Target (dBm)	25.5	25.5	25.5
	Tune-up (dBm)	26.5	26.5	26.5
GSM 1900 EGPRS (GMSK)				
Channel		810	661	512
1 Txslot	Target (dBm)	29	29	29
	Tune-up (dBm)	30	30	30
2 Txslots	Target (dBm)	27.5	27.5	27.5
	Tune-up (dBm)	28.5	28.5	28.5
3 Txslots	Target (dBm)	26.5	26.5	26.5
	Tune-up (dBm)	27.5	27.5	27.5
4 Txslots	Target (dBm)	25.5	25.5	25.5
	Tune-up (dBm)	26.5	26.5	26.5
GSM 1900 EGPRS (8PSK)				
Channel		810	661	512
1 Txslot	Target (dBm)	25	25	25
	Tune-up (dBm)	26	26	26
2 Txslots	Target (dBm)	24.5	24.5	24.5
	Tune-up (dBm)	25.5	25.5	25.5
3 Txslots	Target (dBm)	23	23	23
	Tune-up (dBm)	24	24	24
4 Txslots	Target (dBm)	21.5	21.5	21.5
	Tune-up (dBm)	22.5	22.5	22.5

Table 11.4: WCDMA

WCDMA 850 CS			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	22.5	22.5	22.5
Tune-up (dBm)	23.5	23.5	23.5
WCDMA 1700 CS			
Channel	Channel 1513	Channel 1412	Channel 1312
Target (dBm)	23	23	23
Tune-up (dBm)	24	24	24
WCDMA 1900 CS			
Channel	Channel 9538	Channel 9400	Channel 9262
Target (dBm)	22	22	22
Tune-up (dBm)	23	23	23

Item	band	FDD V result			
	ARFCN	Channel	4132	4182	4233
HSUPA	1&5	Target (dBm)	22	22	22
		Tune-up(dBm)	23	23	23
	2-4	Target (dBm)	21	21	21
		Tune-up(dBm)	22	22	22
DC-HSDPA	1-4	Target (dBm)	22	22	22
		Tune-up(dBm)	23	23	23
Item	band	FDD IV result			
	ARFCN	Channel	1312	1412	1512
HSUPA	1&5	Target (dBm)	22	22	22
		Tune-up(dBm)	23	23	23
	2&4	Target (dBm)	21	21	21
		Tune-up(dBm)	22	22	22
	3	Target (dBm)	21.5	21.5	21.5
		Tune-up(dBm)	22.5	22.5	22.5
DC-HSDPA	1-4	Target (dBm)	22	22	22
		Tune-up(dBm)	23	23	23
Item	band	FDD II result			
	ARFCN	Channel	9262	9400	9538
HSUPA	1&4&5	Target (dBm)	21	21	21
		Tune-up(dBm)	22	22	22
	2	Target (dBm)	20.5	20.5	20.5
		Tune-up(dBm)	21.5	21.5	21.5
	3	Target (dBm)	20	20	20
		Tune-up(dBm)	21	21	21
DC-HSDPA	1-4	Target (dBm)	21.5	21.5	21.5
		Tune-up(dBm)	22.5	22.5	22.5

Table 11.5: LTE

Mode	Target (dBm)	Tune-up (dBm)
LTE Band 2	22.4	23.4
LTE Band 4	22.5	23.5
LTE Band 5	23	24
LTE Band 12	23	24
LTE Band 30	22	23

LTE MPR will follow up 3GPP setting as below:

Modulation	Channel bandwidth / Transmission bandwidth (NRB)						MPR (dB)
	1.4MHz	3.0MHz	5MHz	10MHz	15MHz	20MHz	
QPSK	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	0
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	2

Table 11.6: Bluetooth

GFSK			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	6	6	6
Tune-up (dBm)	7	7	7

Table 11.7: WiFi

WiFi 802.11b (2.4GHz)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	16	16	16
Tune-up (dBm)	17	17	17
WiFi 802.11g (2.4GHz) (Rate 6M-54M)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	12.5	12.5	12.5
Tune-up (dBm)	13.5	13.5	13.5
WiFi 802.11n HT20 (2.4GHz) (MCS0-MCS1)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	12	12	12
Tune-up (dBm)	13	13	13
WiFi 802.11n HT20 (2.4GHz) (MCS2-MCS3)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	12	12	12
Tune-up (dBm)	13	13	13
WiFi 802.11n HT20 (2.4GHz) (MCS4-MCS6)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	12	12	12

Tune-up (dBm)	13	13	13
WiFi 802.11n HT20 (2.4GHz) (MCS7)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	12	12	12
Tune-up (dBm)	13	13	13
WiFi 802.11a (5GHz)			
Channel	Ch 36~Ch64	Ch100~Ch140	Ch149~Ch165
Target (dBm)	9.8	12	10
Tune-up (dBm)	10.8	13	11
WiFi 802.11n HT20(5GHz)			
Channel	Ch 36~Ch64	Ch100~140	Ch149~Ch165
Target (dBm)	9	11	8.5
Tune-up (dBm)	10	12	9.5
WiFi 802.11n HT40(5GHz)			
Channel	Ch 38	Ch46~Ch54	Ch62
Target (dBm)	8	9.5	8
Tune-up (dBm)	9	10.5	9
Channel	Ch 102	Ch110~Ch126	Ch134
Target (dBm)	9	12	10
Tune-up (dBm)	10	13	11
Channel	Ch151~Ch159	/	/
Target (dBm)	7.5	/	/
Tune-up (dBm)	8.5	/	/

11.2 Hotspot

The conducted power is normal for all bands except LTE Band 30. There is power reduction enabled for LTE band 30. The power reduction is enabled when the user enables hotspot mode via the manufacturer software. The tables below show the measured powers with hotspot.

Table 11.8: The conducted Power for LTE

Band 30							
Bandwidth (MHz)	RB allocation	Frequency (MHz)	Max. Target Power (dBm)	QPSK		16QAM	
	RB offset (Start RB)			Actual output power (dBm)	MPR	Actual output power (dBm)	MPR
5 MHz	1RB High (24)	2312.5	22	20.74	0	20.75	0
		2310	22	20.86	0	20.69	0
		2307.5	22	20.76	0	20.10	0
	1RB Middle (12)	2312.5	22	20.71	0	20.68	0
		2310	22	20.82	0	20.21	0
		2307.5	22	20.72	0	20.87	0
	1RB Low (0)	2312.5	22	20.86	0	20.75	0
		2310	22	20.79	0	20.66	0
		2307.5	22	20.80	0	20.67	0
	12RB High (13)	2312.5	22	20.95	0	20.08	0
		2310	22	21.08	0	20.11	0
		2307.5	22	21.06	0	20.06	0
	12RB Middle (6)	2312.5	22	21.15	0	20.17	0
		2310	22	21.04	0	20.16	0
		2307.5	22	21.08	0	20.11	0
	12RB Low (0)	2312.5	22	21.17	0	20.20	0
		2310	22	21.13	0	20.17	0
		2307.5	22	21.07	0	20.09	0
	25RB (0)	2312.5	22	21.11	0	20.16	0
		2310	22	21.10	0	20.07	0
		2307.5	22	21.05	0	20.10	0
10 MHz	1RB High (49)	2310	22	20.83	0	21.08	0
	1RB Middle (24)	2310	22	21.34	0	21.23	0
	1RB Low (0)	2310	22	21.19	0	21.47	0
	25RB High (25)	2310	22	21.16	0	20.04	0
	25RB Middle (12)	2310	22	21.11	0	20.07	0
	25RB Low (0)	2310	22	21.15	0	20.11	0
	50RB (0)	2310	22	21.08	0	20.21	0

11.3 GSM Measurement result

During the process of testing, the EUT was controlled via Agilent Digital Radio Communication tester (E5515C) to ensure the maximum power transmission and proper modulation. This result contains conducted output power for the EUT. In all cases, the measured peak output power should be greater and within 5% than EMI measurement.

Table 11.9: The conducted power measurement results for GSM850/1900

GSM 850MHz	Conducted Power (dBm)		
	Channel 251(848.8MHz)	Channel 190(836.6MHz)	Channel 128(824.2MHz)
	32.18	32.51	32.44
GSM 1900MHz	Conducted Power (dBm)		
	Channel 810(1909.8MHz)	Channel 661(1880MHz)	Channel 512(1850.2MHz)
	28.58	28.58	28.68

Table 11.10: The conducted power measurement results for GPRS and EGPRS

GSM 850 GPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	251	190	128		251	190	128
1 Txslot	32.22	32.55	32.48	-9.03	23.19	23.52	23.45
2 Txslots	30.53	30.68	30.65	-6.02	24.51	24.66	24.63
3Txslots	28.64	28.76	28.74	-4.26	24.38	24.50	24.48
4 Txslots	27.41	27.52	27.51	-3.01	24.40	24.51	24.50
GSM 850 EGPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	251	190	128		251	190	128
1 Txslot	32.15	32.48	32.38	-9.03	23.12	23.45	23.35
2 Txslots	30.46	30.63	30.58	-6.02	24.44	24.61	24.56
3Txslots	28.60	28.71	28.69	-4.26	24.34	24.45	24.43
4 Txslots	27.37	27.48	27.49	-3.01	24.36	24.47	24.48
GSM 850 EGPRS (8PSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	251	190	128		251	190	128
1 Txslot	26.15	26.10	26.10	-9.03	17.12	17.07	17.07
2 Txslots	25.11	25.07	25.02	-6.02	19.09	19.05	19.00
3Txslots	23.52	23.52	23.40	-4.26	19.26	19.26	19.14
4 Txslots	21.71	21.72	21.70	-3.01	18.70	18.71	18.69
PCS1900 GPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	810	661	512		810	661	512
1 Txslot	28.57	28.58	28.68	-9.03	19.54	19.55	19.65
2 Txslots	27.87	27.99	28.08	-6.02	21.85	21.97	22.06
3Txslots	25.96	26.16	26.30	-4.26	21.70	21.90	22.04
4 Txslots	24.71	24.88	25.04	-3.01	21.70	21.87	22.03
PCS1900 EGPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	810	661	512		810	661	512
1 Txslot	28.52	28.63	28.71	-9.03	19.49	19.60	19.68
2 Txslots	27.82	27.94	28.04	-6.02	21.80	21.92	22.02

3Txslots	25.95	26.17	26.30	-4.26	21.69	21.91	22.04
4 Txslots	24.68	24.87	25.02	-3.01	21.67	21.86	22.01
PCS1900 EGPRS (8PSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	810	661	512		810	661	512
1 Txslot	25.66	25.76	25.84	-9.03	16.63	16.73	16.81
2 Txslots	24.50	24.52	24.68	-6.02	18.48	18.50	18.66
3Txslots	22.69	22.89	22.98	-4.26	18.43	18.63	18.72
4 Txslots	21.16	21.26	21.45	-3.01	18.15	18.25	18.44

NOTES:

1) Division Factors

To average the power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB

2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB

3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB

According to the conducted power as above, the body measurements are performed with 2Txslot for GPRS and EGPRS.

11.4 WCDMA Measurement result

Table 11.11: The conducted Power for WCDMA

Item	band	FDDV result		
	ARFCN	4233 (846.6MHz)	4182 (836.4MHz)	4132 (826.4MHz)
WCDMA	\	22.62	22.72	22.75
HSUPA	1	21.28	21.34	21.65
	2	20.59	20.73	20.43
	3	20.2	20.33	20.6
	4	21.08	21.23	21.17
	5	21.63	21.68	21.72
DC-HSDPA	1	21.27	21.29	21.30
	2	21.29	21.27	21.34
	3	21.28	21.28	21.29
	4	21.25	21.32	21.29
Item	band	FDDIV result		
	ARFCN	1513 (1752.6MHz)	1412 (1732.4MHz)	1312 (1712.4MHz)
WCDMA	\	23.52	23.44	23.51
HSUPA	1	22.22	21.94	21.81
	2	20.86	20.92	21.18
	3	20.99	21.38	21.22
	4	21.91	21.99	21.16
	5	22.46	22.53	22.4
DC-HSDPA	1	22.08	21.94	21.98

	2	22.07	22.02	22.00
	3	22.02	22.00	22.08
	4	22.06	22.02	22.01
Item	band	FDDII result		
	ARFCN	9538 (1907.6MHz)	9400 (1880MHz)	9262 (1852.4MHz)
WCDMA	1	22.00	22.01	21.94
HSUPA	1	20.45	20.57	20.52
	2	20	19.96	19.55
	3	19.55	19.64	19.01
	4	20.42	20.54	20.47
	5	20.85	20.86	20.86
DC-HSDPA	1	20.85	20.72	20.74
	2	20.80	20.70	20.71
	3	20.79	20.75	20.65
	4	20.70	20.74	20.72

11.5 LTE Measurement result

Table 11.12: The conducted Power for LTE

Band 2							
Bandwidth (MHz)	RB allocation	Frequency (MHz)	Max. Target Power (dBm)	QPSK		16QAM	
	RB offset (Start RB)			Actual output power (dBm)	MPR	Actual output power (dBm)	MPR
1.4 MHz	1RB High (5)	1909.3	23.4	22.62	0	22.01	1
		1880	23.4	22.49	0	21.14	1
		1850.7	23.4	22.73	0	21.35	1
	1RB Middle (3)	1909.3	23.4	22.92	0	21.72	1
		1880	23.4	22.70	0	21.79	1
		1850.7	23.4	22.98	0	21.97	1
	1RB Low (0)	1909.3	23.4	22.85	0	22.00	1
		1880	23.4	22.87	0	21.96	1
		1850.7	23.4	22.98	0	22.08	1
	3RB High (3)	1909.3	23.4	22.68	0	21.98	1
		1880	23.4	22.66	0	21.34	1
		1850.7	23.4	22.73	0	21.91	1
	3RB Middle (1)	1909.3	23.4	23.21	0	21.87	1
		1880	23.4	22.66	0	21.80	1
		1850.7	23.4	22.81	0	21.95	1
	3RB Low (0)	1909.3	23.4	22.72	0	21.74	1
		1880	23.4	22.78	0	21.73	1
		1850.7	23.4	22.80	0	21.82	1
	6RB (0)	1909.3	23.4	21.67	1	20.88	2
		1880	23.4	21.57	1	20.74	2
		1850.7	23.4	21.79	1	20.95	2

3 MHz	1RB High (14)	1908.5	23.4	22.58	0	21.86	1
		1880	23.4	22.78	0	21.77	1
		1851.5	23.4	22.97	0	21.69	1
	1RB Middle (7)	1908.5	23.4	22.73	0	21.76	1
		1880	23.4	22.69	0	21.65	1
		1851.5	23.4	22.66	0	21.59	1
	1RB Low (0)	1908.5	23.4	22.68	0	21.80	1
		1880	23.4	22.69	0	21.77	1
		1851.5	23.4	22.74	0	21.90	1
	8RB High (7)	1908.5	23.4	21.62	1	20.98	2
		1880	23.4	21.62	1	20.57	2
		1851.5	23.4	21.73	1	20.56	2
	8RB Middle (4)	1908.5	23.4	21.77	1	20.95	2
		1880	23.4	21.64	1	20.94	2
		1851.5	23.4	21.72	1	20.57	2
	8RB Low (0)	1908.5	23.4	21.72	1	21.06	2
		1880	23.4	21.68	1	20.51	2
		1851.5	23.4	21.70	1	20.89	2
	15RB (0)	1908.5	23.4	21.80	1	20.85	2
		1880	23.4	21.69	1	20.70	2
		1851.5	23.4	21.80	1	20.82	2
5 MHz	1RB High (24)	1907.5	23.4	22.47	0	20.78	1
		1880	23.4	22.77	0	21.37	1
		1852.5	23.4	22.37	0	21.28	1
	1RB Middle (12)	1907.5	23.4	22.49	0	20.85	1
		1880	23.4	22.36	0	21.24	1
		1852.5	23.4	22.52	0	21.53	1
	1RB Low (0)	1907.5	23.4	22.50	0	20.78	1
		1880	23.4	22.40	0	21.29	1
		1852.5	23.4	22.59	0	21.27	1
	12RB High (13)	1907.5	23.4	21.69	1	20.64	2
		1880	23.4	21.60	1	20.71	2
		1852.5	23.4	21.70	1	20.89	2
	12RB Middle (6)	1907.5	23.4	21.67	1	20.64	2
		1880	23.4	21.67	1	20.62	2
		1852.5	23.4	21.77	1	20.77	2
	12RB Low (0)	1907.5	23.4	21.66	1	20.70	2
		1880	23.4	21.62	1	20.59	2
		1852.5	23.4	21.75	1	20.83	2
	25RB (0)	1907.5	23.4	21.79	1	20.61	2
		1880	23.4	21.67	1	20.66	2
		1852.5	23.4	21.77	1	21.08	2
10 MHz	1RB	1905	23.4	22.86	0	21.83	1

	High (49)	1880	23.4	22.61	0	22.01	1
		1855	23.4	22.70	0	21.85	1
	1RB Middle (24)	1905	23.4	22.99	0	21.83	1
		1880	23.4	22.99	0	21.85	1
		1855	23.4	23.02	0	21.72	1
	1RB Low (0)	1905	23.4	22.96	0	21.97	1
		1880	23.4	22.84	0	22.16	1
		1855	23.4	22.94	0	22.16	1
	25RB High (25)	1905	23.4	21.73	1	20.57	2
		1880	23.4	21.66	1	20.61	2
		1855	23.4	21.71	1	20.65	2
	25RB Middle (12)	1905	23.4	21.79	1	20.67	2
		1880	23.4	21.67	1	20.59	2
		1855	23.4	21.76	1	20.72	2
	25RB Low (0)	1905	23.4	21.79	1	20.60	2
		1880	23.4	21.68	1	20.67	2
		1855	23.4	21.83	1	20.81	2
	50RB (0)	1905	23.4	21.67	1	20.65	2
		1880	23.4	21.66	1	20.65	2
		1855	23.4	21.70	1	20.76	2
15 MHz	1RB High (74)	1902.5	23.4	22.75	0	22.35	1
		1880	23.4	22.63	0	21.65	1
		1857.5	23.4	22.76	0	21.64	1
	1RB Middle (37)	1902.5	23.4	22.62	0	21.78	1
		1880	23.4	22.71	0	21.78	1
		1857.5	23.4	22.68	0	21.69	1
	1RB Low (0)	1902.5	23.4	22.89	0	22.07	1
		1880	23.4	22.86	0	21.86	1
		1857.5	23.4	22.83	0	21.89	1
	36RB High (38)	1902.5	23.4	21.73	1	20.72	2
		1880	23.4	21.64	1	20.65	2
		1857.5	23.4	21.71	1	20.59	2
	36RB Middle (19)	1902.5	23.4	21.75	1	20.82	2
		1880	23.4	21.68	1	20.75	2
		1857.5	23.4	21.68	1	20.68	2
	36RB Low (0)	1902.5	23.4	21.70	1	20.85	2
		1880	23.4	21.64	1	20.73	2
		1857.5	23.4	21.70	1	20.63	2
	75RB (0)	1902.5	23.4	21.64	1	20.68	2
		1880	23.4	21.61	1	20.60	2
		1857.5	23.4	21.60	1	20.58	2
20 MHz	1RB High (99)	1900	23.4	23.08	0	22.21	1
		1880	23.4	22.89	0	22.24	1
		1860	23.4	23.00	0	22.27	1
	1RB	1900	23.4	23.21	0	22.39	1

	Middle (50)	1880	23.4	23.15	0	21.82	1
		1860	23.4	22.97	0	22.07	1
		1900	23.4	23.14	0	21.72	1
	1RB Low (0)	1880	23.4	22.81	0	22.00	1
		1860	23.4	22.72	0	22.01	1
		1900	23.4	21.72	1	20.69	2
	50RB High (50)	1880	23.4	21.63	1	20.75	2
		1860	23.4	21.68	1	20.73	2
		1900	23.4	21.75	1	20.85	2
	50RB Middle (25)	1880	23.4	21.66	1	20.77	2
		1860	23.4	21.70	1	20.70	2
		1900	23.4	21.72	1	20.75	2
	50RB Low (0)	1880	23.4	21.82	1	20.87	2
		1860	23.4	21.74	1	20.66	2
		1900	23.4	21.74	1	20.76	2
100RB (0)	1880	23.4	21.58	1	20.61	2	
	1860	23.4	21.69	1	20.70	2	
	Band 4						
Bandwidth (MHz)	RB allocation	Frequency (MHz)	Max. Target Power (dBm)	QPSK		16QAM	
	RB offset (Start RB)			Actual output power (dBm)	MPR	Actual output power (dBm)	MPR
1.4 MHz	1RB High (5)	1754.3	23.5	22.63	0	21.63	1
		1732.5	23.5	22.53	0	21.53	1
		1710.7	23.5	22.78	0	21.86	1
	1RB Middle (3)	1754.3	23.5	22.54	0	21.77	1
		1732.5	23.5	22.64	0	21.68	1
		1710.7	23.5	22.74	0	21.87	1
	1RB Low (0)	1754.3	23.5	22.58	0	21.44	1
		1732.5	23.5	22.62	0	21.77	1
		1710.7	23.5	22.73	0	21.78	1
	3RB High (3)	1754.3	23.5	22.68	0	21.45	1
		1732.5	23.5	22.62	0	21.72	1
		1710.7	23.5	22.75	0	21.71	1
	3RB Middle (1)	1754.3	23.5	22.92	0	21.72	1
		1732.5	23.5	22.46	0	21.82	1
		1710.7	23.5	22.72	0	21.69	1
	3RB Low (0)	1754.3	23.5	22.56	0	21.54	1
		1732.5	23.5	22.48	0	21.19	1
		1710.7	23.5	22.51	0	21.79	1
	6RB (0)	1754.3	23.5	21.46	1	20.74	2
		1732.5	23.5	21.37	1	20.45	2
		1710.7	23.5	21.53	1	20.65	2
3 MHz	1RB High (14)	1753.5	23.5	22.67	0	21.85	1
		1732.5	23.5	22.60	0	21.75	1
		1711.5	23.5	22.62	0	21.75	1
	1RB	1753.5	23.5	22.52	0	21.71	1

	Middle (7)	1732.5	23.5	22.30	0	22.17	1
		1711.5	23.5	22.54	0	22.34	1
	1RB Low (0)	1753.5	23.5	22.49	0	21.81	1
		1732.5	23.5	22.59	0	22.17	1
		1711.5	23.5	22.78	0	22.36	1
	8RB High (7)	1753.5	23.5	21.58	1	20.57	2
		1732.5	23.5	21.39	1	20.48	2
		1711.5	23.5	21.56	1	20.83	2
	8RB Middle (4)	1753.5	23.5	21.52	1	20.51	2
		1732.5	23.5	21.47	1	20.47	2
		1711.5	23.5	21.54	1	20.65	2
	8RB Low (0)	1753.5	23.5	21.47	1	20.49	2
		1732.5	23.5	21.48	1	20.48	2
		1711.5	23.5	21.44	1	20.86	2
	15RB (0)	1753.5	23.5	21.54	1	20.59	2
		1732.5	23.5	21.55	1	20.48	2
		1711.5	23.5	21.48	1	20.52	2
5 MHz	1RB High (24)	1752.5	23.5	22.61	0	21.29	1
		1732.5	23.5	22.36	0	20.62	1
		1712.5	23.5	22.64	0	20.96	1
	1RB Middle (12)	1752.5	23.5	22.36	0	21.21	1
		1732.5	23.5	22.51	0	21.25	1
		1712.5	23.5	22.58	0	20.63	1
	1RB Low (0)	1752.5	23.5	22.53	0	21.17	1
		1732.5	23.5	22.44	0	21.10	1
		1712.5	23.5	22.27	0	21.39	1
	12RB High (13)	1752.5	23.5	21.60	1	20.66	2
		1732.5	23.5	21.49	1	20.52	2
		1712.5	23.5	21.58	1	20.74	2
	12RB Middle (6)	1752.5	23.5	21.47	1	20.56	2
		1732.5	23.5	21.53	1	20.49	2
		1712.5	23.5	21.56	1	20.64	2
	12RB Low (0)	1752.5	23.5	21.50	1	20.60	2
		1732.5	23.5	21.48	1	20.50	2
		1712.5	23.5	21.63	1	20.72	2
	25RB (0)	1752.5	23.5	21.57	1	20.61	2
		1732.5	23.5	21.53	1	20.43	2
		1712.5	23.5	21.55	1	20.71	2
10 MHz	1RB High (49)	1750	23.5	22.72	0	21.74	1
		1732.5	23.5	22.40	0	21.61	1
		1715	23.5	22.74	0	21.79	1
	1RB	1750	23.5	22.92	0	21.85	1

	Middle (24)	1732.5	23.5	22.77	0	21.77	1
		1715	23.5	23.06	0	21.94	1
	1RB Low (0)	1750	23.5	22.74	0	21.84	1
		1732.5	23.5	22.72	0	21.61	1
		1715	23.5	22.66	0	22.01	1
	25RB High (25)	1750	23.5	21.55	1	20.58	2
		1732.5	23.5	21.50	1	20.48	2
		1715	23.5	21.61	1	20.70	2
	25RB Middle (12)	1750	23.5	21.61	1	20.62	2
		1732.5	23.5	21.51	1	20.53	2
		1715	23.5	21.67	1	20.69	2
	25RB Low (0)	1750	23.5	21.62	1	20.63	2
		1732.5	23.5	21.52	1	20.55	2
		1715	23.5	21.57	1	20.58	2
	50RB (0)	1750	23.5	21.58	1	20.73	2
		1732.5	23.5	21.52	1	20.63	2
		1715	23.5	21.58	1	20.59	2
15 MHz	1RB High (74)	1747.5	23.5	22.56	0	21.69	1
		1732.5	23.5	22.60	0	21.63	1
		1717.5	23.5	22.69	0	21.83	1
	1RB Middle (37)	1747.5	23.5	22.58	0	21.90	1
		1732.5	23.5	22.56	0	22.23	1
		1717.5	23.5	22.70	0	22.33	1
	1RB Low (0)	1747.5	23.5	22.64	0	22.07	1
		1732.5	23.5	22.79	0	22.37	1
		1717.5	23.5	22.92	0	22.10	1
	36RB High (38)	1747.5	23.5	21.62	1	20.62	2
		1732.5	23.5	21.57	1	20.53	2
		1717.5	23.5	21.70	1	20.64	2
	36RB Middle (19)	1747.5	23.5	21.62	1	20.71	2
		1732.5	23.5	21.51	1	20.37	2
		1717.5	23.5	21.68	1	20.66	2
	36RB Low (0)	1747.5	23.5	21.66	1	20.75	2
		1732.5	23.5	21.56	1	20.44	2
		1717.5	23.5	21.69	1	20.68	2
	75RB (0)	1747.5	23.5	21.64	1	20.66	2
		1732.5	23.5	21.56	1	20.59	2
		1717.5	23.5	21.60	1	20.62	2
20 MHz	1RB High (99)	1745	23.5	22.70	0	21.89	1
		1732.5	23.5	22.78	0	22.02	1
		1720	23.5	22.66	0	21.91	1
	1RB Middle (50)	1745	23.5	22.99	0	21.98	1
		1732.5	23.5	22.74	0	21.95	1
		1720	23.5	22.80	0	22.01	1

	1RB Low (0)	1745	23.5	22.85	0	21.87	1
		1732.5	23.5	22.97	0	21.88	1
		1720	23.5	22.91	0	22.12	1
	50RB High (50)	1745	23.5	21.56	1	20.66	2
		1732.5	23.5	21.53	1	20.57	2
		1720	23.5	21.58	1	20.66	2
	50RB Middle (25)	1745	23.5	21.69	1	20.72	2
		1732.5	23.5	21.49	1	20.53	2
		1720	23.5	21.59	1	20.71	2
	50RB Low (0)	1745	23.5	21.60	1	20.64	2
		1732.5	23.5	21.54	1	20.65	2
		1720	23.5	21.68	1	20.73	2
	100RB (0)	1745	23.5	21.57	1	20.74	2
		1732.5	23.5	21.58	1	20.63	2
		1720	23.5	21.67	1	20.73	2
Band 5							
Bandwidth (MHz)	RB allocation	Frequency (MHz)	Max. Target Power (dBm)	QPSK		16QAM	
	RB offset (Start RB)			Actual output power (dBm)	MPR	Actual output power (dBm)	MPR
1.4 MHz	1RB High (5)	848.3	24	23.10	0	22.26	1
		836.5	24	23.10	0	22.11	1
		824.7	24	22.88	0	21.52	1
	1RB Middle (3)	848.3	24	23.22	0	22.47	1
		836.5	24	23.05	0	22.25	1
		824.7	24	23.13	0	22.13	1
	1RB Low (0)	848.3	24	23.16	0	22.26	1
		836.5	24	23.19	0	22.08	1
		824.7	24	22.89	0	21.77	1
	3RB High (3)	848.3	24	23.02	0	22.26	1
		836.5	24	23.01	0	22.12	1
		824.7	24	23.11	0	22.21	1
	3RB Middle (1)	848.3	24	23.21	0	22.30	1
		836.5	24	23.06	0	22.21	1
		824.7	24	23.28	0	22.33	1
	3RB Low (0)	848.3	24	23.05	0	22.28	1
		836.5	24	23.06	0	22.34	1
		824.7	24	23.09	0	22.35	1
	6RB (0)	848.3	24	22.03	1	21.16	2
		836.5	24	22.02	1	21.10	2
		824.7	24	22.11	1	21.10	2
3 MHz	1RB	847.5	24	22.88	0	22.15	1

	High (14)	836.5	24	22.99	0	22.03	1
		825.5	24	23.18	0	22.81	1
	1RB Middle (7)	847.5	24	22.88	0	21.99	1
		836.5	24	22.83	0	21.91	1
		825.5	24	22.91	0	22.08	1
	1RB Low (0)	847.5	24	23.03	0	22.27	1
		836.5	24	23.17	0	22.29	1
		825.5	24	23.16	0	22.12	1
	8RB High (7)	847.5	24	22.02	1	21.20	2
		836.5	24	22.07	1	21.08	2
		825.5	24	22.14	1	21.32	2
	8RB Middle (4)	847.5	24	22.06	1	21.18	2
		836.5	24	22.08	1	21.22	2
		825.5	24	22.08	1	21.28	2
	8RB Low (0)	847.5	24	22.12	1	21.25	2
		836.5	24	22.09	1	21.33	2
		825.5	24	22.09	1	21.22	2
	15RB (0)	847.5	24	22.12	1	21.01	2
		836.5	24	22.10	1	21.14	2
		825.5	24	22.20	1	21.15	2
5 MHz	1RB High (24)	846.5	24	22.61	0	21.31	1
		836.5	24	22.76	0	21.78	1
		826.5	24	22.65	0	21.44	1
	1RB Middle (12)	846.5	24	22.64	0	21.18	1
		836.5	24	22.67	0	21.70	1
		826.5	24	22.92	0	21.23	1
	1RB Low (0)	846.5	24	22.71	0	21.54	1
		836.5	24	22.71	0	21.65	1
		826.5	24	23.01	0	21.76	1
	12RB High (13)	846.5	24	22.05	1	20.97	2
		836.5	24	21.96	1	20.96	2
		826.5	24	22.15	1	21.22	2
	12RB Middle (6)	846.5	24	22.10	1	20.92	2
		836.5	24	22.02	1	21.10	2
		826.5	24	22.15	1	21.08	2
	12RB Low (0)	846.5	24	21.97	1	20.75	2
		836.5	24	22.03	1	21.01	2
		826.5	24	22.20	1	21.19	2
	25RB (0)	846.5	24	21.98	1	20.92	2
		836.5	24	22.10	1	21.22	2
		826.5	24	22.21	1	21.33	2
10 MHz	1RB	844.0	24	22.97	0	22.16	1

	High (49)	836.5	24	22.87	0	22.14	1
		829.0	24	22.94	0	22.17	1
	1RB Middle (24)	844.0	24	23.19	0	21.97	1
		836.5	24	23.11	0	22.26	1
		829.0	24	23.15	0	22.72	1
	1RB Low (0)	844.0	24	23.08	0	22.13	1
		836.5	24	23.02	0	22.44	1
		829.0	24	23.26	0	22.43	1
	25RB High (25)	844.0	24	21.98	1	20.89	2
		836.5	24	22.00	1	20.89	2
		829.0	24	22.08	1	21.01	2
	25RB Middle (12)	844.0	24	22.02	1	20.93	2
		836.5	24	22.10	1	20.97	2
		829.0	24	22.16	1	21.09	2
	25RB Low (0)	844.0	24	21.99	1	21.02	2
		836.5	24	22.07	1	21.10	2
		829.0	24	22.23	1	21.06	2
	50RB (0)	844.0	24	21.97	1	21.00	2
		836.5	24	22.07	1	21.07	2
		829.0	24	22.15	1	21.16	2
Band 12							
Bandwidth (MHz)	RB allocation	Frequency (MHz)	Max. Target Power (dBm)	QPSK		16QAM	
	RB offset (Start RB)			Actual output power (dBm)	MPR	Actual output power (dBm)	MPR
1.4 MHz	1RB High (5)	715.3	24	22.87	0	22.16	1
		707.5	24	23.03	0	22.23	1
		699.7	24	22.55	0	21.84	1
	1RB Middle (3)	715.3	24	23.04	0	22.12	1
		707.5	24	23.08	0	22.20	1
		699.7	24	22.83	0	22.11	1
	1RB Low (0)	715.3	24	22.79	0	21.99	1
		707.5	24	22.97	0	22.11	1
		699.7	24	22.92	0	22.49	1
	3RB High (3)	715.3	24	22.80	0	22.03	1
		707.5	24	22.92	0	22.13	1
		699.7	24	22.80	0	21.85	1
	3RB Middle (1)	715.3	24	23.04	0	21.97	1
		707.5	24	22.85	0	22.01	1
		699.7	24	22.91	0	21.90	1
	3RB Low (0)	715.3	24	22.80	0	22.11	1
		707.5	24	22.83	0	22.19	1

	6RB (0)	699.7	24	22.74	0	21.83	1
		715.3	24	21.75	1	20.81	2
		707.5	24	21.83	1	21.00	2
		699.7	24	21.77	1	21.00	2
3 MHz	1RB High (14)	714.5	24	22.60	0	22.03	1
		707.5	24	22.81	0	22.05	1
		700.5	24	22.54	0	22.00	1
	1RB Middle (7)	714.5	24	22.67	0	21.97	1
		707.5	24	22.77	0	21.95	1
		700.5	24	22.47	0	21.85	1
	1RB Low (0)	714.5	24	22.54	0	22.01	1
		707.5	24	22.73	0	21.89	1
		700.5	24	22.64	0	21.94	1
	8RB High (7)	714.5	24	21.82	1	21.13	2
		707.5	24	21.94	1	21.20	2
		700.5	24	21.85	1	21.04	2
	8RB Middle (4)	714.5	24	21.83	1	20.95	2
		707.5	24	21.86	1	21.02	2
		700.5	24	21.78	1	20.90	2
	8RB Low (0)	714.5	24	21.78	1	21.00	2
		707.5	24	21.83	1	21.07	2
		700.5	24	21.74	1	20.96	2
	15RB (0)	714.5	24	21.84	1	20.89	2
		707.5	24	21.97	1	20.90	2
		700.5	24	21.84	1	20.87	2
5 MHz	1RB High (24)	713.5	24	22.54	0	21.02	1
		707.5	24	22.59	0	21.58	1
		701.5	24	22.36	0	21.00	1
	1RB Middle (12)	713.5	24	22.55	0	21.43	1
		707.5	24	22.63	0	21.09	1
		701.5	24	22.51	0	21.03	1
	1RB Low (0)	713.5	24	22.51	0	21.34	1
		707.5	24	22.27	0	21.01	1
		701.5	24	22.37	0	21.02	1
	12RB High (13)	713.5	24	21.87	1	20.95	2
		707.5	24	22.00	1	21.02	2
		701.5	24	21.85	1	20.92	2
	12RB Middle (6)	713.5	24	21.84	1	20.94	2
		707.5	24	21.97	1	20.82	2
		701.5	24	21.87	1	20.86	2
	12RB Low (0)	713.5	24	21.80	1	20.80	2
		707.5	24	21.78	1	20.96	2
		701.5	24	21.85	1	20.76	2

	25RB (0)	713.5	24	21.77	1	20.90	2
		707.5	24	21.88	1	20.96	2
		701.5	24	21.80	1	20.93	2
10 MHz	1RB High (49)	711	24	22.80	0	22.02	1
		707.5	24	22.66	0	21.85	1
		704	24	22.66	0	22.08	1
	1RB Middle (24)	711	24	23.12	0	22.32	1
		707.5	24	22.87	0	22.11	1
		704	24	22.85	0	21.94	1
	1RB Low (0)	711	24	22.91	0	22.02	1
		707.5	24	22.74	0	21.95	1
		704	24	22.60	0	21.70	1
	25RB High (25)	711	24	21.92	1	20.84	2
		707.5	24	21.94	1	20.91	2
		704	24	21.93	1	20.81	2
	25RB Middle (12)	711	24	21.98	1	20.90	2
		707.5	24	21.92	1	20.93	2
		704	24	21.82	1	20.74	2
	25RB Low (0)	711	24	21.94	1	20.93	2
		707.5	24	21.76	1	20.68	2
		704	24	21.79	1	20.73	2
	50RB (0)	711	24	21.85	1	20.86	2
		707.5	24	21.73	1	20.61	2
		704	24	21.79	1	20.79	2
Band 30							
Bandwidth (MHz)	RB allocation	Frequency (MHz)	Max. Target Power (dBm)	QPSK		16QAM	
	RB offset (Start RB)			Actual output power (dBm)	MPR	Actual output power (dBm)	MPR
5 MHz	1RB High (24)	2312.5	23	21.76	0	20.07	1
		2310	23	21.88	0	20.11	1
		2307.5	23	21.84	0	20.95	1
	1RB Middle (12)	2312.5	23	21.72	0	20.02	1
		2310	23	21.80	0	20.27	1
		2307.5	23	21.85	0	20.88	1
	1RB Low (0)	2312.5	23	21.96	0	20.63	1
		2310	23	21.93	0	20.10	1
		2307.5	23	22.03	0	20.97	1
	12RB High (13)	2312.5	23	21.00	1	20.10	2
		2310	23	21.02	1	20.14	2
		2307.5	23	20.97	1	20.05	2
	12RB Middle (6)	2312.5	23	21.07	1	20.19	2
		2310	23	20.99	1	20.10	2
		2307.5	23	21.01	1	20.13	2
	12RB	2312.5	23	21.09	1	20.22	2

	Low (0)	2310	23	21.07	1	19.91	2
		2307.5	23	21.07	1	20.11	2
	25RB (0)	2312.5	23	21.13	1	20.19	2
		2310	23	21.04	1	20.17	2
		2307.5	23	21.08	1	20.13	2
10 MHz	1RB High (49)	2310	23	22.09	0	21.10	1
	1RB Middle (24)	2310	23	22.20	0	21.24	1
	1RB Low (0)	2310	23	22.14	0	21.17	1
	25RB High (25)	2310	23	21.05	1	20.09	2
	25RB Middle (12)	2310	23	21.10	1	20.17	2
	25RB Low (0)	2310	23	21.05	1	20.11	2
	50RB (0)	2310	23	21.08	1	20.18	2

11.6 Wi-Fi and BT Measurement result

The output power of BT antenna is as following:

Mode	Conducted Power (dBm)		
	Channel 0 (2402MHz)	Channel 39 (2441MHz)	Channel 78 (2480MHz)
GFSK	6.70	6.90	5.54

The average conducted power for 2.4GWi-Fi is as following:

802.11b (dBm)

Channel\data rate	1Mbps	2Mbps	5.5Mbps	11Mbps
1	15.26	/	15.72	/
6	15.89	16.08	16.24	16.15
11	15.67	/	15.78	/

802.11g (dBm)

Channel\data rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
1	11.72	/	/	/	/	/	/	/
6	12.40	12.19	12.16	12.11	12.04	11.97	11.87	11.85
11	11.86	/	/	/	/	/	/	/

802.11n (dBm) - HT20 (2.4G)

Channel\data rate	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
1	10.83	/	/	/	/	/	/	/
6	11.50	11.46	11.42	11.35	11.28	11.19	11.15	11.13
11	11.02	/	/	/	/	/	/	/

The average conducted power for 5GWi-Fi is as following:

802.11a(dBm)								
Channel\data rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
36(5180 MHz)	9.49	/	/	/	/	/	/	/
40(5200 MHz)	10.59	10.54	10.52	10.48	10.40	10.33	10.24	10.21
44(5220 MHz)	10.34	/	/	/	/	/	/	/
48(5240 MHz)	10.38	/	/	/	/	/	/	/
52(5260 MHz)	9.97	9.93	9.91	9.87	9.79	9.72	9.62	9.59
56(5280 MHz)	9.52	/	/	/	/	/	/	/
60(5300 MHz)	9.12	/	/	/	/	/	/	/
64(5320 MHz)	8.91	/	/	/	/	/	/	/
100(5500 MHz)	11.92	11.91	/	/	/	/	/	/
104(5520 MHz)	11.59	11.85	/	/	/	/	/	/
108(5540 MHz)	12.26	12.25	/	/	/	/	/	/
112(5560 MHz)	12.25	12.51	/	/	/	/	/	/
116(5580 MHz)	12.58	12.84	12.81	12.75	12.67	12.60	12.50	12.47

120(5600 MHz)	12.24	12.24	/	/	/	/	/	/
124(5620 MHz)	12.16	12.15	/	/	/	/	/	/
128(5640 MHz)	12.08	12.09	/	/	/	/	/	/
132(5660 MHz)	12.09	12.10	/	/	/	/	/	/
136(5680 MHz)	11.70	11.71	/	/	/	/	/	/
140(5700 MHz)	11.59	11.58	/	/	/	/	/	/
149(5745 MHz)	9.33	/	/	/	/	/	/	/
153(5765 MHz)	9.43	/	/	/	/	/	/	/
157(5785 MHz)	9.42	/	/	/	/	/	/	/
161(5805 MHz)	9.52	9.49	9.48	9.42	9.34	9.25	9.25	9.12
165(5825 MHz)	9.21	/	/	/	/	/	/	/
802.11n(dBm)-20MHz								
Channel\data rate	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
36(5180 MHz)	9.16	/	/	/	/	/	/	/
40(5200 MHz)	9.66	9.60	9.57	9.49	9.44	9.34	9.32	9.28
44(5220 MHz)	9.61	/	/	/	/	/	/	/
48(5240 MHz)	9.65	/	/	/	/	/	/	/
52(5260 MHz)	9.11	9.06	9.01	8.94	8.87	8.80	8.76	8.73
56(5280 MHz)	8.85	/	/	/	/	/	/	/
60(5300 MHz)	8.25	/	/	/	/	/	/	/
64(5320 MHz)	8.31	/	/	/	/	/	/	/
100(5500 MHz)	10.83	/	/	/	/	/	/	/
104(5520 MHz)	10.76	/	/	/	/	/	/	/
108(5540 MHz)	11.15	/	/	/	/	/	/	/
112(5560 MHz)	11.42	/	/	/	/	/	/	/
116(5580 MHz)	11.96	11.72	11.67	11.58	11.52	11.44	11.40	11.37
120(5600 MHz)	11.12	/	/	/	/	/	/	/
124(5620 MHz)	11.30	/	/	/	/	/	/	/
128(5640 MHz)	11.23	/	/	/	/	/	/	/
132(5660 MHz)	11.02	/	/	/	/	/	/	/
136(5680 MHz)	10.64	/	/	/	/	/	/	/
140(5700 MHz)	10.55	/	/	/	/	/	/	/
149(5745 MHz)	8.42	8.36	8.31	8.22	8.16	8.07	8.03	7.99
153(5765 MHz)	8.28	/	/	/	/	/	/	/
157(5785 MHz)	8.26	/	/	/	/	/	/	/
161(5805 MHz)	8.35	/	/	/	/	/	/	/
165(5825 MHz)	8.09	/	/	/	/	/	/	/
802.11n(dBm)-40MHz								
Channel\data rate	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
38(5190 MHz)	7.38	/	/	/	/	/	/	/
46(5230 MHz)	9.99	9.91	9.83	9.71	9.55	9.47	9.41	9.37


54(5270 MHz)	9.67	9.60	9.50	9.38	9.23	9.14	9.10	9.04
62(5310 MHz)	7.57	/	/	/	/	/	/	/
102(5510 MHz)	9.05	/	/	/	/	/	/	/
110(5550 MHz)	11.75	/	/	/	/	/	/	/
118(5590 MHz)	12.09	12.02	11.93	11.82	11.67	11.58	11.55	11.51
126(5630 MHz)	11.91	/	/	/	/	/	/	/
134(5670 MHz)	10.06	/	/	/	/	/	/	/
151(5755 MHz)	7.57	7.47	7.39	7.28	7.13	7.03	6.99	6.94
159(5795 MHz)	7.55	/	/	/	/	/	/	/

12 Simultaneous TX SAR Considerations

12.1 Introduction

The following procedures adopted from “FCC SAR Considerations for Cell Phones with Multiple Transmitters” are applicable to handsets with built-in unlicensed transmitters such as 802.11 a/b/g and Bluetooth devices which may simultaneously transmit with the licensed transmitter. For this device, the BT and Wi-Fi can transmit simultaneous with other transmitters.

12.2 Transmit Antenna Separation Distances



Picture 12.1 Antenna Locations

12.3 SAR Measurement Positions

According to the KDB941225 D06 Hot Spot SAR v01, the edges with less than 2.5 cm distance to the antennas need to be tested for SAR.

SAR measurement positions						
Mode	Front	Rear	Left edge	Right edge	Top edge	Bottom edge
Main antenna	Yes	Yes	Yes	Yes	No	Yes
WLAN antenna	Yes	Yes	No	Yes	Yes	No

12.4 Standalone SAR Test Exclusion Considerations

Standalone 1-g head or body SAR evaluation by measurement or numerical simulation is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied. The 1-g SAR test exclusion threshold for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
 for 1-g SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Table 12.1: Standalone SAR test exclusion considerations

Band/Mode	F(GHz)	Position	SAR test exclusion threshold (mW)	RF output power		SAR test exclusion
				dBm	mW	
Bluetooth	2.441	Head	9.60	7	5.01	Yes
		Body	19.20	7	5.01	Yes
2.4GHz WLAN 802.11 b	2.45	Head	9.58	17	50.12	No
		Body	19.17	17	50.12	No
WLAN 5GHz	5.2	Head	6.58	10.8	12.02	No
		Body	13.16	10.8	12.02	Yes
	5.3	Head	6.52	10.8	12.02	No
		Body	13.03	10.8	12.02	Yes
	5.6	Head	6.34	13	19.95	No
		Body	12.68	13	19.95	No
	5.8	Head	6.23	11	12.59	No
		Body	12.46	11	12.59	No

Note: As above table, WLAN 5G body SAR is not required for 5.2&5.3G. But it is also performed for SAR test because WLAN 5G body SAR is required for 5.6&5.8G.

13 Evaluation of Simultaneous

Table 13.1: The sum of reported SAR values for main antenna and WLAN

	Position	Main antenna	WLAN	Sum	Distance (mm)	Ratio
Maximum reported SAR value for Head	Left hand, Touch cheek	0.34	0.36	0.70	/	/
	Right hand, Touch cheek	0.39	0.13	0.52	/	/
Maximum reported SAR value for Body	Rear	1.40	0.36	1.76	149.3	0.02
			0.32	1.72	152.6	0.01

According to the KDB 447498 D01, when the sum of SAR is larger than the limit, SAR test exclusion is determined by the SAR to peak location separation ratio. The ratio is determined by $(\text{SAR}_1 + \text{SAR}_2)^{1.5} / R_i$, rounded to two decimal digits, and must be ≤ 0.04 for all antenna pairs in the configuration to qualify for 1-g SAR test exclusion.

Find distance of maxima	
☐ Maxima and position w.r.t. Grid Reference Point	associated 1g averages
☐ Zoom Scan (D:\MII2015\I15Z42998(FCC)\WCDMA1700 Body 34a.da53:0/Rear High)	
Max. 1 at (7.02, 1.69, -0.07) cm	1.25 W/kg
☐ Zoom Scan (D:\MII2015\I15Z42998(FCC)\Wifi 5G Body 33a.da53:0/Rear CH52)	
Max. 2 at (-7.05, -3.28, -0.05) cm	0.29 W/kg
☐ Distances and Separation Ratios	
Max. 1 - Max. 2	Distance [cm]: 14.93 / Separation ratio [W/kg/cm]: 0.13

Picture 13.1 Distance evaluation for WCDMA 1700 and WLAN for CH52

Find distance of maxima	
☐ Maxima and position w.r.t. Grid Reference Point	associated 1g averages
☐ Zoom Scan (D:\MII2015\I15Z42998(FCC)\Wifi 5G Body 33a.da53:0/Rear CH157)	
Max. 1 at (-7.34, -3.48, -0.05) cm	0.22 W/kg
☐ Zoom Scan (D:\MII2015\I15Z42998(FCC)\WCDMA1700 Body 34a.da53:0/Rear High)	
Max. 2 at (7.02, 1.69, -0.07) cm	1.25 W/kg
☐ Distances and Separation Ratios	
Max. 1 - Max. 2	Distance [cm]: 15.26 / Separation ratio [W/kg/cm]: 0.12

Picture 13.2 Distance evaluation for WCDMA 1700 and WLAN for CH157

Table 13.2: The sum of reported SAR values for main antenna and Bluetooth

	Position	Main antenna	BT*	Sum
Highest reported SAR value for Head	Right hand, Touch cheek	0.39	0.21	0.60
Highest reported SAR value for Body	Rear	1.40	0.10	1.50

BT* - Estimated SAR for Bluetooth (see the table 13.3)

Table 13.3: Estimated SAR for Bluetooth

Position	F (GHz)	Distance (mm)	Upper limit of power *		Estimated _{1g} (W/kg)
			dBm	mW	
Head	2.441	5	7	5.01	0.21
Body	2.441	10	7	5.01	0.10

* - Maximum possible output power declared by manufacturer

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance,mm)]·[√f(GHz)/x] W/kg for test separation distances ≤ 50 mm;
where x = 7.5 for 1-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

Conclusion:

According to the above tables, the sum of reported SAR values is<1.6W/kg. So the simultaneous transmission SAR with volume scans is not required.

14 SAR Test Result

It is determined by user manual for the distance between the EUT and the phantom bottom.

The distance is 10mm for normal bands and AP ON, 15mm for AP OFF and just applied to the condition of body worn accessory.

It is performed for all SAR measurements with area scan based 1-g SAR estimation (Fast SAR). A zoom scan measurement is added when the estimated 1-gSAR is the highest measured SAR in each exposure configuration, wireless mode and frequency band combination or >1.2W/kg.

The calculated SAR is obtained by the following formula:

$$\text{Reported SAR} = \text{Measured SAR} \times 10^{(P_{\text{Target}} - P_{\text{Measured}})/10}$$

Where P_{Target} is the power of manufacturing upper limit;

P_{Measured} is the measured power in chapter 11.

Table 14.1: Duty Cycle

Duty Cycle	
Speech for GSM850/1900	1:8.3
GPRS&EGPRS	1:4
WCDMA & LTE & Wifi	1:1

14.1 SAR results for Fast SAR

Table 14.1-1: SAR Values (GSM 850 MHz Band - Head)

Ambient Temperature: 22.5 °C						Liquid Temperature: 22.0 °C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
836.6	190	Left	Touch	/	32.51	33.5	0.151	0.19	0.219	0.28	-0.11
836.6	190	Left	Tilt	/	32.51	33.5	0.0958	0.12	0.138	0.17	0.18
848.8	251	Right	Touch	Fig.1	32.18	33.5	0.21	0.28	0.276	0.37	0.16
836.6	190	Right	Touch	/	32.51	33.5	0.179	0.22	0.258	0.32	-0.06
824.2	128	Right	Touch	/	32.44	33.5	0.179	0.23	0.258	0.33	0.06
836.6	190	Right	Tilt	/	32.51	33.5	0.13	0.16	0.186	0.23	0.01

Table 14.1-2: SAR Values (GSM 850 MHz Band - Body)

Ambient Temperature: 22.5 °C						Liquid Temperature: 22.0 °C					
Frequency		Mode (number of timeslots)	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
836.6	190	GPRS (2)	Front	/	30.68	32	0.242	0.33	0.342	0.46	0.01
848.8	251	GPRS (2)	Rear	Fig.2	30.53	32	0.375	0.53	0.683	0.96	-0.09
836.6	190	GPRS (2)	Rear	/	30.68	32	0.389	0.53	0.641	0.87	0.11

824.2	128	GPRS (2)	Rear	/	30.65	32	0.371	0.51	0.619	0.85	-0.04
836.6	190	GPRS (2)	Left	/	30.68	32	0.148	0.20	0.219	0.30	-0.01
836.6	190	GPRS (2)	Right	/	30.68	32	0.318	0.43	0.472	0.64	-0.04
836.6	190	GPRS (2)	Bottom	/	30.68	32	0.144	0.20	0.247	0.33	-0.10
848.8	251	EGPRS (2)	Rear	/	30.53	32	0.364	0.51	0.659	0.92	-0.06

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.1-3: SAR Values (GSM 1900 MHz Band - Head)

Ambient Temperature: 22.5 °C						Liquid Temperature: 22.0 °C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1880	661	Left	Touch	/	28.58	30	0.0345	0.05	0.0583	0.08	0.14
1880	661	Left	Tilt	/	28.58	30	0.0289	0.04	0.0486	0.07	0.15
1909.8	810	Right	Touch	/	28.58	30	0.0435	0.06	0.0768	0.11	0.04
1880	661	Right	Touch	/	28.58	30	0.0458	0.06	0.0805	0.11	0.10
1850.2	512	Right	Touch	Fig.3	28.68	30	0.0555	0.08	0.0894	0.12	0.11
1880	661	Right	Tilt	/	28.58	30	0.0311	0.04	0.0549	0.08	0.02

Table 14.1-4: SAR Values (GSM 1900 MHz Band - Body)

Ambient Temperature: 22.5 °C						Liquid Temperature: 22.0 °C					
Frequency		Mode (number of timeslots)	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1880	661	GPRS (2)	Front	/	27.99	29	0.226	0.29	0.429	0.54	-0.14
1909.8	810	GPRS (2)	Rear	Fig.4	27.87	29	0.472	0.61	0.893	1.16	-0.01
1880	661	GPRS (2)	Rear	/	27.99	29	0.452	0.57	0.851	1.07	-0.12
1850.2	512	GPRS (2)	Rear	/	28.08	29	0.413	0.51	0.782	0.97	-0.12
1880	661	GPRS (2)	Left	/	27.99	29	0.0605	0.08	0.105	0.13	-0.09
1880	661	GPRS (2)	Right	/	27.99	29	0.0733	0.09	0.129	0.16	-0.13
1909.8	810	GPRS (2)	Bottom	/	27.87	29	0.357	0.46	0.664	0.86	0.05
1880	661	GPRS (2)	Bottom	/	27.99	29	0.37	0.47	0.69	0.87	0.02
1850.2	512	GPRS (2)	Bottom	/	28.08	29	0.363	0.45	0.682	0.84	0.03
1909.8	810	EGPRS (2)	Rear	/	27.87	28.5	0.427	0.49	0.855	0.99	-0.16

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.1-5: SAR Values (WCDMA 850 MHz Band - Head)

Ambient Temperature: 22.5 °C						Liquid Temperature: 22.0 °C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
836.4	4182	Left	Touch	/	22.72	23.5	0.137	0.16	0.197	0.24	0.04
836.4	4182	Left	Tilt	/	22.72	23.5	0.0815	0.10	0.116	0.14	-0.05
846.6	4233	Right	Touch	Fig.5	22.62	23.5	0.166	0.20	0.239	0.29	0.19
836.4	4182	Right	Touch	/	22.72	23.5	0.176	0.21	0.255	0.31	0.09
826.4	4132	Right	Touch	Fig.6	22.75	23.5	0.224	0.27	0.291	0.35	0.03
836.4	4182	Right	Tilt	/	22.72	23.5	0.0919	0.11	0.132	0.16	-0.08

Table 14.1-6: SAR Values (WCDMA 850 MHz Band - Body)

Ambient Temperature: 22.5 °C						Liquid Temperature: 22.0 °C				
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
836.4	4182	Front	/	22.72	23.5	0.223	0.27	0.307	0.37	0.01
846.6	4233	Rear	/	22.62	23.5	0.278	0.34	0.455	0.56	-0.03
836.4	4182	Rear	Fig.6	22.72	23.5	0.275	0.33	0.492	0.59	-0.02
826.4	4132	Rear	/	22.75	23.5	0.304	0.36	0.488	0.58	0.05
836.4	4182	Left	/	22.72	23.5	0.157	0.19	0.23	0.28	0.04
836.4	4182	Right	/	22.72	23.5	0.267	0.32	0.389	0.47	0.00
836.4	4182	Bottom	/	22.72	23.5	0.115	0.14	0.191	0.23	0.04

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.1-7: SAR Values (WCDMA 1700 MHz Band - Head)

Ambient Temperature: 22.5 °C						Liquid Temperature: 22.0 °C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1732.4	1412	Left	Touch	/	23.44	24	0.104	0.12	0.178	0.20	0.16
1732.4	1412	Left	Tilt	/	23.44	24	0.0511	0.06	0.0851	0.10	0.01
1752.6	1513	Right	Touch	Fig.7	23.52	24	0.144	0.16	0.228	0.25	0.04
1732.4	1412	Right	Touch	/	23.44	24	0.134	0.15	0.223	0.25	0.13
1712.4	1312	Right	Touch	/	23.51	24	0.125	0.14	0.211	0.24	0.12
1732.4	1412	Right	Tilt	/	23.44	24	0.0556	0.06	0.099	0.11	-0.05

Table 14.1-8: SAR Values (WCDMA 1700 MHz Band - Body)

Ambient Temperature: 22.5 °C						Liquid Temperature: 22.0 °C				
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
1732.4	1412	Front	/	23.44	24	0.4	0.46	0.642	0.73	0.05
1752.6	1513	Rear	Fig.8	23.52	24	0.666	0.74	1.25	1.40	0.06
1732.4	1412	Rear	/	23.44	24	0.576	0.66	1.01	1.15	-0.01
1712.4	1312	Rear	/	23.51	24	0.502	0.56	0.884	0.99	-0.07
1732.4	1412	Left	/	23.44	24	0.137	0.16	0.24	0.27	0.11
1732.4	1412	Right	/	23.44	24	0.174	0.20	0.301	0.34	-0.17
1752.6	1513	Bottom	/	23.52	24	0.5	0.56	0.925	1.03	-0.03
1732.4	1412	Bottom	/	23.44	24	0.423	0.48	0.763	0.87	-0.01
1712.4	1312	Bottom	/	23.51	24	0.35	0.39	0.635	0.71	-0.10

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.1-9: SAR Values (WCDMA 1900 MHz Band - Head)

Ambient Temperature: 22.5 °C						Liquid Temperature: 22.0 °C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1880	9400	Left	Touch	/	22.01	23	0.0551	0.07	0.0921	0.12	0.11
1880	9400	Left	Tilt	/	22.01	23	0.0439	0.06	0.0733	0.09	0.16
1907.6	9538	Right	Touch	/	22.00	23	0.0586	0.07	0.103	0.13	0.08
1880	9400	Right	Touch	/	22.01	23	0.0669	0.08	0.117	0.15	0.07
1852.4	9262	Right	Touch	Fig.9	21.94	23	0.0819	0.10	0.131	0.17	0.07
1880	9400	Right	Tilt	/	22.01	23	0.0497	0.06	0.0903	0.11	-0.11

Table 14.1-10: SAR Values (WCDMA 1900 MHz Band - Body)

Ambient Temperature: 22.5 °C						Liquid Temperature: 22.0 °C				
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
1880	9400	Front	/	22.01	23	0.22	0.28	0.404	0.51	0.01
1880	9400	Rear	/	22.01	23	0.343	0.43	0.615	0.77	0.13
1880	9400	Left	/	22.01	23	0.062	0.08	0.106	0.13	0.17
1880	9400	Right	/	22.01	23	0.0678	0.09	0.118	0.15	0.02
1907.6	9538	Bottom	Fig.10	22.00	23	0.424	0.53	0.807	1.02	-0.04
1880	9400	Bottom	/	22.01	23	0.412	0.52	0.785	0.99	-0.13
1852.4	9262	Bottom	/	21.94	23	0.405	0.52	0.768	0.98	0.12

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.1-11: SAR Values (LTE Band2 - Head)

Ambient Temperature: 22.5 °C						Liquid Temperature: 22.0 °C						
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.											
1900	19100	1RB_Mid	Left	Touch	/	23.21	23.5	0.0684	0.07	0.117	0.13	-0.09
1900	19100	1RB_Mid	Left	Tilt	/	23.21	23.5	0.0479	0.05	0.0827	0.09	0.11
1900	19100	1RB_Mid	Right	Touch	Fig.11	23.21	23.5	0.0894	0.10	0.147	0.16	-0.15
1900	19100	1RB_Mid	Right	Tilt	/	23.21	23.5	0.0413	0.04	0.0761	0.08	0.09
1880	18900	50RB_Low	Left	Touch	/	21.82	22.5	0.0558	0.07	0.095	0.11	0.07
1880	18900	50RB_Low	Left	Tilt	/	21.82	22.5	0.0377	0.04	0.0652	0.08	0.06
1880	18900	50RB_Low	Right	Touch	/	21.82	22.5	0.0706	0.08	0.124	0.15	0.12
1880	18900	50RB_Low	Right	Tilt	/	21.82	22.5	0.0325	0.04	0.0613	0.07	0.09

Note1: The LTE mode is QPSK_20MHz.

Table 14.1-12: SAR Values (LTE Band2 - Body)

Ambient Temperature: 22.5 °C						Liquid Temperature: 22.0 °C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1900	19100	1RB_Mid	Front	/	23.21	23.4	0.174	0.18	0.305	0.32	-0.03
1900	19100	1RB_Mid	Rear	/	23.21	23.4	0.297	0.31	0.536	0.56	-0.14
1900	19100	1RB_Mid	Left	/	23.21	23.4	0.045	0.05	0.0792	0.08	-0.07
1900	19100	1RB_Mid	Right	/	23.21	23.4	0.0615	0.06	0.105	0.11	-0.01
1900	19100	1RB_Mid	Bottom	Fig.12	23.21	23.4	0.36	0.38	0.724	0.76	-0.08
1880	18900	1RB_Mid	Bottom	/	23.15	23.4	0.393	0.42	0.784	0.83	-0.06
1860	18700	1RB_Mid	Bottom	/	22.97	23.4	0.502	0.55	0.973	1.07	0.15
1880	18900	50RB_Low	Front	/	21.82	22.4	0.136	0.16	0.239	0.27	-0.19
1880	18900	50RB_Low	Rear	/	21.82	22.4	0.236	0.27	0.427	0.49	-0.15
1880	18900	50RB_Low	Left	/	21.82	22.4	0.0346	0.04	0.0614	0.07	-0.11
1880	18900	50RB_Low	Right	/	21.82	22.4	0.0487	0.06	0.0839	0.10	-0.15
1880	18900	50RB_Low	Bottom	/	21.82	22.4	0.271	0.31	0.538	0.62	-0.15
1900	19100	100RB	Bottom	/	21.74	22.4	0.304	0.35	0.608	0.71	-0.10

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The LTE mode is QPSK_20MHz.

Table 14.1-13: SAR Values (LTE Band4 - Head)

Ambient Temperature: 22.5 °C						Liquid Temperature: 22.0 °C						
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.											
1745	20300	1RB_Mid	Left	Touch	/	22.99	23.4	0.121	0.13	0.204	0.22	-0.01
1745	20300	1RB_Mid	Left	Tilt	/	22.99	23.4	0.0613	0.07	0.101	0.11	0.17
1745	20300	1RB_Mid	Right	Touch	Fig.13	22.99	23.4	0.149	0.16	0.235	0.26	-0.08
1745	20300	1RB_Mid	Right	Tilt	/	22.99	23.4	0.056	0.06	0.0983	0.11	-0.04
1745	20300	50RB_Mid	Left	Touch	/	21.69	22.4	0.0943	0.11	0.158	0.19	0.08
1745	20300	50RB_Mid	Left	Tilt	/	21.69	22.4	0.0455	0.05	0.0752	0.09	0.07
1745	20300	50RB_Mid	Right	Touch	/	21.69	22.4	0.104	0.12	0.177	0.21	0.12
1745	20300	50RB_Mid	Right	Tilt	/	21.69	22.4	0.0421	0.05	0.0743	0.09	0.00

Note1: The LTE mode is QPSK_20MHz.

Table 14.1-14: SAR Values (LTE Band4 - Body)

Ambient Temperature: 22.5 °C						Liquid Temperature: 22.0 °C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1745	20300	1RB_Mid	Front	/	22.99	23.5	0.298	0.34	0.515	0.58	0.11
1745	20300	1RB_Mid	Rear	/	22.99	23.5	0.42	0.47	0.72	0.81	-0.09
1732.5	20175	1RB_Mid	Rear	Fig.14	22.74	23.5	0.461	0.55	0.852	1.01	-0.02
1720	20050	1RB_Mid	Rear	/	22.80	23.5	0.413	0.49	0.709	0.83	-0.01
1745	20300	1RB_Mid	Left	/	22.99	23.5	0.0736	0.08	0.126	0.14	0.01
1745	20300	1RB_Mid	Right	/	22.99	23.5	0.125	0.14	0.211	0.24	0.07
1745	20300	1RB_Mid	Bottom	/	22.99	23.5	0.355	0.40	0.642	0.72	-0.03
1745	20300	50RB_Mid	Front	/	21.69	22.5	0.216	0.26	0.371	0.45	0.00
1745	20300	50RB_Mid	Rear	/	21.69	22.5	0.307	0.37	0.551	0.66	0.05
1745	20300	50RB_Mid	Left	/	21.69	22.5	0.0563	0.07	0.097	0.12	0.00
1745	20300	50RB_Mid	Right	/	21.69	22.5	0.0995	0.12	0.168	0.20	-0.14
1745	20300	50RB_Mid	Bottom	/	21.69	22.5	0.299	0.36	0.528	0.64	0.09
1720	20050	100RB	Rear	/	21.67	22.5	0.351	0.42	0.611	0.74	0.06

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The LTE mode is QPSK_20MHz.