

Test Report

Applicant : Shenzhen Tcity Electronics Co., Ltd.
10th Floor, Xingqiang Trading Building, No. 4,
Address : Dezheng Road, Shilong Community, Shenzhen
Bao'an District
Product Name : Bluetooth Built-in Tire Pressure Sensor
Brand Mark : N/A
Model : MQ-B
Report Number : BLA-EMC-202601-A10801
Date of Receipt : Feb. 3, 2026
Date of Test : Feb. 3, 2026 to Mar. 3, 2026
Test standard : Item 19 of Article 2 Paragraph 1
Test Result : Pass

Compiled by: *Hugh*Review by: *Xavier*Approved by: *Blue Zheng*

Issued Date: Mar. 3, 2026

BlueAsia Technical Services (Shenzhen) Co., Ltd

Address: No.41, South of Beihuan Road, Shangwu Community, Shiyan

Subdistrict, Bao'an District, Shenzhen, Guangdong, China



The test report is effective only with both signature and specialized stamp and The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full. The results described in this report do not represent the quality or characteristics of the sampled batch, nor do they represent any similar or identical products that are not explicitly stated.

Table of Contents

1	General information	4
1.1	General information	4
1.2	General description of EUT	4
2	Test summary	5
3	Description of Support Units	6
4	Auxiliary equipment	6
5	Laboratory information	6
6	Equipment List	7
7	Radio Technical Requirements Specification	8
8	Transmitter Requirements	9
8.1	EUT test voltage and Frequency	9
8.2	Test frequency	10
8.3	Antenna Requirement	11
8.4	Interference prevention function	12
8.5	RF accessibility	13
8.6	Frequency Error	14
8.7	Occupied Bandwidth (99%)	17
8.8	Antenna Power	20
8.9	Spurious Emissions of Tx	23
9	Receiver Requirements	29
9.1	Spurious Emissions of Rx	29
Appendix A: Photographs of test setup		33
Appendix B: photographs of EUT		34

Revise Record

Version No.	Date	Description
01	Mar. 3, 2026	Original

1 General information

1.1 General information

Applicant	Shenzhen Tcity Electronics Co., Ltd.
Address	10th Floor, Xingqiang Trading Building, No. 4, Dezheng Road, Shilong Community, Shenzhen Bao'an District
Manufacturer	Shenzhen Tcity Electronics Co., Ltd.
Address	10th Floor, Xingqiang Trading Building, No. 4, Dezheng Road, Shilong Community, Shenzhen Bao'an District
Factory	Shenzhen Tcity Electronics Co., Ltd.
Address	10th Floor, Xingqiang Trading Building, No. 4, Dezheng Road, Shilong Community, Shenzhen Bao'an District

1.2 General description of EUT

Product name	Bluetooth Built-in Tire Pressure Sensor
Model no.	MQ-B
Series model	N/A
Test engineer sample no.	BLA-RF-202601-A10801
Operating Frequency	2406MHz~2480MHz
Conducted rated power	F1D: 0.3mW
Modulation Type:	GFSK
Channel Spacing:	2MHz
Rate data:	1Mbps
Number of Channels:	38
Antenna Type:	Metal antenna
Antenna Gain:	-0.9887dBi(Provided by customer)
Power supply or adapter information	DC3V by battery
Hardware Version	SE023A
Software Version	v0050

Note: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

2 Test summary

Test	Test Requirement	Limit/Severity	Result
Antenna Requirement	Item 19 of Article 2 Paragraph 1	Notice 88 Appendix 43,B-1 (1)&(2)	PASS
Test frequency	Item 19 of Article 2 Paragraph 1	Notice 88 Appendix 43, A-3	PASS
Frequency Error	Item 19 of Article 2 Paragraph 1	±50 PPM or less	PASS
Occupied Bandwidth	Item 19 of Article 2 Paragraph 1	Within 26MHz	PASS
Antenna Power	Item 19 of Article 2 Paragraph 1	Designated value: a. FH, FH+ DS, FH+OFDM 3mW/MHz (Used in the range of 2427-2470.75MHz) b. OFDM, DS other than (1): 10mW/MHz c. Other than (1) & (2) 10mW Tolerance: +20%	PASS
E.I.R.P	Item 19 of Article 2 Paragraph 1	Designated value: a. FH, DS+FH, FH+OFDM: 6.91-16.91 dBm (Used in the range of 2427-2470.75MHz) b. OFDM, DS other than (1): 12.14dBm-22.14 dBm c. Other than (1) & (2): 12.14dBm-22.14 dBm	PASS
Half Power Beam Angel	Item 19 of Article 2 Paragraph 1	N/A ^{Note1}	N/A
Spurious Emission of Tx	Item 19 of Article 2 Paragraph 1	a. Below 2387 MHz: -26dBm/MHz b. 2387 to 2400 MHz: -16dBm/MHz c. 2483.5 through 2496.5 MHz: -16dBm/MHz d. Over 2496.5 MHz: -26dBm/MHz	PASS
Dwell Time	Item 19 of Article 2 Paragraph 1	N/A	N/A
Pseudorandom Frequency Hopping Sequence	Item 19 of Article 2 Paragraph 1	Notice 88 Appendix 43	N/A
Interference prevention capability	Item 19 of Article 2 Paragraph 1	Notice 88 Appendix 43	PASS
RF accessibility	Item 19 of Article 2 Paragraph 1	Notice 88 Appendix 43	PASS
Spurious Emission of Rx	Item 19 of Article 2 Paragraph 1	a. Below 1 GHz: -54dBm b. 1GHz or higher: -47dBm	PASS
Remark: EUT: In this whole report EUT means Equipment Under Test. Tx:In this whole report Tx (or tx) means the product in transmitting status. Rx: In this whole report Rx (or rx) means the product in receiving status. RF:In this whole report RF means Radiated Frequency. Note1: Max EIRP power is less than 12.14dBm, so this test item is not applicable.			

3 Description of Support Units

The EUT has been tested stand-alone.

4 Auxiliary equipment

Device Type	Manufacturer	Model Name	Serial No.	Remark
USB TO TTL	N/A	V287	N/A	By laboratory
Note: “--” mean no any auxiliary device during testing.				

5 Laboratory information

The test facility is recognized, certified, or accredited by the following organizations:

Company name:	BlueAsia Technical Services (Shenzhen) Co.,Ltd.
Address:	No.41, South of Beihuan Road, Shangwu Community, Shiyan Subdistrict, Bao'an District, Shenzhen, Guangdong, China
Registration No.:	L9788
Telephone:	+86-755-28682673
FAX:	+86-755-28682673

6 Equipment List

Equipment	Manufacturer	Model	Serial No.	Cal Date	Due Date	Calibration body	Classification
Communication test set test set	Anritsu	MT8852B	06262047872	2025/9/7	2026/9/6	GRGT	(c)
Spectrum Analyzer	Keysight	N9030A	MY52350152	2025/9/7	2026/9/6	GRGT	(c)
Signal Generator	Agilent	E4438C	MY45092582	2025/9/7	2026/9/6	GRGT	(c)
DC regulated power supply	ZHAOXIN	KXN-305D	BLA-EMC-027	2025/9/24	2026/9/23	GRGT	(c)

Remark:

- (a) Calibration conducted by the National Institute of Information and Communications Technology (NICT) in Japan (hereinafter referred to as "NICT") or a designated calibration agency under Article 102-18 paragraph (1) in JRL.
- (b) Correction conducted pursuant to the provisions of Article 135 or Article 144 of the Measurement Act (Act No. 51 of 1992) .
- (c) Calibration conducted in countries except Japan, which shall be equivalent to the calibration conducted by the NICT or a designated calibration agency under Article 102-18 paragraph (1).
- (d) Calibration, etc. conducted by using measuring instruments and other equipment listed in the right column of appended table No. 3, which shall have been given any type of calibration, etc. listed above from (a) to (C)

From JRL Article 24-2, paragraph 4, Item 2

Notice: Calibration duration for above equipments is 1 year.

7 Radio Technical Requirements Specification



Table 1: Radio Technical Requirements Specification for 2.4 GHz band wide-band low-power data communication system (Item 19 of Article 2 Paragraph 1)

Items	Technical standard
Assigned frequency or designated frequency	2400-2483.5MHz
Communication method	One-way communication, simplex, semi-duplex, or duplex operation of digital signal transmission including spread spectrum
Tolerance of frequency ($\times 10^{-6}$)	± 50 PPM
Tolerance of occupied bandwidth	FH: 83.5MHz or less FH + OFDM: 83.5MHz or less Others: 26MHz or less FH + DS: 83.5MHz or less OFDM: 40MHz or less
Antenna power	Designated value a. FH, FH+ DS, FH+OFDM: 3mW/MHz (used in the range of 2427 - 2470.75 MHz) b. OFDM, DS other than (1): 10mW/MHz c. Other than (1) & (2): 10mW Tolerance : +20%
Antenna gain	1) 12.14 dBi or less in principle 2) In case of directional antenna a. FH, FH+DS or FH+OFDM using 2427-2470.75 MHz EIRP $\leq$ 16.91 dBm/MHz b. OFDM or DS other than (1) EIRP $\leq$ 22.14 dBm/MHz c. Other than (1) and (2): 22.14 dBm or less d. OFDM OBW 26 - 40MHz: 19.14dBm/MHz e. Half-power angle of directional antenna (e) in case of the item 2): e $\leq$ 360/A (The A is 10 in maximum.)
Tolerance of spurious emission intensity	a. Below 2387 MHz: 2.5 μ W/MHz; b. 2387 to 2400 MHz: 25 μ W/MHz; c. 2483.5 through 2496.5 MHz: 25 μ W/MHz; d. Over 2496.5 MHz: 2.5 μ W/MHz
Spreading bandwidth	N/A
Limit of secondary radiated emissions	a. Below 1 GHz: 4nW b. 1 GHz or higher: 20nW
Interference prevention function	Shall have the function of automatic transmission and reception of identification sign.
Structure	Shall be of the structure that the RF and modulator sections excluding antenna cannot easily be opened.
Note	DS: Direct spread FH: Frequency hopping OFDM: Orthogonal frequency division multiplexing

Note: The Technical Standards described here do not cover all of the regulated items.

8 Transmitter Requirements

8.1 EUT test voltage and Frequency

EUT test voltage									
Power Supply:	DC 3V								
Test voltage require:	The power supply is DC 3V by battery. The supply voltage of RF part is varied within +/-1% when DC 3V +/- 10%, so DC 3V is shown in the test report.								
Power Supply view:	 Test below: 1: The fluctuation of B point is under $\pm 1\%$, when input voltage from A point to the test equipment is fluctuated by $\pm 10\%$. 								
Power Supply result:	The measurement result of the voltage fluctuation at RF circuit when 3V +/- 10%. <table border="1"> <thead> <tr> <th>DC INPUT</th><th>DC3V</th></tr> </thead> <tbody> <tr> <td>2.7V</td><td>3V</td></tr> <tr> <td>3V</td><td>3V</td></tr> <tr> <td>3.3V</td><td>3V</td></tr> </tbody> </table>	DC INPUT	DC3V	2.7V	3V	3V	3V	3.3V	3V
DC INPUT	DC3V								
2.7V	3V								
3V	3V								
3.3V	3V								

Test condition	Ambient		
	Temperature(°C)	Humidity(%)	Voltage(V)
NTNV	24	48	3
NTLV	N/A	N/A	N/A
NTHV	N/A	N/A	N/A

8.2 Test frequency

Test frequencies:	If the EUT can be set to 3 or more different (carrier) frequencies in 1 allocated band, testing shall be performed using the Lowest, Middle and the Highest frequency (L,M and H). If there are 2 or fewer frequencies, testing shall be performed with the available frequencies.		
	Frequency range over which device operates	Number of frequencies	Location in the range of operation
	1 MHz or less	1	Middle
	1 to 10 MHz	2	1 near top and 1 near bottom
	More than 10 MHz	3	1 near top. 1 near middle and 1 near bottom


EUT channels and frequencies list:

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2406MHz	10	2426MHz	20	2446MHz	30	2466MHz
1	2408MHz	11	2428MHz	21	2448MHz	31	2468MHz
⋮	⋮	⋮	⋮	⋮	⋮	⋮	⋮
8	2422MHz	18	2442MHz	28	2462MHz	36	2478MHz
9	2424MHz	19	2444MHz	29	2464MHz	37	2480MHz

Test frequencies are the lowest channel: 0 channel (2406 MHz), Middle channel, 18 channel (2442 MHz) and highest channel: 37channel (2480 MHz).


8.3 Antenna Requirement

Standard requirement
Applicable for equipment with an antenna terminal, including testing terminals) If an antenna connector is available, all relevant tests will be carried out conducted. If not, tests will be carried out in an anechoic room or with a suitable test-fixture.
EUT Antenna
The antenna is metal antenna and no consideration of replacement. The best case gain of the antenna is -0.9887dBi from 2406~2480MHz



Result: An antenna connector is available; all relevant tests will be carried out conducted.

8.4 Interference prevention function

Measurement system diagram	When transmitting identification code  <pre> graph LR TE[Test equipment] -.-> wireless D[Demodulator] </pre>
Condition of measuring instrument	Demodulator must be able to demodulate the transmitting signal emitted by test equipment and to indicate the identification code.
Condition of test equipment The mode of normal use.	--
Measuring operation procedure	When test equipment has the function to transmit identification code automatically: - Transmit the predetermined identification code from test equipment. - Confirm the transmitted identification code by demodulator.
	
	MAC Address: BE:7F:8B:6D:B9:20
Test result	The unit does meet the requirements (Good).


8.5 RF accessibility

Standard requirement


Article 49-20, paragraph 1 (a)

The EUT shall be constructed in such a way that sensitive RF parts, (like modulation and oscillator parts) cannot be reached easily by the user. These parts shall be covered by soldered metal caps or glue or by other mechanical covers. If the covers are fixed with screws, these shall be not the common type(s) like a Phillips, but special versions like Torx, so that the user cannot open the device with common tools.

RF and Modulation parts are mounted on PCB with surface mount technology, and The product cannot be modified and once disassembled, it will not be usable. The number of IC pins is 24, and the interval of pins is less than 1.5mm.



8.6 Frequency Error

Test Requirement:	Item 19 of Article 2 Paragraph 1		
Test Method:	MIC Notice No.88 Appendix No.43		
Ambient:	Temp.: 24°C	Humid.: 50%	Press.: 1010 mbar
Test Status:	Test the EUT in transmitting mode without modulation. Test in Channel lowest (2406MHz), middle (2442MHz) and highest (2480MHz), keep in continuously transmitting status.		
Test Configuration:			
Test Conditions:	Frequency Counter or Spectrum Analyzer is used for measurement.		
EUT conditions:	Modulation/Spread/Hopping off, CW Tx If EUT does not accept "Modulation OFF" mode in the measurement, you may use "Modulation ON" mode. In that case you can use the Max power Frequency as the measuring results.		
Spectrum Analyzer conditions:	Frequency: Test Frequency Span 1MHz RBW 10KHz VBW 10KHz Sweep Time Auto Detector mode Positive peak Indication mode Max hold		
Technical standard:	Tolerance of frequency: $\pm 50 \times 10^{-6}$		
Test result:	PASS		

Measurement Record: Uncertainty: $\pm 10\text{Hz}$ **8.6.1 Test Result**

Test Condition	Test Mode	Antenna	Channel	CenterFreq [MHz]	Result[ppm]	Limit[ppm]	Verdict
NTNV	CW	Ant1	2406	2406.026	10.80632	± 50	PASS
			2442	2442.027	11.05651	± 50	PASS
			2480	2480.027	10.88710	± 50	PASS


Note: The nominal frequency shall be confirmed by the applicant and test lab.

Result plot as follows:

8.6.2 Test Graphs:



8.7 Occupied Bandwidth (99%)

Test Requirement:	Item 19 of Article 2 Paragraph 1
Test Method:	MIC Notice No.88 Appendix No.43
Ambient:	Temp.: 24°C Humid.: 50% Press.: 1010 mbar
Test Status:	Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.
Test Configuration:	 <pre> graph LR EUT[EUT] --> SA[Spectrum Analyzer] </pre>
EUT conditions:	Modulation/Spread/Hopping on, Modulation Tx For equipment using diffusion code, set to the test diffusion code and modulate with standard coding test signal.
Spectrum Analyzer conditions:	Frequency: Test Frequency Span 3MHz or 6MHz RBW 100KHz VBW 300KHz Sweep Time Auto detector mode Positive peak Indication mode Max hold OBW 99%
Technical standard:	26MHz or less
Test result:	PASS

Measurement Record: Uncertainty: $\pm 10\text{KHz}$ **8.7.1 Test Result**


TestCondition	TestMode	Antenna	Channel	Result [MHz]	Limit [MHz]	Verdict
NTNV	GFSK	Ant1	2406	1.051	≤ 26	PASS
			2442	1.095	≤ 26	PASS
			2480	1.078	≤ 26	PASS

Result plot as follows:

8.7.2 Test Graphs



8.8 Antenna Power

Test Requirement:	Item 19 of Article 2 Paragraph 1		
Test Method:	MIC Notice No.88 Appendix No.43		
Ambient:	Temp.: 24°C	Humid.: 50%	Press.: 1010 mbar
Test Status:	Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.		
Test Configuration:	 <pre> graph LR EUT[EUT] --> SA[Spectrum Analyzer] </pre>		
EUT conditions:	Modulation/Spread/Hopping on, PN9 Modulation Tx For equipment using diffusion code, set to the test diffusion code and modulate with standard coding testsignal.		
Spectrum Analyzer conditions(FHSS):	Frequency: Test Frequency Span 10MHz RBW 3MHz VBW 3MHz Sweep Time Auto Detector mode Positive peak Indication mode Max hold		
Technical standard:	Antenna Power (1) FH, FH+DS , FH+OFDM 3mW/MHz or less (used in the range of 2427- 2470.75 MHz) (2) OFDM , DS other than (1) 10mW/MHz or less (3) Other than (1) & (2) 10mW or less Tolerance: +20%		
Test result:	PASS		

Measurement Record: Uncertainty: ± 10 kHz / ± 1 dB

8.8.1 Test Result

AntennaPower						
TestCondition	TestMode	Antenna	Channel	Result(mW)	Limit(mW)	Verdict
NTNV	GFSK	Ant1	2406	0.152	≤ 10	PASS
			2442	0.235	≤ 10	PASS
			2480	0.199	≤ 10	PASS

Tolerance								
Test Condition	Test Mode	Antenna	Channel	Power (mW)	RatedPower (mW)	Result(%)	Limit(%)	Verdict
NTNV	GFSK	Ant1	2406	0.152	0.3	-49.33	+20	PASS
			2442	0.235	0.3	-21.67	+20	PASS
			2480	0.199	0.3	-33.67	+20	PASS

Remark:


Conducted rated power:F1D: 0.3mW

Tolerance (%) :[(test value- rate power)/rater power]*100


EIRP							
TestCondition	TestMode	Antenna	Channel	Antenna conducted Power (dBm)	EIRP(dBm)	Limit(dBm)	Verdict
NTNV	GFSK	Ant1	2406	-8.185	-9.1737	≤ 12.14	PASS
			2442	-6.295	-7.2837	≤ 12.14	PASS
			2480	-7.018	-8.0067	≤ 12.14	PASS

Result plot as follows:

8.8.2 Test Graphs



8.9 Spurious Emissions of Tx

Test Requirement:	Item 19 of Article 2 Paragraph 1		
Test Method:	MIC Notice No.88 Appendix No.43		
Ambient:	Temp.: 24°C	Humid.: 50%	Press.: 1010 mbar
Test Status:	Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.		
Test Configuration:			
EUT conditions:	Modulation/Spread/Hopping on, PN9 Modulation Tx For equipment using diffusion code, set to the test diffusion code and modulate with standard coding test signal.		
Measurement Procedure:	Step1 All spurious are measured from 30MHz to 13GHz by peak mode.		
Spectrum Analyzer conditions(Step 1):	Frequency: 30MHz – 2400MHz , 2483.5MHz –13GHz RBW 1000kHz (30 – 1GHz) , 1000KHz (over 1GHz) VBW 1000kHz (30 – 1GHz) , 1000KHz (over 1GHz) Sweep Time Auto detector mode Positive peak Indication mode Max hold		
Spectrum Analyzer conditions(Step 2):	Frequency: Spurious Frequency Span 0Hz RBW 1MHz VBW 1MHz Sweep Time Auto Detector mode Sample Indication mode Max hold		
Technical standard:	(1) Below 2387 MHz : 2.5μW/MHz (2) 2387 to 2400 MHz : 25μW/MHz (3) 2483.5 through 2496.5 MHz : 25μW/MHz (4) Over 2496.5 MHz : 2.5μW/MHz		
Test result:	PASS		

Measurement Record: Uncertainty: $\pm 1\text{dB}$ **8.9.1 Test Result**

Test Condition	Test Mode	Channel	Freq.Range [MHz]	Freq [MHz]	Result [dBm/MHz]	Limit [dBm/MHz]	Verdict
NTNV	GFSK	2406	30~2387	32.36	-51.18	≤ -26	PASS
			2387~2400	2399.91	-58.92	≤ -16	PASS
			2483.5~2496.5	2493.01	-62.23	≤ -16	PASS
			2496.5~13000	7217.53	-39.21	≤ -26	PASS
		2442	30~2387	32.06	-51.47	≤ -26	PASS
			2387~2400	2393.87	-61.40	≤ -16	PASS
			2483.5~2496.5	2489.85	-61.36	≤ -16	PASS
			2496.5~13000	3497.53	-38.67	≤ -26	PASS
		2480	30~2387	32.06	-51.36	≤ -26	PASS
			2387~2400	2388.98	-62.79	≤ -16	PASS
			2483.5~2496.5	2483.77	-50.55	≤ -16	PASS
			2496.5~13000	7441.27	-39.48	≤ -26	PASS

Result plot as follows:

8.9.2 Test Graphs










9 Receiver Requirements


9.1 Spurious Emissions of Rx

Test Requirement:	Item 19 of Article 2 Paragraph 1		
Test Method:	MIC Notice No.88 Appendix No.43		
Ambient:	Temp.: 24°C	Humid.: 50%	Press.: 1010 mbar
Test Status:	Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.		
Test Configuration:	 <pre> graph LR EUT[EUT] --> SA[Spectrum Analyzer] </pre>		
EUT conditions:	Rx		
Measurement Procedure:	Step1 All spurious are measured from 30MHz to 13 GHz by peak mode. Step2 IF the value measured by Step1 is exceed the limit of 1/10, measure in average mode.		
Spectrum Analyzer conditions(Step 1):	Frequency: 30MHz – 2400MHz , 2483.5MHz –13GHz RBW 100 kHz (30 – 1GHz) , 1 MHz (over 1GHz) VBW 100 kHz (30 – 1GHz) , 1 MHz (over 1GHz) Sweep Time Auto detector mode Positive peak Indication mode Max hold		
Spectrum Analyzer Conditions(Step 2):	Frequency: Spurious Frequency Span 0 Hz RBW 100 kHz (30 – 1GHz) , 1 MHz (over 1GHz) VBW 100 kHz (30 – 1GHz) , 1 MHz (over 1GHz) Sweep Time Auto detector mode RMS Indication mode Max hold		
Technical standard:	(1) Below 1 GHz : 4 nW or less (2) 1 GHz and over : 20 nW or less		
Test result:	PASS		

9.1.1 Test Result


Test Condition	Test Mode	Channel	Freq.Range [MHz]	Freq [MHz]	Result [dBm]	Limit [dBm]	Verdict
NTNV	GFSK	2406	30~1000	671.29	-91.14	<=-54	PASS
			1000~13000	12326.17	-76.62	<=-47	PASS
		2442	30~1000	991.03	-90.93	<=-54	PASS
			1000~13000	5793.04	-76.58	<=-47	PASS
		2480	30~1000	374.84	-90.74	<=-54	PASS
			1000~13000	12926.80	-76.79	<=-47	PASS

9.1.2 Test Graphs










Appendix A: Photographs of test setup





Appendix B: photographs of EUT





















----END OF REPORT----

The test report is effective only with both signature and specialized stamp, the result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.