

LP0002 5.7

DYNAMIC FREQUENCY SELECTION

TEST REPORT

For

CRESTRON ELECTRONICS, INC.

15 VOLVO DRIVE, ROCKLEIGH, NJ 07647, USA

Brand: CRESTRON
Model: M201928001

Report Type:
Original Report

Product Type:
TABLETOP CONFERENCE
SYSTEM

Report Producer : Jane Chen

陳藝蓁

Report Number : RXZ210924002RF05

Report Date : 2021-10-25

Reviewed By: David Hsu

徐士珩

Prepared By: Bay Area Compliance Laboratories Corp.

(New Taipei Laboratory)

70, Lane 169, Sec. 2, Datong Road, Xizhi Dist.,

New Taipei City 22183, Taiwan, R.O.C.

Tel: +886 (2) 2647 6898

Fax: +886 (2) 2647 6895

www.bacl.com.tw

Revision History

Revision	No.	Report Number	Issue Date	Description	Author/ Revised by
0.0	RXZ210924002	RXZ210924002RF05	2021-10-25	Original Report	Jane Chen

TABLE OF CONTENTS

1	General Information	4
1.1	Product Description for Equipment under Test (EUT)	4
1.2	Statement of Compliance	5
1.3	Test Methodology.....	5
1.4	Test Facility	5
2	System Test Configuration.....	6
2.1	Description of Test Configuration.....	6
2.2	EUT Exercise Software	6
2.3	Support Equipment List and Details.....	6
3	Summary of Test Results.....	7
4	Test Equipment List and Details	8
5	Applicable Standards.....	9
5.1	DFS Requirement	9
5.2	DFS Measurement System	13
5.3	System Block Diagram.....	13
5.4	Test Procedure	15
6	Test Result	16
6.1	Description of EUT	16
6.2	Channel Loading	16
6.3	Conducted Test Setup Configuration	17
6.4	Calibration of DFS Detection Threshold Level.....	17
6.5	Environmental Conditions.....	17
7	Channel Move Time and Channel Closing Transmission Time	28
7.1	Test Procedure	28
7.2	Environmental Conditions.....	28
7.3	Test Results	28
8	Non-Occupancy Period.....	35
8.1	Test Procedure	35
8.2	Environmental Conditions.....	35
8.3	Test Result.....	35

1 General Information

1.1 Product Description for Equipment under Test (EUT)

Applicant	CRESTRON ELECTRONICS, INC.
	15 VOLVO DRIVE, ROCKLEIGH, NJ 07647, USA
Manufacturer	CRESTRON ELECTRONICS, INC.
	15 VOLVO DRIVE, ROCKLEIGH, NJ 07647, USA
Brand(Trade) Name	CRESTRON
Product (Equipment)	TABLETOP CONFERENCE SYSTEM
Main Model Name	M201928001
Series Model Name	N/A
Antenna Specification	Dipole Antenna / 5.0 dBi
Power Operation (Voltage Range)	☐ AC 120V/60Hz ☐ Adapter I/P: 100-240Vac,1.2A ; O/P: 12Vdc, 3A ☐ By AC Power Cord
	☐ DC Type ☐ Battery ☐ DC Power Supply ☐ External from USB Cable ☐ External DC Adapter
	☒ PoE: 48V/500mA
Received Date	Sep. 24, 2021
Date of Test	Oct. 1, 2021 ~ Oct. 3, 2021

*All measurement and test data in this report was gathered from production sample serial number: RXZ210924002 (Assigned by BACL, New Taipei Laboratory).

1.2 Statement of Compliance

This report is prepared on behalf of CRESTRON ELECTRONICS, INC. in accordance with Part 2, Subpart J, Part 15, Subparts A, B and E of the Federal Communication Commission's rules and LP0002 chapter 5.7.7

The tests were performed in order to determine compliance with FCC Part 15.407(h) (2) Radar Detection Function of Dynamic Frequency Selection (DFS).

It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (New Taipei Laboratory)

Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. The determination of the test results does not require consideration of the uncertainty of the measurement, unless the assessment is required by customer agreement, regulation or standard document specification.

1.3 Test Methodology

FCC CFR 47 Part2, Part15.407 (h)

FCC KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02

FCC KDB 905462 D03 UNII Clients without Radar Detection New Rules v01r02

NCC LP0002 chapter 5.7.7

1.4 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (New Taipei Laboratory) to collect test data is located on

☒70, Lane 169, Sec. 2, Datong Road, Xizhi Dist., New Taipei City 22183, Taiwan, R.O.C.

Bay Area Compliance Laboratories Corp. (New Taipei Laboratory) Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 3732) and the FCC designation No.TW3732 under the Mutual Recognition Agreement (MRA) in FCC Test. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.10.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 974454. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

2 System Test Configuration

2.1 Description of Test Configuration

The EUT was configured for testing in a normal mode which was provided by the manufacturer.

2.2 EUT Exercise Software

Used “Telnet V1.0” software.

2.3 Support Equipment List and Details

隨貨附賣

No.	Description	Manufacturer	Model
1	POE	SHENZHEN GOSPELL DIGITAL TECHNOLOGY	G0720-480-050
2	LAN Cable	DEHAO	3.6m
3	LAN Cable	DEHAO	3.6m
4	USB Cable	SURE-FIRE	1.8m

未隨貨附賣

No.	Description	Manufacturer	Model
1	NB	DELL	E6410
2	無線路由器	NETGEAR	R7800

3 Summary of Test Results

A compliant test report to FCC 15.407 shall be sufficient to show compliance of a transmitter or receiver with the requirement of this standard.

The following result table represents the list of measurements required under the CFR §47 Part 15.407(h), and KDB: 905462 D02 UNII DFS Compliance Procedures New Rules v02

Items	Description of Test	Results
Detection Bandwidth	UNII Detection Bandwidth	Not applicable
Performance Requirements Check	Initial Channel Availability Check Time (CAC)	Not applicable
	Radar Burst at the Beginning of the CAC	Not applicable
	Radar Burst at the End of the CAC	Not applicable
In-Service Monitoring	Channel Move Time	Compliant
	Channel Closing Transmission Time	Compliant
	Non-Occupancy Period	Compliant
Radar Detection	Statistical Performance Check	Not applicable

Note:

Not applicable: the EUT is a client unit without radar detection

4 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due Date
Spectrum Analyzer	Rohde & Schwarz	FSV40	101140	2021/1/7	2022/1/6
Signal Generator	Rohde & Schwarz	SMB100A	110700	2021/1/6	2022/1/5
Power Splitter	Mini-Circuits	ZFRSC-183-S+	S F448201614	2021/6/23	2022/6/22

***Statement of Traceability:** BACL Corp. attests that all of the calibrations on the equipment items listed above were traceable to the SI System of Units via the R.O.C. Center for Measurement Standards of the Electronics Testing Center, Taiwan (ETC) or to another internationally recognized National Metrology Institute (NMI), and were compliant with the current Taiwan Accreditation Foundation (TAF) requirements

5 Applicable Standards

5.1 DFS Requirement

CFR §47 Part 15.407(h),

FCC KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02

Table 1: Applicability of DFS Requirements Prior to Use of a Channel

Requirement	Operational Mode		
	Master	Client Without Radar Detection	Client With Radar Detection
<i>Non-Occupancy Period</i>	Yes	Not required	Yes
<i>DFS Detection Threshold</i>	Yes	Not required	Yes
<i>Channel Availability Check Time</i>	Yes	Not required	Not required
<i>U-NII Detection Bandwidth</i>	Yes	Not required	Yes

Table 2: Applicability of DFS requirements during normal operation

Requirement	Operational Mode	
	Master Device or Client with Radar Detection	Client Without Radar Detection
<i>DFS Detection Threshold</i>	Yes	Not required
<i>Channel Closing Transmission Time</i>	Yes	Yes
<i>Channel Move Time</i>	Yes	Yes
<i>U-NII Detection Bandwidth</i>	Yes	Not required

Additional requirements for devices with multiple bandwidth modes	Master Device or Client with Radar Detection	Client Without Radar Detection
<i>U-NII Detection Bandwidth and Statistical Performance Check</i>	All BW modes must be tested	Not required
<i>Channel Move Time and Channel Closing Transmission Time</i>	Test using widest BW mode available	Test using the widest BW mode available for the link
<i>All other tests</i>	Any single BW mode	Not required
Note: Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.		

Table 3: DFS Detection Thresholds for Master Devices and Client Devices With Radar Detection

Maximum Transmit Power	Value (See Notes 1, 2, and 3)
EIRP $\geq$ 200 milliwatt	-64 dBm
EIRP < 200 milliwatt and power spectral density < 10 dBm/MHz	-62 dBm
EIRP < 200 milliwatt that do not meet the power spectral density requirement	-64 dBm

Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna.

Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.

Note3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.

Table 4: DFS Response Requirement Values

Parameter	Value
<i>Non-occupancy period</i>	Minimum 30 minutes
<i>Channel Availability Check Time</i>	60 seconds
<i>Channel Move Time</i>	10 seconds See Note 1.
<i>Channel Closing Transmission Time</i>	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.
<i>U-NII Detection Bandwidth</i>	Minimum 100% of the U- NII 99% transmission power bandwidth. See Note 3.

Note 1: *Channel Move Time* and the *Channel Closing Transmission Time* should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst.

Note 2: The *Channel Closing Transmission Time* is comprised of 200 milliseconds starting at the beginning of the *Channel Move Time* plus any additional intermittent control signals required to facilitate a *Channel* move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

Note 3: During the *U-NII Detection Bandwidth* detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.

Table 5 – Short Pulse Radar Test Waveforms

Radar Type	Pulse Width (μsec)	PRI (μsec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Number of Trials
0	1	1428	18	See Note 1	See Note 1
1	1	Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a Test B: 15 unique PRI values randomly selected within the range of 518-3066 μsec, with a minimum increment of 1 μsec, excluding PRI values selected in Test A	Roundup $\left\{ \left(\frac{1}{360} \right) \cdot \left(\frac{19 \cdot 10^6}{\text{PRI}_{\mu\text{sec}}} \right) \right\}$	60%	30
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120
Note 1: Short Pulse Radar Type 0 should be used for the detection bandwidth test, channel move time, and channel closing time tests.					

A minimum of 30 unique waveforms are required for each of the Short Pulse Radar Types 2 through 4. If more than 30 waveforms are used for Short Pulse Radar Types 2 through 4, then each additional waveform must also be unique and not repeated from the previous waveforms. If more than 30 waveforms are used for Short Pulse Radar Type 1, then each additional waveform is generated with Test B and must also be unique and not repeated from the previous waveforms in Tests A or B.

For example if in Short Pulse Radar Type 1 Test B a PRI of 3066 usec is selected, the number of pulses

would be $\text{Roundup} \left\{ \left(\frac{1}{360} \right) \cdot \left(\frac{19 \cdot 10^6}{3066} \right) \right\} = \text{Roundup} \{17.2\} = 18.$

Table 5a - Pulse Repetition Intervals Values for Test A

Pulse Repetition Frequency Number	Pulse Repetition Frequency (Pulses Per Second)	Pulse Repetition Interval (Microseconds)
1	1930.5	518
2	1858.7	538
3	1792.1	558
4	1730.1	578
5	1672.2	598
6	1618.1	618
7	1567.4	638
8	1519.8	658
9	1474.9	678
10	1432.7	698
11	1392.8	718
12	1355	738
13	1319.3	758
14	1285.3	778
15	1253.1	798
16	1222.5	818
17	1193.3	838
18	1165.6	858
19	1139	878
20	1113.6	898
21	1089.3	918
22	1066.1	938
23	326.2	3066

The aggregate is the average of the percentage of successful detections of Short Pulse Radar Types 1-4. For example, the following table indicates how to compute the aggregate of percentage of successful detections.

Radar Type	Number of Trials	Number of Successful Detections	Minimum Percentage of Successful Detection
1	35	29	82.9%
2	30	18	60%
3	30	27	90%
4	50	44	88%
Aggregate $(82.9\% + 60\% + 90\% + 88\%)/4 = 80.2\%$			

Table 6 – Long Pulse Radar Test Waveform

Radar Type	Pulse Width (μsec)	Chirp Width (MHz)	PRI (μsec)	Number of Pulses per Burst	Number of Bursts	Minimum Percentage of Successful Detection	Minimum Number of Trials
5	50-100	5-20	1000-2000	1-3	8-20	80%	30


Table 7 – Frequency Hopping Radar Test Waveform

Radar Type	Pulse Width (μsec)	PRI (μsec)	Pulses per Hop	Hopping Rate (kHz)	Hopping Sequence Length (msec)	Minimum Percentage of Successful Detection	Minimum Number of Trials
6	1	333	9	0.333	300	70%	30


5.2 DFS Measurement System

BACL DFS measurement system consists of two subsystems: (1) The radar signal generating subsystem and (2) the traffic monitoring subsystem.


5.3 System Block Diagram




Conducted Method




Setup for Master with injection at the Master



Setup for Client with injection at the Master



Setup for Client with injection at the Client**5.4 Test Procedure**

A spectrum analyzer is used as a monitor verifies that the EUT status including Channel Closing Transmission Time and Channel Move Time, and does not transmit on a Channel during the Non-Occupancy Period after the diction and Channel move. It is also used to monitor EUT transmissions during the Channel Availability Check Time.

6 Test Result

6.1 Description of EUT

The EUT operates in 5250-5350 MHz and 5470-5725 MHz range.

The rated output power of master device is >23 dBm (EIRP), therefore the required interference threshold level is -64 dBm, the required radiated threshold at antenna port is -64dBm.

Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.

The calibrated radiated DFS detection threshold level is set to $-62 + (\text{Master antenna gain}) = -62 + 0.11 = -61.89$ dBm.

6.2 Channel Loading


System testing will be performed with channel-loading using means appropriate to the data types that are used by the unlicensed device. The following requirements apply:

- a) The data file must be of a type that is typical for the device (i.e., MPEG-2, MPEG-4, WAV, MP3, MP4, AVI, etc.) and must generally be transmitting in a streaming mode.
- b) Software to ping the client is permitted to simulate data transfer but must have random ping intervals.
- c) Timing plots are required with calculations demonstrating a minimum channel loading of approximately 17% or greater. For example, channel loading can be estimated by setting the spectrum analyzer for zero span and approximate the Time On/ (Time On + Off Time). This can be done with any appropriate channel BW and modulation type.
- d) Unicast or Multicast protocols are preferable but other protocols may be used. The appropriate protocol used must be described in the test procedures.


The sample is use method (C)

WLAN traffic is generated by streaming the video file TestFile.mpg, this file is used by IP and Frame based systems for loading the test channel during the In-service compliance testing of the U-NII device. The file is streamed from the Access Point to the Client in full motion video mode using the media player with the V2.61 Codec package.

6.3 Conducted Test Setup Configuration



6.4 Calibration of DFS Detection Threshold Level



6.5 Environmental Conditions


Temperature:	25.7 °C
Relative Humidity:	51 %
ATM Pressure:	1010 hPa

The testing was performed by Boris Kao on 2021-10-03.

Plots of Radar Waveforms


5290 MHz:

Radar Type 0




Date: 1.OCT.2021 15:54:18

Radar Type 1A




Date: 1.OCT.2021 15:51:21

Radar Type 1B




Date: 1.OCT.2021 15:53:14

Radar Type 2




Date: 1.OCT.2021 15:15:40

Radar Type 3




Date: 1.OCT.2021 15:14:18

Radar Type 4




Date: 1.OCT.2021 15:13:04

Radar Type 5




Date: 1.OCT.2021 15:08:59

Radar Type 5 pulse




Date: 1.OCT.2021 15:10:58

Radar Type 6-1



Date: 4.JAN.2019 13:15:49


Radar Type 6-2



Date: 1.OCT.2021 15:02:39


5530 MHz:

Radar Type 0




Date: 1.OCT.2021 14:18:47

Radar Type 1A




Date: 1.OCT.2021 14:22:59

Radar Type 1B




Date: 1.OCT.2021 14:23:51

Radar Type 2




Date: 1.OCT.2021 14:27:38

Radar Type 3




Date: 1.OCT.2021 14:30:08

Radar Type 4




Date: 1.OCT.2021 14:32:23

Radar Type 5




Date: 1.OCT.2021 14:38:24

Radar Type 5 pulse




Radar Type 6-1



Date: 1.OCT.2021 15:00:28

Radar Type 6-2



7 Channel Move Time and Channel Closing Transmission Time

7.1 Test Procedure

Perform type 0 short pulse radar waveform. The aggregate channel closing transmission time is calculated as follows:

$$\text{Aggregate Transmission Time} = N * \text{Dwell Time}$$

N is the number of spectrum analyzer bins showing a device transmission Dwell Time is the dwell time per bin (i.e. $\text{Dwell Time} = S/B$, S is the sweep time and B is the number of bin, i.e. 10000)

7.2 Environmental Conditions

Temperature:	25.7 °C
Relative Humidity:	51 %
ATM Pressure:	1010 hPa

The testing was performed by Boris Kao on 2021-10-03.

7.3 Test Results


Frequency (MHz)	Bandwidth (MHz)	Radar Type	Results
5290	80	Type 0	Compliant
5310	80	Type 0	Compliant

Please refer to the following tables and plots.

5290 MHz

Type 0 radar channel move time result:



Item	Time (s)	Limit (s)
Channel move time	0.478	10





Date: 3.OCT.2021 10:31:44

Type0 radar channel closing transmission time result:

Item	Time (ms)	Limit (ms)
Closing Transmission Time	5.62	60






5530 MHz

Type 0 radar channel move time result:



Item	Time (s)	Limit (s)
Channel move time	0.470	10





Date: 3.OCT.2021 16:40:21

Type0 radar channel closing transmission time result:

Item	Time (ms)	Limit (ms)
Closing Transmission Time	5.62	60





8 Non-Occupancy Period

8.1 Test Procedure

Measure the EUT for more than 30 minutes following the channel close/move time to verify that the EUT does not resume any transmissions on this channel. Provide one plot to demonstrate no transmission on the channel for the non-occupancy period (30 minutes observation time)

8.2 Environmental Conditions

Temperature:	25.7 °C
Relative Humidity:	51 %
ATM Pressure:	1010 hPa


The testing was performed by Boris Kao on 2021-10-03.

8.3 Test Result

Frequency(MHz)	Bandwidth (MHz)	Spectrum Analyzer Display
5290	80	No transmission within 30 minutes
5530	80	No transmission within 30 minutes


Please refer to the following plots.

5290 MHz



Date: 3.OCT.2021 13:09:14

5530 MHz



Date: 3.OCT.2021 18:31:38

***** END OF REPORT *****