NCC Test Report

Equipment	:	**Bluetooth in-ear headphones**
Model No.	:	**SEBT1**
Brand Name	:	**SENNHEISER**
Applicant	:	**Sennheiser electronic GmbH & Co. KG**
Address	:	**Am Labor 1, 30900 Wedemark, Germany**
Standard	:	**LP0002 Section 3.10.1 (2018-01-10)**
Received Date	:	**Aug. 14, 2019**
Tested Date	:	**Sep. 16 ~ Oct. 02, 2019**

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by: **Approved by:**

Along Chen / Assistant Manager **Gary Chang / Manager**

Testing Laboratory 2732

Table of Contents

1 GENERAL DESCRIPTION 5

1.1 Information 5
1.2 Local Support Equipment List 8
1.3 Test Setup Chart 8
1.4 The Equipment List 9
1.5 Test Standards 10
1.6 Deviation from Test Standard and Measurement Procedure 10
1.7 Measurement Uncertainty 10

2 TEST CONFIGURATION 11

2.1 Testing Condition 11
2.2 The Worst Test Modes and Channel Details 11

3 TRANSMITTER TEST RESULTS 13

3.1 Conducted Emissions 13
3.2 Unwanted Emissions into Restricted Frequency Bands 16
3.3 Unwanted Emissions into Non-Restricted Frequency Bands 33
3.4 Conducted Output Power 38
3.5 Number of Hopping Frequency 41
3.6 20dB and Occupied Bandwidth 44
3.7 Channel Separation 49
3.8 Number of Dwell Time 54

4 RECEIVER TEST RESULTS 60

4.1 Conducted Emissions 60
4.2 Unwanted Emissions into Restricted Frequency Bands 63

5 TEST LABORATORY INFORMATION 69

Release Record

Report No.	Version	Description	Issued Date
TR981406AD	Rev. 01	Initial issue	Dec. 04, 2019

Summary of Test Results

NCC Rules	Test Items	Measured	Result
2.3	Conducted Emissions	[dBuV]: 0.162MHz 54.91 (Margin -10.43dB) - QP	Pass
3.10.1.5 2.8	Radiated Emissions	[dBuV/m at 3m]: 9760.00MHz 47.35 (Margin -6.65dB) - AV	Pass
3.10.1.5	Band Edge	Meet the requirement of limit	Pass
3.10.1.2(1)(B)	Conducted Output Power	Power [dBm]: 10.35	Pass
3.10.1.6(1)(A)	Number of Hopping Channels	Meet the requirement of limit	Pass
3.10.1.6(1)(A)	Hopping Channel Separation	Meet the requirement of limit	Pass
3.10.1.6(1)(A)	Dwell Time	Meet the requirement of limit	Pass
3.10.1.4	Antenna Requirement	Meet the requirement of limit	Pass

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information				
Frequency Range (MHz)	**Bluetooth Mode**	**Ch. Frequency (MHz)**	**Channel Number**	**Data Rate**
2400-2483.5	BR	2402-2480	0-78 [79]	1 Mbps
2400-2483.5	EDR	2402-2480	0-78 [79]	2 Mbps
2400-2483.5	EDR	2402-2480	0-78 [79]	3 Mbps
Note 1: RF output power specifies that Maximum Peak Conducted Output Power. Note 2: Bluetooth BR uses a GFSK. Note 3: Bluetooth EDR uses a combination of π/4-DQPSK and 8DPSK.				

1.1.2 Antenna Details

Ant. No.	Type	Connector	Gain (dBi)	Remarks
1	Chip Antenna	N/A	0	---

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	5Vdc from adapter 5Vdc from host 3.7dc from battery

1.1.4 Accessories

Accessories		
No.	**Equipment**	**Description**
1	Battery	Brand Name: SENNHEISER Model Name: AHB480832PLT Power Rating: 3.7Vdc, 100mAh
2	Type C-Charging Cable	Brand Name: SENNHEISER Model Name: 501-30303L4342-0 Power Line: 0.15m shielded cable w/o core

1.1.5 Channel List

Frequency band (MHz)				2400~2483.5			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461	---	---

1.1.6 Test Tool and Duty Cycle

Test Tool	CBT	
Duty Cycle and Duty Factor	**Duty Cycle (%)**	**Duty Factor (dB)**
DH5	77.99	1.08
2DH5	78.62	1.04
3DH5	79.71	0.98

1.1.7 Power Index of Test Tool

Modulation Mode	Test Frequency (MHz)		
	2402	**2441**	**2480**
GFSK/1Mbps	default	default	default
π/4-DQPSK /2Mbps	default	default	default
8DPSK/3Mbps	default	default	default

1.2 Local Support Equipment List

Support Equipment List					
No.	**Equipment**	**Brand**	**Model**	**FCC ID**	**Remarks**
1	Notebook	DELL	Latitude E5470	DoC	---

1.3 Test Setup Chart

Test Setup Diagram



No.	Signal cable / Length (m)
1	Type C-Charging Cable, 0.15m shielded.

1.4 The Equipment List

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Tested Date	Sep. 23, 2019				
Instrument	**Manufacturer**	**Model No.**	**Serial No.**	**Calibration Date**	**Calibration Until**
Receiver	R&S	ESR3	101657	Jan. 08, 2019	Jan. 07, 2020
LISN	R&S	ENV216	101579	Mar. 08, 2019	Mar. 07, 2020
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Oct. 23, 2018	Oct. 22, 2019
Measurement Software	AUDIX	e3	6.120210k	NA	NA
Wireless connectivity tester	ROHDE&SCHWARZ	CMW270	100856	Oct. 17, 2018	Oct. 16, 2019
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Radiated Emission				
Test Site	966 chamber1 / (03CH01-WS)				
Tested Date	Sep. 16 ~ Sep. 17, 2019				
Instrument	**Manufacturer**	**Model No.**	**Serial No.**	**Calibration Date**	**Calibration Until**
Spectrum Analyzer	R&S	FSV40	101498	Dec. 27, 2018	Dec. 26, 2019
Receiver	R&S	ESR3	101658	Dec. 11, 2018	Dec. 10, 2019
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jul. 12, 2019	Jul. 11, 2020
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 18, 2018	Dec. 17, 2019
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 15, 2018	Nov. 14, 2019
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 09, 2018	Nov. 08, 2019
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 08, 2018	Oct. 07, 2019
Preamplifier	EMC	EMC02325	980225	Jul. 09, 2019	Jul. 08, 2020
Preamplifier	Agilent	83017A	MY39501308	Oct. 04, 2018	Oct. 03, 2019
Preamplifier	EMC	EMC184045B	980192	Aug. 01, 2019	Jul. 31, 2020
RF Cable	EMC	EMC105-SM-SM-8000	180512	Oct. 22, 2018	Oct. 21, 2019
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16018/4	Oct. 22, 2018	Oct. 21, 2019
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16015/4	Oct. 22, 2018	Oct. 21, 2019
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-003	Oct. 22, 2018	Oct. 21, 2019
LF cable 10M	EMCC	CFD400-E	CFD400-001	Oct. 22, 2018	Oct. 21, 2019
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Wireless connectivity tester	ROHDE&SCHWARZ	CMW270	100856	Oct. 17, 2018	Oct. 16, 2019
Note: Calibration Interval of instruments listed above is one year.					

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Tested Date	Oct. 02, 2019				
Instrument	**Manufacturer**	**Model No.**	**Serial No.**	**Calibration Date**	**Calibration Until**
Spectrum Analyzer	R&S	FSV40	101063	Apr. 17, 2019	Apr. 16, 2020
Power Meter	Anritsu	ML2495A	1241002	Oct. 09, 2018	Oct. 08, 2019
Power Sensor	Anritsu	MA2411B	1207366	Oct. 09, 2018	Oct. 08, 2019
DC POWER SOURCE	GW INSTEK	GPC-6030D	EM892433	Oct. 25, 2018	Oct. 24, 2019
AC POWER SOURCE	APC	AFC-500W	F312060012	Nov. 29, 2018	Nov. 28, 2019
Measurement Software	Sporton	SENSE-15247_FS	V5.10.1	NA	NA
Wireless connectivity tester	ROHDE&SCHWARZ	CMW270	100856	Oct. 17, 2018	Oct. 16, 2019
Note: Calibration Interval of instruments listed above is one year.					

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

LP0002 Section 3.10.1 (2018-01-10)
ANSI C63.10-2013
FCC KDB 558074 D01 15.247 Meas Guidance v05r02

1.6 Deviation from Test Standard and Measurement Procedure

None

1.7 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty	
Parameters	**Uncertainty**
Bandwidth	±34.130 Hz
Conducted power	±0.808 dB
Power density	±0.583 dB
Conducted emission	±2.715 dB
AC conducted emission	±2.92 dB
Radiated emission ≤ 1GHz	±3.41 dB
Radiated emission > 1GHz	±4.59 dB

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	24°C / 60%	Alex Tsai
Radiated Emissions	03CH01-WS	24-26°C / 64-65%	Akun Chung
RF Conducted	TH01-WS	22°C / 63%	Brad Wu

- FCC Designation No.: TW2732
- FCC site registration No.: 181692
- ISED#: 10807A
- CAB identifier: TW2732

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data Rate (Mbps)	Mode
Conducted Emissions	8DPSK	2402	3Mbps	Tx
Radiated Emissions ≤ 1GHz	8DPSK	2402	3Mbps	Tx
Radiated Emissions > 1GHz	GFSK 8DPSK	2402, 2441, 2480 2402, 2441, 2480	1Mbps 3Mbps	Tx
Conducted Output Power	GFSK π/4 DQPSK 8DPSK	2402, 2441, 2480 2402, 2441, 2480 2402, 2441, 2480	1Mbps 2Mbps 3Mbps	Tx
Number of Hopping Channels	GFSK π/4 DQPSK 8DPSK	2402~2480 2402~2480 2402~2480	1Mbps 2Mbps 3Mbps	Tx
Hopping Channel Separation 20dB and Occupied bandwidth	GFSK π/4 DQPSK 8DPSK	2402, 2441, 2480 2402, 2441, 2480 2402, 2441, 2480	1Mbps 2Mbps 3Mbps	Tx
Dwell Time	GFSK π/4 DQPSK 8DPSK	2441 2441 2441	1Mbps 2Mbps 3Mbps	Tx

NOTE:

1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **X-plane** results were found as the worst case and were shown in this report.
2. Two powers (notebook charging mode and adapter charging mode) had been covered during the pretest, and found that notebook charging mode was the worst case and was selected for final test.

Test item	Mode	Test Frequency (MHz)	Data Rate	Mode
AC Power Line Conducted Emissions	8DPSK	2402	3Mbps	Rx
Radiated Emissions	8DPSK	2402	3Mbps	Rx

NOTE:

3. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **X-plane** results were found as the worst case and were shown in this report.
4. Two powers (notebook charging mode and adapter charging mode) had been covered during the pretest, and found that notebook charging mode was the worst case and was selected for final test.

3 Transmitter Test Results

3.1 Conducted Emissions

3.1.1 Limit of Conducted Emissions

Conducted Emissions Limit		
Frequency Emission (MHz)	**Quasi-Peak**	**Average**
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50
Note 1: * Decreases with the logarithm of the frequency.		

3.1.2 Test Procedures

1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V/60Hz

3.1.3 Test Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.4 Test Result of Conducted Emissions

Modulation Mode	8DPSK	Test Freq. (MHz)	2402
Power Phase	Line		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.162	41.33	55.34	-14.01	31.74	9.53	0.06	Average
2*	0.162	54.91	65.34	-10.43	45.32	9.53	0.06	QP
3	0.237	20.44	52.22	-31.78	10.82	9.55	0.07	Average
4	0.237	38.05	62.22	-24.17	28.43	9.55	0.07	QP
5	0.270	26.76	51.12	-24.36	17.14	9.55	0.07	Average
6	0.270	40.39	61.12	-20.73	30.77	9.55	0.07	QP
7	0.466	20.57	46.58	-26.01	10.91	9.58	0.08	Average
8	0.466	34.58	56.58	-22.00	24.92	9.58	0.08	QP
9	3.603	25.15	46.00	-20.85	15.28	9.61	0.26	Average
10	3.603	36.29	56.00	-19.71	26.42	9.61	0.26	QP
11	9.757	22.14	50.00	-27.86	12.05	9.65	0.44	Average
12	9.757	28.82	60.00	-31.18	18.73	9.65	0.44	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

Modulation Mode	8DPSK	Test Freq. (MHz)	2402
Power Phase	Neutral		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.159	41.83	55.52	-13.69	32.21	9.57	0.05	Average
2*	0.159	54.88	65.52	-10.64	45.26	9.57	0.05	QP
3	0.219	32.74	52.88	-20.14	23.09	9.58	0.07	Average
4	0.219	44.58	62.88	-18.30	34.93	9.58	0.07	QP
5	0.270	28.82	51.12	-22.30	19.16	9.59	0.07	Average
6	0.270	39.76	61.12	-21.36	30.10	9.59	0.07	QP
7	0.481	25.98	46.32	-20.34	16.28	9.62	0.08	Average
8	0.481	38.06	56.32	-18.26	28.36	9.62	0.08	QP
9	3.881	24.38	46.00	-21.62	14.45	9.66	0.27	Average
10	3.881	36.36	56.00	-19.64	26.43	9.66	0.27	QP
11	9.913	30.49	50.00	-19.51	20.34	9.71	0.44	Average
12	9.913	35.94	60.00	-24.06	25.79	9.71	0.44	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

3.2 Unwanted Emissions into Restricted Frequency Bands

3.2.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	**Field Strength (uV/m)**	**Field Strength (dBuV/m)**	**Measure Distance (m)**
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit
Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.2.2 Test Procedures

1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:

1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. Radiated emission above 1GHz / Peak value
   RBW=1MHz, VBW=3MHz and Peak detector
3. Radiated emission above 1GHz / Average value for harmonics
   The average value is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula for DH5 packet type which has worst duty factor:

$$20\log(\text{Duty cycle}) = 20\log\frac{1s / 1600 * 5}{100\ ms} = -30.1dB$$

4. Radiated emission above 1GHz / Average value for other emissions
   RBW=1MHz, VBW=1/T and Peak detector

3.2.3 Test Setup

Radiated Emissions below 1 GHz



Radiated Emissions above 1 GHz



3.2.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	8DPSK	**Test Freq. (MHz)**	2402
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	145.43	24.90	43.50	-18.60	33.58	-8.68	Peak	---	---
2	242.43	24.79	46.00	-21.21	34.93	-10.14	Peak	---	---
3	263.77	28.51	46.00	-17.49	37.94	-9.43	Peak	---	---
4	311.30	30.44	46.00	-15.56	38.14	-7.70	Peak	---	---
5	360.77	26.22	46.00	-19.78	32.84	-6.62	Peak	---	---
6	408.30	28.17	46.00	-17.83	33.55	-5.38	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	48.43	22.62	40.00	-17.38	31.09	-8.47	Peak	---	---
2	156.10	21.35	43.50	-22.15	29.79	-8.44	Peak	---	---
3	258.92	20.45	46.00	-25.55	30.15	-9.70	Peak	---	---
4	298.69	22.46	46.00	-23.54	30.59	-8.13	Peak	---	---
5	343.31	23.38	46.00	-22.62	30.51	-7.13	Peak	---	---
6	408.30	24.47	46.00	-21.53	29.85	-5.38	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.2.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK

Modulation	GFSK	**Test Freq. (MHz)**	2402
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.85	54.00	-16.15	40.92	-3.07	Average	372	349
2	2390.00	51.35	74.00	-22.65	54.42	-3.07	Peak	372	349
3	4804.00	16.70	54.00	-37.30	13.20	3.50	Average	213	285
4	4804.00	46.80	74.00	-27.20	43.30	3.50	Peak	213	285
5	12010.00	27.56	54.00	-26.44	14.30	13.26	Average	100	152
6	12010.00	57.66	74.00	-16.34	44.40	13.26	Peak	100	152

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.55	54.00	-16.45	40.62	-3.07	Average	100	270
2	2390.00	51.03	74.00	-22.97	54.10	-3.07	Peak	100	270
3	4804.00	15.05	54.00	-38.95	11.55	3.50	Average	100	52
4	4804.00	45.15	74.00	-28.85	41.65	3.50	Peak	100	52
5	12010.00	26.58	54.00	-27.42	13.32	13.26	Average	100	176
6	12010.00	56.68	74.00	-17.32	43.42	13.26	Peak	100	176

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2441
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	38.55	54.00	-15.45	41.62	-3.07	Average	100	317
2	2390.00	51.41	74.00	-22.59	54.48	-3.07	Peak	100	317
3	2483.50	38.34	54.00	-15.66	41.56	-3.22	Average	100	317
4	2483.50	51.09	74.00	-22.91	54.31	-3.22	Peak	100	317
5	4882.00	15.62	54.00	-38.38	12.01	3.61	Average	100	295
6	4882.00	45.72	74.00	-28.28	42.11	3.61	Peak	100	295
7	7323.00	22.83	54.00	-31.17	14.04	8.79	Average	320	360
8	7323.00	52.93	74.00	-21.07	44.14	8.79	Peak	320	360

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2441
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	38.80	54.00	-15.20	41.87	-3.07	Average	100	269
2	2390.00	51.45	74.00	-22.55	54.52	-3.07	Peak	100	269
3	2483.50	38.47	54.00	-15.53	41.69	-3.22	Average	100	269
4	2483.50	52.16	74.00	-21.84	55.38	-3.22	Peak	100	269
5	4882.00	15.26	54.00	-38.74	11.65	3.61	Average	100	110
6	4882.00	45.36	74.00	-28.64	41.75	3.61	Peak	100	110
7	7323.00	24.42	54.00	-29.58	15.63	8.79	Average	247	109
8	7323.00	54.52	74.00	-19.48	45.73	8.79	Peak	247	109

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	38.60	54.00	-15.40	41.82	-3.22	Average	170	311
2	2483.50	50.55	74.00	-23.45	53.77	-3.22	Peak	170	311
3	4960.00	15.86	54.00	-38.14	12.00	3.86	Average	100	271
4	4960.00	45.96	74.00	-28.04	42.10	3.86	Peak	100	271
5	7440.00	23.18	54.00	-30.82	14.64	8.54	Average	221	24
6	7440.00	53.28	74.00	-20.72	44.74	8.54	Peak	221	24

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	37.76	54.00	-16.24	40.98	-3.22	Average	374	257
2	2483.50	49.78	74.00	-24.22	53.00	-3.22	Peak	374	257
3	4960.00	15.14	54.00	-38.86	11.28	3.86	Average	100	151
4	4960.00	45.24	74.00	-28.76	41.38	3.86	Peak	100	151
5	7440.00	22.76	54.00	-31.24	14.22	8.54	Average	100	273
6	7440.00	52.86	74.00	-21.14	44.32	8.54	Peak	100	273

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.2.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 8DPSK

Modulation	8DPSK	**Test Freq. (MHz)**	2402
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.88	54.00	-16.12	40.95	-3.07	Average	100	321
2	2390.00	51.85	74.00	-22.15	54.92	-3.07	Peak	100	321
3	4804.00	15.78	54.00	-38.22	12.28	3.50	Average	100	274
4	4804.00	45.88	74.00	-28.12	42.38	3.50	Peak	100	274
5	12010.00	26.90	54.00	-27.10	13.64	13.26	Average	100	279
6	12010.00	57.00	74.00	-17.00	43.74	13.26	Peak	100	279

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.79	54.00	-16.21	40.86	-3.07	Average	101	270
2	2390.00	51.45	74.00	-22.55	54.52	-3.07	Peak	101	270
3	4804.00	15.48	54.00	-38.52	11.98	3.50	Average	100	214
4	4804.00	45.58	74.00	-28.42	42.08	3.50	Peak	100	214
5	12010.00	26.77	54.00	-27.23	13.51	13.26	Average	100	104
6	12010.00	56.87	74.00	-17.13	43.61	13.26	Peak	100	104

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	8DPSK	Test Freq. (MHz)	2441
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.56	54.00	-16.44	40.63	-3.07	Average	100	318
2	2390.00	51.39	74.00	-22.61	54.46	-3.07	Peak	100	318
3	2483.50	37.75	54.00	-16.25	40.97	-3.22	Average	100	318
4	2483.50	51.35	74.00	-22.65	54.57	-3.22	Peak	100	318
5	4882.00	16.03	54.00	-37.97	12.42	3.61	Average	100	283
6	4882.00	46.13	74.00	-27.87	42.52	3.61	Peak	100	283
7	7323.00	23.04	54.00	-30.96	14.25	8.79	Average	100	111
8	7323.00	53.14	74.00	-20.86	44.35	8.79	Peak	100	111

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	8DPSK	Test Freq. (MHz)	2441
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.43	54.00	-16.57	40.50	-3.07	Average	100	271
2	2390.00	51.72	74.00	-22.28	54.79	-3.07	Peak	100	271
3	2483.50	37.67	54.00	-16.33	40.89	-3.22	Average	100	271
4	2483.50	49.58	74.00	-24.42	52.80	-3.22	Peak	100	271
5	4882.00	15.97	54.00	-38.03	12.36	3.61	Average	100	164
6	4882.00	46.07	74.00	-27.93	42.46	3.61	Peak	100	164
7	7323.00	23.24	54.00	-30.76	14.45	8.79	Average	100	266
8	7323.00	53.34	74.00	-20.66	44.55	8.79	Peak	100	266

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	40.01	54.00	-13.99	43.23	-3.22	Average	166	310
2	2483.50	52.91	74.00	-21.09	56.13	-3.22	Peak	166	310
3	4960.00	16.36	54.00	-37.64	12.50	3.86	Average	100	96
4	4960.00	46.46	74.00	-27.54	42.60	3.86	Peak	100	96
5	7440.00	22.76	54.00	-31.24	14.22	8.54	Average	100	58
6	7440.00	52.86	74.00	-21.14	44.32	8.54	Peak	100	58

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	37.85	54.00	-16.15	41.07	-3.22	Average	104	267
2	2483.50	51.71	74.00	-22.29	54.93	-3.22	Peak	104	267
3	4960.00	16.29	54.00	-37.71	12.43	3.86	Average	100	86
4	4960.00	46.39	74.00	-27.61	42.53	3.86	Peak	100	86
5	7440.00	22.55	54.00	-31.45	14.01	8.54	Average	100	280
6	7440.00	52.65	74.00	-21.35	44.11	8.54	Peak	100	280

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.3 Unwanted Emissions into Non-Restricted Frequency Bands

3.3.1 Limit of Unwanted Emissions into Non-Restricted Frequency Bands

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

3.3.2 Test Procedures

Reference level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Use the peak marker function to determine the maximum PSD level

Emission level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Scan Frequency range is up to 25GHz
4. Use the peak marker function to determine the maximum amplitude level

3.3.3 Test Setup



3.3.4 Unwanted Emissions into Non-Restricted Frequency Bands

BT-BR(1Mbps) **CSE NdB**

2402MHz



Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.40198G	7.01	-12.99	2.14018G	-48.89	2.4G	-46.11	2.48454G	-47.76	16.63868G	-49.58	1

BT-BR(1Mbps) **CSE NdB**

2441MHz



Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.441G	6.71	-13.29	1.7767G	-49.12	2.39866G	-47.99	2.4836G	-48.44	17.55333G	-50.41	1

BT-BR(1Mbps) **CSE NdB**

2480MHz



Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.47999G	6.01	-13.99	2.15469G	-49.10	2.398G	-47.94	2.48352G	-46.94	16.38539G	-49.14	1

BT-EDR(2Mbps) **CSE NdB**

2402MHz



Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.40199G	6.08	-13.92	2.16179G	-48.77	2.39999G	-45.01	2.48527G	-47.93	17.49423G	-49.37	1

BT-EDR(2Mbps) **CSE NdB**

2441MHz



Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.44084G	5.77	-14.23	2.13752G	-48.67	2.39947G	-48.93	2.4838G	-47.42	16.28689G	-49.81	1

BT-EDR(2Mbps) **CSE NdB**

2480MHz



Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.48001G	5.04	-14.96	2.14581G	-48.73	2.39891G	-48.37	2.48499G	-47.30	16.41353G	-49.42	1

BT-EDR(3Mbps) **CSE NdB**

2402MHz



Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.40217G	5.95	-14.05	2.3092G	-48.60	2.39999G	-43.68	2.48442G	-48.04	16.4276G	-48.37	1

BT-EDR(3Mbps) **CSE NdB**

2441MHz



Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.44117G	5.94	-14.06	2.10526G	-49.42	2.39862G	-48.74	2.48359G	-46.91	16.39946G	-49.90	1

BT-EDR(3Mbps) **CSE NdB**

2480MHz



Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.47999G	5.74	-14.26	2.12183G	-49.04	2.39875G	-48.70	2.48408G	-47.02	16.34599G	-48.86	1

BT-BR(1Mbps)

2441MHz

Hopping Ch Bandedge (Non-restricted Band)



Limit(dBm)	Ref(Hz)	Ref(dBm)	BE-l(Hz)	BE-l(dBm)	BE-h(Hz)	BE-h(dBm)
-12.93	2.410957G	7.07	2.393913G	-48.44	2.486087G	-49.65

BT-EDR(2Mbps)

2441MHz

Hopping Ch Bandedge (Non-restricted Band)



Limit(dBm)	Ref(Hz)	Ref(dBm)	BE-l(Hz)	BE-l(dBm)	BE-h(Hz)	BE-h(dBm)
-13.79	2.410957G	6.21	2.399826G	-48.68	2.484G	-50.72

BT-EDR(3Mbps)

2441MHz

Hopping Ch Bandedge (Non-restricted Band)



Limit(dBm)	Ref(Hz)	Ref(dBm)	BE-l(Hz)	BE-l(dBm)	BE-h(Hz)	BE-h(dBm)
-13.75	2.404174G	6.25	2.399652G	-49.25	2.485043G	-50.41

3.4 Conducted Output Power

3.4.1 Limit of Conducted Output Power

☐ 1 Watt
For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band.

☒ 0.125 Watt
For all other frequency hopping systems in the 2400–2483.5 MHz band.

☐ 0.125 Watt
For Frequency hopping systems operating in the 2400–2483.5 MHz band have hopping channel carrier frequencies that are separated by two-thirds of the 20 dB bandwidth of the hopping channel.

3.4.2 Test Procedures

1. A wideband power meter is used for power measurement. Bandwidth of power senor and meter is 50MHz
2 If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power

3.4.3 Test Setup

3.4.4 Test Result of Conducted Output Power

Summary of Peak Conducted Output Power

Mode	Power (dBm)	Power (W)
2.4-2.4835GHz	-	-
BT-BR(1Mbps)	8.08	0.00643
BT-EDR(2Mbps)	9.83	0.00962
BT-EDR(3Mbps)	**10.35**	0.01084

Result

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-BR(1Mbps)	-	-	-	-
2402MHz	Pass	0.00	8.08	21.00
2441MHz	Pass	0.00	7.77	21.00
2480MHz	Pass	0.00	7.57	21.00
BT-EDR(2Mbps)	-	-	-	-
2402MHz	Pass	0.00	9.83	21.00
2441MHz	Pass	0.00	9.54	21.00
2480MHz	Pass	0.00	9.29	21.00
BT-EDR(3Mbps)	-	-	-	-
2402MHz	Pass	0.00	**10.35**	21.00
2441MHz	Pass	0.00	10.09	21.00
2480MHz	Pass	0.00	9.83	21.00

Summary of Conducted (Average) Output Power

Mode	Power	Power
	(dBm)	(W)
2.4-2.4835GHz	-	-
BT-BR(1Mbps)	8.01	0.00632
BT-EDR(2Mbps)	7.26	0.00532
BT-EDR(3Mbps)	7.25	0.00531

Result

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-BR(1Mbps)	-	-	-	-
2402MHz	Pass	0.00	8.01	
2441MHz	Pass	0.00	7.70	
2480MHz	Pass	0.00	7.49	
BT-EDR(2Mbps)	-	-	-	
2402MHz	Pass	0.00	7.26	
2441MHz	Pass	0.00	6.99	
2480MHz	Pass	0.00	6.74	
BT-EDR(3Mbps)	-	-	-	
2402MHz	Pass	0.00	7.25	
2441MHz	Pass	0.00	6.98	
2480MHz	Pass	0.00	6.74	

Note: Average power is for reference only.

3.5 Number of Hopping Frequency

3.5.1 Limit of Number of Hopping Frequency

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

3.5.2 Test Procedures

1. Set RBW = 100kHz, VBW = 300kHz, Sweep time = Auto, Detector = Peak Trace max hold.
2 Allow trace to stabilize.

3.5.3 Test Setup



3.5.4 Test Result of Number of Hopping Frequency

Summary

Mode	Max-Hop No
2.4-2.4835GHz	-
BT-BR(1Mbps)	79
BT-EDR(2Mbps)	79
BT-EDR(3Mbps)	79

Result

Mode	Result	Hopping No	Limit
BT-BR(1Mbps)	-	-	-
2441MHz	Pass	79	15
BT-EDR(2Mbps)	-	-	-
2441MHz	Pass	79	15
BT-EDR(3Mbps)	-	-	-
2441MHz	Pass	79	15

BT-BR(1Mbps) **Hopping Ch**

2441MHz



BT-EDR(2Mbps) **Hopping Ch**

2441MHz



BT-EDR(3Mbps) **Hopping Ch**

2441MHz



3.6 20dB and Occupied Bandwidth

3.6.1 Test Procedures

20dB Bandwidth

1. Set RBW=10kHz VBW= 30kHz for BT BR mode, RBW=20kHz, VBW=100kHz for other modes, Sweep time = Auto, Detector=Peak , Trace max hold
2 Allow trace to stabilize
3 Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth

1. Set RBW=10kHz VBW= 30kHz for BT BR mode, RBW=20kHz, VBW=100kHz for other modes, Sweep time = Auto, Detector=Sample , Trace max hold
2 Allow trace to stabilize
3. Use Occupied bandwidth function of spectrum analyzer to measuring 99% occupied bandwidth

3.6.2 Test Setup



3.6.3 Test result of 20dB and Occupied Bandwidth

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
BT-BR(1Mbps)	920.29k	871.925k	872KF1D	920.29k	861.071k
BT-EDR(2Mbps)	1.351M	1.201M	1M20G1D	1.326M	1.194M
BT-EDR(3Mbps)	1.341M	1.205M	1M21G1D	1.308M	1.201M

Max-N dB = Maximum20dB downbandwidth;**Max-OBW** = Maximum99% occupied bandwidth;
Min-N dB = Minimum20dB downbandwidth;**Min-OBW** = Minimum99% occupied bandwidth;

Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
BT-BR(1Mbps)	-	-	-	-
2402MHz	Pass	Inf	920.29k	871.925k
2441MHz	Pass	Inf	920.29k	868.307k
2480MHz	Pass	Inf	920.29k	861.071k
BT-EDR(2Mbps)	-	-	-	-
2402MHz	Pass	Inf	1.326M	1.201M
2441MHz	Pass	Inf	1.337M	1.198M
2480MHz	Pass	Inf	1.351M	1.194M
BT-EDR(3Mbps)	-	-	-	-
2402MHz	Pass	Inf	1.319M	1.201M
2441MHz	Pass	Inf	1.341M	1.205M
2480MHz	Pass	Inf	1.308M	1.201M

Port X-N dB = Port **X**20dB downbandwidth; **Port X-OBW** = Port **X**99% occupied bandwidth;

BT-BR(1Mbps) **EBW**

2402MHz



20dB(Hz)	Fl-20dB(Hz)	Fh-20dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
920.29k	2.40154G	2.40246G	871.925k	2.401551G	2.402423G	Inf	1

BT-BR(1Mbps) **EBW**

2441MHz



20dB(Hz)	Fl-20dB(Hz)	Fh-20dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
920.29k	2.44054G	2.44146G	868.307k	2.440551G	2.44142G	Inf	1

BT-BR(1Mbps) **EBW**

2480MHz



20dB(Hz)	Fl-20dB(Hz)	Fh-20dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
920.29k	2.47954G	2.48046G	861.071k	2.479555G	2.480416G	Inf	1

BT-EDR(2Mbps) **EBW**

2402MHz



20dB(Hz)	Fl-20dB(Hz)	Fh-20dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
1.326M	2.40133G	2.402656G	1.201M	2.401392G	2.402593G	Inf	1

BT-EDR(2Mbps) **EBW**

2441MHz



20dB(Hz)	Fl-20dB(Hz)	Fh-20dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
1.337M	2.440326G	2.441663G	1.198M	2.440392G	2.44159G	Inf	1

BT-EDR(2Mbps) **EBW**

2480MHz



20dB(Hz)	Fl-20dB(Hz)	Fh-20dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
1.351M	2.479319G	2.48067G	1.194M	2.479392G	2.480586G	Inf	1

BT-EDR(3Mbps) **EBW**

2402MHz



20dB(Hz)	Fl-20dB(Hz)	Fh-20dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
1.319M	2.401322G	2.402641G	1.201M	2.401385G	2.402586G	Inf	1

BT-EDR(3Mbps) **EBW**

2441MHz



20dB(Hz)	Fl-20dB(Hz)	Fh-20dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
1.341M	2.440319G	2.441659G	1.205M	2.440381G	2.441586G	Inf	1

BT-EDR(3Mbps) **EBW**

2480MHz



20dB(Hz)	Fl-20dB(Hz)	Fh-20dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
1.308M	2.479326G	2.480634G	1.201M	2.479381G	2.480582G	Inf	1

3.7 Channel Separation

3.7.1 Limit of Channel Separation

☐ Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

☒ Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

3.7.2 Test Procedures

1. Set RBW=30kHz, VBW=100kHz,Sweep time = Auto, Detector=Peak Trace max hold
2 Allow trace to stabilize
3 Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The EUT shall show compliance with the appropriate regulatory limit

3.7.3 Test Setup



3.7.4 Test result of Channel Separation

Summary

Mode	Max-Space (Hz)	Min-Space (Hz)
2.4-2.4835GHz	-	-
BT-BR(1Mbps)	1M	1M
BT-EDR(2Mbps)	1.004348M	1M
BT-EDR(3Mbps)	1.004348M	1M

Result

Mode	Result	Fl (Hz)	Fh (Hz)	Ch.Space (Hz)	Limit (Hz)
BT-BR(1Mbps)	-	-	-	-	-
2402MHz	Pass	2.402048G	2.403048G	1M	612.91314k
2441MHz	Pass	2.441048G	2.442048G	1M	612.91314k
2480MHz	Pass	2.479048G	2.480048G	1M	612.91314k
BT-EDR(2Mbps)	-	-	-	-	-
2402MHz	Pass	2.401983G	2.402983G	1M	883.116k
2441MHz	Pass	2.440978G	2.441983G	1.004348M	890.442k
2480MHz	Pass	2.478983G	2.479983G	1M	899.766k
BT-EDR(3Mbps)	-	-	-	-	-
2402MHz	Pass	2.401978G	2.402983G	1.004348M	878.454k
2441MHz	Pass	2.440983G	2.441983G	1M	893.106k
2480MHz	Pass	2.478978G	2.479983G	1.004348M	871.128k

BT-BR(1Mbps) **Channel Separation**

2.402G/2.403GHz



Fl(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.402048G	2.403048G	1M	612.91314k

BT-BR(1Mbps) **Channel Separation**

2.441G/2.442GHz



Fl(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.441048G	2.442048G	1M	612.91314k

BT-BR(1Mbps) **Channel Separation**

2.48G/2.479GHz



Fl(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.479048G	2.480048G	1M	612.91314k

BT-EDR(2Mbps) **Channel Separation**

2.402G/2.403GHz



Fl(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.401983G	2.402983G	1M	883.116k

BT-EDR(2Mbps) **Channel Separation**

2.441G/2.442GHz



Fl(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.440978G	2.441983G	1.004348M	890.442k

BT-EDR(2Mbps) **Channel Separation**

2.48G/2.479GHz



Fl(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.478983G	2.479983G	1M	899.766k

BT-EDR(3Mbps) **Channel Separation**

2.402G/2.403GHz



Fl(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.401978G	2.402983G	1.004348M	878.454k

BT-EDR(3Mbps) **Channel Separation**

2.441G/2.442GHz



Fl(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.440983G	2.441983G	1M	893.106k

BT-EDR(3Mbps) **Channel Separation**

2.48G/2.479GHz



Fl(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.478978G	2.479983G	1.004348M	871.128k

3.8 Number of Dwell Time

3.8.1 Limit of Dwell time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.8.2 Test Procedures

1. Set RBW=300kHz,VBW=1MHz,Sweep time = 10 ms, Detector=Peak, Span=0Hz,Trace max hold
2 Enable gating and trigger function of spectrum analyzer to measure burst on time.
3. The DH1 packet can cover a single time slot. A maximum length packet has duration of 1 time slots.
   Non AFH mode
   The hopping rate is 1600 hops/second so the maximum dwell time is 1/1600 seconds. DH1 Packet permit maximum 1600 / 79 /2 = 10.12 hops per second in each channel (1 time slot TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times 10.12 x 31.6 = 320 within 31.6 seconds.
   AFH mode
   The hopping rate is 800 hops/second so the maximum dwell time is 1/800 seconds. DH1 Packet permit maximum 800 /20/2 = 20 hops per second in each channel (1 time slot TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times 20 x 8 = 160 within 8 seconds.
4. The DH3 packet can cover up to 3 time slots. A maximum length packet has duration of 3 time slots.
   Non AFH mode
   The hopping rate is 1600 hops/second so the maximum dwell time is 3/1600 seconds. DH3 Packet permit maximum 1600 / 79 / 4 = 5.06 hops per second in each channel (3 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times 5.06 x 31.6 = 160 within 31.6 seconds.
   AFH mode
   The hopping rate is 800hops/second so the maximum dwell time is 3/800 seconds. DH3 Packet permit maximum 800 / 20 / 4 = 10 hops per second in each channel (3 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times 10 x 8 = 80 within 8 seconds.
5 The DH5 packet can cover up to 5 time slots. Operate DH5 at maximum dwell time and maximum duty cycle. A maximum length packet has duration of 5 time slots.
   Non AFH mode
   The hopping rate is 1600 hops/second so the maximum dwell time is 5/1600 seconds, or 3.125ms. DH5 Packet permit maximum 1600/ 79 / 6 = 3.37 hops per second in each channel (5 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times 3.37 x 31.6 = 106.6 within 31.6 seconds
   AFH mode
   The hopping rate is 800 hops/second so the maximum dwell time is 5/800 seconds. DH5 Packet permit maximum 800/20 / 6 =6.667 hops per second in each channel (5 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times6.667 x 8 = 53.33 within 8 seconds

3.8.3 Test Setup



3.8.4 Test Result of Dwell Time

Summary

Mode	Max-Dwell (s)
2.4-2.4835GHz	-
BT-BR(1Mbps)	310.530435m_DH5
BT-EDR(2Mbps)	310.530435m_DH5
BT-EDR(3Mbps)	310.530435m_DH5

Result/ Non AFH mode

Mode	Result	Period (s)	Dwell (s)	Limit (s)	Tx On (s)
BT-BR(1Mbps)	-	-	-	-	-
2441MHz	Pass	31.6	310.530435m_DH5	400m	2.913043m
2441MHz	Pass	31.6	266.666667m_DH3	400m	1.666667m
2441MHz	Pass	31.6	129.855072m_DH1	400m	405.797101u
BT-EDR(2Mbps)	-	-	-	-	-
2441MHz	Pass	31.6	310.530435m_DH5	400m	2.913043m
2441MHz	Pass	31.6	266.666667m_DH3	400m	1.666667m
2441MHz	Pass	31.6	134.492754m_DH1	400m	420.289855u
BT-EDR(3Mbps)	-	-	-	-	-
2441MHz	Pass	31.6	310.530435m_DH5	400m	2.913043m
2441MHz	Pass	31.6	264.347826m_DH3	400m	1.652174m
2441MHz	Pass	31.6	134.492754m_DH1	400m	420.289855u

Result/ AFH mode

Mode	Result	Period (s)	Dwell (s)	Limit (s)	Tx On (s)
BT-BR(1Mbps)	-	-	-	-	-
2441MHz	Pass	8	155.3526m_DH5	400m	2.913043m
2441MHz	Pass	8	133.3334m_DH3	400m	1.666667m
2441MHz	Pass	8	64.92754m_DH1	400m	405.797101u
BT-EDR(2Mbps)	-	-	-	-	-
2441MHz	Pass	8	155.3526m_DH5	400m	2.913043m
2441MHz	Pass	8	133.3334m_DH3	400m	1.666667m
2441MHz	Pass	8	67.24638m_DH1	400m	420.289855u
BT-EDR(3Mbps)	-	-	-	-	-
2441MHz	Pass	8	155.3526m_DH5	400m	2.913043m
2441MHz	Pass	8	132.1739m_DH3	400m	1.652174m
2441MHz	Pass	8	67.24638m_DH1	400m	420.289855u

BT-BR(1Mbps) **Dwell**

2441MHz



DH5

Period(s)	Dwell(s)	Limit(s)	Tx On(s)
31.6	310.530435m_[	400m	2.913043m

BT-BR(1Mbps) **Dwell**

2441MHz



DH3

Period(s)	Dwell(s)	Limit(s)	Tx On(s)
31.6	266.666667m_[	400m	1.666667m

BT-BR(1Mbps) **Dwell**

2441MHz



DH1

Period(s)	Dwell(s)	Limit(s)	Tx On(s)
31.6	129.855072m_[	400m	405.797101u

BT-EDR(2Mbps) **Dwell**

2441MHz



DH5

Period(s)	Dwell(s)	Limit(s)	Tx On(s)
31.6	310.530435m_[	400m	2.913043m

BT-EDR(2Mbps) **Dwell**

2441MHz



DH3

Period(s)	Dwell(s)	Limit(s)	Tx On(s)
31.6	266.666667m_[	400m	1.666667m

BT-EDR(2Mbps) **Dwell**

2441MHz



DH1

Period(s)	Dwell(s)	Limit(s)	Tx On(s)
31.6	134.492754m_[	400m	420.289855u

BT-EDR(3Mbps) **Dwell**

2441MHz



DH5

BT-EDR(3Mbps) **Dwell**

2441MHz



DH3

BT-EDR(3Mbps) **Dwell**

2441MHz



DH1

4 Receiver Test Results

4.1 Conducted Emissions

4.1.1 Limit of Conducted Emissions

Conducted Emissions Limit		
Frequency Emission (MHz)	**Quasi-Peak**	**Average**
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50
Note 1: * Decreases with the logarithm of the frequency.		

4.1.2 Test Procedures

1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V / 60Hz.

4.1.3 Test Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

4.1.4 Test Result of Conducted Emissions

Modulation Mode	8DPSK	Test Freq. (MHz)	2402
Power Phase	Line		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.156	41.39	55.69	-14.30	31.81	9.53	0.05	Average
2*	0.156	54.84	65.69	-10.85	45.26	9.53	0.05	QP
3	0.174	28.79	54.77	-25.98	19.19	9.54	0.06	Average
4	0.174	51.11	64.77	-13.66	41.51	9.54	0.06	QP
5	0.255	28.10	51.60	-23.50	18.48	9.55	0.07	Average
6	0.255	40.14	61.60	-21.46	30.52	9.55	0.07	QP
7	0.300	20.27	50.24	-29.97	10.63	9.56	0.08	Average
8	0.300	36.41	60.24	-23.83	26.77	9.56	0.08	QP
9	0.454	22.04	46.80	-24.76	12.39	9.57	0.08	Average
10	0.454	34.77	56.80	-22.03	25.12	9.57	0.08	QP
11	3.840	25.37	46.00	-20.63	15.49	9.61	0.27	Average
12	3.840	36.43	56.00	-19.57	26.55	9.61	0.27	QP
13	9.757	21.31	50.00	-28.69	11.22	9.65	0.44	Average
14	9.757	28.18	60.00	-31.82	18.09	9.65	0.44	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

Modulation Mode	8DPSK	Test Freq. (MHz)	2402
Power Phase	Neutral		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.153	41.00	55.82	-14.82	31.38	9.57	0.05	Average
2*	0.153	54.69	65.82	-11.13	45.07	9.57	0.05	QP
3	0.171	21.66	54.90	-33.24	12.03	9.57	0.06	Average
4	0.171	41.97	64.90	-22.93	32.34	9.57	0.06	QP
5	0.216	24.14	52.96	-28.82	14.49	9.58	0.07	Average
6	0.216	40.47	62.96	-22.49	30.82	9.58	0.07	QP
7	0.484	24.32	46.27	-21.95	14.62	9.62	0.08	Average
8	0.484	38.17	56.27	-18.10	28.47	9.62	0.08	QP
9	3.840	24.28	46.00	-21.72	14.35	9.66	0.27	Average
10	3.840	36.04	56.00	-19.96	26.11	9.66	0.27	QP
11	9.757	30.50	50.00	-19.50	20.35	9.71	0.44	Average
12	9.757	35.87	60.00	-24.13	25.72	9.71	0.44	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

4.2 Unwanted Emissions into Restricted Frequency Bands

4.2.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	**Field Strength (uV/m)**	**Field Strength (dBuV/m)**	**Measure Distance (m)**
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit
Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

4.2.2 Test Procedures

1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:

1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=3MHz and RMS detector is for average measured value of radiated emission above 1GHz.

4.2.3 Test Setup

Radiated Emissions below 1 GHz



Radiated Emissions above 1 GHz



4.2.4 Receiver Radiated Unwanted Emissions

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	154.16	23.42	43.50	-20.08	31.86	-8.44	Peak	---	---
2	245.34	23.21	46.00	-22.79	33.24	-10.03	Peak	---	---
3	263.77	29.27	46.00	-16.73	38.70	-9.43	Peak	---	---
4	311.30	30.59	46.00	-15.41	38.29	-7.70	Peak	---	---
5	360.77	25.24	46.00	-20.76	31.86	-6.62	Peak	---	---
6	408.30	29.04	46.00	-16.96	34.42	-5.38	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	46.49	20.76	40.00	-19.24	29.22	-8.46	Peak	---	---
2	142.52	21.19	43.50	-22.31	29.97	-8.78	Peak	---	---
3	156.10	23.16	43.50	-20.34	31.60	-8.44	Peak	---	---
4	251.16	19.95	46.00	-26.05	29.91	-9.96	Peak	---	---
5	263.77	20.84	46.00	-25.16	30.27	-9.43	Peak	---	---
6	311.30	22.38	46.00	-23.62	30.08	-7.70	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

4.2.5 Receiver Radiated Unwanted Emissions (Above 1GHz)

Modulation	8DPSK	**Test Freq. (MHz)**	2402
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	5753.00	38.00	54.00	-16.00	32.64	5.36	Average	100	133
2	5753.00	51.71	74.00	-22.29	46.35	5.36	Peak	100	133
3	7313.00	42.17	54.00	-11.83	33.36	8.81	Average	100	217
4	7313.00	55.89	74.00	-18.11	47.08	8.81	Peak	100	217
5	9760.00	47.31	54.00	-6.69	34.11	13.20	Average	100	247
6	9760.00	61.15	74.00	-12.85	47.95	13.20	Peak	100	247

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	5753.00	37.90	54.00	-16.10	32.54	5.36	Average	100	133
2	5753.00	51.59	74.00	-22.41	46.23	5.36	Peak	100	133
3	7313.00	42.08	54.00	-11.92	33.27	8.81	Average	100	217
4	7313.00	56.00	74.00	-18.00	47.19	8.81	Peak	100	217
5	9760.00	47.35	54.00	-6.65	34.15	13.20	Average	100	247
6	9760.00	61.17	74.00	-12.83	47.97	13.20	Peak	100	247

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

5 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website http://www.icertifi.com.tw.

Linkou	**Kwei Shan**	**Kwei Shan Site II**
Tel: 886-2-2601-1640	Tel: 886-3-271-8666	Tel: 886-3-271-8640
No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan, R.O.C.	No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.	No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666
Fax: 886-3-318-0155
Email: ICC_Service@icertifi.com.tw

══END══