

TEST REPORT

Report No.: 8234EU010815W

Applicant: Zeroplus Technology Corporation

Address: 3F, No.121, Jian 8th Rd, Chung Ho District New Taipei City, 235, Taiwan

Product Name: Cat CPU Plus

Model No.: ZPP006R

Trademark: BROOK

Test Standard(s): MIC Notice No.88 Appendix No.43
Ordinance of MPT No.37, 1981:
Article 2 paragraph 1 item (19)

Date of Receipt: Oct. 08, 2024

Test Date: Oct. 08, 2024 – Jan. 20, 2025

Date of Issue: Feb. 08, 2025

ISSUED BY:

SHENZHEN EU TESTING LABORATORY LIMITED



Prepared by:

Mikey zhu

Mikey Zhu/ Engineer

Reviewed and Approved by:

Sally zhang

Sally Zhang/ Manager

Revision Record

Report Version	Issued Date	Description	Status
V0	Feb. 08, 2025	Original	Valid

Table of Contents

1	COVER PAGE.....	1
2	GENERAL INFORMATION	5
2.1	APPLICANT INFORMATION.....	5
2.2	MANUFACTURER INFORMATION.....	5
2.3	FACTORY INFORMATION.....	5
2.4	GENERAL DESCRIPTION OF E.U.T.....	5
2.5	TECHNICAL INFORMATION OF E.U.T.....	6
3	TEST SUMMARY.....	7
3.1	TEST STANDARD.....	7
3.2	TEST VERDICT.....	7
3.3	TEST LABORATORY.....	7
4	TEST CONFIGURATION.....	8
4.1	TEST ENVIRONMENT.....	8
4.2	TEST EQUIPMENT.....	9
4.3	DESCRIPTION OF SUPPORT UNIT.....	9
4.4	MEASUREMENT UNCERTAINTY.....	10
5	TEST ITEMS.....	11
5.1	FREQUENCY TOLERANCE TEST.....	11
5.1.1	Test Requirement.....	11
5.1.2	Test Setup Diagram.....	11
5.1.3	Test Procedure.....	11
5.1.4	Test Deviation.....	11
5.1.5	EUT Operation during Test.....	11
5.1.6	Test Data.....	11
5.2	OCCUPIED BANDWIDTH.....	12
5.2.1	Test Requirement.....	12
5.2.2	Test Setup Diagram.....	12
5.2.3	Test Procedure.....	12
5.2.4	Test Deviation.....	12
5.2.5	EUT Operation during Test.....	12
5.2.6	Test Data.....	12
5.3	ANTENNA POWER / EIRP ANTENNA POWER TEST.....	13
5.3.1	Test Requirement.....	13
5.3.2	Test Setup Diagram.....	13
5.3.3	Test Procedure.....	13
5.3.4	Test Deviation.....	13
5.3.5	EUT Operation during Test.....	13
5.3.6	Test Data.....	13
5.4	SPURIOUS EMISSIONS INTENSITY TEST.....	14
5.4.1	Test Requirement.....	14
5.4.2	Test Setup Diagram.....	14
5.4.3	Test Procedure.....	14
5.4.4	Test Deviation.....	14
5.4.5	EUT Operation during Test.....	14
5.4.6	Test Data.....	14
5.5	SECONDARY RADIATED EMISSIONS TEST.....	15
5.5.1	Test Requirement.....	15
5.5.2	Test Setup Diagram.....	15
5.5.3	Test Procedure.....	15
5.5.4	Test Deviation.....	15

5.5.5	EUT Operation during Test	15
5.5.6	Test Data	15
5.6	INTERFERENCE PREVENTION FUNCTION	16
5.6.1	Test Requirement.....	16
5.6.2	Test Setup Diagram	16
5.6.3	Test Procedure.....	16
5.6.4	Test Deviation	16
5.6.5	EUT Operation during Test	16
5.6.6	Test Data	16
5.7	TRANSMISSION RADIATION ANGLE WIDTH (3dB BEAMWIDTH) MEASUREMENT	17
5.7.1	Test Requirement.....	17
5.7.2	Test Setup Diagram	17
5.7.3	Test Procedure.....	17
5.7.4	Test Deviation	17
5.7.5	EUT Operation during Test	17
5.7.6	Test Data	17
5.8	CONSTRUCTION PROTECTION CONFIRMATION METHOD	18
ANNEX A	TEST SETUP PHOTOS	19
ANNEX B	EXTERNAL PHOTOS	19
ANNEX C	INTERNAL PHOTOS	19
ANNEX D	TEST DATA	19

2 General Information

2.1 Applicant Information

Applicant	Zeroplus Technology Corporation
Address	3F, No.121, Jian 8th Rd, Chung Ho District New Taipei City, 235, Taiwan

2.2 Manufacturer Information

Manufacturer	Zeroplus Technology Corporation
Address	3F, No.121, Jian 8th Rd, Chung Ho District New Taipei City, 235, Taiwan

2.3 Factory Information

Factory	Zeroplus Technology Corporation
Address	3F, No.121, Jian 8th Rd, Chung Ho District New Taipei City, 235, Taiwan

2.4 General Description of E.U.T.

Product Name	Cat CPU Plus
Model No. Under Test	ZPP006R
List Model No.	N/A
Description of Model differentiation	N/A
Rating(s)	Input: 5V $\pm$ 1A Battery Capacity: 3.7VDC, 90mAh
Product Type	☐ Mobile ☒ Portable ☐ Fix Location
Test Sample No.	-1/2(Normal Sample), -2/2(Engineering Sample)
Hardware Version	C23056-Battle Cats GamePad _V17
Software Version	ZP0210C0_1.0.90.1
Remark	1) The above information are declared by the applicant, EU-LAB is not responsible for the information accuracy provided by the applicant. 2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.5 Technical Information of E.U.T.

Network and Wireless Connectivity	Bluetooth (BLE)
-----------------------------------	-----------------

The requirement for the following technical information of the EUT was tested in this report:

Technology	Bluetooth
Operation Mode	☒ BLE
Modulation Type	GFSK
Operating Frequency	2402-2480MHz
Transfer Rate	1 Mbps
Number of Channel	40
Antenna Type	PCB Antenna
Antenna Gain(Peak)	-0.38 dBi
Antenna Impedance	50Ω
Rated output Power	2.000 mW
Remark	The above information are declared by the applicant, EU-LAB is not responsible for the information accuracy provided by the applicant.

All channels were listed on the following table:

Channel Number	Freq. (MHz)	Channel Number	Freq. (MHz)	Channel Number	Freq. (MHz)	Channel Number	Freq. (MHz)
00	2402	10	2422	20	2442	30	2462
01	2404	11	2424	21	2444	31	2464
02	2406	12	2426	22	2446	32	2466
03	2408	13	2428	23	2448	33	2468
04	2410	14	2430	24	2450	34	2470
05	2412	15	2432	25	2452	35	2472
06	2414	16	2434	26	2454	36	2474
07	2416	17	2436	27	2456	37	2476
08	2418	18	2438	28	2458	38	2478
09	2420	19	2440	29	2460	39	2480

3 Test Summary

3.1 Test Standard

The tests were performed according to following standards:

No.	Identity	Document Title
1	MIC Notice No.88 Appendix No.43 Ordinance of MPT No.37, 1981: Article 2 paragraph 1 item (19)	Low power data communications system in the 2.4GHz band

Remark:

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product maybe which result in lowering the emission should be checked to ensure compliance has been maintained.

3.2 Test Verdict

No.	Description	Test Mode	Data Rate (Mbps)	Verdict	Remark
1	Frequency Tolerance	GFSK	1	Pass	--
2	Occupied Bandwidth	GFSK	1	Pass	--
3	Antenna Power / EIRP Antenna Power	GFSK	1	Pass	--
4	Spurious Emission Intensity	GFSK	1	Pass	--
5	Secondary Radiated Emission	GFSK	1	Pass	--
6	Spurious Emissions	GFSK	1	Pass	--
7	Interference Prevention Function	GFSK	1	Pass	--
8	Transmission Radiated Angle Width (3dB Beam Bandwidth)	GFSK	1	N/A	Note ²
9	Construction Protection Confirmation	GFSK	1	Compliance	--
10	Carrier Sense Function (1)	GFSK	1	N/A	Note ³
11	Carrier Sense Function (2)	GFSK	1	N/A	Note ⁴

Note 1: The tests were performed according to the method of measurements prescribed in MIC Notice No.88 Appendix No.43.

Note 2: This test is not applicable for antenna gain is less than 2.14 dBi.

Note 3: Not apply to this device, since EIRP does not require compensation through Antenna Power.

Note 4: Application to transmitting devices with OFDM modulation and the occupied bandwidth greater than 26MHz.

3.3 Test Laboratory

Test Laboratory	Shenzhen EU Testing Laboratory Limited
Address	101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China

4 Test Configuration

4.1 Test Environment

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	52%	
Atmospheric Pressure	103 kPa	
Temperature	NT (Normal Temperature)	+26°C
Working Voltage of the EUT	NV (Normal Voltage)	3.70V
	LV (Low Voltage)	3.33V
	HV (High Voltage)	4.07V

Power Supply Voltage Fluctuation Test

Voltage Fluctuation Test	Normal Voltage	High Voltage +10% of Normal Voltage	Low Voltage -10% of Normal Voltage
Input To EUT	DC 3.70V	DC 4.07V	DC 3.33V
Output To RF Module	DC 3.3V	DC 3.3V	DC 3.3V
Voltage Variation (%)	--	0.00%	0.00%

Note:

Voltage Variation (%)=(Output high or Low Voltage - Output Normal Voltage)/ Output Normal Voltage* 100%

For extreme voltage test, we have tested the relationship between the external power supply and RF IC power supply. Base on the test results, only the normal voltage was selected to perform all items.

4.2 Test Equipment

Radiated Emission and RF Test					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
EMI Test Receiver	ROHDE & SCHWARZ	ESPI	EE-006	2025/01/08	2026/01/07
Bilog Broadband Antenna	SCHWARZBECK	VULB 9163	EE-007	2023/01/14	2026/01/13
Double Ridged Horn Antenna	A-INFOMW	LB-10180-NF	EE-008	2023/01/12	2026/01/11
Pre-amplifier	Agilent	8447D	EE-009	2025/01/08	2026/01/07
Pre-amplifier	Agilent	8449B	EE-010	2025/01/08	2026/01/07
MXA Signal Analyzer	Agilent	N9020A	EE-011	2025/01/08	2026/01/07
MXG RF Vector Signal Generator	Agilent	N5182A	EE-012	2025/01/08	2026/01/07
Test Software	Farad	EZ-EMC	EE-015	N.C.R	N.C.R
MIMO Power Measurement Module	TSTPASS	TSPS 2023R	EE-016	2025/01/08	2026/01/07
RF Test Software	TSTPASS	TS32893 V2.0	EE-017	N.C.R	N.C.R
Wideband Radio Communication Tester	ROHDE & SCHWARZ	CMW500	EE-402	2024/02/15	2025/02/14
Loop Antenna	TESEQ	HLA6121	EE-403	2024/02/15	2025/02/14
MXG RF Analog Signal Generator	Agilent	N5181A	EE-406	2024/02/15	2025/02/14
Constant Temperature Humidity Chamber	Guangxin	GXP-401	ES-002	2024/07/30	2025/07/29
Power Sensor	ROHDE&SCHWA RZN	NRP18S	ES-052	2024/02/15	2025/02/14
Note ¹ : Calibration Company: Shenzhen Academy Of Metrology& Quality inspection.					
Note ² : Calibration method: Calibration conducted in foreign countries, which is equivalent to calibration conducted by the NICT or a designated calibration agency under Article 102-18-1 and Article 24-2, Paragraph 4 of the Radio Act.					

4.3 Description of Support Unit

No.	Title	Manufacturer	Model No.	Serial No.
1	Adapter	Apple	A1443	EMC-PJ-001

4.4 Measurement Uncertainty

Parameters	Uncertainty
Frequency Error / 99% Bandwidth	$(3.2 \times f \times 10^{-6})$ Hz
Antenna Power	1.82 dB
TX-RX Spurious Emissions	1.84 dB
Transmission Antenna Gain	5.36 dB
Temperature	0.8 °C
Humidity	4 %
DC / AC Power Source	0.04%
Duty Cycle	0.05%
Noet: "f" is the nominal signal frequency in Hz.	

Note: This uncertainty represents as expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

5 Test Items

5.1 Frequency Tolerance Test

5.1.1 Test Requirement

Item	Limits
Frequency Tolerance	$\leq \pm 50$ ppm

5.1.2 Test Setup Diagram



5.1.3 Test Procedure

Test Frequency= test channel
RBW=VBW=10KHz
Span=1MHz
Sweep time=Auto
Detector mode=Positive peak
Indication mode=Max hold
EUT have transmitted unmodulated signal and fixed channelize. f is using the mark cursor to mark the peak frequency value, fc is declaring of channel frequency.

5.1.4 Test Deviation

There is no deviation with the original standard.

5.1.5 EUT Operation during Test

The EUT was programmed to be in continuous transmit, carrier mode.

5.1.6 Test Data

PASS.

Please refer to Annex D for details.

5.2 Occupied Bandwidth

5.2.1 Test Requirement

Item	Limits
Occupied Band Width	FHSS $\leq$ 83.5MHz; OFDM $\leq$ 40MHz, DSSS $\leq$ 26MHz; Others $\leq$ 26MHz

5.2.2 Test Setup Diagram



5.2.3 Test Procedure

- Set the spectrum analyzer as follows:
Center frequency: Test frequency
Span: Approximately 2 to 3.5 times nominal bandwidth
Resolution bandwidth: Within 3% of the technical standard
Video bandwidth: equivalent to resolvable bandwidth
Sweep time: auto
Sweep mode: Continuous sweep
Detection: Positive peak
Trace mode: Maximum hold
- After repeating sweeps until the display shows steady data, store the values at all data points into the computer array variables.
- Convert the dB values at all data points to antilogarithm on the power dimension.
- Obtain sum total of the power at all data points, and store it as "total power".

5.2.4 Test Deviation

There is no deviation with the original standard.

5.2.5 EUT Operation during Test

The EUT was programmed to be in continuous transmit, channel-selected mode.

5.2.6 Test Data

PASS.

Please refer to Annex D for details.

5.3 Antenna Power / EIRP Antenna Power Test

5.3.1 Test Requirement

Item	Limits
Antenna Power Density	a) FH, FH+DS, or FH+OFDM form 2427 - 2470.75 MHz: ≤ 3 mW/MHz b) DS but other than a) from 2400~2483.5 MHz: ≤ 10 mW/MHz c) OFDM, but other than a): For OCB of 26MHz or less: ≤ 10 mW/MHz For OCB of over 26 MHz to 40 MHz: ≤ 5 mW/MHz d) Other than a), b) and c): ≤ 10 mW
Antenna Power Error	+20% (Base on manufacturer declare antenna power density)
EIRP Power	12.14 dBm

5.3.2 Test Setup Diagram



5.3.3 Test Procedure

[Setting 1] – Search for peak power frequency	
Center Frequency:	Test frequency
Span:	Approximately twice the occupied bandwidth
RBW:	$\geq$ OBW
VBW:	Approximately three times the RBW
Sweep time:	Auto
Sweep data points:	1001 or greater
Detector mode:	Positive peak
Indication mode:	Max hold
[Setting 2] – Measurement of average antenna power other than for FHSS, DSSS, OFDM	
Frequency:	Frequency of peak power found using [Setting 1]
Span:	0 Hz
RBW:	Bandwidth sufficient to cover that occupied by the carrier
VBW:	Bandwidth sufficient to cover that occupied by the carrier
Detector mode:	Sample
Sweep:	Minimum time required to make an accurate measurement.
	For burst type (intermittent) transmission sweep time shall be greater than one burst interval
Sweep data points:	1001 or greater

5.3.4 Test Deviation

There is no deviation with the original standard.

5.3.5 EUT Operation during Test

The EUT was programmed to be in continuous transmit, channel-selected mode.

5.3.6 Test Data

PASS.

Please refer to Annex D for details.

5.4 Spurious Emissions Intensity Test

5.4.1 Test Requirement

Item	Limits
TX Spurious Emission	$\leq 2.5\mu\text{W}/\text{MHz}$ ($2387\text{MHz} > f$; $2496.5\text{MHz} < f$)
	$\leq 25\mu\text{W}/\text{MHz}$ ($2387\text{MHz} \leq f < 2400\text{MHz}$) and ($2483.5\text{MHz} < f \leq 2496.5\text{MHz}$)

5.4.2 Test Setup Diagram



5.4.3 Test Procedure

Spectrum Parameter	Setting
Attenuation	Auto
RB	30-1000 MHz: 1 MHz/1 MHz
VB	Above 1GHz: 1 MHz/1 MHz
Detector	Peak
Trace	Max Hold
Sweep	Auto

1. The EUT is placed in transmit mode at maximum power/modulation at a fixed channel.
2. Setting of SA is following as: RBW/VBW = 1MHz; / AT: 10dB / Ref: 0dBm / Sweep time: Auto / Sweep Mode: Continuous sweep / Detect mode: Positive peak / Trace mode: Max hold
3. Setting of SA is following as 30 MHz and stop frequency 2387 MHz Then to mark peak reading value + cable loss shall be less than 2.5 μW
4. SA adjusted to start frequency 2387 MHz and stop frequency 2400 MHz. Then to mark peak reading value + cable loss shall be less than 25 μW .
5. SA adjusted to start frequency 2483.5 MHz and stop frequency 2496.5 MHz Then to mark peak reading value + cable loss shall be less than 25 μW
6. SA adjusted to start frequency 2496.5 MHz and stop frequency 12500 MHz Then to mark peak reading value + cable loss shall be less than 2.5 μW
7. If the Result_Value is over the requirement, take total sum of 1MHz band centered at the spur frequency like ACLP measurement as Result_Value.

5.4.4 Test Deviation

There is no deviation with the original standard.

5.4.5 EUT Operation during Test

The EUT was programmed to be in continuous transmit, channel-selected mode.

5.4.6 Test Data

PASS.

Please refer to Annex D for details.

5.5 Secondary Radiated Emissions Test

5.5.1 Test Requirement

Item	Limits
RX Spurious Emission	$\leq 4\text{nW}$ ($f < 1\text{GHz}$)
	$\leq 20\text{nW}$ ($1\text{GHz} \leq f$)

5.5.2 Test Setup Diagram



5.5.3 Test Procedure

Spectrum Parameter	Setting
Attenuation	Auto
RB	30-1000 MHz: 100KHz/100KHz
VB	Above 1GHz: 1 MHz/1 MHz
Detector	Peak
Trace	Max Hold
Sweep	Auto

1. The EUT is placed in Rx mode and set to a fixed channel.
2. Setting of SA is following as RB / VB: 100 kHz (below 1GHz emissions) / 1 MHz (above 1GHz emissions) / AT:10 dB / Ref: 0dBm / Sweep time: Auto / Sweep Mode: Continuous sweep / Detect mode: Positive peak / Trace mode: Max hold
3. SA set RB: 100 kHz and VB: 100 kHz. Then adjust to start frequency 30 MHz and stop frequency 1000 MHz. Search to mark peak reading value + cable loss shall be less than 4 nW
4. SA set RB: 1 MHz and VB: 1 MHz. Then adjust to start frequency 1000 MHz and stop frequency 12500 MHz. Search to mark peak reading value + cable loss shall be less than 20 nW
5. If power level of lower emissions are more than 1/10 of limit (0.4nW for $f < 1\text{GHz}$, 2 nW for $f \geq 1\text{GHz}$), all those are to be indicated in the 2nd and 3rd lines. If others are 1/10 or less more of the limit, no necessary to be indicated

5.5.4 Test Deviation

There is no deviation with the original standard.

5.5.5 EUT Operation during Test

The EUT was programmed to be in continuous transmit, channel-selected mode.

5.5.6 Test Data

PASS.


Please refer to Annex D for details.

5.6 Interference Prevention Function

5.6.1 Test Requirement

Item	Limits
Identification	≥ 48 bits

5.6.2 Test Setup Diagram



5.6.3 Test Procedure

1. In the case that the EUT has the function of automatically transmitting the identification code:
 - a. Transmit the predetermined identification codes from EUT.
 - b. Check the transmitted identification codes with the demodulator.
2. In the case of receiving the identification code:
 - a. Transmit the predetermined identification codes from the counterpart.
 - b. Check if communication is normal.
 - c. Transmit the signals other than predetermined ID codes from the counterpart.
 - d. check if the EUT stops the transmission, or if it displays that identification codes are different from the predetermined ones.

5.6.4 Test Deviation

There is no deviation with the original standard.

5.6.5 EUT Operation during Test

The EUT was programmed to be in continuous transmit, channel-selected mode.

5.6.6 Test Data

PASS.


Mode	ID Code	Test Results
BLE	F5:12:B1:36:A8:24	Pass

5.7 Transmission Radiation Angle Width (3dB Beamwidth) Measurement

5.7.1 Test Requirement

Item	Limits
3dB antenna beam width	$360/A$ (If $A < 1$; then $A = 1$) $A = \{ \text{EIRP Power [mW]} / 16.36 \text{ for DS, OFDM} \}$ or $A = \{ \text{EIRP Power [mW]} / 4.9 \text{ for FH} \}$
Note: This test item will not be applied to the transmission antenna which has a gain of 2.14dBi or less.	

5.7.2 Test Setup Diagram



5.7.3 Test Procedure

1. Set EUT and measuring antenna at the same height and roughly facing each other.
2. Set spectrum analyzer with RBW=1 MHz, VBW=1 KHz, Y scale=5 dB, Detector=Peak, Trace mode=Max Hold, and tune reference level to observe receiving signal position.
3. Rotate directions of the EUT horizontally and vertically to find the maximum receiving power.
4. Move the measuring antenna height up and down within $\pm 50\text{cm}$ of EUT height and swing it to find the maximum output of measuring antenna. The output level at the spectrum analyzer is read as "E"
5. Calculate permitted radiation angle in horizontal and vertical using EIRP measured in another test method.
6. Calculate 3dB antenna beam width by the formula below $360/A$ (If $A < 1$; then $A = 1$). $A = \{ \text{EIRP Power [mW]} / 16.36 \text{ for DS, OFDM} \}$ or $A = \{ \text{EIRP Power [mW]} / 4.9 \text{ for FH} \}$

5.7.4 Test Deviation

There is no deviation with the original standard.

5.7.5 EUT Operation during Test


The EUT was programmed to be in continuous transmit, channel-selected mode.

5.7.6 Test Data

Note: This test is not applicable for antenna gain is less than 2.14 dBi.

5.8 Construction Protection Confirmation Method

The RF and modulation portions are protected against illegal modification as following method:

Protected Method	Description
Structure protection	The terminal number is 41, terminal pitch is 1mm. it can't be easily opened and modified.
Reference Photo	
	

ANNEX A TEST SETUP PHOTOS

Please refer to the document "8234EU010815W-AA.PDF"

ANNEX B EXTERNAL PHOTOS

Please refer to the document "8234EU010815W-AB.PDF"

ANNEX C INTERNAL PHOTOS

Please refer to the document "8234EU010815W-AC.PDF"

ANNEX D TEST DATA

Please refer to the document "8234EU010815W-AD.PDF"

STATEMENT

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--- End of Report ---