



ML910G/ML920G User Manual V1.0

Learn how to set up your new MiCODUS Tracker



1.Main Features



4G LTE+2G GSM



Real-time Tracking



Historical Route
Playback



Superstrong
Magnetic



Waterproof IP65



Movement Alarm



10000/20000mAh



Voice Monitor



Overspeed Alarm



Vibration alarm



Geo-fence



Teardown Alarm

2.Specifications

Device Information

Model	ML910G/ML920G
Weight	ML910G:306g ML920G:467g
Dimensions	ML910G: 115(L)*65(W)*31(H)mm ML920G: 115(L)*65(W)*47(H)mm
Battery	3.7V 10000/20000mAh Li-Polymer Battery

Working Parameters

Battery Life	ML910G: Real-time Tracking mode: 12-15 days; Power Saving Mode: around 30 days; Hibernate Mode: around 60 days ML920G: Real-time Tracking mode: 25-30 days; Power Saving Mode: around 60 days; Hibernate Mode: around 120 days
Working Temperature	-20°C - 60°C

Working Humidity 5%-95%RH

SIM Card Normal Size

Celluar Specifications

Celluar Antenna Built-in

Working Frequency
4G LTE CAT1: B1/B2/B3/B4/B5/B7/B8/B28/B66
2G GSM/GPRS: 850/900/1800/1900MHz

GNSS GPS+GLONASS+BDS

Hot/warm/cold Start <3s, <35s, <45s @ Open Sky

GNSS Specifications

GNSS Antenna Built-in Ceramics GNSS Antenna

Positioning Type GNSS+LBS+AGPS

Accuracy
GNSS Accuracy: <5M @ Open Sky
LBS Accuracy: 100-2000m
(Depend on density of base stations)

3. Activate Device

First Step: Prepare and Install SIM Card

- * If use your local SIM card, please make sure the SIM card already enabled SMS, internet data traffic, call and caller ID displaying functions;
- * If use our spionlink SIM card, then please recharge it via this website www.spionlink.com to get data plan firstly



[ML910G]



[ML920G]



LED	Event	State
POWER LED (RED)	Charging	Solid
	Charger inserted and battery has been fully charged	Dark
	Charger has not been inserted	Dark
CELL LED (YELLOW)	Searching for network	Flash every 1 second
	Network has been registered	Solid
GPS LED (Blue)	GPS is in fixing	Flash every 1 second
	GPS has fixed	Solid
ALL LED	Device is working but stopped more than 5min	ALL LED TURN OFF
	Device has not been turn on	
	Device ran out of battery	

Second Step: Configure APN

Please get the exact correct APN name from local SIM card provider. Take the tracker to a good signal place for operation and configure the APN for it as below:

SMS Command Format	Reply	Example	Note
apn,apn content, apnuser,apnpasswd#	apn ok	apn,orange,orange, orange#	If there has APN user and APN apnpassword, then please use this command for configuration
apn,apn content#	apn ok	apn,internet#	If there doesn't have APN user and APN password, then please use this command for configuration

Note: The APN information is very important, it must 100% correct to register with the service of the carrier. If you configured wrong APN, the tracker after will reply "GPRS APN ok" but it will not get online.

4.Package Content

ML910G or ML920G Tracker	x 1
USB Charging Cable	x 1
User Guide	x 1
Packing Box	x 1

5.Functions Explanation

1. Voice Monitor

* Set up a center number for the device:

CENTER,A,CENTER NUMBER#

For example, if you want to set up this number as center number +8613366668888, the command should be sent like this:
CENTER,A,+8613366668888#

For example:

ML910G/ML920G

CENTER,A,+8613366668888#

SET CENTER NUMBER OK

MONITOR,+8613366668888#

SET MONITOR OK

Note: Please put the country code as prefix with the center number.

- * Use the center number to set up a number for the tracker to call back: **MONITOR,number for monitor#**

For example, if you send this command:

MONITOR,+8613366668888# then the tracker will make a call to this number **+8613366668888** and this number can pick up the call to monitor the voice around it.

For example:



2. Set Working Mode

- * Command format: **MODE,A,T1,T2#**

- * For example: Realtime Tracking Mode: **MODE,1,10,3600#**

This means the tracker will upload every 10 seconds when it is moving, and every 3600 seconds when it is static.

- * For example: Power Saving Mode: **MODE,2,0800,1#**

This means the tracker will enter into power saving mode at 08:00am and upload every 1 hour. If now is 09:00am, then the tracker will enter power saving mode at 08:00am of tomorrow.

- * For example: Hibernation Mode: **MODE,3,0800,1#**

This means the tracker will enter into power saving mode at 08:00am and upload every 1 hour.

Note: The difference between the mode 2 and mode 3 is that, under mode 2, the device can be waked up by sms, call and light sensor, under mode 3 the device will just can be waked up by light sensor.

3. Vibration Alarm

- * Set up a center number for the device:

CENTER,A,CENTER NUMBER#

For example, if you want to set up this number as center number: +8613366668888, the command should be sent like this:

CENTER,A,+8613366668888#

Note: Please put the country code as prefix with the center number.

- * Set up SOS contact numbers:

SOS,A,SOS1,SOS2,SOS3#

For example, **SOS,A,+8613366667777,+8613366667778,+8613366667779#**

Note: You can set up 3 SOS alarm numbers for the device at the same time.

- * Set up the vibration alarm way: **SENALM,ON,2#**

For example:

ML910G/ML920G

CENTER,A,+8613366668888#

SET CENTER NUMBER OK

SOS,A,+861336667777,+861336667778,+861336667779#

SET SOS NUMBER OK

SENALM,ON,2#

SET VIBRATE ALARM OK

6.Installation Recommendation



- ① Driving seat sundries box
- ② Front bumper
- ③ Driving sundries box
- ④ Under the chassis
- ⑤ Rear windscreen
- ⑥ Rear bumper

7.Trouble Shooting

Type	Use
Unable to connect to tracking platform	Check the APN and settings. Check whether the data service of SIM card is enabled. Check the balance of SIM card.
Tracker shows offline	Check whether external power is still connected. Check if the vehicle entered network blind area. Check the balance of SIM card.
Unable to locate	Make sure the top side facing upward without metallic things shielded. Make sure it's not in area with no satellite coverage.
Location drift	In area with poor GNSS signal (tall building around or basement), drifting may happen. Check whether vibration happens around to trigger the accelerator.
No command reply	Make sure command format is correct. Vehicle may be in network blind area. Make sure SIM card is well inserted and has SMS servi

8. Full SMS Commands List

Query Commands

Functions	Command Format	Example
Version Inquiry	VERSION#	Device Reply Example: ID: ID number of the tracker IMEI: IMEI number of the tracker ICCID: The ICCID number of the SIM card in the tracker VERSION: The firmware version of the tracker
Parameter Inquiry	PARAM#	Device Reply Example: ID: ID number of the tracker IMEI: IMEI number of the ICCID: The ICCID number of the SIM card in the tracker APN: APN name, APN user, APN password, IP: Domain name and port number or IP address, port number MODE: Working mode; interval or starting time, upload interval SPEEDLIMIT: The overspeed threshold ANGLERPT: Data uploading angle CENTER: Center number of the tracker SOS: SOS1, SOS2, SOS3 GMT: Time zone
Status Inquiry	STATUS#	BATTERY: XX% (Built-in Battery Power Percent) INTERNET: CLOSED (No Network) FAILED (Connecting Network or Failure) SUCCESS (Connected to Network) NET: NONE (No GSM Signal), HIGH/MED/LOW (Signal Strength) 18 GPS: CLOSED (GPS Module Closed), FIXED, N (Positioned and satellite number), UNFIX, 0 (Not Positioned yet) SPEED: 30KM/H (The current speed of the target) SENSOR: ON/OFF (Sensor on or off), LEVEL: 3 (Sensitivity level 1-9) STATE: ARM (Arm or Disarm)
Alarms Parameters	ALARM#	ID: 19172012644 (Device ID number) STATE: ARM (DISARM) (Fortified state of device) SPEED: ON(OFF); 30km/h (speed limit); alarm ways SHIFT: ON(OFF); 300m (shift limit); alarm ways VIBRATE: ON(OFF); 3 (sensitivity of sensor); alarm ways LOW BATTERY: ON(OFF); alarm ways TEARDOWN: ON(OFF); alarm ways

Functions	Command Format	Example
Latitude& Longitude Inquiry	WHERE#	LAT:N23.02930,LON:E114.32180,SPEED:0.00KM/H,DATETIME:2023-01-05 14:39:11
Map URL Inquiry	URL#	<a href="http://map.google.com/?q=22.557868,113.935090<0.0km/h 0.0> <2023-01-05 14:39:11> IMEI:354188047752402">http://map.google.com/?q=22.557868,113.935090<0.0km/h 0.0> <2023-01-05 14:39:11> IMEI:354188047752402

Setting Commands

Functions	Command Format	Example
APN Setting	APN,APN Name, APN User, APN Password#	Example: APN,CMNET# (if no APN User & APN Password) APN,internet,internet,internet# (if with APN User & APN Password)
Server Setting	If set with Domain Name: SERVER,1,Domain,Port#	SERVER,1,d.micodus.net,7700#
	If set with IP: SERVER,0,IP,Port#	SERVER,0,47.254.77.28,7700#
Restore factory settings	FACTORY#	FACTORY OK
Restart device	RESTART#	RESTART OK
Internet Traffic Switch	TRAFFIC,ON#	OPEN TRAFFIC OK
	TRAFFIC,OFF#	CLOSE TRAFFIC OK
Set the angle upload	ANGLEREP,X,A,B#	Example: ANGLEREP,ON,30,3# (Means the tracker will send a data supplement when the angle change exceeds 30 degrees and lasts for 3 seconds) X=ON/OFF, default: ON; A=5~180 degrees, diversion angle degree, default: 30 degrees; B=2~5 seconds, detecting time, default: 3 seconds,
	ANGLEREP,OFF#	CANCEL UPLOAD ANGLE OK

Functions	Command Format	Example
Time Zone Setting	GMT,Time zone orientation,Whole Time Zone [Half Time Zone]#	Example:GMT,E,8#(if no half time zone) GMT,W,9,30#(if has half time zone) NOTE: Parameter : E / W: 0 ~ 12; 0/15/30/45
Mileage Statistics	MILEAGE,A,B#	A=ON/OFF, On/Off mileage calculation, default: Off B=0~999999,Mileage initial value , unit: km ; default: 0, mileage return to zero
	MIELEAGE#	Query current mileage
Add SOS Administrator Number	SOS,A,1st number, 2nd number, 3rd number#	Set 3 numbers at a time: SOS,A,13800138000,13800138001,13800138002# Set the first number separately: SOS,A,13800138000# Set the second number separately: SOS,A,,13800138001# Means to set 3rd number separately: SOS,A,,,13800138002#
Delete SOS Administrator Number	SOS,D,1st number, 2nd number, 3rd number# or SOS,D,1,2,3#	Directly delete the number: SOS,D,13800138000# Delete 1st number: SOS,D,1# Delete 2nd number: SOS,D,2# Delete the 2nd and 3rd number: SOS,D,2,3#
Add Center Number	CENTER,A,center number#	Example: CENTER,A,+8613800138000# NOTE: Please set up the center number with the country code as prefix!
Delete Center Number	CENTER,D#	DEL CENTER OK
Sleep Mode Setting	SLEEP#	NOTE: After set this sleep mode, the device will enter into sleep mode automatically when the device keep stationary status more than 5min.
	SLEEP,OFF#	CANEL SLEEP MODE OK
Voice Monitor	MONITOR,N#	Example: MONITOR,+8613366669999# (Means the tracker will make call to +8613366669999, and this number +8613366669999 can pick up the call to monitor the voice) N: Number for Voice Monitoring NOTE: 1. Please send this monitor command via the center number; 2. Any number can be set up to monitor the voice, the tracker will make a call to the number N and it will can pick up the call to monitor voice

Functions	Command Format	Example
Working Mode Setting	MODE,A,T1,T2#	A=1/2/3, 1: Tracking mode 2: Power saving mode 3: Hibernation mode; Default mode: 1 A=1 (For example: MODE,1,10,3600# means the tracker will work under mode 1, it will upload every 10s under moving status and 3600s under static status) T1: upload interval of GPS data in moving status, unit: second,10-3600s; default: 10s T2: upload interval of GPS data in static status, unit: second, 180-65535s; default: 3600s A=2 (For example: MODE,2,0800,1# means the tracker will work with power saving mode since the next 08:00am, and upload every 1 hour) T1: interval start time,format: HH:MM T2: time interval,range: 1-72 unit: hour,default interval: 24hours A=3 (For example: MODE,3,0800,1# means the tracker will work with hibernation mode since the next 08:00am, and upload every 1 hour) T1: interval start time,format: HH:MM T2: time interval,range: 1-72 unit: hour,default interval: 24hours NOTE: The difference between Mode 2 and Mode 3 is that under Mode 2 the device can be wake up by SMS, Call and light sensor, but under Mode 3 the device just can be wake up by light sensor!
Heartbeat Packet Upload	HBT,time#	Example: HBT,3# (Means the tracker will send heartbeat data package to server very 3min to keep the network connected) Time: 1-60min, default 3min
Sensor Sensitivity	SENLEVEL, sensitivity#	Example: SENLEVEL,4# (Means shake sensor level is set to 4) A=1-9 NOTE: 1-9 is from weak to strong vibration

Alarm Setting Commands

Functions	Command Format	Example
Vibration Alarm Setting	SENALM,A,M#	Example: SENALM,ON,2# (Means the vibration alarm already been enabled and the alarm message will be sent via Server, SMS and Call) A=ON/OFF, default: OFF; M=0/1/2, way of alarming, 0 :GPRS only,1: SMS+GPRS, 2: GPRS+SMS+phone call, default:1
	SENALM,OFF#	CANEL VIBRATE ALARM OK
Overspeed Alarm Setting	SPEED,A,B,M#	Example: SPEED,ON,120,1# (Means the speed limit is 120km/h and the alarm way is via SMS and Server) A=ON/OFF, open or close over speed alarm, default: OFF B=1~255(km/h), speed limit, default: 100(km/h); M=0/1/2, way of alarm, 0 : GPRS only, 1: SMS+GPRS, 2:GPRS+SMS+CALL; default: 1
	SPEED,OFF#	CANCEL OVERSPEED ALARM OK
Shift Alarm Setting	SHIFT,A,B,M#	Example: SHIFT,ON,100,1# (Means Setting 100 meters shift alarm range, when the ignition turned off, vehicle's 100 meters' shift will trigger the alarm and the alarm message will be sent via Server and SMS) A=ON/OFF; default:ON B=Shift Distance (Range: 100-9999m) M=0/1/2; way of alarm, 0 : SERVER only, 1: SERVER+SMS, 2: SERVER+SMS+CALL, default:1
	SHIFT,OFF#	CANCEL SHIFT ALARM OK
Low Battery Alarm Setting	BATALM,A,M#	Example: BATALM,ON,1# (Means the low battery alarm already been enabled and the alarm message will be sent via Server and SMS) A=ON/OFF,default: ON; M=0/1/2, way of alarming,0: SERVER only,1: SERVER+SMS, 2: SERVER+SMS+Call, default:1; NOTE: Once the battery level is below 20% device will alarm
	BATALM,OFF#	CANCEL LOW BATTERY ALARM OK

Functions	Command Format	Example
Disassemble Alarm Setting	TEARDOWN,A,M#	Example: TEARDOWN,ON,2# (Means the teardown alarm already been enabled and the alarm message will be sent via Server, SMS and Call) A=ON/OFF; default:ON M=0/1/2; way of alarm, 0 : SERVER only, 1: SERVER+SMS, 2: SERVER+SMS+CALL, default:1
	TEARDOWN,OFF#	CANCEL DISASSEMBLE ALARM OK

9.After-sale Contact Information

E-mail:support@micodus.com

Skype:MiCODUS

10. Download APP

Search "MiCODUS" in iOS APP store or Google Play Store, or just scan the QR code as below to download MiCODUS APP:

