NCC RADIO TEST REPORT

Equipment	:	**Wireless Activity Tracker**
Brand Name	:	**Fitbit**
Model Name	:	**FB418**
Applicant	:	**FITBIT, INC.** **199 FREMONT, 14TH FLOOR, SAN FRANCISCO, CA**
Manufacturer	:	**FITBIT, INC.** **199 FREMONT, 14TH FLOOR, SAN FRANCISCO, CA**
Standard	:	**NCC LP0002 (2018-01-10)**

The product was received on Jun. 17, 2020 and testing was started from Jun. 30, 2020 and completed on Jul. 14, 2020. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures NCC LP0002 (2018-01-10) and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

Table of Contents

History of this test report **3**
Summary of Test Result **4**
1 General Description **5**
1.1 Product Feature of Equipment Under Test 5
1.2 Modification of EUT 5
1.3 Testing Location 6
1.4 Applicable Standards 6
2 Test Configuration of Equipment Under Test **7**
2.1 Carrier Frequency Channel 7
2.2 Test Mode 8
2.3 Connection Diagram of Test System 9
2.4 Support Unit used in test configuration and system 10
2.5 EUT Operation Test Setup 10
2.6 Measurement Results Explanation Example 11
3 Test Result **12**
3.1 6dB and 99% Bandwidth Measurement 12
3.2 Output Power Measurement 17
3.3 Power Spectral Density Measurement 18
3.4 Conducted Band Edges and Spurious Emission Measurement 23
3.5 Radiated Band Edges and Spurious Emission Measurement 28
3.6 AC Conducted Emission Measurement 33
3.7 Antenna Requirements 35
4 List of Measuring Equipment **36**
5 Uncertainty of Evaluation **38**
Appendix A. Conducted Test Results
Appendix B. AC Conducted Emission Test Result
Appendix C. Radiated Spurious Emission
Appendix D. Radiated Spurious Emission Plots
Annex A. Receiver Radiated Emission
Appendix E. Duty Cycle Plots
Appendix F. Setup Photographs

History of this test report

Report No.	Version	Description	Issued Date
TR060607-02	01	Initial issue of report	Jul. 27, 2020

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	LP0002 3.10.1.6 (2)(A)	6dB Bandwidth	Pass	-
3.1	-	99% Occupied Bandwidth	Reporting only	-
3.2	LP0002 3.10.1.2 (1)(C)	Output Power	Pass	-
3.3	LP0002 3.10.1.6 (2)(B)	Power Spectral Density	Pass	-
3.4	LP0002 3.10.1.5	Conducted Band Edges and Spurious Emission	Pass	-
3.5	LP0002 3.10.1.5	Radiated Band Edges and Spurious Emission	Pass	Under limit 8.31 dB at 2483.520 MHz
3.6	LP0002 2.3	AC Conducted Emission	Pass	Under limit 8.87 dB at 0.155 MHz
3.7	LP0002 2.2 3.10.1.3 3.10.1.4	Antenna Requirement	Pass	-
Annex A	LP0002 2.11	Receiver Radiated Emission	Pass	Please refer to Annex A

Note: Except receiver radiated emission is carrying out, TR060607-02 report reuses conducted emission test data from the TE060607-03 report and reuses conducted test data from the TR060607-02 report.

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Dara Chiu

1 General Description

1.1 Product Feature of Equipment Under Test

Bluetooth

Product Specification subjective to this standard	
Sample 1	EUT with Battery 1
Sample 2	EUT with Battery 2
Sample 3	EUT with Battery 3

Specification of Accessory		
Battery 1	**Brand Name**	VDL
	Model Name	401219
Battery 2	**Brand Name**	Lishen
	Model Name	SP041221SE
Battery 3	**Brand Name**	ATL
	Model Name	401220-Rincon
USB Cable	**Brand Name**	Fitbit
	Model Name	N/A
Charging Cable	**Brand Name**	Fitbit
	Model Name	N/A

Antenna Information				
Antenna	**Brand Name**	Shengwei、JXY	**Peak gain**	Bluetooth: -0.86 dBi
	Model Name	304001706812、304001707631	**Type**	IFA Antenna

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	**Sporton Site No.**	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	**Sporton Site No.**
	03CH12-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW0007

1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- NCC LP0002 (2018-01-10)
- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- FCC KDB 414788 D01 Radiated Test Site v01r01
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

2.2 Test Mode

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	**Data Rate / Modulation**
	Bluetooth – LE / GFSK
Conducted Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
Radiated Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
AC Conducted Emission	Mode 1: Bluetooth Link with Mobile Phone + Vibrate + Screen Flicker + Metal Strap + Charging Cable (Charging from Adapter) for Sample 1 Mode 2: Bluetooth Link with Mobile Phone + Vibrate + Screen Flicker + Metal Strap Charging Cable (Charging from Notebook) for Sample 2 Mode 3: Bluetooth Link with Mobile Phone + Vibrate + Screen Flicker + Metal Strap + Charging Cable + (Charging from Adapter) for Sample 3 Mode 4: Bluetooth Link with Mobile Phone + Vibrate + Screen Flicker + Plastic Strap + Charging Cable (Charging from Notebook) for Sample 2
Remark: 1. The worst case of conducted emission is mode 4; only the test data of it was reported. 2. For Radiated Test Cases, the tests were performed with Sample 2.	

2.3 Connection Diagram of Test System

<AC Conducted Emissions Mode with Adapter>



<AC Conducted Emissions Mode with Notebook>



<Bluetooth-LE Tx Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Smart Phone	SAMSAUNG	SM-A730F/DS	N/A	N/A	N/A
2.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
3.	iPod	Apple	A1285	FCC DoC	Shielded, 1.0 m	N/A
4.	Notebook	Dell	Latitude 3400	FCC DOC	N/A	AC I/P：Unshielded, 1.2m DC O/P：Shielded, 1.8m
5.	Adapter	DVE	DSA-5FPM-05 FUS	FCC DoC	N/A	N/A
6.	Adapter	SUNYES	002-1W	N/A	N/A	N/A

Remark: Applicant has ensured accessory would not be attached with the product on the market, accessory is provided by lab for testing.

2.5 EUT Operation Test Setup

The RF test items, utility “Tera Term Ver.4.95” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.2 + 10 = 14.2 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) ≥ 3 * RBW.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

6 dB Bandwidth Plot on Channel 00



Date: 9.JUL.2020 09:55:21

6 dB Bandwidth Plot on Channel 19



Date: 9.JUL.2020 10:02:18

6 dB Bandwidth Plot on Channel 39



Date: 9.JUL.2020 10:07:53

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

99% Bandwidth Plot on Channel 00



Date: 9.JUL.2020 09:59:04

99% Occupied Bandwidth Plot on Channel 19



Date: 9.JUL.2020 10:04:43

99% Occupied Bandwidth Plot on Channel 39



Date: 9.JUL.2020 10:14:28

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT was connected to the power meter by RF cable and attenuator.
3. The path loss was compensated to the results for each measurement.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.3.6 Test Result of Power Spectral Density Plots (100kHz)

PSD 100kHz Plot on Channel 00



Date: 9.JUL.2020 09:56:29

PSD 100kHz Plot on Channel 19



Date: 9.JUL.2020 10:03:38

PSD 100kHz Plot on Channel 39



Date: 9.JUL.2020 10:08:47

3.3.7 Test Result of Power Spectral Density Plots (3kHz)

PSD 3kHz Plot on Channel 00



Date: 9.JUL.2020 09:55:58

PSD 3kHz Plot on Channel 19



Date: 9.JUL.2020 10:02:53

PSD 3kHz Plot on Channel 39



Date: 9.JUL.2020 10:08:18

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.

3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Low Band Edge Plot on Channel 00



Date: 9.JUL.2020 09:57:09

High Band Edge Plot on Channel 39



Date: 9.JUL.2020 10:10:58

3.4.6 Test Result of Conducted Spurious Emission Plots

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 00



Date: 14.JUL.2020 11:33:13

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 00



Date: 14.JUL.2020 11:35:09

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 19



Date: 14.JUL.2020 11:36:36

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 19



Date: 14.JUL.2020 11:37:16

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 39



Date: 14.JUL.2020 11:38:14

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 39



Date: 14.JUL.2020 11:38:41

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the NCC LP0002 section 2.8 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

3.5.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
   (1) Span shall wide enough to fully capture the emission being measured;
   (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
   (3) Set RBW = 1 MHz, VBW= 3MHz for f ≥ 1 GHz for peak measurement.
   For average measurement:
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



For radiated emissions above 18GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per NCC LP0002 section 5.13 was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



AMN = Artificial mains network (LISN)
AE = Associated equipment
EUT = Equipment under test
ISN = Impedance stabilization network

3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the LP0002 Section 2.2, Section 3.10.1.3, and Section 3.10.1.4.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jun. 30, 2020~ Jul. 08, 2020	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 15, 2019	Jun. 30, 2020~ Jul. 08, 2020	Nov. 14, 2020	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Nov. 07, 2019	Jun. 30, 2020~ Jul. 08, 2020	Nov. 06, 2020	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 20, 2019	Jun. 30, 2020~ Jul. 08, 2020	Nov. 19, 2020	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 15, 2019	Jun. 30, 2020~ Jul. 08, 2020	Nov. 14, 2020	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jun. 30, 2020~ Jul. 08, 2020	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 02, 2020	Jun. 30, 2020~ Jul. 08, 2020	Jan. 01, 2021	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 02, 2020	Jun. 30, 2020~ Jul. 08, 2020	Jan. 01, 2021	Conduction (CO05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Dec. 26, 2019	Jul. 08, 2020 ~ Jul. 14, 2020	Dec. 25, 2020	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N -06	37059 & 01	30MHz~1GHz	Oct. 12, 2019	Jul. 08, 2020 ~ Jul. 14, 2020	Oct. 11, 2020	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1328	1GHz~18GHz	Nov. 14, 2019	Jul. 08, 2020 ~ Jul. 14, 2020	Nov. 13, 2020	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170584	18GHz~40GHz	Dec. 10, 2019	Jul. 08, 2020 ~ Jul. 14, 2020	Dec. 09, 2020	Radiation (03CH12-HY)
Preamplifier	COM-POWER	PA-103	161075	10MHz~1GHz	Mar. 25, 2020	Jul. 08, 2020 ~ Jul. 14, 2020	Mar. 24, 2021	Radiation (03CH12-HY)
Preamplifier	Agilent	8449B	3008A02375	1GHz~26.5GHz	Mar. 26, 2020	Jul. 08, 2020 ~ Jul. 14, 2020	Mar. 25, 2021	Radiation (03CH12-HY)
Preamplifier	Jet-Power	JPA0118-55-303K	1710001800054002	1GHz~18GHz	Aug. 06, 2019	Jul. 08, 2020 ~ Jul. 14, 2020	Aug. 05, 2020	Radiation (03CH12-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz~40GHz	Dec. 13, 2019	Jul. 08, 2020 ~ Jul. 14, 2020	Dec. 12, 2020	Radiation (03CH12-HY)
Spectrum Analyzer	Agilent	N9010A	MY53470118	10Hz~44GHz	Mar. 12, 2020	Jul. 08, 2020 ~ Jul. 14, 2020	Mar. 11, 2021	Radiation (03CH12-HY)
Signal Generator	Rohde & Schwarz	SMB100A	101107	100kHz~40GHz	Aug. 27, 2019	Jul. 08, 2020 ~ Jul. 14, 2020	Aug. 26, 2020	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0058/126E	30MHz~18GHz	Dec. 12, 2019	Jul. 08, 2020 ~ Jul. 14, 2020	Dec. 11, 2020	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY15539/4	30MHz~18GHz	Feb. 25, 2020	Jul. 08, 2020 ~ Jul. 14, 2020	Feb. 24, 2021	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30MHz~40GHz	Feb. 25, 2020	Jul. 08, 2020 ~ Jul. 14, 2020	Feb. 24, 2021	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	800740/2	30MHz~40GHz	Feb. 25, 2020	Jul. 08, 2020 ~ Jul. 14, 2020	Feb. 24, 2021	Radiation (03CH12-HY)
Hygrometer	TECPEL	DTM-303B	TP140349	N/A	Oct. 25, 2019	Jul. 08, 2020 ~ Jul. 14, 2020	Oct. 24, 2020	Radiation (03CH12-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Jul. 08, 2020 ~ Jul. 14, 2020	N/A	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Jul. 08, 2020 ~ Jul. 14, 2020	N/A	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Jul. 08, 2020 ~ Jul. 14, 2020	N/A	Radiation (03CH12-HY)
Software	Audix	E3 6.2009-8-24	RK-000989	N/A	N/A	Jul. 08, 2020 ~ Jul. 14, 2020	N/A	Radiation (03CH12-HY)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	Testo	HTC-1	2	N/A	Mar. 02, 2020	Jul. 01, 2020 ~ Jul. 14, 2020	Mar. 01, 2021	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	17I00015SNO36	10MHz~6GHz	Jan. 22, 2020	Jul. 01, 2020 ~ Jul. 14, 2020	Jan. 21, 2021	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9KHz-40GHz	Dec. 09, 2019	Jul. 01, 2020 ~ Jul. 14, 2020	Dec. 08, 2020	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-1405-0	EC1900157	N/A	Aug. 15, 2019	Jul. 01, 2020 ~ Jul. 14, 2020	Aug. 14, 2020	Conducted (TH05-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.3

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.1

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.6

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Jacob Yu	Temperature:	21~25	°C
Test Date:	2020/7/1-2020/7/14	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.074	0.686	0.50	Pass
BLE	1Mbps	1	19	2440	1.086	0.692	0.50	Pass
BLE	1Mbps	1	39	2480	1.128	0.692	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail	Power Setting
BLE	1Mbps	1	0	2402	3.65	30.00	-0.86	2.79	36.00	Pass	Default
BLE	1Mbps	1	19	2440	3.85	30.00	-0.86	2.99	36.00	Pass	Default
BLE	1Mbps	1	39	2480	3.55	30.00	-0.86	2.69	36.00	Pass	Default

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	4.41	-10.90	-0.86	8.00	Pass
BLE	1Mbps	1	19	2440	4.46	-10.86	-0.86	8.00	Pass
BLE	1Mbps	1	39	2480	4.35	-11.14	-0.86	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

Appendix B. AC Conducted Emission Test Results

Test Engineer :	Tom Lee and Howard Huang	**Temperature :**	23~25℃
		Relative Humidity :	42~50%

EUT Information

Report NO :	060607-03
Test Mode :	Mode 4
Test Voltage :	Power From System
Phase :	Line

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.150000	---	40.77	56.00	15.23	L1	OFF	19.5
0.150000	54.70	---	66.00	11.30	L1	OFF	19.5
0.166920	---	29.82	55.11	25.29	L1	OFF	19.5
0.166920	45.74	---	65.11	19.37	L1	OFF	19.5
0.182670	---	34.49	54.36	19.87	L1	OFF	19.5
0.182670	48.52	---	64.36	15.84	L1	OFF	19.5
0.234600	---	34.87	52.29	17.42	L1	OFF	19.5
0.234600	39.46	---	62.29	22.83	L1	OFF	19.5
0.501450	---	31.09	46.00	14.91	L1	OFF	19.5
0.501450	35.80	---	56.00	20.20	L1	OFF	19.5
0.568590	---	28.95	46.00	17.05	L1	OFF	19.5
0.568590	34.65	---	56.00	21.35	L1	OFF	19.5
0.633570	---	27.36	46.00	18.64	L1	OFF	19.5
0.633570	34.20	---	56.00	21.80	L1	OFF	19.5
1.428000	---	33.80	46.00	12.20	L1	OFF	19.6
1.428000	40.00	---	56.00	16.00	L1	OFF	19.6
13.618500	---	23.55	50.00	26.45	L1	OFF	19.8
13.618500	28.11	---	60.00	31.89	L1	OFF	19.8

EUT Information

Report NO :	060607-03
Test Mode :	Mode 4
Test Voltage :	Power From System
Phase :	Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.154590	---	39.65	55.75	16.10	N	OFF	19.5
0.154590	56.88	---	65.75	8.87	N	OFF	19.5
0.166920	---	29.41	55.11	25.70	N	OFF	19.5
0.166920	46.25	---	65.11	18.86	N	OFF	19.5
0.177000	---	28.89	54.63	25.74	N	OFF	19.5
0.177000	50.11	---	64.63	14.52	N	OFF	19.5
0.188340	---	38.77	54.11	15.34	N	OFF	19.5
0.188340	50.02	---	64.11	14.09	N	OFF	19.5
0.204000	---	24.17	53.45	29.28	N	OFF	19.5
0.204000	41.90	---	63.45	21.55	N	OFF	19.5
0.232890	---	38.05	52.35	14.30	N	OFF	19.5
0.232890	45.87	---	62.35	16.48	N	OFF	19.5
0.271680	---	29.41	51.07	21.66	N	OFF	19.5
0.271680	39.50	---	61.07	21.57	N	OFF	19.5
0.499740	---	32.59	46.00	13.41	N	OFF	19.5
0.499740	37.10	---	56.00	18.90	N	OFF	19.5
1.100220	---	30.78	46.00	15.22	N	OFF	19.6
1.100220	36.98	---	56.00	19.02	N	OFF	19.6
1.236750	---	32.93	46.00	13.07	N	OFF	19.6
1.236750	38.71	---	56.00	17.29	N	OFF	19.6
1.342680	---	34.11	46.00	11.89	N	OFF	19.6

1.342680	40.01	---	56.00	15.99	N	OFF	19.6
1.443750	---	34.67	46.00	11.33	N	OFF	19.6
1.443750	39.83	---	56.00	16.17	N	OFF	19.6
1.552560	---	33.11	46.00	12.89	N	OFF	19.6
1.552560	37.69	---	56.00	18.31	N	OFF	19.6
1.650750	---	31.35	46.00	14.65	N	OFF	19.6
1.650750	37.69	---	56.00	18.31	N	OFF	19.6
1.747950	---	29.74	46.00	16.26	N	OFF	19.6
1.747950	34.65	---	56.00	21.35	N	OFF	19.6
1.851000	---	28.35	46.00	17.65	N	OFF	19.6
1.851000	32.98	---	56.00	23.02	N	OFF	19.6
1.988700	---	27.12	46.00	18.88	N	OFF	19.6
1.988700	31.69	---	56.00	24.31	N	OFF	19.6
24.755730	---	21.33	50.00	28.67	N	OFF	20.0
24.755730	25.67	---	60.00	34.33	N	OFF	20.0

Appendix C. Radiated Spurious Emission

Test Engineer :	Chuan Chu	Temperature :	24.3~26.4°C
		Relative Humidity :	56.1~68.1%

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2310.63	54.72	-19.28	74	44.88	27.76	15.72	33.64	166	74	P	H
		2316.825	44.11	-9.89	54	34.29	27.73	15.73	33.64	166	74	A	H
	*	2402	89.28	-	-	79.59	27.5	15.87	33.68	166	74	P	H
	*	2402	88.16	-	-	78.47	27.5	15.87	33.68	166	74	A	H
													H
													H
		2330.265	54.94	-19.06	74	45.16	27.68	15.75	33.65	100	77	P	V
		2370.06	44.59	-9.41	54	34.88	27.56	15.82	33.67	100	77	A	V
	*	2402	96.95	-	-	87.26	27.5	15.87	33.68	100	77	P	V
	*	2402	96.35	-	-	86.66	27.5	15.87	33.68	100	77	A	V
													V
													V
BLE CH 19 2440MHz		2358.16	54.91	-19.09	74	45.19	27.58	15.8	33.66	138	70	P	H
		2313.64	44.08	-9.92	54	34.24	27.75	15.73	33.64	138	70	A	H
	*	2440	90.92	-	-	81.28	27.42	15.92	33.7	138	70	P	H
	*	2440	90.28	-	-	80.64	27.42	15.92	33.7	138	70	A	H
		2491.88	54.72	-19.28	74	45.14	27.32	15.99	33.73	138	70	P	H
		2490.62	43.96	-10.04	54	34.38	27.32	15.99	33.73	138	70	A	H
		2316.58	54.8	-19.2	74	44.98	27.73	15.73	33.64	100	89	P	V
		2346.26	44.03	-9.97	54	34.29	27.61	15.78	33.65	100	89	A	V
	*	2440	97.01	-	-	87.37	27.42	15.92	33.7	100	89	P	V
	*	2440	96.36	-	-	86.72	27.42	15.92	33.7	100	89	A	V
		2499.02	54.53	-19.47	74	44.96	27.3	16	33.73	100	89	P	V
		2486.84	44.05	-9.95	54	34.45	27.33	15.99	33.72	100	89	A	V

BLE CH 39 2480MHz	*	2480	92.49	-	-	82.89	27.34	15.98	33.72	137	72	P	H
	*	2480	91.79	-	-	82.19	27.34	15.98	33.72	137	72	A	H
		2483.56	56.29	-17.71	74	46.7	27.33	15.98	33.72	137	72	P	H
		2484.4	44.42	-9.58	54	34.83	27.33	15.98	33.72	137	72	A	H
													H
													H
	*	2480	98.37	-	-	88.77	27.34	15.98	33.72	125	87	P	V
	*	2480	97.42	-	-	87.82	27.34	15.98	33.72	125	87	A	V
		2483.56	60.55	-13.45	74	50.96	27.33	15.98	33.72	125	87	P	V
		2483.52	45.69	-8.31	54	36.1	27.33	15.98	33.72	125	87	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	42.13	-31.87	74	61.65	31.1	9.84	60.46	100	0	P	H
													H
													H
													H
		4804	44.05	-29.95	74	63.57	31.1	9.84	60.46	100	0	P	V
													V
													V
													V
BLE CH 19 2440MHz		4880	42.79	-31.21	74	62.16	31.1	9.93	60.4	100	0	P	H
		7320	46.16	-27.84	74	56.28	36.38	12.61	59.11	100	0	P	H
													H
													H
		4880	41.65	-32.35	74	61.02	31.1	9.93	60.4	100	0	P	V
		7320	45.73	-28.27	74	55.85	36.38	12.61	59.11	100	0	P	V
													V
													V
BLE CH 39 2480MHz		4960	42.5	-31.5	74	61.56	31.24	10.03	60.33	100	0	P	H
		7440	45.69	-28.31	74	55.43	36.4	12.9	59.04	100	0	P	H
													H
													H
		4960	44.53	-29.47	74	63.59	31.24	10.03	60.33	100	0	P	V
		7440	45.92	-28.08	74	55.66	36.4	12.9	59.04	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission above 18GHz

2.4GHz BLE

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4G BLE		21444	40.15	-33.85	74	43.27	38.04	12.33	53.49	150	0	P	H
													H
													H
													H
													H
													H
		22494	40.57	-33.43	74	42.52	38.69	12.86	53.5	150	0	P	V
													V
													V
													V
													V
													V

Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE LF		30.97	24.53	-15.47	40	29.65	24.01	0.51	29.64	-	-	P	H
		133.79	26.2	-17.3	43.5	37.26	17.4	1.16	29.62	-	-	P	H
		752.65	32.8	-13.2	46	30.16	28.04	3.2	28.6	-	-	P	H
		855.47	34.83	-11.17	46	30.65	29.03	3.52	28.37	-	-	P	H
		910.76	36.46	-9.54	46	31.74	29.15	3.75	28.18	-	-	P	H
		955.38	36.52	-9.48	46	30.18	30.79	3.68	28.13	100	0	P	H
													H
													H
													H
													H
													H
													H
		30	30.07	-9.93	40	34.89	24.31	0.51	29.64	-	-	P	V
		101.78	28.47	-15.03	43.5	41.07	16.07	0.94	29.61	-	-	P	V
		669.23	29.9	-16.1	46	29.51	26.25	2.81	28.67	-	-	P	V
		786.6	32.66	-13.34	46	29.79	28.1	3.28	28.51	-	-	P	V
		897.18	36.74	-9.26	46	32.19	28.99	3.76	28.2	100	0	P	V
		958.29	36.15	-9.85	46	29.73	30.83	3.71	28.12	-	-	P	V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Note symbol

*	**Fundamental Frequency** which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is **over limit** line.
P/A	**P**eak or **A**verage
H/V	**H**orizontal or **V**ertical

A calculation example for radiated spurious emission is shown as below:

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =

Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Chuan Chu	Temperature :	24.3~26.4°C
		Relative Humidity :	56.1~68.1%

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Fundamental
Peak		
Avg.		

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Vertical	Fundamental
Peak		
Avg		

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition : PEAK_BE_74 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 060607	 Site : 03CH12-HY Condition : PEAK_74 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 060607
Avg.	 Site : 03CH12-HY Condition : AVG_BE_54 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 060607	 Site : 03CH12-HY Condition : AVG_54 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 060607

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Horizontal	Fundamental
Peak		Left blank
Avg.		Left blank

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Vertical	Fundamental
Peak		
Avg.		

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Vertical	Fundamental
Peak		Left blank
Avg.		Left blank

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Fundamental
Peak		
Avg.		

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Vertical	Fundamental
Peak		
Avg.		

2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Vertical
Peak Avg.		

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH19 2440MHz	
	Horizontal	Vertical
Peak Avg.		

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Vertical
Peak		

Emission above 18GHz

2.4GHz BLE (SHF)

WIFI	2.4GHz 2400~2483.5MHz	
	BLE (SHF)	
	Horizontal	Vertical
Peak Avg.		

Emission below 1GHz

2.4GHz BLE (LF)

BLE	2.4GHz 2400~2483.5MHz	
	BLE LF	
	Horizontal	Vertical
QP / Peak		

Annex. A Receiver Radiated Emission Measurement

A.1 Limit of Receiver Radiated Emission

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

A.2 Measuring Instruments

See list of measuring equipment of this test report.

A.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dBμV/m) = 20 log Emission level (μV/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

A.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



A.5 Test Result of Receiver Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per NCC LP0002 section 5.13 was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

A.6 Connection Diagram of Test System



A.7 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Phone	ASUS	Zenfone 5	N/A	N/A	N/A
2.	Adapter	SUNYES	002-1W	N/A	N/A	N/A

Remark: Applicant has ensured accessory would not be attached with the product on the market, accessory is provided by lab for testing.

A.8 Test Result of Receiver Radiated Spurious Emission (30MHz ~ 5th Harmonic)

Test Engineer :	Chuan Chu	**Temperature :**	24.3~26.4°C
		Relative Humidity :	56.1~68.1%
Frequency	954.410 MHz	**Margin**	Under 9.51 dB
Test Mode	Bluetooth Idle		

	Idle Mode	
	Horizontal	**Vertical**
Peak **Avg.**	 Site : 03CH12-HY Condition : PEAK_74 3m HORN_9120D_1328 HORIZONTAL Detector : Peak Project : 060607-02	 Site : 03CH12-HY Condition : PEAK_74 3m HORN_9120D_1328 VERTICAL Detector : Peak Project : 060607-02

Horizontal:

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	30.97	24.84	-15.16	40.00	29.96	24.01	0.48	29.64	---	---	Peak
2	141.55	19.49	-24.01	43.50	30.72	17.21	1.07	29.61	---	---	Peak
3	608.12	30.28	-15.72	46.00	30.98	25.52	2.41	28.86	---	---	Peak
4	758.47	32.73	-13.27	46.00	30.04	28.06	2.90	28.59	---	---	Peak
5	870.99	34.68	-11.32	46.00	30.37	29.02	3.21	28.31	---	---	Peak
6	938.89	36.23	-9.77	46.00	30.57	30.12	3.24	28.15	100	0	Peak
7	2008.00	46.74	-27.26	74.00	48.89	26.13	5.20	33.48	---	---	Peak
8	2434.00	46.89	-27.11	74.00	47.27	27.43	5.89	33.70	---	---	Peak
9	7965.00	48.35	-25.65	74.00	55.73	36.89	14.08	59.00	---	---	Peak
10	8640.00	48.99	-25.01	74.00	55.78	37.36	14.40	59.04	---	---	Peak
11	15555.00	48.74	-25.26	74.00	51.62	37.99	19.11	60.61	---	---	Peak
12	16530.00	49.91	-24.09	74.00	49.48	39.18	19.79	59.18	100	0	Peak

Vertical:

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	30.97	28.30	-11.70	40.00	33.42	24.01	0.48	29.64	---	---	Peak
2	100.81	25.17	-18.33	43.50	37.93	15.92	0.84	29.61	---	---	Peak
3	594.54	30.05	-15.95	46.00	30.82	25.50	2.38	28.88	---	---	Peak
4	743.92	32.56	-13.44	46.00	29.98	28.02	2.85	28.60	---	---	Peak
5	825.40	33.62	-12.38	46.00	30.47	28.17	3.05	28.43	---	---	Peak
6	954.41	36.49	-9.51	46.00	30.17	30.77	3.22	28.13	100	0	Peak
7	1416.00	48.26	-25.74	74.00	52.11	25.77	4.19	33.81	---	---	Peak
8	2462.00	48.99	-25.01	74.00	49.40	27.38	5.92	33.71	---	---	Peak
9	7785.00	46.36	-27.64	74.00	55.11	36.17	13.61	59.00	---	---	Peak
10	8490.00	47.37	-26.63	74.00	54.84	36.68	14.23	58.90	---	---	Peak
11	15330.00	48.79	-25.21	74.00	50.84	38.99	19.06	60.73	---	---	Peak
12	16455.00	49.98	-24.02	74.00	50.07	38.82	19.71	59.26	100	0	Peak

<Receiver Radiated Emission>

LF

HF



Appendix E. Duty Cycle Plots

Band	Duty Cycle (%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor (dB)
Bluetooth -LE	84.33	2125.00	0.47	1kHz	0.74

Bluetooth - LE



Date: 1.JUL.2020 11:44:56

Appendix F. Setup Photographs

<Conducted Emission>

Mode 4

Remote View



Rear View

<Radiated Emission>

Y Plane

LF



HF



SHF



———THE END———