Prüfbericht-Nr.: *Test Report No.*:	**50142270 001**	**Auftrags-Nr.:** *Order No.*:	114074441	Seite 1 von 44 *Page 1 of 44*
Kunden-Referenz-Nr.: *Client Reference No.*:	N/A	**Auftragsdatum:** *Order date*:	12-Feb-2018	
Auftraggeber: *Client*:	TGI Technology Pte Ltd. 140 Paya Lebar Road #06-25 AZ @ Paya Lebar Singapore 409015			
Prüfgegenstand: *Test item*:	Wireless speaker			
Bezeichnung / Typ-Nr.: *Identification / Type No.*:	E3,E4,S3,S3 mini,S4			
Auftrags-Inhalt: *Order content*:	FCC Part 15C / NCC LP0002 Test report (BDR/EDR)			
Prüfgrundlage: *Test specification*:	FCC 47CFR Part 15: Subpart C Section 15.247 NCC Low-power Radio-frequency Devices Technical Regulations LP0002(2018)			
Wareneingangsdatum: *Date of receipt*:	22-Feb-2018			
Prüfmuster-Nr.: *Test sample No.*:	A000698693-007 A000698693-008			
Prüfzeitraum: *Testing period*:	21-Mar-2018 - 30-Mar-2018			
Ort der Prüfung: *Place of testing*:	EMC Laboratory Taipei			
Prüflaboratorium: *Testing laboratory*:	TUV Rheinland Taiwan Ltd.			
Prüfergebnis*: *Test result**:	Pass			

Report date / *tested by*:			**kontrolliert von /** *reviewed by*:		
2018-04-27	Sam C.J. Kuo/Engineer	Sam	2018-04-27	Arvin Ho/Vice General Manager	
Datum *Date*	**Name / Stellung** *Name / Position*	**Unterschrift** *Signature*	**Datum** *Date*	**Name / Stellung** *Name / Position*	**Unterschrift** *Signature*

Sonstiges / *Other*:
The wireless speaker with different Speaker unit and enclosure size,the model number are E3,S3 mini,E4,S3 and S4,all of them are electrically identical.
during the evaluation and pre-test found that E3 was worst case.Please refer to the appendixD for the detail.

Zustand des Prüfgegenstandes bei Anlieferung: *Condition of the test item at delivery*:	Prüfmuster vollständig und unbeschädigt *Test item complete and undamaged*

* Legende:	1 = sehr gut	2 = gut	3 = befriedigend	4 = ausreichend	5 = mangelhaft
	P(ass) = entspricht o.g. Prüfgrundlage(n)		F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet
Legend:	*1 = very good*	*2 = good*	*3 = satisfactory*	*4 = sufficient*	*5 = poor*
	P(ass) = passed a.m. test specification(s)		*F(ail) = failed a.m. test specification(s)*	*N/A = not applicable*	*N/T = not tested*

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.
This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.

TEST SUMMARY

5.1.1 ANTENNA REQUIREMENT
RESULT: Passed

5.1.2 PEAK OUTPUT POWER
RESULT: Passed

5.1.3 20DB BANDWIDTH
RESULT: Passed

5.1.4 99% BANDWIDTH
RESULT: Passed

5.1.5 CONDUCTED SPURIOUS EMISSIONS AND FREQUENCY BAND EDGE MEASURED IN 100KHZ BANDWIDTH
RESULT: Passed

5.1.6 SPURIOUS EMISSION
RESULT: Passed

5.1.7 FREQUENCY SEPARATION
RESULT: Passed

5.1.8 NUMBER OF HOPPING FREQUENCY
RESULT: Passed

5.1.9 TIME OF OCCUPANCY
RESULT: Passed

5.2.1 MAINS CONDUCTED EMISSIONS
RESULT: Passed

6.1.1 ELECTROMAGNETIC FIELDS
RESULT: Passed

Contents

1. GENERAL REMARKS 5
1.1 COMPLEMENTARY MATERIALS 5
2. TEST SITES 6
2.1 TEST LABORATORY 6
2.2 TEST FACILITY 6
2.3 LIST OF TEST AND MEASUREMENT INSTRUMENTS 7
2.4 TRACEABILITY 8
2.5 CALIBRATION 8
2.6 MEASUREMENT UNCERTAINTY 8
3. GENERAL PRODUCT INFORMATION 9
3.1 PRODUCT FUNCTION AND INTENDED USE 9
3.2 SYSTEM DETAILS AND RATINGS 9
3.3 INDEPENDENT OPERATION MODES 10
3.4 NOISE GENERATING AND NOISE SUPPRESSING PARTS 11
3.5 SUBMITTED DOCUMENTS 11
4. TEST SET-UP AND OPERATION MODES 12
4.1 PRINCIPLE OF CONFIGURATION SELECTION 12
4.2 TEST OPERATION AND TEST SOFTWARE 12
4.3 SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT 12
4.4 COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE 13
4.5 TEST SETUP DIAGRAM 13
5. TEST RESULTS 15
5.1 TRANSMITTER REQUIREMENT & TEST SUITES 15
5.1.1 Antenna Requirement 15
5.1.2 Peak Output Power 16
5.1.3 20dB Bandwidth 17
5.1.4 99% Bandwidth 21
5.1.5 Conducted spurious emissions and Frequency Band Edge measured in 100kHz Bandwidth 22
5.1.6 Spurious Emission 30
5.1.7 Frequency Separation 31
5.1.8 Number of hopping frequency 33
5.1.9 Time of Occupancy 36
5.2 MAINS EMISSIONS 39
5.2.1 Mains Conducted Emissions 39

6. SAFETY HUMAN EXPOSURE 40

6.1 RADIO FREQUENCY EXPOSURE COMPLIANCE 40

6.1.1 Electromagnetic Fields 40

7. PHOTOGRAPHS OF THE TEST SET-UP 41

8. LIST OF TABLES 44

9. LIST OF PHOTOGRAPHS 44

1. General Remarks

1.1 Complementary Materials

The following attachments are integral parts of this test report:

Appendix P: Photo Documentation
(File Name: 50142270APPENDIX P)
Appendix D: Test Result of Radiated Emissions
(File Name: 50142270APPENDIX D)

Test Specifications

The following standards were applied

Table 1: Applied Standard and Test Levels

Radio
FCC CFR47 Part 15: Subpart C Section 15.247 ANSI C63.10:2013 NCC Low-power Radio-frequency Devices Technical Regulations LP0002(2018)(107 年 1 月 10 日)

2. Test Sites

2.1 Test Laboratory

TUV Rheinland Taiwan Ltd.
Taichung Branch Office

No.9, Lane 36, Minsheng Rd., Sec. 3, Daya District,
Taichung City 428
Taiwan (R.O.C.)

2.2 Test Facility

TUV Rheinland Taiwan Ltd.
Taipei Office

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.
Taipei City 105
Taiwan (R.O.C.)

FCC RegistrationNo.: 340738
IC Canada Registration No.: 9465A-1
TAF Accredited NCC Test Lab. No.:0759
TAF ISO17025 Certification effective periods: 2016-Jul-1st to 2019-Jun-30th

Testing Laboratory
0759

2.3 List of Test and Measurement Instruments

Table 2: List of Test and Measurement Equipment

Kind of Equipment	Manu-facturer	Type	S/N	Last Calibration	Next Calibration
Test Software	Farad	EZ_EMC	Ver. TUV3A1	N/A	N/A
EMI Test Receiver	R&S	ESR 7	101549	2017/11/10	2018/11/10
Spectrum Analyzer	R&S	FSV 40	100921	2017/05/02	2018/05/01
Spectrum Analyzer	Agilent	N9010A	MY53470241	2017/05/23	2018/05/22
Preamplifier (30MHz -1GHz)	HP	8447F	2805A03335	2017/08/14	2018/08/14
Preamplifier (18 GHz -40 GHz)	COM-POWER	PAM-840	461257	2018/01/18	2019/01/18
Pre-Amplifier (1GHz~18GHz)	EM Electronics	EM01G18G	60558	2017/11/21	2018/11/21
Bilog Antenna	TESEQ	CBL6111D	29804	2017/08/18	2018/08/18
Horn Antenna	ETS-Lindgren	3117	201918	2017/08/18	2018/08/18
Horn Antenna (18GHz~40GHz)	COM-POWER	AH-840	101029	2017/11/28	2018/11/28
Loop Antenna	Schwarzbeck	FMZB 1513	1513-076	2017/06/14	2018/06/14
EMI Test Receiver	R&S	ESR 7	101549	2017/11/10	2018/11/10
Spectrum Analyzer	R&S	FSL3	101943	2015/09/07	2018/09/07
Temp. & Humid. Chamber	Giant Force	GCT-099-40-S	MAF0103-007	2017/03/09	2019/03/09
LISN (1 phase)	R&S	ENV216	101243	2017/06/18	2018/06/18
LISN	R&S	ENV216	101262	2017/06/22	2018/06/21

2.4 Traceability

All measurement equipment calibrations are traceable to NML(Taiwan)/NIST(USA) or where calibration is performed outside Taiwan, to equivalent nationally recognized standards organizations.

2.5 Calibration

requiring calibration is calibrated periodically in a suitably accredited Calibration Lab. Additionally all equipment is verified for proper performance on a regular basics using in house standards or comparisons.

2.6 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements:.

Table 3: Emission Measurement Uncertainty

Parameter	Uncertainty
RF power, conducted	± 1.5 dB
Adjacent channel power	± 3 dB
Radiated emission of transmitter, valid up to 26 GHz	± 6 dB
Radiated emission of receiver, valid up to 26 GHz	± 6 dB
Temperature	± 2 ºC
Humidity	± 10 %

3. General Product Information

3.1 Product Function and Intended Use

The EUT is a Bluetooth Speaker enabling the user to communicate data through a Wireless interface.
For details refer to the User Guide, Data Sheet and Circuit Diagram.

3.2 System Details and Ratings

Table 4: Basic Information of EUT

Item	EUT information
Kind of Equipment/Test Item	Wireless speaker
Type Identification	E3,E4,S3,S3 mini,S4
Brand Name	Ub+
FCC ID	2AD2ME3A

Table 5: Technical Specification of EUT

Technical Specification	Value
Operating Frequency	2402 MHz ~ 2480 MHz
Channel Spacing	1 MHz
Channel number	79
Operation Voltage	7.4 Vdc
Modulation	GFSK, π/4 DQPSK, 8 DPSK
Antenna gain	-0.61 dBi

Table 6: Frequency hopping information

Technical Specification	Description
Hopping Range	Hereby we declare that the maximum frequency of this device is: 2402-2480MHz. This is according the Bluetooth Core Specification V2.1+EDR for devices which will be operated in the USA. This was checked during the Bluetooth Qualification tests (Test Case: TRM/CA/04).
Hopping Sequence	Example of a 79 hopping sequence in data mode: 33,04,21,44,23,42,53,46,55,48,40,59,72,29,76,31,08,73, 07,75,09,45,60,39,58,13,47,11,77,52,35,50,65,54,67,56, 69,62,71,64, 7,25,27,66,57,70,74,61,78,63,10,41,05,43, 15,44,64,68,02,70,06,01,51,03,55,05,03,66,53,49,36,47,
Receiver input bandwidth	The input bandwidth of the receiver is 1MHz. In every connection one Bluetooth device is the master and the other one is the slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally the type of connection is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also the slave of the connection will use these settings. Repeating of a packer has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.

3.3 Independent Operation Modes

The basic operation modes are:

A. Transmitting
   1. Low channel
   2. Middle channel
   3. High channel
   4. Hopping mode

B. Receiving
   1. Low channel
   2. Middle channel
   3. High channel

3.4 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

3.5 Submitted Documents

- Circuit Diagram
- Instruction Manual
- Rating Label
- Technical Description

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The equipment under test (EUT) was configured to measure its maximum power level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 4. All testing were performed according to the procedures in ANSI C63.10: 2013

The samples were used as follows:
Conducted: **A000698693-008**
Radiation: **A000698693-007**

Full test was applied on all test modes, but only worst case was shown.

4.3 Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

Description	Manufacturer	Model No.	Serial No.
Notebook(EMC-06)	Lenovo	TP00048A	PB-0F8B2

4.4 Countermeasures to achieve EMC Compliance

The test sample which has been tested containing the noise suppression parts as in the Photo Appendix and the Test Setup Photos. No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test



Note: Measurements above 1 GHz are done with a table height of 1.5m

Diagram of Measurement Equipment Configuration for Mains Conduction Measurement



Diagram of Measurement Equipment Configuration for Conducted Transmitter Measurement



5. Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT: **Passed**

Test standard	:	LP0002(2018): 2.2, 3.10.1.3, 3.10.1.4 FCC Part 15.247(b)(4), Part 15.203 and RSS-Gen 8.3
Requirement	:	use of approved antennas only with directional gains that do not exceed 6 dBi

According to the manufacturer declaration, the EUT has an antenna with a directional gain of -0.61 dBi. The antenna is a printed PCB trace with no possibility of replacement with a non-approved antenna by the end-user. Therefore, the EUT is considered to comply with this provision.

Refer to EUT photo for details.

5.1.2 Peak Output Power

RESULT: **Passed**

Test standard	:	FCC Part 15.247(b)(1), RSS-247 5.4(2) LP0002(2018): 3.10.1.2
Basic standard	:	ANSI C63.10:2013 LP0002(2018) Appendix II
Kind of test site	:	Shielded room

Test setup

Test Channel	:	Low/ Middle/ High
Operation Mode	:	A

Ambient temperature	:	22-26 °C
Relative humidity	:	50-65 %
Atmospheric pressure	:	100-103 kPa

Table 7: Test result of Peak Output Power, GFSK modulation

Channel	Channel Frequency	Peak Output Power		Limit
	(MHz)	(dBm)	(W)	(W)
Low Channel	2402	7.56	0.0057	0.125
Middle Channel	2441	8.88	0.00773	0.125
High Channel	2480	9.01	0.00796	0.125

Table 8: Test result of Peak Output Power, 8DPSK modulation

Channel	Channel Frequency	Peak Output Power		Limit
	(MHz)	(dBm)	(W)	(W)
Low Channel	2402	6.69	0.00467	0.125
Middle Channel	2441	8.28	0.00673	0.125
High Channel	2480	8.35	0.00684	0.125

Pmax: 7.96 mW

5.1.3 20dB Bandwidth

RESULT: **Passed**

Test standard	:	FCC Part 15.247(a)(1), RSS-247 5.1(1) LP0002(2018): 3.10.1.6 (1)(A)
Basic standard	:	ANSI C63.10:2013 LP0002(2018) Appendix II
Kind of test site	:	Shielded room

Test setup

Test Channel	:	Low/ Middle/ High
Operation Mode	:	A
Ambient temperature	:	22-26°C
Relative humidity	:	50-65%
Atmospheric pressure	:	100-103kPa

Table 9: Test result of 20dB Bandwidth, GFSK modulation

Channel	Channel Frequency (MHz)	20dB Bandwidth (kHz)	Limit (MHz)	Result
Low Channel	2402	948	1.5	Pass
Mid Channel	2441	940.4	1.5	Pass
High Channel	2480	942.4	1.5	Pass

Note: Limit is for Channel Separation of 1 MHz and a power limit of 125 mW.

Table 10: Test result of 20dB Bandwidth, 8DPSK modulation

Channel	Channel Frequency (MHz)	20dB Bandwidth (kHz)	Limit (MHz)	Result
Low Channel	2402	1.265	1.5	Pass
Mid Channel	2441	1.266	1.5	Pass
High Channel	2480	1.272	1.5	Pass

Note: Limit is for Channel Separation of 1 MHz and a power limit of 125 mW.

If the carrier separation frequency of a Bluetooth Device is set at 1 MHz due to the firmware setting and the Bluetooth Standard, then for power <125 mW the limit for the 20 dB Bandwidth, becomes 1 MHz / 0.66666 = 1.5 MHz.

Test Plot of 20dB Bandwidth, GFSK modulation

Low Channel



Middle Channel



High Channel



Test Plot of 20dB Bandwidth, 8DPSK modulation

Low Channel



Middle Channel



High Channel



5.1.4 99% Bandwidth

RESULT: **Passed**

Test standard	:	RSS-Gen (Issue 4)
Basic standard	:	RSS-Gen (Issue 4)
Kind of test site	:	Shielded room

Test setup

Test Channel	:	Middle
Operation Mode	:	A

Ambient temperature	:	22-26°C
Relative humidity	:	50-65%
Atmospheric pressure	:	100-103kPa

Table 11: Test result of 99% Bandwidth, GFSK modulation

Channel	Channel Frequency (MHz)	99% Bandwidth (kHz)
Mid Channel	2441	853.41

Table 12: Test result of 99% Bandwidth, PSK modulation

Channel	Channel Frequency (MHz)	99% Bandwidth (MHz)
Mid Channel	2441	1.1751

5.1.5 Conducted spurious emissions and Frequency Band Edge measured in 100kHz Bandwidth

RESULT: **Passed**

Test standard	:	FCC part 15.247(d), RSS-247 5.5 LP0002(2018): 3.10.1.5
Basic standard	:	ANSI C63.10:2013 LP0002(2018) Appendix II
Limit	:	20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power)
Kind of test site	:	Shielded room

Test setup

Test Channel	:	Low/ Middle/ High for Conducted Spurious Emissions Low/ High/ Hopping on for Frequency Band Edge
Operation Mode	:	A

Ambient temperature	:	22-26°C
Relative humidity	:	50-65%
Atmospheric pressure	:	100-103 kPa

All emissions are more than 20dB below fundamental, details refer to following test plot, and compliance is achived as well.
Due to the small size of the product and that there are no inductive components of significant size, 9kHz to 30MHz frequency range is not tested based on technical judgment.

Test Plot of 100kHz Conducted Emissions, GFSK modulation

Low Channel

Middle Channel

High Channel

Test Plot of 100kHz Conducted Emissions, 8DPSK modulation

Low Channel

Middle Channel

High Channel

Test Plot of 100kHz Bandwidth of Frequency Band Edge, GFSK modulation

Low Channel



High Channel



Hopping ON


Keysight Spectrum Analyzer - Swept SA
Display Line -11.25 dBm
Avg Type: Log-Pwr
Trig: Free Run
Atten: 30 dB
Ref Offset 1.9 dB
10 dB/div
Ref 20.00 dBm
Mkr1 2.439 16 GHz
8.75 dBm
Start 2.38000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.50000 GHz
Sweep 11.53 ms (1001 pts)
1 N 1 f 2.439 16 GHz 8.75 dBm
2 N 1 f 2.400 00 GHz -46.465 dBm
3 N 1 f 2.483 50 GHz -54.839 dBm
Display
Annotation
Title
Graticule
Display Line
System Display Settings

Test Plot of 100kHz Bandwidth of Frequency Band Edge, 8DPSK modulation

Low Channel



High Channel



Hopping ON


Keysight Spectrum Analyzer - Swept SA
Display Line -12.70 dBm
Avg Type: Log-Pwr
Trig: Free Run
Atten: 30 dB
PNO: Fast
IFGain:Low
Ref Offset 1.9 dB
10 dB/div
Ref 20.00 dBm
Log
Mkr1 2.443 96 GHz
7.30 dBm
Start 2.38000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.50000 GHz
Sweep 11.53 ms (1001 pts)
1 N 1 f 2.443 96 GHz 7.30 dBm
2 N 1 f 2.400 00 GHz -44.004 dBm
3 N 1 f 2.483 50 GHz -53.633 dBm
Display
Annotation
Title
Graticule
Display Line
System Display Settings

5.1.6 Spurious Emission

RESULT: **Passed**

Test standard	:	FCC part 15.247(d), FCC 15.205, FCC 15.209, RSS-210 2.2, RSS-247 5.5 and RSS-Gen 8.9 LP0002(2018): 3.10.1.5
Basic standard	:	ANSI C63.10
Limits	:	Radiated emissions which fall in the restricted bands, as defined in FCC 15.205(a) and RSS-Gen i4, 8.9 (Table 6), must comply with the radiated emission limits specified in FCC 15.209(a) and RSS-Gen i4, 8.9 (Table 4 and 5). Radiated emissions which fall in the restricted bands, as defined in LP0002(2018): 2.7 , must comply with the radiated emission limits specified in LP0002(2018): 2.8 Emission radiated outside the specified frequency bands must comply with the radiated emission limits specified in FCC 15.209(a) and FCC 15.249(a), RSS-Gen i4, 8.9 (Table 4 and 5) and RSS-210 A2.9(a). Emission radiated outside the specified frequency bands must comply with the radiated emission limits specified in LP0002(2018): 2.8
Kind of test site	:	3m Semi-Anechoic Chamber

Test setup

Test Channel	:	Low/ Middle/ High
Operation Mode	:	A, B
Ambient temperature	:	22-26 °C
Relative humidity	:	50-65 %
Atmospheric pressure	:	100-103 kPa

Remark: Testing was carried out within frequency range 30MHz to the tenth harmonic. For details refer to Appendix D. The Radiated Emissions testing was performed in the X, Y and Z axis orientation. The worst-case Axis orientation is recorded in this test report. Due to the small size of the product and that there are no inductive components of significant size, 9kHz to 30MHz frequency range is not tested based on technical judgment.

5.1.7 Frequency Separation

RESULT: **Passed**

Test standard	:	FCC part 15.247(a)(1) RSS-247 5.1 LP0002(2018): 3.10.1.6 (1) (A)
Basic standard	:	ANSI C63.10:2013 LP0002(2018) Appendix II
Limit	:	≥ 25kHz or 2/3 of 20dB bandwidth, whichever is greater
Kind of test site	:	Shielded room

Test setup

Test Channel	:	Middle
Operation Mode	:	A
Ambient temperature	:	22-26 °C
Relative humidity	:	50-65 %
Atmospheric pressure	:	100-103 kPa

Table 13: Test result of Frequency Separation

Channel	Channel Frequency (MHz)	Measured Channel Separation (MHz)	Limit (kHz)	Result
Record Channel	2441	1	≥ 25kHz or 2/3 of 20dB bandwidth	Pass
Record Channel adj 1	2440			
Record Channel adj 2	2442			

Test Plot of Frequency Separation

5.1.8 Number of hopping frequency

RESULT: **Passed**

Test standard	:	FCC part 15.247(a)(1)(iii) RSS-247 5.1(5) LP0002(2018): 3.10.1.6 (1) (A)
Basic standard	:	ANSI C63.10:2013 LP0002(2018) Appendix II
Kind of test site	:	Shielded room

Test setup

Test Channel	:	Hopping On
Operation Mode	:	Hopping Mode
Ambient temperature	:	22-26°C
Relative humidity	:	50-65%
Atmospheric pressure	:	100-103 kPa

Table 14: Test result of Number of hopping frequency

Frequency Range	Measured Quantity of Hopping Channel	Limit	Result
2400 to 2483.5 MHz	79	≥15	Pass

Test Plot of Number of hopping frequencies




Keysight Spectrum Analyzer - Swept SA
Stop Freq 2.441500000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 30 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
09:18:35 AM Mar 22, 2018
Frequency
Auto Tune
Center Freq
2.420750000 GHz
Start Freq
2.400000000 GHz
Stop Freq
2.441500000 GHz
CF Step
4.150000 MHz
Auto
Man
Freq Offset
0 Hz
Ref Offset 1.9 dB
10 dB/div
Ref 20.00 dBm
Log
Start 2.40000 GHz
#Res BW 1.0 MHz
#VBW 1.0 MHz
Stop 2.44150 GHz
Sweep 1.000 ms (1001 pts)


Keysight Spectrum Analyzer - Swept SA
Stop Freq 2.483500000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 30 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
09:18:17 AM Mar 22, 2018
Trace/Detector
Select Trace
1
Clear Write
Trace Average
Max Hold
Min Hold
View Blank
Trace On
More
1 of 3
Ref Offset 1.9 dB
10 dB/div
Ref 20.00 dBm
Log
Start 2.44150 GHz
#Res BW 1.0 MHz
#VBW 1.0 MHz
Stop 2.48350 GHz
Sweep 1.000 ms (1001 pts)

5.1.9 Time of Occupancy

RESULT: **Passed**

Test standard	:	FCC part 15.247(a)(1)(iii) RSS-247 5.1(5) LP0002(2018): 3.10.1.6 (1) (A)
Basic standard	:	ANSI C63.10:2013 LP0002(2018) Appendix II
Limits	:	0.4s
Kind of test site	:	Shield room

Test setup

Test Channel	:	Low
Operation Mode	:	A
Ambient temperature	:	22-26°C
Relative humidity	:	50-65%
Atmospheric pressure	:	100-103 kPa

Table 15: Test result of Time of Occupancy

Data Mode	Captured Burst (s)	Dwell time (s)	On+Off time (s)	Limit (s)	Result
DH5	0.003	0.3192	0.00376	0.4	Pass
3DH5	0.00303	0.3224	0.00376	0.4	Pass

Note:
Dwell time = Pulse width x (Hopping rate / Number of channels) x Period

Period = 0.4 (seconds/ channel) x 79 (channel) = 31.6 seconds.

Hopping rate = 1 / (On+Off time) = 266 Hz

Test Plot of Time of Occupancy, GFSK modulation





Test Plot of Time of Occupancy, 8DPSK modulation





5.2 Mains Emissions

5.2.1 Mains Conducted Emissions

RESULT: **Passed**

Test standard	:	FCC Part 15.207 FCC Part 15.107 RSS-Gen 8.8 LP0002(2018): 2.3
Limits	:	Mains Conducted emissions as defined in above test standards must comply with the mains conducted emission limits specified
Kind of test site	:	Shielded Room

Test setup

Test Channel	:	Hopping Channel
Operation mode	:	Normal Mode

Remark: For details refer to Appendix D.

6. Safety Human exposure

6.1 Radio Frequency Exposure Compliance

6.1.1 Electromagnetic Fields

RESULT: **Passed**

Test standard : 47CFR 1.1310
47CFR 2.1091
RSS-102 issue 5, Table 4

The EUT will maintain a 20 cm distance to all persons.

Maximum Exposure:

Power to Antenna (mW)	7.96 mW
Power to Antenna (dBm)	9.0 dBm
Antenna Gain	0 dBi
Power+Ant Gain	8.0 mW
Distance	20 cm
S=	0.002 mW/cm^2

Limit FCC: 0.61 mW/cm^2

FCC:

0.3-1.34 MHz	(100) mW/cm^2
1.34-30 MHz	(180/f^2) mW/cm^2
30-300 MHz	0.2 mW/cm^2
300-1500 MHz	f/1500 mW/cm^2
1500-100,000 MHz	1.0 mW/cm^2

---End---

7. Photographs of the Test Set-Up

Photograph 1: Set-up for Spurious Emissions (Front View)



Photograph 2: Set-up for Spurious Emissions (Back View 1)



Photograph 3: Set-up for Spurious Emissions (Back View 2)



Photograph 4: Set-up for Conducted testing

Photograph 5: Set-up for Mains Conducted testing Back



Photograph 6: Set-up for for Mains Conducted testing Front



8. List of Tables

Table 1: Applied Standard and Test Levels 5
Table 2: List of Test and Measurement Equipment 7
Table 3: Emission Measurement Uncertainty.....8
Table 4: Basic Information of EUT 9
Table 5: Technical Specification of EUT 9
Table 6: Frequency hopping information.....10
Table 7: Test result of Peak Output Power, GFSK modulation.....16
Table 8: Test result of Peak Output Power, 8DPSK modulation.....16
Table 9: Test result of 20dB Bandwidth, GFSK modulation.....17
Table 10: Test result of 20dB Bandwidth, 8DPSK modulation.....17
Table 11: Test result of 99% Bandwidth, GFSK modulation.....21
Table 12: Test result of 99% Bandwidth, PSK modulation.....21
Table 13: Test result of Frequency Separation 31
Table 14: Test result of Number of hopping frequency.....33
Table 15: Test result of Time of Occupancy.....36

9. List of Photographs

Photograph 1: Set-up for Spurious Emissions (Front View).....41
Photograph 2: Set-up for Spurious Emissions (Back View 1).....41
Photograph 3: Set-up for Spurious Emissions (Back View 2).....42
Photograph 4: Set-up for Conducted testing.....42
Photograph 5: Set-up for Mains Conducted testing Back 43
Photograph 6: Set-up for for Mains Conducted testing Front.....43