TEST REPORT

Report No.:	8427EU011417W
Applicant:	Guangzhou Boju Information Technology Co., Ltd
Address:	Room 201-3, Building E, No. 31, Xicha Road, Tongde Street, Baiyun District, Guangzhou, China
Product Name:	Portable Refrigerator
Model No.:	CRH02001 (refer to clause 2.4)
Trademark:	BOugeRV
Test Standard(s):	MIC Notice No.88 Appendix No.43 Ordinance of MPT No.37, 1981: Article 2 paragraph 1 item (19)
Test Result:	Pass
Date of Receipt:	Jan. 14, 2026
Test Date:	Jan. 15, 2026 - Apr. 15, 2026
Date of Issue:	Apr. 22, 2026

ISSUED BY:

SHENZHEN EU TESTING LABORATORY LIMITED

SHENZHEN EU TESTING LABORATORY LIMITED APPROVED

Prepared by: **Reviewed and Approved by:**

Landon Qiu/ Engineer

Sally Zhang/ Manager

複製禁止

Revision Record

Report Version	Issued Date	Description	Status
V0	Apr. 22, 2026	Original	Valid

Table of Contents

1 COVER PAGE 1
2 GENERAL INFORMATION 5
2.1 APPLICANT INFORMATION 5
2.2 MANUFACTURER INFORMATION 5
2.3 FACTORY INFORMATION 5
2.4 GENERAL DESCRIPTION OF E.U.T. 5
2.5 TECHNICAL INFORMATION OF E.U.T. 6
3 TEST SUMMARY 7
3.1 TEST STANDARD 7
3.2 TEST VERDICT 7
3.3 TEST LABORATORY 7
4 TEST CONFIGURATION 8
4.1 TEST ENVIRONMENT 8
4.2 TEST EQUIPMENT 9
4.3 DESCRIPTION OF SUPPORT UNIT 9
4.4 MEASUREMENT UNCERTAINTY 10
5 TEST ITEMS 11
5.1 FREQUENCY TOLERANCE TEST 11
5.1.1 Test Requirement 11
5.1.2 Test Setup Diagram 11
5.1.3 Test Procedure 11
5.1.4 Test Deviation 11
5.1.5 EUT Operation during Test 11
5.1.6 Test Data 11
5.2 OCCUPIED BANDWIDTH 12
5.2.1 Test Requirement 12
5.2.2 Test Setup Diagram 12
5.2.3 Test Procedure 12
5.2.4 Test Deviation 12
5.2.5 EUT Operation during Test 12
5.2.6 Test Data 12
5.3 ANTENNA POWER / EIRP ANTENNA POWER TEST 13
5.3.1 Test Requirement 13
5.3.2 Test Setup Diagram 13
5.3.3 Test Procedure 13
5.3.4 Test Deviation 13
5.3.5 EUT Operation during Test 13
5.3.6 Test Data 13
5.4 SPURIOUS EMISSIONS INTENSITY TEST 14
5.4.1 Test Requirement 14
5.4.2 Test Setup Diagram 14
5.4.3 Test Procedure 14
5.4.4 Test Deviation 14
5.4.5 EUT Operation during Test 14
5.4.6 Test Data 14
5.5 SECONDARY RADIATED EMISSIONS TEST 15
5.5.1 Test Requirement 15
5.5.2 Test Setup Diagram 15
5.5.3 Test Procedure 15
5.5.4 Test Deviation 15

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

5.5.5 EUT Operation during Test 15
5.5.6 Test Data 15
5.6 INTERFERENCE PREVENTION FUNCTION 16
5.6.1 Test Requirement 16
5.6.2 Test Setup Diagram 16
5.6.3 Test Procedure 16
5.6.4 Test Deviation 16
5.6.5 EUT Operation during Test 16
5.6.6 Test Data 16
5.7 TRANSMISSION RADIATION ANGLE WIDTH (3DB BEAMWIDTH) MEASUREMENT 17
5.7.1 Test Requirement 17
5.7.2 Test Setup Diagram 17
5.7.3 Test Procedure 17
5.7.4 Test Deviation 17
5.7.5 EUT Operation during Test 17
5.7.6 Test Data 17
5.8 CONSTRUCTION PROTECTION CONFIRMATION METHOD 18
ANNEX A TEST SETUP PHOTOS 19
ANNEX B EXTERNAL PHOTOS 19
ANNEX C INTERNAL PHOTOS 19
ANNEX D TEST DATA 20

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

2 General Information

2.1 Applicant Information

Applicant	Guangzhou Boju Information Technology Co., Ltd
Address	Room 201-3, Building E, No. 31, Xicha Road, Tongde Street, Baiyun District, Guangzhou, China

2.2 Manufacturer Information

Manufacturer	Guangzhou Boju Information Technology Co., Ltd
Address	Room 201-3, Building E, No. 31, Xicha Road, Tongde Street, Baiyun District, Guangzhou, China

2.3 Factory Information

Factory	Foshan Alpicool Electric Appliance Co., LTD
Address	2/F, 13A, Xinlong Road, Lunjiao Town, Shunde District, Foshan City, Guangdong, 528300, China

2.4 General Description of E.U.T.

Product Name	Portable Refrigerator
Model No. Under Test	CRH02001
List Model No.	CRH02002, CRH02003, CRH02004, CRH02004B, CRH02003B, CRH02002B, CRH02001B
Description of Model differentiation	All models are same with electrical parameters and internal circuit structure, but only differ in appearance color, capacity and model name. (this information provided by the customer)
Rating(s)	When powered by car charger: Input: 12V⎓5A, 24V⎓2.5A When powered by adapter: Input: 14.5V⎓6.0A, 87.0W (Adapter Input: 100-240V~, 50/60Hz, 2.5A Max; Output: 14.5V⎓6.0A, 87.0W) Battery Capacity: 16VDC, 15000mAh, 240Wh
Adapter	Model No.: GRT90-145600 Input: 100-240V~, 50/60Hz, 2.5A Max Output: 14.5V⎓, 6.0A, 87.0W Manufacturer: FoShan Great Power Co.,Ltd.
Product Type	☒ Mobile ☐ Portable ☐ Fix Location
Test Sample No.	-1/2(Normal Sample), -2/2(Engineering Sample)
Hardware Version	LR-SYZBATP NO:02
Software Version	1.0.1
Remark	For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.5 Technical Information of E.U.T.

Network and Wireless Connectivity	Bluetooth Low Energy (BLE)

The requirement for the following technical information of the EUT was tested in this report:

Technology	**Bluetooth**
Operation Mode	☒ BLE
Modulation Type	GFSK
Operating Frequency	2402-2480MHz
Transfer Rate	1 Mbps
Number of Channel	40
Antenna Type	PCB Antenna
Antenna Gain(Peak)	2.338 dBi
Antenna Impedance	50Ω
Rated output Power	2.200 mW
Remark	The above information are declared by the applicant, EU-LAB is not responsible for the information accuracy provided by the applicant.

All channels were listed on the following table:

Channel Number	Freq. (MHz)	Channel Number	Freq. (MHz)	Channel Number	Freq. (MHz)	Channel Number	Freq. (MHz)
00	**2402**	10	2422	20	2442	30	2462
01	2404	11	2424	21	2444	31	2464
02	2406	12	2426	22	2446	32	2466
03	2408	13	2428	23	2448	33	2468
04	2410	14	2430	24	2450	34	2470
05	2412	15	2432	25	2452	35	2472
06	2414	16	2434	26	2454	36	2474
07	2416	17	2436	27	2456	37	2476
08	2418	18	2438	28	2458	38	2478
09	2420	**19**	**2440**	29	2460	**39**	**2480**

3 Test Summary

3.1 Test Standard

The tests were performed according to following standards:

No.	Identity	Document Title
1	MIC Notice No.88 Appendix No.43 Ordinance of MPT No.37, 1981: Article 2 paragraph 1 item (19)	Low power data communications system in the 2.4GHz band

Remark:
Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product maybe which result in lowering the emission should be checked to ensure compliance has been maintained.

3.2 Test Verdict

No.	Description	Test Mode	Data Rate (Mbps)	Verdict	Remark
1	Frequency Tolerance	GFSK	1	Pass	--
2	Occupied Bandwidth	GFSK	1	Pass	--
3	Antenna Power / EIRP Antenna Power	GFSK	1	Pass	--
4	Spurious Emission Intensity	GFSK	1	Pass	--
5	Secondary Radiated Emission	GFSK	1	Pass	--
6	Spurious Emissions	GFSK	1	Pass	--
7	Interference Prevention Function	GFSK	1	Pass	--
8	Transmission Radiated Angle Width (3dB Beam Bandwidth)	GFSK	1	N/A	Note 2
9	Construction Protection Confirmation	GFSK	1	Compliance	--
10	Carrier Sense Function (1)	GFSK	1	N/A	Note 3
11	Carrier Sense Function (2)	GFSK	1	N/A	Note 4

Note 1: The tests were performed according to the method of measurements prescribed in MIC Notice No.88 Appendix No.43.
Note 2: Note: Because the EIRP is less than 12.14 dBm, this item is not applicable.
Note 3: Not apply to this device, since EIRP does not require compensation through Antenna Power.
Note 4: Application to transmitting devices with OFDM modulation and the occupied bandwidth greater than 26MHz.

3.3 Test Laboratory

Test Laboratory	Shenzhen EU Testing Laboratory Limited
Address	101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China

4 Test Configuration

4.1 Test Environment

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	52%	
Atmospheric Pressure	103 kPa	
Temperature	NT (Normal Temperature)	+26℃
Working Voltage of the EUT	NV (Normal Voltage)	100VAC
	LV (Low Voltage)	90VAC
	HV (High Voltage)	110VAC
Working Voltage of the EUT	NV (Normal Voltage)	24.0VDC
	LV (Low Voltage)	21.6VDC
	HV (High Voltage)	26.4VDC
Working Voltage of the EUT	NV (Normal Voltage)	16.0VDC
	LV (Low Voltage)	14.4VDC
	HV (High Voltage)	17.6VDC

Power Supply Voltage Fluctuation Test (For Adapter)

Voltage Fluctuation Test	Normal Voltage	High Voltage +10% of Normal Voltage	Low Voltage -10% of Normal Voltage
Input To EUT	100VAC	110VAC	90VAC
Output To RF Module	3.3VDC	3.3VDC	3.3VDC
Voltage Variation (%)	--	0.00%	0.00%

Power Supply Voltage Fluctuation Test (For Car Charger)

Voltage Fluctuation Test	Normal Voltage	High Voltage +10% of Normal Voltage	Low Voltage -10% of Normal Voltage
Input To EUT	24.0VDC	21.6VDC	26.4VDC
Output To RF Module	3.3VDC	3.3VDC	3.3VDC
Voltage Variation (%)	--	0.00%	0.00%

Power Supply Voltage Fluctuation Test (For Battery)

Voltage Fluctuation Test	Normal Voltage	High Voltage +10% of Normal Voltage	Low Voltage -10% of Normal Voltage
Input To EUT	16.0VDC	14.4VDC	17.6VDC
Output To RF Module	3.3VDC	3.3VDC	3.3VDC
Voltage Variation (%)	--	0.00%	0.00%

Note:
Voltage Variation (%)=(Output high or Low Voltage - Output Normal Voltage)/ Output Normal Voltage* 100%
For extreme voltage test, we have tested the relationship between the external power supply and RF IC power supply. Base on the test results, only the normal voltage was selected to perform all items.

4.2 Test Equipment

Radiated Emission and RF Test					
Equipment	**Manufacturer**	**Model No**	**Serial No**	**Cal Date**	**Cal Due Date**
EMI Test Receiver	ROHDE & SCHWARZ	ESPI	EE-006	2026/01/07	2027/01/06
Bilog Broadband Antenna	SCHWARZBECK	VULB 9163	EE-007	2026/01/13	2029/01/12
Double Ridged Horn Antenna	A-INFOMW	LB-10180-NF	EE-008	2026/01/11	2029/01/10
Pre-amplifier	Agilent	8447D	EE-009	2026/01/07	2027/01/06
Pre-amplifier	Agilent	8449B	EE-010	2026/01/07	2027/01/06
MXA Signal Analyzer	Agilent	N9020A	EE-011	2026/01/07	2027/01/06
MXG RF Vector Signal Generator	Agilent	N5182A	EE-012	2026/01/07	2027/01/06
Test Software	Farad	EZ-EMC	EE-015	N.C.R	N.C.R
MIMO Power Measurement Module	TSTPASS	TSPS 2023R	EE-016	2026/01/07	2027/01/06
RF Test Software	TSTPASS	TS32893 V2.0	EE-017	N.C.R	N.C.R
Wideband Radio Communication Tester	ROHDE & SCHWARZ	CMW500	EE-402	2026/02/13	2027/02/12
Loop Antenna	TESEQ	HLA6121	EE-403	2026/02/13	2027/02/12
MXG RF Analog Signal Generator	Agilent	N5181A	EE-406	2026/02/13	2027/02/12
Constant Temperature Humidity Chamber	Guangxin	GXP-401	ES-002	2025/07/29	2026/07/28
Power Sensor	ROHDE&SCHWARZN	NRP18S	ES-052	2026/02/13	2027/02/12
DC Power Source	QJE	QJ3020E	ES-037	2025/07/29	2026/07/28
Note[1]: Calibration Company: Shenzhen Academy Of Metrology& Quality inspection. Note[2]: Calibration method: Calibration conducted in foreign countries, which is equivalent to calibration conducted by the NICT or a designated calibration agency under Article 102-18-1 and Article 24-2, Paragraph 4 of the Radio Act.					

4.3 Description of Support Unit

No.	Title	Manufacturer	Model No.	Serial No.
1	Adapter	refer to clause 2.4	refer to clause 2.4	--

4.4 Measurement Uncertainty

Parameters	Uncertainty
Frequency Error / 99% Bandwidth	(3.2 x f x 10^{-6}) Hz
Antenna Power	1.82 dB
TX-RX Spurious Emissions	1.84 dB
Transmission Antenna Gain	5.36 dB
Temperature	0.8 ℃
Humidity	4 %
DC / AC Power Source	0.04%
Noet: “f” is the nominal signal frequency in Hz.	

Note: This uncertainty represents as expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

複製禁止

5 Test Items

5.1 Frequency Tolerance Test

5.1.1 Test Requirement

Item	Limits
Frequency Tolerance	≤±50 ppm

5.1.2 Test Setup Diagram



5.1.3 Test Procedure

Test Frequency= test channel
RBW=VBW=100KHz
Span=2MHz
Sweep time=Auto
Detector mode=Positive peak
Indication mode=Max hold
EUT have transmitted modulation signal and fixed channelize. fL, fH are using the mark cursor to mark the frequency values, fc is declaring of channel frequency. The calculated frequency formula is: f= (fL+fH)/2;
Then the frequency error formula is (fc-f)/fc×106ppm and the limit is less than ±50 ppm.

5.1.4 Test Deviation

There is no deviation with the original standard.

5.1.5 EUT Operation during Test

The EUT was programmed to be in continuous transmit, carrier mode.

5.1.6 Test Data

PASS.
Please refer to Annex D for details.

5.2 Occupied Bandwidth

5.2.1 Test Requirement

Item	Limits
Occupied Band Width	FHSS≦83.5MHz; OFDM≦40MHz, DSSS≦26MHz; Others≦26MHz

5.2.2 Test Setup Diagram



5.2.3 Test Procedure

1. Set the spectrum analyzer as follows:
   Center frequency: Test frequency
   Span: Approximately 2 to 3.5 times nominal bandwidth
   Resolution bandwidth: Within 3% of the technical standard
   Video bandwidth: equivalent to resoluble bandwidth
   Sweep time: auto
   Sweep mode: Continuous sweep
   Detection: Positive peak
   Trace mode: Maximum hold
2. After repeating sweeps until the display shows steady data, store the values at all data points into the computer array variables.

5.2.4 Test Deviation

There is no deviation with the original standard.

5.2.5 EUT Operation during Test

The EUT was programmed to be in continuous transmit, channel-selected mode.

5.2.6 Test Data

PASS.
Please refer to Annex D for details.

5.3 Antenna Power / EIRP Antenna Power Test

5.3.1 Test Requirement

Item	Limits
Antenna Power Density	a) FH, FH+DS, or FH+OFDM form 2427 - 2470.75 MHz: ≦3 mW/MHz b) DS but other than a) from 2400~2483.5 MHz: ≦10 mW/MHz c) OFDM, but other than a): For OCB of 26MHz or less: ≦10 mW/MHz For OCB of over 26 MHz to 40 MHz: ≦5 mw/MHz d) Other than a), b) and c): ≦10 mW
Antenna Power Error	+20% (Base on manufacturer declare antenna power density)
EIRP Power	12.14 dBm

5.3.2 Test Setup Diagram



5.3.3 Test Procedure

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast responding diode detector.

5.3.4 Test Deviation

There is no deviation with the original standard.

5.3.5 EUT Operation during Test

The EUT was programmed to be in continuous transmit, channel-selected mode.

5.3.6 Test Data

PASS.
Please refer to Annex D for details.

5.4 Spurious Emissions Intensity Test

5.4.1 Test Requirement

Item	Limits
TX Spurious Emission	≦2.5μW/MHz (2387MHz>f ; 2496.5MHz<f)
	≦25μW/MHz (2387MHz≦f<2400MHz) and (2483.5MHz<f≦2496.5MHz)

5.4.2 Test Setup Diagram



5.4.3 Test Procedure

Spectrum Parameter	Setting
Attenuation	Auto
RB	30-1000 MHz: 1 MHz/1 MHz
VB	Above 1GHz: 1 MHz/1 MHz
Detector	Peak
Trace	Max Hold
Sweep	Auto

1. The EUT is placed in transmit mode at maximum power/modulation at a fixed channel.
2. Setting of SA is following as: RBW/VBW = 1MHz; / AT: 10dB / Ref: 0dBm / Sweep time: Auto / Sweep Mode: Continuous sweep / Detect mode: Positive peak / Trace mode: Max hold
3. Setting of SA is following as 30 MHz and stop frequency 2387 MHz Then to mark peak reading value + cable loss shall be less than 2.5 μW
4. SA adjusted to start frequency 2387 MHz and stop frequency 2400 MHz. Then to mark peak reading value + cable loss shall be less than 25 μW.
5. SA adjusted to start frequency 2483.5 MHz and stop frequency 2496.5 MHz Then to mark peak reading value + cable loss shall be less than 25 μW
6. SA adjusted to start frequency 2496.5 MHz and stop frequency 12500 MHz Then to mark peak reading value + cable loss shall be less than 2.5 μW
7. If the Result_Value is over the requirement, take total sum of 1MHz band centered at the spur frequency like ACLP measurement as Result_Value.

5.4.4 Test Deviation

There is no deviation with the original standard.

5.4.5 EUT Operation during Test

The EUT was programmed to be in continuous transmit, channel-selected mode.

5.4.6 Test Data

PASS.
Please refer to Annex D for details.

5.5 Secondary Radiated Emissions Test

5.5.1 Test Requirement

Item	Limits
RX Spurious Emission	≦4nW (f<1GHz)
	≦20nW (1GHz≦f)

5.5.2 Test Setup Diagram



5.5.3 Test Procedure

Spectrum Parameter	Setting
Attenuation	Auto
RB	30-1000 MHz: 100KHz/100KHz
VB	Above 1GHz: 1 MHz/1 MHz
Detector	Peak
Trace	Max Hold
Sweep	Auto

1. The EUT is placed in Rx mode and set to a fixed channel.
2. Setting of SA is following as RB / VB: 100 kHz (below 1GHz emissions) / 1 MHz (above 1GHz emissions) / AT:10 dB / Ref: 0dBm / Sweep time: Auto / Sweep Mode: Continuous sweep / Detect mode: Positive peak / Trace mode: Max hold
3. SA set RB: 100 kHz and VB: 100 kHz. Then adjust to start frequency 30 MHz and stop frequency 1000 MHz. Search to mark peak reading value + cable loss shall be less than 4 nW
4. SA set RB: 1 MHz and VB: 1 MHz. Then adjust to start frequency 1000 MHz and stop frequency 12500 MHz. Search to mark peak reading value + cable loss shall be less than 20 nW
5. If power level of lower emissions are more than 1/10 of limit (0.4nW for f < 1 GHz, 2 nW for f≥ 1GHz), all those are to be indicated in the 2nd and 3rd lines. If others are 1/10 or less more of the limit, no necessary to be indicated

5.5.4 Test Deviation

There is no deviation with the original standard.

5.5.5 EUT Operation during Test

The EUT was programmed to be in continuous transmit, channel-selected mode.

5.5.6 Test Data

PASS.
Please refer to Annex D for details.

5.6 Interference Prevention Function

5.6.1 Test Requirement

Item	Limits
Identification	≥ 48 bits

5.6.2 Test Setup Diagram



5.6.3 Test Procedure

1. In the case that the EUT has the function of automatically transmitting the identification code:
   a. Transmit the predetermined identification codes form EUT.
   b. Check the transmitted identification codes with the demodulator.
2. In the case of receiving the identification code:
   a. Transmit the predetermined identification codes form the counterpart.
   b. Check if communication is normal.
   c. Transmit the signals other than predetermined ID codes form the counterpart.
   d. check if the EUT stops the transmission, or if it displays that identification codes are different from the predetermined ones.

5.6.4 Test Deviation

There is no deviation with the original standard.

5.6.5 EUT Operation during Test

The EUT was programmed to be in continuous transmit, channel-selected mode.

5.6.6 Test Data

PASS.

Mode	ID Code	Test Results
BLE	38:D1:F7:03:52:A8	Pass

5.7 Transmission Radiation Angle Width (3dB Beamwidth) Measurement

5.7.1 Test Requirement

Item	Limits
3dB antenna beam width	360/A (If A<1; then A=1) A = {EIRP Power [mW] / 16.36 for DS, OFDM} or A = {EIRP Power [mW] / 4.9 for FH}
Note: This test item will not be applied to the transmission antenna which has a gain of 2.14dBi or less.	

5.7.2 Test Setup Diagram



5.7.3 Test Procedure

1. Set EUT and measuring antenna at the same height and roughly facing each other.
2. Set spectrum analyzer with RBW=1 MHz, VBW=1 KHz, Y scale=5 dB, Detector=Peak, Trace mode=Max Hold, and tune reference level to observe receiving signal position.
3. Rotate directions of the EUT horizontally and vertically to find the maximum receiving power.
4. Move the measuring antenna height up and down within ± 50cm of EUT height and swing it to find the maximum output of measuring antenna. The output level at the spectrum analyzer is read as “E”
5. Calculate permitted radiation angle in horizontal and vertical using EIRP measured in another test method.
6. Calculate 3dB antenna beam width by the formula below 360/A (If A<1; then A=1). A = {EIRP Power [mW] / 16.36 for DS, OFDM} or A = {EIRP Power [mW] / 4.9 for FH}

5.7.4 Test Deviation

There is no deviation with the original standard.

5.7.5 EUT Operation during Test

The EUT was programmed to be in continuous transmit, channel-selected mode.

5.7.6 Test Data

Note: Because the EIRP is less than 12.14 dBm, this item is not applicable.

5.8 Construction Protection Confirmation Method

The RF and modulation portions are protected against illegal modification as following method:

Protected Method	Description
Structure protection	The product has the special screws for the housing, The screws hold the product in place, so it can't be easily opened and modified.
Reference Photo	



ANNEX A TEST SETUP PHOTOS

Please refer to the document “8427EU011417W-AA.PDF”

ANNEX B EXTERNAL PHOTOS

Please refer to the document “8427EU011417W-AB.PDF”

ANNEX C INTERNAL PHOTOS

Please refer to the document “8427EU011417W-AC.PDF”

ANNEX D TEST DATA

1. Frequency Error

1.1 Test Result

1.1.1 Ant1

Ant1							
ENV	Mode	TX Type	Frequency (MHz)	Measured Frequency (MHz)	Tolerance (ppm)		Verdict
					Result	Limit	
NTNV	1M	SISO	2402	2402.056	23.23	-50 to 50	Pass
			2480	2480.059	23.75	-50 to 50	Pass

1.2 Test Graph

1.2.1 Ant1

1M_2402MHz_Ant1_NTNV



1M_2480MHz_Ant1_NTNV



2. Occupied Bandwidth

2.1 Test Result

2.1.1 OBW

ENV	Mode	TX Type	Frequency (MHz)	99% Occupied Bandwidth (MHz)		Verdict
				ANT1	Limit	
NTNV	1M	SISO	2402	1.202	<=26	Pass
			2480	1.205	<=26	Pass

2.2 Test Graph

2.2.1 OBW

1M_2402MHz_Ant1_NTNV



1M_2480MHz_Ant1_NTNV



3. Spread Bandwidth

3.1 Test Result

3.1.1 SPBW

ENV	Mode	TX Type	Frequency (MHz)	Spread Bandwidth (MHz)		Verdict
				ANT1	Limit	
NTNV	1M	SISO	2402	0.803	/	Pass
			2480	0.803	/	Pass

3.2 Test Graph

3.2.1 SPBW

1M_2402MHz_Ant1_NTNV



1M_2480MHz_Ant1_NTNV



4. Antenna Power

4.1 Test Result

4.1.1 Power

ENV	Mode	TX Type	Frequency (MHz)	ANT	Antenna Power (mW)		Nominal Power (mW)	Tolerance (%)		Verdict
					Measured	Limit		Measured	Limit	
NTNV	1M	SISO	2402	1	0.617	<=10.00	2.200	-71.95	<=20	Pass
			2480	1	0.621	<=10.00	2.200	-71.77	<=20	Pass

4.1.2 EIRP

ENV	Mode	TX Type	Frequency (MHz)	ANT	Gain (dBi)	Measured Power (dBm)	EIRP (dBm)		Verdict
							Result	Limit	
NTNV	1M	SISO	2402	1	2.338	-2.10	0.24	12.14	Pass
			2480	1	2.338	-2.07	0.27	12.14	Pass
Note: E.I.R.P = Measured Power + Antenna Gain									

5. Spurious Emission Intensity

5.1 Test Result

5.1.1 TxSe_NTNV

NTNV												
Mode	TX Type	Freq. (MHz)	ANT	Freq. Range		Marker					Limit (uW /MHz)	Verdict
				Start (MHz)	Stop (MHz)	Freq. (MHz)	PK Power (dBm /MHz)	PK Power (uW /MHz)	AV Power (dBm /MHz)	AV Power (uW /MHz)		
1M	SISO	2402	1	30	2387	111	-57.69	0.002	/	/	2.5	Pass
				2387	2400	2399.987	-41.44	0.072	/	/	25	Pass
				2483.5	2496.5	2490.897	-57.75	0.002	/	/	25	Pass
				2496.5	12500	3203.5	-42.18	0.061	/	/	2.5	Pass
		2480	1	30	2387	110.5	-57.92	0.002	/	/	2.5	Pass
				2387	2400	2399.701	-57.94	0.002	/	/	25	Pass
				2483.5	2496.5	2483.539	-54.03	0.004	/	/	25	Pass
				2496.5	12500	3307.5	-41.57	0.070	/	/	2.5	Pass

5.2 Test Graph

5.2.1 TxSe_NTNV

1M_2402MHz_Ant1_NTNV



1M_2402MHz_Ant1_NTNV



Start (MHz)	Stop (MHz)	RBW (MHz)	VBW (MHz)	Freq (MHz)	PK Power (dBm)	AV Power (dBm)	Limit (dBm)	Result
30	2387	1	1	111.000	-57.69	/	-26	Pass
2387	2400	1	1	2399.987	-41.44	/	-16	Pass
2483.5	2496.5	1	1	2490.897	-57.75	/	-16	Pass
2496.5	12500	1	1	3203.500	-42.18	/	-26	Pass

1M_2480MHz_Ant1_NTNV



1M_2480MHz_Ant1_NTNV



Start (MHz)	Stop (MHz)	RBW (MHz)	VBW (MHz)	Freq (MHz)	PK Power (dBm)	AV Power (dBm)	Limit (dBm)	Result
30	2387	1	1	110.500	-57.92	/	-26	Pass
2387	2400	1	1	2399.701	-57.94	/	-16	Pass
2483.5	2496.5	1	1	2483.539	-54.03	/	-16	Pass
2496.5	12500	1	1	3307.500	-41.57	/	-26	Pass

6. Secondary Radiated Emission

6.1 Test Result

6.1.1 RxSe_NTNV

NTNV												
Mode	TX Type	Freq. (MHz)	ANT	Freq. Range		Marker					Limit (nW)	Verdict
				Start (MHz)	Stop (MHz)	Freq. (MHz)	PK Power (dBm)	PK Power (nW)	AV Power (dBm)	AV Power (nW)		
1M	SISO	2402	1	30	1000	440	-73.42	0.045	/	/	4	Pass
				1000	12500	5541	-64.15	0.385	/	/	20	Pass
		2480	1	30	1000	440	-73.30	0.047	/	/	4	Pass
				1000	12500	11664	-63.87	0.410	/	/	20	Pass

6.2 Test Graph

6.2.1 RxSe_NTNV

1M_2402MHz_Ant1_NTNV



1M_2402MHz_Ant1_NTNV



Start (MHz)	Stop (MHz)	RBW (MHz)	VBW (MHz)	Freq (MHz)	PK Power (dBm)	AV Power (dBm)	Limit (dBm)	Result
30	1000	0.1	0.1	440.000	-73.42	/	-54	Pass
1000	12500	1	1	5541.000	-64.15	/	-47	Pass

1M_2480MHz_Ant1_NTNV



1M_2480MHz_Ant1_NTNV



Start (MHz)	Stop (MHz)	RBW (MHz)	VBW (MHz)	Freq (MHz)	PK Power (dBm)	AV Power (dBm)	Limit (dBm)	Result
30	1000	0.1	0.1	440.000	-73.30	/	-54	Pass
1000	12500	1	1	11664.000	-63.87	/	-47	Pass

STATEMENT

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the “inspection and testing dedicated stamp” or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--- End of Report ---