NCC Test Report

Equipment	:	**802.11ac Wave 2** 同步雙頻整合式無線網路基地台
Model No.	:	**WAC6303D-S**
Brand Name	:	**ZYXEL**
Applicant	:	合勤科技股份有限公司
Address	:	新北市新店區北新路 **3** 段 **223** 號 **11** 樓
Standard	:	**LP0002 Section 3.10.1 (2016-08-23)**
Received Date	:	**Jun. 22, 2017**
Tested Date	:	**Sep. 13 ~ Oct. 18, 2017**

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:

Along Chen / Assistant Manager

Approved by:

Gary Chang / Manager

Testing Laboratory 2732

Table of Contents

1 GENERAL DESCRIPTION 5

1.1 Information 5
1.2 Local Support Equipment List 7
1.3 Test Setup Chart 8
1.4 Test Equipment List and Calibration Data 9
1.5 Test Standards 10
1.6 Measurement Uncertainty 10

2 TEST CONFIGURATION 11

2.1 Testing Condition 11
2.2 The Worst Test Modes and Channel Details 11

3 TRANSMITTER TEST RESULTS 12

3.1 Conducted Emissions 12
3.2 6dB and Occupied Bandwidth 17
3.3 RF Output Power 19
3.4 Power Spectral Density 21
3.5 Emissions in Restricted Frequency Bands 23
3.6 Emissions in non-restricted Frequency Bands 35

4 RECEIVER TEST RESULTS 37

4.1 Conducted Emissions 37
4.2 Radiated Emissions 42

5 TEST LABORATORY INFORMATION 50

Release Record

Report No.	Version	Description	Issued Date
TR762203AE	Rev. 01	Initial issue	Nov. 03, 2017

Summary of Test Results

NCC Rules	Test Items	Measured	Result
2.3	AC Power Line Conducted Emissions	[dBuV]: 0.561MHz 38.69 (Margin -7.31dB) - AV	Pass
3.10.1.5 2.8	Radiated Emissions	[dBuV/m at 3m]: 124.09MHz 40.42 (Margin -3.08dB) - QP	Pass
3.10.1.2(1)(C)	Maximum Output Power	Power [dBm]: 3.72	Pass
3.10.1.6(2)(A)	6dB Bandwidth	Meet the requirement of limit	Pass
3.10.1.6(2)(B)	Power Spectral Density	Meet the requirement of limit	Pass
3.10.1.4	Antenna Requirement	Meet the requirement of limit	Pass

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information				
Frequency Range (MHz)	**Bluetooth Mode**	**Ch. Freq. (MHz)**	**Channel Number**	**Data Rate**
2400-2483.5	V4.1 LE	2402-2480	0-39 [40]	1 Mbps
Note 1: Bluetooth LE (Low energy) uses GFSK modulation.				

1.1.2 Antenna Details

Model	Type	Connector	Gain (dBi)	Remarks
BT-2 to IPEX	PIFA	IPEX	3.85	---

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	From AC adapter: 12Vdc From PoE: 54Vdc

1.1.4 Accessories

N/A

1.1.5 Channel List

Frequency band (MHz)				2400~2483.5			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
37	2402	9	2422	18	2442	28	2462
0	2404	10	2424	19	2444	29	2464
1	2406	38	2426	20	2446	30	2466
2	2408	11	2428	21	2448	31	2468
3	2410	12	2430	22	2450	32	2470
4	2412	13	2432	23	2452	33	2472
5	2414	14	2434	24	2454	34	2474
6	2416	15	2436	25	2456	35	2476
7	2418	16	2438	26	2458	36	2478
8	2420	17	2440	27	2460	39	2480

1.1.6 Test Tool and Duty Cycle

Test tool	putty, V0.6
Duty cycle of test signal (%)	62.39%
Duty Factor (dB)	2.05



1.1.7 Power Setting

Modulation Mode	Test Frequency (MHz)		
	2402	2440	2480
GFSK/1Mbps	3	3	3

1.2 Local Support Equipment List

Support Equipment List					
No.	Equipment	Brand	Model	S/N	Signal cable / Length (m)
1	Notebook	DELL	Latitude E6430	9ZFB4X1	RJ45, 10m non-shielded.
2	POE	ZYXEL	GS1900-8HP	---	---
3	Adapter	APD	WA-24Q12R	---	---

1.3 Test Setup Chart

Test Setup Diagram (Adapter mode)



1. RJ45, 10m non-shielded
2. RJ45, 1m non-shielded with load

Test Setup Diagram (PoE mode)



1. RJ45, 10m non-shielded
2. RJ45, 1m non-shielded with load
3. RJ45, 1m non-shielded

1.4 Test Equipment List and Calibration Data

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Tested Date	Oct. 06, 2017				
Instrument	**Manufacturer**	**Model No.**	**Serial No.**	**Calibration Date**	**Calibration Until**
Receiver	R&S	ESR3	101657	Dec. 21, 2016	Dec. 20, 2017
LISN	R&S	ENV216	101579	Jan. 19, 2017	Jan. 18, 2018
RF Cable-CON	EMC	EMCCFD300-BM-BM-6000	50821	Dec. 20, 2016	Dec. 19, 2017
Measurement Software	AUDIX	e3	6.120210k	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Radiated Emission				
Test Site	966 chamber 3 / (03CH03-WS)				
Tested Date	Sep. 13 ~ Sep. 28, 2017				
Instrument	**Manufacturer**	**Model No.**	**Serial No.**	**Calibration Date**	**Calibration Until**
Spectrum Analyzer	ROHDE&SCHWARZ	FSV40	101486	Nov. 15, 2016	Nov. 14, 2017
Receiver	Agilent	N9038A	MY53290044	Oct. 06, 2016	Oct. 05, 2017
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-685	Apr. 28, 2017	Apr. 27, 2018
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1206	Feb. 09, 2017	Feb. 08, 2018
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Oct. 25, 2016	Oct. 24, 2017
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 10, 2016	Nov. 09, 2017
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Dec. 09, 2016	Dec. 08, 2017
Preamplifier	EMC	EMC02325	980187	Sep. 04, 2017	Sep. 03, 2018
Preamplifier	Agilent	83017A	MY53270014	Aug. 21, 2017	Aug. 20, 2018
Preamplifier	EMC	EMC184045B	980192	Aug. 22, 2017	Aug. 21, 2018
RF cable-3M	HUBER+SUHNER	SUCOFLEX104	MY22620/4	Feb. 04, 2017	Feb. 03, 2018
RF cable-8M	HUBER+SUHNER	SUCOFLEX104	MY22600/4	Feb. 04, 2017	Feb. 03, 2018
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22624/4	Feb. 04, 2017	Feb. 03, 2018
LF cable-0.8M	EMC	EMC8D-NM-NM-800	EMC8D-NM-NM-800-001	Feb. 04, 2017	Feb. 03, 2018
LF cable-3M	EMC	EMC8D-NM-NM-3000	131103	Feb. 04, 2017	Feb. 03, 2018
LF cable-13M	EMC	EMC8D-NM-NM-13000	131104	Feb. 04, 2017	Feb. 03, 2018
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Tested Date	Oct. 18, 2017				
Instrument	**Manufacturer**	**Model No.**	**Serial No.**	**Calibration Date**	**Calibration Until**
Spectrum Analyzer	R&S	FSV40	101063	Mar. 15, 2017	Mar. 14, 2018
Power Meter	Anritsu	ML2495A	1241002	Oct. 16, 2017	Oct. 15, 2018
Power Sensor	Anritsu	MA2411B	1207366	Oct. 16, 2017	Oct. 15, 2018
AC POWER SOURCE	APC	AFC-500W	F312060012	Oct. 28, 2016	Oct. 27, 2017
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

LP0002 Section 3.10.1 (2016-08-23)
ANSI C63.10-2013
ANSI C63.4-2014
FCC KDB 558074 D01 DTS Meas Guidance v04

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty	
Parameters	**Uncertainty**
Bandwidth	±34.134 Hz
Conducted power	±0.808 dB
Power density	±0.463 dB
Conducted emission	±2.670 dB
AC conducted emission	±2.90 dB
Radiated emission ≤ 1GHz	±3.66 dB
Radiated emission > 1GHz	±5.63 dB

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	23°C / 59%	Alex Tsai
Radiated Emissions	03CH03-WS	24°C / 66-67%	Aska Huang Brad Wu
RF Conducted	TH01-WS	23°C / 64%	Felix Sung

- FCC Designation No.: TW0009
- FCC site registration No.: 207696
- IC site registration No.: 10807C-1

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data Rate	Test Configuration
AC Power Line Conducted Emissions Radiated Emissions ≤ 1GHz	BT LE	2402	1Mbps	1, 2
Maximum Output Power 6dB bandwidth Power spectral density Radiated Emissions > 1GHz	BT LE	2402, 2440, 2480	1Mbps	1

NOTE:

1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **X-plane** results were found as the worst case and were shown in this report.
2. This device can be powered by AC adapter or POE. Each power supply was selected for final testing as below configuration.
   1) Test configuration 1: POE mode
   2) Test configuration 2: Adapter mode

Test item	Modulation Mode	Test Frequency (MHz)	Mode	Test Configuration
Conducted Emissions	BT LE	2402	RX	1, 2
Radiated Emissions ≤1GHz	BT LE	2402	RX	1, 2
Radiated Emissions >1GHz	BT LE	2402	RX	1

NOTE:

1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **X-plane** results were found as the worst case and were shown in this report.
2. This device can be powered by AC adapter or POE. Each power supply was selected for final testing as below configuration.
   1) Test configuration 1: POE mode
   2) Test configuration 2: Adapter mode

3 Transmitter Test Results

3.1 Conducted Emissions

3.1.1 Limit of Conducted Emissions

Conducted Emissions Limit		
Frequency Emission (MHz)	**Quasi-Peak**	**Average**
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50
Note 1: * Decreases with the logarithm of the frequency.		

3.1.2 Test Procedures

1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V/60Hz

3.1.3 Test Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.4 Test Result of Conducted Emissions

Modulation Mode	GFSK	Test Freq. (MHz)	2402
Power Phase	Line	Test Configuration	1



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.192	22.79	53.93	-31.14	13.25	9.50	0.04	Average
2	0.192	35.75	63.93	-28.18	26.21	9.50	0.04	QP
3	0.282	34.58	50.76	-16.18	24.99	9.55	0.04	Average
4	0.282	35.26	60.76	-25.50	25.67	9.55	0.04	QP
5@	0.561	38.66	46.00	-7.34	29.07	9.55	0.04	Average
6	0.561	39.52	56.00	-16.48	29.93	9.55	0.04	QP
7	1.124	34.21	46.00	-11.79	24.68	9.49	0.04	Average
8	1.124	34.96	56.00	-21.04	25.43	9.49	0.04	QP
9	2.246	25.01	46.00	-20.99	15.34	9.61	0.06	Average
10	2.246	26.01	56.00	-29.99	16.34	9.61	0.06	QP
11	18.820	24.27	50.00	-25.73	14.31	9.71	0.25	Average
12	18.820	30.64	60.00	-29.36	20.68	9.71	0.25	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

Modulation Mode	GFSK	Test Freq. (MHz)	2402
Power Phase	Neutral	Test Configuration	1



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.282	34.57	50.76	-16.19	24.96	9.57	0.04	Average
2	0.282	35.28	60.76	-25.48	25.67	9.57	0.04	QP
3@	0.561	38.69	46.00	-7.31	29.06	9.59	0.04	Average
4	0.561	39.56	56.00	-16.44	29.93	9.59	0.04	QP
5	1.123	34.57	46.00	-11.43	24.88	9.65	0.04	Average
6	1.123	35.12	56.00	-20.88	25.43	9.65	0.04	QP
7	2.246	25.92	46.00	-20.08	16.31	9.55	0.06	Average
8	2.246	25.93	56.00	-30.07	16.32	9.55	0.06	QP
9	4.525	11.42	46.00	-34.58	1.54	9.71	0.17	Average
10	4.525	21.19	56.00	-34.81	11.31	9.71	0.17	QP
11	18.920	25.33	50.00	-24.67	15.37	9.71	0.25	Average
12	18.920	32.62	60.00	-27.38	22.66	9.71	0.25	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

Modulation Mode	GFSK	Test Freq. (MHz)	2402
Power Phase	Line	Test Configuration	2



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.195	30.88	53.80	-22.92	21.34	9.50	0.04	Average
2	0.195	39.90	63.80	-23.90	30.36	9.50	0.04	QP
3@	0.369	38.22	48.52	-10.30	28.59	9.59	0.04	Average
4	0.369	40.29	58.52	-18.23	30.66	9.59	0.04	QP
5	1.552	13.69	46.00	-32.31	4.08	9.57	0.04	Average
6	1.552	22.35	56.00	-33.65	12.74	9.57	0.04	QP
7	4.549	22.01	46.00	-23.99	12.33	9.51	0.17	Average
8	4.549	29.75	56.00	-26.25	20.07	9.51	0.17	QP
9	14.907	25.74	50.00	-24.26	15.82	9.69	0.23	Average
10	14.907	31.96	60.00	-28.04	22.04	9.69	0.23	QP
11	18.920	24.96	50.00	-25.04	15.00	9.71	0.25	Average
12	18.920	30.88	60.00	-29.12	20.92	9.71	0.25	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

Modulation Mode	GFSK	Test Freq. (MHz)	2402
Power Phase	Neutral	Test Configuration	2



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.195	29.65	53.80	-24.15	20.01	9.60	0.04	Average
2	0.195	38.09	63.80	-25.71	28.45	9.60	0.04	QP
3@	0.371	29.21	48.47	-19.26	19.62	9.55	0.04	Average
4	0.371	35.40	58.47	-23.07	25.81	9.55	0.04	QP
5	1.585	18.41	46.00	-27.59	8.80	9.57	0.04	Average
6	1.585	22.39	56.00	-33.61	12.78	9.57	0.04	QP
7	4.454	20.22	46.00	-25.78	10.34	9.71	0.17	Average
8	4.454	28.79	56.00	-27.21	18.91	9.71	0.17	QP
9	14.288	24.51	50.00	-25.49	14.59	9.69	0.23	Average
10	14.288	30.92	60.00	-29.08	21.00	9.69	0.23	QP
11	19.950	24.92	50.00	-25.08	14.94	9.72	0.26	Average
12	19.950	29.89	60.00	-30.11	19.91	9.72	0.26	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

3.2 6dB and Occupied Bandwidth

3.2.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

3.2.2 Test Procedures

6dB Bandwidth

1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
2. Detector = Peak, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth

1. Set resolution bandwidth (RBW) = 30 kHz, Video bandwidth = 100 kHz.
2. Detector = Sample, Trace mode = max hold.
3 Sweep = auto couple, Allow the trace to stabilize.
4. Use the OBW measurement function of spectrum analyzer to measure the occupied bandwidth.

3.2.3 Test Setup



3.2.4 Test Result of 6dB and Occupied Bandwidth

Mode	Freq. (MHz)	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit of 6dB Bandwidth (kHz)
BT LE	2402	0.717	1.05	500
BT LE	2440	0.717	1.05	500
BT LE	2480	0.713	1.05	500

Worst Plots	
6dB Bandwidth	**99% Occupied Bandwidth**
	

3.3 RF Output Power

3.3.1 Limit of RF Output Power

Conducted power shall not exceed 1Watt.

☒ Antenna gain <= 6dBi, no any corresponding reduction is in output power limit.

☐ Antenna gain > 6dBi

☐ Non Fixed, point to point operations.
The conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dB

☐ Fixed, point to point operations
Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point Operations, maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 5725–5850 MHz band that are used exclusively for fixed, point-to-point operations ,no any corresponding reduction is in transmitter peak output power

3.3.2 Test Procedures

☒ Maximum Peak Conducted Output Power

☐ **Spectrum analyzer**

1. Set RBW = 1MHz, VBW = 3MHz, Detector = Peak.
2. Sweep time = auto, Trace mode = max hold, Allow trace to fully stabilize.
3. Use the spectrum analyzer channel power measurement function with the band limits set equal to the DTS bandwidth edges.

☒ **Power meter**

1. A broadband Peak RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

☒ Maximum Conducted Average Output Power (For reference only)

☒ **Power meter**

1. A broadband Average RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

3.3.3 Test Setup

3.3.4 Test Result of Maximum Output Power

Mode	Freq. (MHz)	Peak Power			Antenna gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)
		Power (mW)	Power (dBm)	Limit (dBm)			
BT LE	2402	2.355	3.72	30	3.85	7.57	36
BT LE	2440	2.291	3.60	30	3.85	7.45	36
BT LE	2480	2.265	3.55	30	3.85	7.40	36

Mode	Freq. (MHz)	AV Power (mW)	AV Power (dBm)	Limit (dBm)
BT LE	2402	2.275	3.57	---
BT LE	2440	2.203	3.43	---
BT LE	2480	2.173	3.37	---

Note: Average power is for reference only

3.4 Power Spectral Density

3.4.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

3.4.2 Test Procedures

☒ Maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit.

1. Set the RBW = 3kHz, VBW = 10kHz.
2. Detector = Peak, Sweep time = auto couple.
3. Trace mode = max hold, allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

☐ Maximum (average) conducted output power was used to demonstrate compliance to the fundamental output power limit.

1. Set the RBW = 100kHz, VBW = 300 kHz.
2. Detector = RMS, Sweep time = auto couple.
3. Set the sweep time to: ≥ 10 x (number of measurement points in sweep) x (maximum data rate per stream).
4. Perform the measurement over a single sweep.
5. Use the peak marker function to determine the maximum amplitude level.

3.4.3 Test Setup



3.4.4 Test Result of Power Spectral Density

Mode	Freq. (MHz)	Total Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
BT LE	2402	-12.19	8
BT LE	2440	-12.44	8
BT LE	2480	-12.78	8

Worst Plot


3.5 Emissions in Restricted Frequency Bands

3.5.1 Limit of Emissions in Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	**Field Strength (uV/m)**	**Field Strength (dBuV/m)**	**Measure Distance (m)**
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit
Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.5.2 Test Procedures

1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:

1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

3.5.3 Test Setup

Radiated Emissions below 1 GHz



Radiated Emissions above 1 GHz



3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	GFSK	**Test Freq. (MHz)**	2402
Polarization	Horizontal	**Test Configuration**	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	124.09	35.87	43.50	-7.63	46.40	-10.53	Peak	---	---
2	149.31	33.59	43.50	-9.91	42.03	-8.44	Peak	---	---
3	223.03	37.66	46.00	-8.34	48.43	-10.77	Peak	---	---
4	249.22	42.81	46.00	-3.19	52.20	-9.39	QP	100	109
5	374.35	34.99	46.00	-11.01	41.05	-6.06	Peak	---	---
6	874.87	39.74	46.00	-6.26	36.50	3.24	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical	Test Configuration	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	39.70	36.77	40.00	-3.23	45.55	-8.78	QP	100	16
2	124.09	40.39	43.50	-3.11	50.92	-10.53	QP	100	91
3	249.22	42.51	46.00	-3.49	51.90	-9.39	Peak	---	---
4	374.35	31.80	46.00	-14.20	37.86	-6.06	Peak	---	---
5	533.43	37.35	46.00	-8.65	40.01	-2.66	Peak	---	---
6	624.61	38.51	46.00	-7.49	39.22	-0.71	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Horizontal	Test Configuration	2



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	124.09	32.90	43.50	-10.60	43.43	-10.53	Peak	---	---
2	249.22	40.50	46.00	-5.50	49.89	-9.39	Peak	---	---
3	374.35	35.56	46.00	-10.44	41.62	-6.06	Peak	---	---
4	533.43	33.30	46.00	-12.70	35.96	-2.66	Peak	---	---
5	624.61	40.02	46.00	-5.98	40.73	-0.71	Peak	---	---
6	874.87	38.38	46.00	-7.62	35.14	3.24	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical	Test Configuration	2



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	50.51	34.86	40.00	-5.14	43.05	-8.19	QP	101	83
2	221.09	38.31	46.00	-7.69	49.20	-10.89	Peak	---	---
3	374.35	32.35	46.00	-13.65	38.41	-6.06	Peak	---	---
4	499.48	34.83	46.00	-11.17	38.19	-3.36	Peak	---	---
5	624.61	40.36	46.00	-5.64	41.07	-0.71	Peak	---	---
6	874.87	38.44	46.00	-7.56	35.20	3.24	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK

Modulation	GFSK	**Test Freq. (MHz)**	2402
Polarization	Horizontal		



		Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1		2390.00	39.01	54.00	-14.99	40.98	-1.97	Average	100	320
2		2390.00	50.31	74.00	-23.69	52.28	-1.97	Peak	100	320
3	*	2402.00	98.43			100.35	-1.92	Average	100	320
4	*	2402.00	99.41			101.33	-1.92	Peak	100	320
5		4804.00	33.14	54.00	-20.86	28.52	4.62	Average	100	242
6		4804.00	44.55	74.00	-29.45	39.93	4.62	Peak	100	242
7		12010.00	42.99	54.00	-11.01	29.08	13.91	Average	100	142
8		12010.00	54.93	74.00	-19.07	41.02	13.91	Peak	100	142

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3:"*" is Peak / Average value of fundamental frequency

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical		



		Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1		2390.00	38.62	54.00	-15.38	40.59	-1.97	Average	248	331
2		2390.00	49.73	74.00	-24.27	51.70	-1.97	Peak	248	331
3	*	2402.00	96.41			98.33	-1.92	Average	248	331
4	*	2402.00	97.39			99.31	-1.92	Peak	248	331
5		4804.00	34.39	54.00	-19.61	29.77	4.62	Average	100	6
6		4804.00	44.94	74.00	-29.06	40.32	4.62	Peak	100	6
7		12010.00	43.71	54.00	-10.29	29.80	13.91	Average	100	108
8		12010.00	54.51	74.00	-19.49	40.60	13.91	Peak	100	108

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3:"*" is Peak / Average value of fundamental frequency

Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Horizontal		



		Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1		2390.00	38.89	54.00	-15.11	40.86	-1.97	Average	100	231
2		2390.00	50.68	74.00	-23.32	52.65	-1.97	Peak	100	231
3	*	2440.00	99.56			101.34	-1.78	Average	100	315
4	*	2440.00	100.58			102.36	-1.78	Peak	100	315
5		2483.50	38.90	54.00	-15.10	40.52	-1.62	Average	100	315
6		2483.50	50.99	74.00	-23.01	52.61	-1.62	Peak	100	315
7		4880.00	33.20	54.00	-20.80	28.42	4.78	Average	100	231
8		4880.00	44.61	74.00	-29.39	39.83	4.78	Peak	100	231
9		7320.00	38.04	54.00	-15.96	28.70	9.34	Average	100	186
10		7320.00	50.17	74.00	-23.83	40.83	9.34	Peak	100	186
11		12200.00	43.22	54.00	-10.78	29.57	13.65	Average	100	158
12		12200.00	55.13	74.00	-18.87	41.48	13.65	Peak	100	158

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3:"*" is Peak / Average value of fundamental frequency

Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Vertical		



		Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1		2390.00	38.51	54.00	-15.49	40.48	-1.97	Average	242	338
2		2390.00	50.49	74.00	-23.51	52.46	-1.97	Peak	242	338
3	*	2440.00	96.93			98.71	-1.78	Average	242	338
4	*	2440.00	97.58			99.36	-1.78	Peak	242	338
5		2483.50	38.95	54.00	-15.05	40.57	-1.62	Average	242	338
6		2483.50	50.95	74.00	-23.05	52.57	-1.62	Peak	242	338
7		4880.00	34.48	54.00	-19.52	29.70	4.78	Average	100	2
8		4880.00	45.34	74.00	-28.66	40.56	4.78	Peak	100	2
9		7320.00	38.03	54.00	-15.97	28.69	9.34	Average	100	227
10		7320.00	49.98	74.00	-24.02	40.64	9.34	Peak	100	227
11		12200.00	43.18	54.00	-10.82	29.53	13.65	Average	100	118
12		12200.00	55.36	74.00	-18.64	41.71	13.65	Peak	100	118

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3:"*" is Peak / Average value of fundamental frequency

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Horizontal		



		Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	*	2480.00	101.05			102.68	-1.63	Average	100	331
2	*	2480.00	102.04			103.67	-1.63	Peak	100	331
3		2483.50	44.58	54.00	-9.42	46.20	-1.62	Average	100	331
4		2483.50	54.55	74.00	-19.45	56.17	-1.62	Peak	100	331
5		4960.00	33.85	54.00	-20.15	28.92	4.93	Average	100	249
6		4960.00	45.07	74.00	-28.93	40.14	4.93	Peak	100	249
7		7440.00	38.25	54.00	-15.75	28.57	9.68	Average	100	174
8		7440.00	50.40	74.00	-23.60	40.72	9.68	Peak	100	174
9		12400.00	43.44	54.00	-10.56	30.07	13.37	Average	100	152
10		12400.00	55.50	74.00	-18.50	42.13	13.37	Peak	100	152

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3:"*" is Peak / Average value of fundamental frequency

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical		



		Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	*	2480.00	97.00			98.63	-1.63	Average	243	340
2	*	2480.00	98.03			99.66	-1.63	Peak	243	340
3		2483.50	41.27	54.00	-12.73	42.89	-1.62	Average	243	340
4		2483.50	51.92	74.00	-22.08	53.54	-1.62	Peak	243	340
5		4960.00	34.85	54.00	-19.15	29.92	4.93	Average	100	8
6		4960.00	45.75	74.00	-28.25	40.82	4.93	Peak	100	8
7		7440.00	38.25	54.00	-15.75	28.57	9.68	Average	100	216
8		7440.00	50.24	74.00	-23.76	40.56	9.68	Peak	100	216
9		12400.00	43.54	54.00	-10.46	30.17	13.37	Average	100	126
10		12400.00	55.59	74.00	-18.41	42.22	13.37	Peak	100	126

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3:"*" is Peak / Average value of fundamental frequency

3.6 Emissions in non-restricted Frequency Bands

3.6.1 Emissions in non-restricted frequency bands limit

The peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

3.6.2 Test Procedures

Reference Level Measurement

1. Set the RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
2. Set Sweep time = auto couple, Trace mode = max hold.
3. Allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

Unwanted Emissions Level Measurement

1. Set RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
2. Trace Mode = max hold, Sweep = auto couple.
3. Allow the trace to stabilize.
4. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

3.6.3 Test Setup



3.6.4 Test Result of Emissions in non-restricted Frequency Bands

Tx 2402MHz / Reference Level



Tx 2402MHz / 30MHz~25GHz (down 20dBc)



Tx 2440MHz / Reference Level



Tx 2440MHz / 30MHz~25GHz (down 20dBc)



Tx 2480MHz / Reference Level



Tx 2480MHz / 30MHz~25GHz (down 20dBc)



4 Receiver Test Results

4.1 Conducted Emissions

4.1.1 Limit of Conducted Emissions

Conducted Emissions Limit		
Frequency Emission (MHz)	**Quasi-Peak**	**Average**
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50
Note 1: * Decreases with the logarithm of the frequency.		

4.1.2 Test Procedures

5. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
6. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
7. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
8. This measurement was performed with AC 120V/60Hz

4.1.3 Test Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

4.1.4 Test Result of Conducted Emissions

Modulation Mode	GFSK	Test Freq. (MHz)	2402
Power Phase	Line	Test Configuration	1



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.195	26.30	53.80	-27.50	16.76	9.50	0.04	Average
2	0.195	35.29	63.80	-28.51	25.75	9.50	0.04	QP
3	0.279	33.95	50.85	-16.90	24.36	9.55	0.04	Average
4	0.279	34.59	60.85	-26.26	25.00	9.55	0.04	QP
5@	0.561	38.58	46.00	-7.42	28.99	9.55	0.04	Average
6	0.561	39.45	56.00	-16.55	29.86	9.55	0.04	QP
7	1.123	34.49	46.00	-11.51	24.96	9.49	0.04	Average
8	1.123	35.10	56.00	-20.90	25.57	9.49	0.04	QP
9	2.246	25.16	46.00	-20.84	15.49	9.61	0.06	Average
10	2.246	26.16	56.00	-29.84	16.49	9.61	0.06	QP
11	18.820	23.59	50.00	-26.41	13.63	9.71	0.25	Average
12	18.820	30.28	60.00	-29.72	20.32	9.71	0.25	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

Modulation Mode	GFSK	Test Freq. (MHz)	2402
Power Phase	Neutral	Test Configuration	1



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.282	34.63	50.76	-16.13	25.02	9.57	0.04	Average
2	0.282	35.36	60.76	-25.40	25.75	9.57	0.04	QP
3@	0.561	38.63	46.00	-7.37	29.00	9.59	0.04	Average
4	0.561	39.49	56.00	-16.51	29.86	9.59	0.04	QP
5	1.123	34.58	46.00	-11.42	24.89	9.65	0.04	Average
6	1.123	35.24	56.00	-20.76	25.55	9.65	0.04	QP
7	2.249	23.80	46.00	-22.20	14.19	9.55	0.06	Average
8	2.249	24.46	56.00	-31.54	14.85	9.55	0.06	QP
9	4.525	11.39	46.00	-34.61	1.51	9.71	0.17	Average
10	4.525	22.75	56.00	-33.25	12.87	9.71	0.17	QP
11	18.721	24.87	50.00	-25.13	14.91	9.71	0.25	Average
12	18.721	32.16	60.00	-27.84	22.20	9.71	0.25	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

Modulation Mode	GFSK	Test Freq. (MHz)	2402
Power Phase	Line	Test Configuration	2



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.192	29.62	53.93	-24.31	20.08	9.50	0.04	Average
2	0.192	39.27	63.93	-24.66	29.73	9.50	0.04	QP
3	0.358	20.40	48.78	-28.38	10.78	9.58	0.04	Average
4@	0.358	35.51	58.78	-23.27	25.89	9.58	0.04	QP
5	2.121	21.25	46.00	-24.75	11.57	9.63	0.05	Average
6	2.121	24.41	56.00	-31.59	14.73	9.63	0.05	QP
7	4.696	21.41	46.00	-24.59	11.73	9.51	0.17	Average
8	4.696	29.13	56.00	-26.87	19.45	9.51	0.17	QP
9	14.907	25.59	50.00	-24.41	15.67	9.69	0.23	Average
10	14.907	31.71	60.00	-28.29	21.79	9.69	0.23	QP
11	20.056	24.73	50.00	-25.27	14.76	9.71	0.26	Average
12	20.056	29.95	60.00	-30.05	19.98	9.71	0.26	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

Modulation Mode	GFSK	Test Freq. (MHz)	2402
Power Phase	Neutral	Test Configuration	2



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1@	0.363	29.75	48.65	-18.90	20.16	9.55	0.04	Average
2	0.363	35.94	58.65	-22.71	26.35	9.55	0.04	QP
3	1.060	19.51	46.00	-26.49	9.81	9.66	0.04	Average
4	1.060	22.69	56.00	-33.31	12.99	9.66	0.04	QP
5	2.121	21.48	46.00	-24.52	11.89	9.54	0.05	Average
6	2.121	25.29	56.00	-30.71	15.70	9.54	0.05	QP
7	4.549	20.03	46.00	-25.97	10.15	9.71	0.17	Average
8	4.549	28.36	56.00	-27.64	18.48	9.71	0.17	QP
9	14.828	25.01	50.00	-24.99	15.09	9.69	0.23	Average
10	14.828	31.21	60.00	-28.79	21.29	9.69	0.23	QP
11	19.740	23.62	50.00	-26.38	13.64	9.72	0.26	Average
12	19.740	28.99	60.00	-31.01	19.01	9.72	0.26	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

4.2 Radiated Emissions

4.2.1 Limit of Radiated Emissions

Restricted Band Emissions Limit			
Frequency Range (MHz)	**Field Strength (uV/m)**	**Field Strength (dBuV/m)**	**Measure Distance (m)**
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit
Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

4.2.2 Test Procedures

1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:

1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=3MHz and RMS detector is for average measured value of radiated emission above 1GHz.

4.2.3 Test Setup

Radiated Emissions below 1 GHz



Radiated Emissions above 1 GHz



4.2.4 Receiver Emissions (Below 1GHz)

Modulation	GFSK	**Test Freq. (MHz)**	2402
Polarization	Horizontal	**Test Configuration**	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	124.09	35.39	43.50	-8.11	45.92	-10.53	Peak	---	---
2	158.04	33.42	43.50	-10.08	41.73	-8.31	Peak	---	---
3	215.27	36.91	43.50	-6.59	47.89	-10.98	Peak	---	---
4	249.22	42.82	46.00	-3.18	52.21	-9.39	QP	100	115
5	374.35	34.87	46.00	-11.13	40.93	-6.06	Peak	---	---
6	874.87	38.07	46.00	-7.93	34.83	3.24	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical	Test Configuration	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	39.70	36.85	40.00	-3.15	45.63	-8.78	QP	100	17
2	124.09	40.42	43.50	-3.08	50.95	-10.53	QP	100	89
3	249.22	42.55	46.00	-3.45	51.94	-9.39	Peak	---	---
4	374.35	31.40	46.00	-14.60	37.46	-6.06	Peak	---	---
5	533.43	36.98	46.00	-9.02	39.64	-2.66	Peak	---	---
6	624.61	38.58	46.00	-7.42	39.29	-0.71	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Horizontal	Test Configuration	2



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	124.09	32.74	43.50	-10.76	43.27	-10.53	Peak	---	---
2	249.22	39.21	46.00	-6.79	48.60	-9.39	Peak	---	---
3	374.35	36.29	46.00	-9.71	42.35	-6.06	Peak	---	---
4	499.48	33.55	46.00	-12.45	36.91	-3.36	Peak	---	---
5	624.61	40.07	46.00	-5.93	40.78	-0.71	Peak	---	---
6	874.87	37.71	46.00	-8.29	34.47	3.24	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical	Test Configuration	2



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	51.42	34.91	40.00	-5.09	43.16	-8.25	QP	103	83
2	221.09	39.44	46.00	-6.56	50.33	-10.89	Peak	---	---
3	374.35	31.90	46.00	-14.10	37.96	-6.06	Peak	---	---
4	499.48	35.77	46.00	-10.23	39.13	-3.36	Peak	---	---
5	624.61	39.43	46.00	-6.57	40.14	-0.71	Peak	---	---
6	874.87	38.83	46.00	-7.17	35.59	3.24	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

4.2.5 Receiver Emissions (Above 1GHz)

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1067.00	36.98	54.00	-17.02	45.26	-8.28	Average	100	324
2	1067.00	41.07	74.00	-32.93	49.35	-8.28	Peak	100	324
3	1600.00	37.56	54.00	-16.44	42.24	-4.68	Average	160	72
4	1600.00	41.76	74.00	-32.24	46.44	-4.68	Peak	160	72
5	3200.00	29.88	54.00	-24.12	29.33	0.55	Average	165	356
6	3200.00	40.89	74.00	-33.11	40.34	0.55	Peak	165	356

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1067.00	40.12	54.00	-13.88	48.40	-8.28	Average	188	100
2	1067.00	43.19	74.00	-30.81	51.47	-8.28	Peak	188	342
3	1600.00	37.79	54.00	-16.21	42.47	-4.68	Average	388	0
4	1600.00	42.23	74.00	-31.77	46.91	-4.68	Peak	388	0
5	3200.00	30.28	54.00	-23.72	29.73	0.55	Average	100	6
6	3200.00	40.50	74.00	-33.50	39.95	0.55	Peak	100	6

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

5 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website http://www.icertifi.com.tw.

Linkou	**Kwei Shan**	**Kwei Shan Site II**
Tel: 886-2-2601-1640	Tel: 886-3-271-8666	Tel: 886-3-271-8640
No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan, R.O.C.	No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.	No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666
Fax: 886-3-318-0155
Email: ICC_Service@icertifi.com.tw

═END═