



Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

## TEST REPORT

### Ordinance Article 2 paragraph 1 item (19)

Report Reference No.....: CTA26010902101

Compiled by

( position+printed name+signature)...: File administrators Zoey Cao

Supervised by

( position+printed name+signature)...: Project Engineer Ace Chai

Approved by

( position+printed name+signature)...: RF Manager Eric Wang

Date of issue.....: Jan. 26, 2026

Testing Laboratory Name .....: Shenzhen CTA Testing Technology Co., Ltd.

Address .....: Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name .....: EJEK TECHNOLOGY CO.,LTD.

Address .....: No. 106, Zhongshan 3<sup>rd</sup> Rd., Daya Dist., Taichung City 428, Taiwan (R.O.C.)

Test specification .....

Standard .....: Ordinance Article 2 paragraph 1 item (19)

Shenzhen CTA Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTA Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTA Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description .....: BT5.1 Music Bluetooth Module

Trade Mark .....: N/A

Manufacturer .....: Anplus Tech CO.,LTD.

Model/Type reference.....: AI00750

Listed Models .....: N/A

Modulation .....: GFSK

Frequency.....: From 2402MHz-2480MHz

Ratings .....: Input: 5V --- 24mA

Result.....: PASS

## TEST REPORT

Equipment under Test : BT5.1 Music Bluetooth Module

Model /Type : AI00750

Listed Models : N/A

Applicant : EJEK TECHNOLOGY CO.,LTD.

Address : No. 106, Zhongshan 3<sup>rd</sup> Rd., Daya Dist., Taichung City 428, Taiwan  
(R.O.C.)

Manufacturer : Anplus Tech CO.,LTD.

Address : 2F, Building C, No. 44, Qianfeng North Road, Shiji Town, Panyu  
District, Guangzhou, Guangdong Province, China

Test Result:

PASS

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## Contents

|     |                                                       |    |
|-----|-------------------------------------------------------|----|
| 1   | SUMMARY.....                                          | 4  |
| 1.1 | Test Standards .....                                  | 4  |
| 1.2 | Test Description .....                                | 4  |
| 1.3 | TEST ENVIRONMENT .....                                | 5  |
| 1.4 | Measurement Uncertainty .....                         | 5  |
| 2   | GENERAL INFORMATION.....                              | 6  |
| 2.1 | General Remarks .....                                 | 6  |
| 2.2 | Environmental conditions .....                        | 6  |
| 2.3 | General Description of EUT.....                       | 6  |
| 2.4 | Description of Test Modes.....                        | 7  |
| 2.5 | Measurement Instruments List.....                     | 7  |
| 2.6 | Table for Parameters of Test Software Setting .....   | 8  |
| 2.7 | Description of Test Modes.....                        | 8  |
| 2.8 | Test Voltage .....                                    | 8  |
| 3   | Test conditions and Results .....                     | 9  |
| 3.1 | Frequency Error .....                                 | 9  |
| 3.2 | Antenna Output Power and Output Power Tolerance ..... | 10 |
| 3.3 | Occupied Bandwidth and Spreading Bandwidth .....      | 11 |
| 3.4 | Unwanted Emission Strength .....                      | 12 |
| 3.5 | Secondary Radiated Emission Strength.....             | 13 |
| 3.6 | Construction Protection Method .....                  | 14 |
| 3.7 | Interference Prevention Function .....                | 15 |
| 3.8 | Carrier Sensing Function.....                         | 16 |
| 4   | Test Setup Photos of the EUT .....                    | 17 |
| 5   | Photos of the EUT .....                               | 18 |

## 1 SUMMARY

### 1.1 Test Standards

The tests were performed according to following standards:

[ARIB STD-T66](#): Second-Generation Low-Power Data Communication System/Wireless LAN System  
[MIC Notice No.88 Appendix No. 43](#): 2.4 GHz band wide-band low-power data communication system

### 1.2 Test Description

| ARIB STD-T66        |                                                    |          |
|---------------------|----------------------------------------------------|----------|
| CLAUSE              | Description of Test (Transmitter Parameters)       | Result   |
| 3.2 (2)             | Antenna Power                                      | Complies |
| 3.2 (3)             | Tolerances for Antenna Power                       | Complies |
| 3.2 (4)             | Frequency Tolerance                                | Complies |
| 3.2 (5)             | Transmission Rate                                  | Complies |
| 3.2 (7)             | Occupied Frequency Bandwidth                       | Complies |
| 3.2 (8)             | Spread Bandwidth                                   | Complies |
| 3.2 (11)            | Dwell Time                                         | N/A      |
| 3.2 (6)             | Spurious Emissions                                 | Complies |
| 3.6                 | Transmission Antenna Gain (EIRP Antenna Power)     | N/A      |
| 3.6                 | Transmission Radiated Angle Width (3dB Beam width) | N/A      |
| /                   | Interference prevention function                   | Complies |
| /                   | Carrier Sensing function                           | N/A      |
| Receiver Parameters |                                                    |          |
| 3.3 (1)             | Secondary Radiated Emissions                       | Complies |

Note: (1) N/A is an abbreviation for Not Applicable.  
 (2) N/T means this test item is not tested.

Note: 1: "N/A" denotes test is not applicable in this Test Report

2: MIC Public Notice 88:2004, annex 1 and annex 43

3: MIC Ordinance Regulating Radio Equipment Section 4.17 of Article 49.20

4: Referenced in the standard ARIB STD-T66

### 1.3 TEST ENVIRONMENT

#### 1.3.1 Address of the test laboratory

**Shenzhen CTA Testing Technology Co., Ltd.**

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

#### 1.3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

**Shenzhen CTA Testing Technology Co., Ltd.**

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

#### 1.3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

**FCC-Registration No.: 517856      Designation Number: CN1318**

Shenzhen CTA Testing Technology Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

**A2LA-Lab Cert. No.: 6534.01**

Shenzhen CTA Testing Technology Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2

### 1.4 Measurement Uncertainty

For the test methods, according to the present document, the measurement uncertainty figures shall be calculated in accordance with TR100028-1 [2] and shall correspond to an expansion factor (coverage factor)  $K=1.96$  or  $K=2$  (which provide confidence levels of respectively 95% and 95.5% in the case where the distributions characterizing the actual measurement uncertainties are normal).

| Parameter                           | Uncertainty              |
|-------------------------------------|--------------------------|
| Frequency error / 99%&90% bandwidth | $\pm 1.62 \cdot 10^{-6}$ |
| Total RF power, conducted           | $\pm 0.8\text{dB}$       |
| Spurious emissions, conducted       | $\pm 0.8\text{dB}$       |
| DC and low frequency voltages       | $\pm 0.05\%$             |
| Humidity                            | $\pm 5\%$                |
| Temperature                         | $\pm 1^\circ\text{C}$    |

## 2 GENERAL INFORMATION

### 2.1 General Remarks

|                                |   |               |
|--------------------------------|---|---------------|
| Date of receipt of test sample | : | Jan. 09, 2026 |
| Testing commenced on           | : | Jan. 09, 2026 |
| Testing concluded on           | : | Jan. 26, 2026 |

### 2.2 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

|         |                    |          |
|---------|--------------------|----------|
| Voltage | Normal Voltage     | DC 5.00V |
|         | High Voltage       | DC 5.50V |
|         | Low Voltage        | DC 4.50V |
| Other   | Normal Temperature | 25°C     |
|         | Relative Humidity  | 55 %     |
|         | Air Pressure       | 989 hPa  |

### 2.3 General Description of EUT

|                       |                                                                      |
|-----------------------|----------------------------------------------------------------------|
| Product Name:         | BT5.1 Music Bluetooth Module                                         |
| Model/Type reference: | AI00750                                                              |
| Power supply:         | Input: 5V $\approx$ 24mA                                             |
| Hardware version:     | V1.0                                                                 |
| Software version:     | V1.0                                                                 |
| Testing sample:       | CTA260109021-1# (Engineer sample)<br>CTA260109021-2# (Normal sample) |
| Bluetooth BLE         |                                                                      |
| Supported type:       | Bluetooth for low Energy                                             |
| Modulation:           | GFSK                                                                 |
| Operation frequency:  | 2402MHz to 2480MHz                                                   |
| Channel number:       | 40                                                                   |
| Channel separation:   | 2 MHz                                                                |
| Rated power           | 1.0 mW                                                               |
| Antenna type:         | PCB antenna                                                          |
| Antenna gain:         | 1.0 dBi                                                              |

Note: For more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

## 2.4 Description of Test Modes

The EUT has been tested under typical operating condition. The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing.

Operation Frequency List BLE:

| Channel | Frequency (MHz) |
|---------|-----------------|
| 00      | 2402            |
| 01      | 2404            |
| 02      | 2406            |
| ⋮       | ⋮               |
| 19      | 2440            |
| ⋮       | ⋮               |
| 37      | 2476            |
| 38      | 2478            |
| 39      | 2480            |

Note: Test performed at the lowest/middle/highest frequencies selected in the list above for EUT supported while working on specified mode.

## 2.5 Measurement Instruments List

| Item | Test Equipment          | Manufacturer | Model No. | Equipment No. | Cal. Institution | Calibration Date | Calibration Due Date |
|------|-------------------------|--------------|-----------|---------------|------------------|------------------|----------------------|
| 1    | Spectrum Analyzer       | Agilent      | N9020A    | CTA-301       | LISAI            | 2025/07/30       | 2026/07/29           |
| 2    | Vector Signal generator | Agilent      | N5182A    | CTA-305       | LISAI            | 2025/07/30       | 2026/07/29           |
| 3    | Spectrum analyzer       | R&S          | FSV40-N   | CTA-344       | LISAI            | 2025/05/17       | 2026/05/16           |
| 4    | Power Meter             | R&S          | NRVS      | CTA-354       | LISAI            | 2025/07/30       | 2026/07/29           |
| 5    | DC Power Supply         | Agilent      | LW-K3010D | CTA-033       | LISAI            | 2025/07/30       | 2026/07/29           |
| 6    | Oscilloscope            | Tektronix    | TDS3052   | CTA-010       | LISAI            | 2025/07/30       | 2026/07/29           |
| 7    | Automatic control unit  | Tonscend     | JS0806-2  | CTA-351       | LISAI            | 2025/07/30       | 2026/07/29           |

Cal. Institution: LiSai-Guangzhou LiSai Calibration and Testing Co.,LTD.

Calibration by the calibration agencies listed in the table correspond to paragraph 4 (ii) (c) of Article 24-2 in the Radio Law".

☐ (a) Calibration conducted by the National Institute of Information and Communications Technology (NICT) or a designated calibration agency under Article 102-18-1 of the Radio Act.

☐ (b) Calibration conducted based on the regulations of Article 135 or 144 of the Measurement Act.

☒ (c) Calibration conducted in foreign countries, which is equivalent to calibration conducted by the NICT or a designated calibration agency under Article 102-18-1 of the Radio Act.

☐ (d) Calibration, etc. conducted by using measuring instruments and other facilities listed at the bottom of appended table 3 of the Radio Act, which is to have been calibrated as described in (a) through (c) above.

## 2.6 Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters:

| Test Software Version | FCC assist 1.0.2.2 |         |         |
|-----------------------|--------------------|---------|---------|
| Frequency             | 2402MHz            | 2440MHz | 2480MHz |
| Bluetooth             | Default            | Default | Default |

## 2.7 Description of Test Modes

| Tested channel, Frequency and Modulation Information |         |             |
|------------------------------------------------------|---------|-------------|
| CH0                                                  | 2402MHz | GFSK(1Mbps) |
| CH19                                                 | 2440MHz | GFSK(1Mbps) |
| CH39                                                 | 2480MHz | GFSK(1Mbps) |

Note: According exploratory test, EUT has maximum output power for GFSK modulation, All the test modes were tested, but only the worst case was recorded in this report.

## 2.8 Test Voltage

### POWER SUPPLY VOLTAGE FLUCTUATION TEST

| Voltage Fluctuation Test | Normal Voltage | High Voltage +10% of Normal Voltage | Low Voltage -10% of Normal Voltage |
|--------------------------|----------------|-------------------------------------|------------------------------------|
| Input To EUT             | DC 5.00V       | DC 5.50V                            | DC 4.50V                           |
| Output To RF Module      | DC 3.30V       | DC 3.336V                           | DC 3.224V                          |
| Voltage Variation (%)    | --             | 1.1                                 | -2.3                               |

Note:

Voltage Variation (%)

= (Output high or Low Voltage - Output Normal Voltage) / Output Normal Voltage \* 100

During the input supply voltage to the EUT from the external power source is varied by +/- 10%, if output voltage had been confirmed that the fluctuation of power supply to the RF circuit of EUT (excluding power source) is equal to or less than +/-1%. Exempt extremely high and low supply voltage condition test, EUT only operated in normal voltage to test all regulations.

During the input supply voltage to the EUT from the external power source is varied by  $\pm 10\%$ , the fluctuation of input voltage to the circuit of RF unit of test equipment is exceed  $\pm 1\%$ . So, all measurement has been conducted by normal and limit voltage.


### **3 Test conditions and Results**

#### **3.1 Frequency Error**

##### **LIMIT**

Tolerance of frequency shall be  $\pm 50 \times 10^{-6}$ .

##### **TEST CONFIGURATION**



##### **TEST PROCEDURE**

The EUT was directly connected to the spectrum analyser and antenna output port as show in the block diagram as TEST CONFIGURATION shows.

EUT Condition: non-modulation

Spectrum Condition:

Frequency: test frequency

Span: 300 KHz

RBW: 10 KHz

VBW: 10 KHz

Sweep time: Auto

Detector mode: Positive peak

Indication mode: max hold

##### **TEST RESULTS**

Please refer to the Appendix RF Test Data for BLE

### 3.2 Antenna Output Power and Output Power Tolerance

#### LIMIT

- $\leq 3 \text{ mW /MHz}$  (FHSS from 2402-2480 MHz)
- $\leq 10 \text{ mW/MHz}$  (OFDM, DSSS from 2400-2483.5 MHz)
- $\leq 10 \text{ mW}$  (other from 2400-2483.5 MHz)


The Output Power Tolerance must be within +20%.

E.i.r.p:

- $\leq 12.14 \text{ dBm}$  (other from 2400-2483.5 MHz)

Note: E.I.R.P will not be applied to the transmission antenna which has a gain of 2.14dBi or less.

#### TEST CONFIGURATION



#### TEST PROCEDURE

- EUT have transmitted continuous maximum power
- Antenna Power Error is definition that actual measure antenna power tolerance within +20% power range that base on manufacturer declare the conducted power density.

#### TEST RESULTS

##### Conducted Antenna Power

Normal Voltage:

| Mode          | Channel (MHz) | Average burst power (dBm) | Output power (mW) | Limit (mW) | Rated output power (mW) | Tolerance (%) | Limit | Result |
|---------------|---------------|---------------------------|-------------------|------------|-------------------------|---------------|-------|--------|
| GFSK (1 Mbps) | 2402          | -2.57                     | 0.5534            | 10         | 1.00                    | -44.66%       | 20%   | Pass   |
|               | 2440          | -2.61                     | 0.5483            | 10         | 1.00                    | -45.17%       |       |        |
|               | 2480          | -2.56                     | 0.5546            | 10         | 1.00                    | -44.54%       |       |        |

Low Voltage:

| Mode          | Channel (MHz) | Average burst power (dBm) | Output power (mW) | Limit (mW) | Rated output power (mW) | Tolerance (%) | Limit | Result |
|---------------|---------------|---------------------------|-------------------|------------|-------------------------|---------------|-------|--------|
| GFSK (1 Mbps) | 2402          | -2.71                     | 0.5358            | 10         | 1.00                    | -46.42%       | 20%   | Pass   |
|               | 2440          | -2.78                     | 0.5272            | 10         | 1.00                    | -47.28%       |       |        |
|               | 2480          | -2.67                     | 0.5408            | 10         | 1.00                    | -45.92%       |       |        |

High Voltage:

| Mode          | Channel (MHz) | Average burst power (dBm) | Output power (mW) | Limit (mW) | Rated output power (mW) | Tolerance (%) | Limit | Result |
|---------------|---------------|---------------------------|-------------------|------------|-------------------------|---------------|-------|--------|
| GFSK (1 Mbps) | 2402          | -2.85                     | 0.5188            | 10         | 1.00                    | -48.12%       | 20%   | Pass   |
|               | 2440          | -2.92                     | 0.5105            | 10         | 1.00                    | -48.95%       |       |        |
|               | 2480          | -2.76                     | 0.5297            | 10         | 1.00                    | -47.03%       |       |        |

Note:


- Test Result: Pass.
- $EIRP = \text{Antenna conducted power} + \text{Antenna gain}$

### 3.3 Occupied Bandwidth and Spreading Bandwidth

#### LIMIT

- Occupied bandwidth: FH  $\leq$  83.5 MHz; OFDM  $\leq$  40 MHz; DS  $\leq$  26 MHz; Others  $\leq$  26 MHz
- Spread Bandwidth:  $\geq$  500 kHz (FH, DS)
- Spread factor  $>5$ .

#### TEST CONFIGURATION



#### TEST PROCEDURE

Setting of SA is following as follow:

RBW: 300 kHz

VBW: 300 kHz

Sweep time: Auto

Sweep Mode: Continuous sweep

Detect mode: Positive peak

Trace mode: Max hold

EUT have transmitted the maximum modulation signal and fixed channelize. SA set to 99% of occupied bandwidth to measure occupied bandwidth.

EUT have transmitted the maximum modulation signal and fixed channelize. SA set to 90% of occupied bandwidth to measure spread bandwidth.

Spread Factor=Spread Bandwidth/modulation rate.

The modulation rate: MR=1.375Mbps for 802.11b

#### TEST RESULTS

Please refer to the Appendix RF Test Data for BLE


### 3.4 Unwanted Emission Strength

#### LIMIT

Permissible mean power of spurious emission of each frequency supplied to a feeder, that is, mean power of spurious emission in the 1 MHz bandwidth at frequency  $f$  other than frequency band used shall be as follows:

- a.  $2,387\text{MHz} \leq f \leq 2,400\text{MHz}$  and  $2,483.5\text{MHz} < f \leq 2,496.5\text{MHz}$  25  $\mu\text{W}$  or less
- b.  $2,387\text{MHz} > f$  and  $2,496.5\text{MHz} < f$  2.5  $\mu\text{W}$  or less

#### TEST CONFIGURATION



#### TEST PROCEDURE

The EUT was directly connected to the spectrum analyser and antenna output port as show in the block diagram as TEST CONFIGURATION shows.

EUT Condition: modulation

Spectrum Condition:

Frequency: 30MHz-12.5GHz

RBW: 1 MHz (30MHz-1GHz), 1 MHz (1GHz-12.5GHz)

VBW: 1 MHz (30MHz-1GHz), 1 MHz (1GHz-12.5GHz)

Sweep time: Auto

Detector mode: Positive peak

Indication mode: max hold

#### TEST RESULTS


Please refer to the Appendix RF Test Data for BLE

### 3.5 Secondary Radiated Emission Strength

#### LIMIT

The limit on secondary emissions radiated from the receiving equipment within which the function of other radio equipment will not be impaired shall be, in terms of the power of a dummy antenna circuit that has the same electrical constant as the receiving antenna, 4nW or less at a frequency below 1 GHz and 20 nW or less at a frequency of 1 GHz or higher as measured using the circuit.

#### TEST CONFIGURATION



#### TEST PROCEDURE

The EUT was directly connected to the spectrum analyser and antenna output port as show in the block diagram as TEST CONFIGURATION shows.

EUT Condition: modulation

Spectrum Condition:

Frequency: 30MHz-12.5GHz

RBW: 100 KHz (30MHz-1GHz), 1MHz (1GHz-12.5GHz)

VBW: 100 KHz (30MHz-1GHz), 1MHz (1GHz-12.5GHz)

Sweep time: Auto

Detector mode: Positive peak

Indication mode: max hold

#### TEST RESULTS

Please refer to the Appendix RF Test Data for BLE


### 3.6 Construction Protection Method

#### REQUIREMENT

The high-frequency section and modulation section of the radio equipment except for the antenna system shall not be capable of being opened easily.

#### CONFIRMATION METHOD

all high-frequency section and modulation section was shiled by metal shield. As follow:



### 3.7 Interference Prevention Function

#### REQUIREMENT

Clarify the one automatically to transmit and to receive identification code with the wireless equipment of the wireless station used in the same premises.

| Item                | Limits         |
|---------------------|----------------|
| Identification code | $\geq 48$ bits |


#### CONFIRMATION METHOD

A communication link was made where the ID code is correct (Identical).

#### TEST PROCEDURE

1. In the case that the EUT has the function of automatically transmitting the identification code: a. Transmit the predetermined identification codes from EUT. b. Check the transmitted identification codes with the demodulator.
2. In the case of receiving the identification code: a. Transmit the predetermined identification codes from the counterpart. b. Check if communication is normal. c. Transmit the other signals than predetermined ID codes from the counterpart. d. check if the EUT stops the transmission, or if it displays that identification codes are different from the predetermined ones.

#### TEST CONFIGURATION



#### TEST RESULTS

PASS

MAC: 2B: E5: 1D: A3: C6: 4E

### 3.8 Carrier Sensing Function

#### LIMIT

| Item          | Limits                                                                                                                                         |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Carrier Sense | Good – EUT stop RF transmission signal after carrier inject to EUT.<br>(On $22.79 + Gr - 20 \cdot \log(f)$ [dBm] (Gr: dBi; f: MHz) or 100mV/m) |

#### INSTRUMENTS SETTING


The following table is the setting of spectrum analyser and receiver.

| Spectrum Parameter | Setting    |
|--------------------|------------|
| Attenuation        | Auto       |
| RB / VB            | 1 MHz      |
| Span               | 0 MHz      |
| Sweep              | Continuous |
| Detector           | Peak       |
| Trigger mode       | Video      |

#### TEST PROCEDURE

- SSG adjusted the frequency as same as the EUT transmitted signal and emitted the absence of modulation from SSG and power level is (On  $22.79 + Gr - 20 \cdot \log(f)$  [dBm] (Gr: dBi; f: MHz). Then turn off the RF signal of SSG.
- EUT have transmitted the maximum modulation signal and fixed channelize.
- Setting of SA is following as: RB: 1MHz / VB: 1MHz / SPAN: 50MHz / AT: 10dB / Ref: 0dBm / Sweep time: Auto / Sweep Mode: Continuous sweep / Detect mode: Positive peak.
- SSG RF Signal On.
- EUT shall be stop the transmitted any signal and SSG RF Signal Off. Then EUT will be continuous transmitted signal.


#### TEST CONFIGURATION






#### TEST RESULTS




Not Applicable.

#### 4 Test Setup Photos of the EUT



## 5 Photos of the EUT





\*\*\*\*\* End of Report \*\*\*\*\*