


NCC

低功率射頻器材型式試驗報告

產品名稱 : TRUE WIRELESS EARPHONES
型號 : AONIC FREE
廠牌 : SHURE
商標 : 
申請者 : Shure Incorporated
申請者地址 : 5800 West Touhy Avenue, Niles, IL 60714-4608, USA
測試標準 : LP0002 (109 年版)
參考法規 : ANSI C63.10-2013
測試結果 : 符合
接收日期 : 2021/6/30
測試日期 : 2021/7/3~2021/7/7

測試工程師 : 
(陳駿豪)
報告審核人 : 
(陳柏均)
報告簽署人 : 
(柯承志)



修訂紀錄

報告編號	版本	描述	發行日期
2106TW0114-T4	1.0	Original Report	2021-07-16

CONTENTS

Description	Page
1. 一般資訊	5
2. 產品描述	6
2.1 產品資訊	6
2.2 產品規格	7
2.3 測試模式	8
2.4 測試配置	9
2.5 測試周邊	10
2.6 操作程序	10
3. 測試設備明細	11
4. 量測不確定度	12
5. 測試結果	13
5.1 電源傳導測試	14
5.1.1 量測方法	14
5.1.2 限制要求	14
5.1.3 測試架構圖	14
5.1.4 電源傳導測試結果	15
5.2 峰值傳導輸出功率	17
5.2.1 量測方法	17
5.2.2 限制要求	17
5.2.3 測試架構圖	17
5.2.4 峰值傳導輸出功率測試結果	18
5.3 天線之要求	20
5.3.1 限制要求	20
5.3.2 天線樣式	20
5.4 帶外發射限制	21
5.4.1 量測方法	21
5.4.2 限制要求	21
5.4.3 測試架構圖	22
5.4.4 帶外輻射測試結果	23
5.5 輻射電場強度	27
5.5.1 量測方法	27
5.5.2 限制要求	27
5.5.3 測試架構圖	28
5.5.4 輻射電場強度測試結果	30

5.6 頻帶邊緣	48
5.6.1 量測方法	48
5.6.2 限制要求	48
5.6.3 測試架構圖	49
5.6.4 頻帶邊緣測試結果	50
5.7. 占用頻寬	58
5.7.1 量測方法	58
5.7.2 限制要求	58
5.7.3 測試架構圖	58
5.7.4 占用頻寬測試結果	59
5.8. 功率頻譜密度	61
5.8.1 量測方法	61
5.8.2 限制要求	61
5.8.3 測試架構圖	61
5.8.4 功率頻譜密度測試結果	62

1. 一般資訊

申請者	Shure Incorporated
申請者地址	5800 West Touhy Avenue, Niles, IL 60714-4608, USA
製造商	Shure Incorporated
製造商地址	5800 West Touhy Avenue, Niles, IL 60714-4608, USA
實驗室	台灣曼瑞檢測科技有限公司
實驗室地址	33377 台灣桃園市龜山區復興二路 38 號
實驗室資訊	1. MRT facility is a FCC registered (Reg. No. 291082) test facility with the site description report on file and is designated by the FCC as an Accredited Test Firm. 2. MRT facility is an IC registered (MRT Reg. No. 21723) test laboratory with the site description on file at Industry Canada. 3. MRT Lab is accredited to ISO 17025 by the Taiwan Accreditation Foundation (TAF Cert. No. 3261) in EMC, Telecommunications and Radio testing for FCC (Designation Number: TW3261), Industry Taiwan, EU and TELEC Rules.
實驗室測試環境條件	溫度 (°C) : 20-35 / 濕度 (%RH) : 30-65

2. 產品描述

2.1 產品資訊

產品名稱	TRUE WIRELESS EARPHONES
產品型號	AONIC FREE
頻率範圍	2402~2480MHz
規格	Bluetooth Dual Mode: V5.1
調變模式	GFSK
待測物電壓	DC 3.7V (by battery)
最大峰值輸出功率	10.663dBm
配件	
充電盒	Brand: SHURE M/N: ITW1
USB Cable	Brand: Perfect Fortune Electric Wire & Cable (Shenzhen) Co., Ltd. M/N:122331440002 Length: 0.2m

2.2 產品規格

Type of modulation	GFSK
Data Rate	1Mbps(GFSK)

Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2404 MHz	02	2406 MHz
03	2408 MHz	04	2410 MHz	05	2412 MHz
06	2414 MHz	07	2416 MHz	08	2418 MHz
09	2420 MHz	10	2422 MHz	11	2424 MHz
12	2426 MHz	13	2428 MHz	14	2430 MHz
15	2432 MHz	16	2434 MHz	17	2436 MHz
18	2438 MHz	19	2440 MHz	20	2442 MHz
21	2444 MHz	22	2446 MHz	23	2448 MHz
24	2450 MHz	25	2452 MHz	26	2454 MHz
27	2456 MHz	28	2458 MHz	29	2460 MHz
30	2462 MHz	31	2464 MHz	32	2466 MHz
33	2468 MHz	34	2470 MHz	35	2472 MHz
36	2474 MHz	37	2476 MHz	38	2478 MHz
39	2480 MHz	N/A	N/A	N/A	N/A

2.3 測試模式


Test Mode	Mode 1: 發射器- 1Mbps(LE)
	Mode 2: 發射器- 2Mbps(LE)
	Mode 3: 接收機- 1Mbps(LE)

Note:

1. 經初測驗證過，1GHz 以下的 Mode 1 & Mode 2 並無明顯差異，故僅檢附最差狀況之 Mode1。

2.4 測試配置

待測物測試配置圖



Signal Cable Type		Signal Cable Description
A	Signal Cable(Dupont Line)	Non-shielded, 0.2m (Brand: Tun-Hwa , M/N: 0.2m)
B	USB Cable	Shielded, 1.8m (Brand: QUALCOMM , M/N: TRBI200)
C	USB Mouse Cable	Shielded, 1.6m

2.5 測試周邊

待測裝置測試時，其搭配系統測試時之週邊裝置包括如下：

No.	周邊名稱	廠牌	型號	序號	電源線
1	UART Board	QUALCOMM	TRBI200	N/A	N/A
2	Notebook PC	Lenovo	T450	N/A	Non-shielded, 0.8m
3	USB Mouse	Lenovo	M110	N/A	N/A

2.6 操作程序

1.	Turn on the power of all equipment.
2.	Execute “BlueTest3.2.3” program
3.	Configure the test channel and the data rate.
4.	Start test.

3. 測試設備明細

電源傳導 – SR2

儀器名稱	廠牌	型號	財產編號	校正年限	校正有效日期
Two-Line V-Network	R&S	ENV216	MRTTWA00019	1 year	2022/3/23
Two-Line V-Network	R&S	ENV216	MRTTWA00020	1 year	2022/4/28
EMI Test Receiver	R&S	ESR3	MRTTWA00045	1 year	2022/5/25

輻射干擾 – AC1

儀器名稱	廠牌	型號	財產編號	校正年限	校正有效日期
Broadband TRILOG Antenna	SCHWARZBECK	VULB 9162	MRTTWA00001	1 year	2021/10/5
Broadband Horn antenna	SCHWARZBECK	BBHA 9120D	MRTTWA00003	1 year	2022/4/21
Broadband Preamplifier	SCHWARZBECK	BBV 9718	MRTTWA00005	1 year	2022/4/21
Signal Analyzer	R&S	FSV40	MRTTWA00007	1 year	2022/3/23
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2022/3/24

傳導量測設備 –SR2

儀器名稱	廠牌	型號	財產編號	校正年限	校正有效日期
EXA Signal Analyzer	KEYSIGHT	N9010A	MRTTWA00012	1 year	2021/10/14
EXA Signal Analyzer	KEYSIGHT	N9010B	MRTTWA00074	1 year	2021/7/14
X-Series USB Peak and Average Power Sensor	KEYSIGHT	U2021XA	MRTTWA00015	1 year	2022/3/24

EMI 測試軟體

軟體名稱	廠牌	版本
e3	Audix	9.160520a
EMI	Quietek	V3

4. 量測不確定度

電源傳導量測-電源線 (Conducted Emission- Power Line)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 0.15MHz~30MHz: $\pm 2.53\text{dB}$
輻射干擾量測 (Radiated Spurious Emission)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 9kHz~30MHz: $\pm 3.92\text{dB}$ 30MHz~1GHz: $\pm 4.25\text{dB}$ 1GHz~18GHz: $\pm 4.40\text{dB}$ 18GHz~40GHz: $\pm 4.45\text{dB}$
頻率誤差量測 (Frequency Error)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 78.4\text{Hz}$
傳導功率量測 (Conducted Power)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 0.84\text{dB}$
傳導干擾量測 (Conducted Spurious Emission)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 2.65\text{ dB}$
佔用頻寬量測 (Occupied Bandwidth)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 3.3%
溫度 / 濕度 (Temp. / Humidity)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 0.82^\circ\text{C}/ \pm 3\%$
直流電源 (DC Voltage)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 0.3\%$

5. 測試結果


產品名稱 **TRUE WIRELESS EARPHONES**
 型號 **AONIC FREE**

法規章節	量測項目	限制值	測試結果	測試數據
3.3	電源傳導	低功率射頻器材技術規範 3.3 節	符合	第 5.1 章節
4.10.1.2	峰值傳導輸出功率	$\leq 30.00\text{dBm}$	符合	第 5.2 章節
4.10.1.3	天線之要求	低功率射頻器材技術規範 4.10.1.3 節	符合	第 5.3 章節
4.10.1.5	帶外發射限制	$\leq 20\text{dBc(Peak)}$	符合	第 5.4 章節
3.6	輻射電場強度	低功率射頻器材技術規範 3.6 節	符合	第 5.5 章節
3.5	頻帶邊緣	$\leq 74\text{dBuV/m(Peak)}$ $\leq 54\text{dBuV/m(Average)}$	符合	第 5.6 章節
4.10.1.6(2)(A)	占用頻寬	$\geq 500\text{KHz}$	符合	第 5.7 章節
4.10.1.6(2)(B)	功率頻譜密度	$\leq 8\text{dBm}$	符合	第 5.8 章節

備註：符合性的判定是基於測試結果符合規範的限制值或客戶的宣告要求，測試結果的判定是不考慮測量不確定度的值。

5.1.4 電源傳導測試結果

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-03
Factor	CE_ENV216-L1 (Filter ON)	Temp. / Humidity	25.5°C / 48%
Polarity	Line1	Site / Test Engineer	SR2 / Jay
Test Mode	BLE_TX_1Mbps_CH19	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	0.154	28.84	9.61	38.45	-27.30	65.75	QP
2	0.154	12.75	9.61	22.36	-33.40	55.75	Average
3	0.199	25.37	9.61	34.99	-28.64	63.63	QP
4	0.199	8.79	9.61	18.40	-35.23	53.63	Average
5	0.510	16.40	9.63	26.03	-29.97	56.00	QP
6	0.510	10.70	9.63	20.33	-25.67	46.00	Average
7	1.500	12.72	9.67	22.39	-33.61	56.00	QP
8	1.500	8.26	9.67	17.94	-28.06	46.00	Average
9	3.354	6.19	9.71	15.90	-40.10	56.00	QP
10	3.354	-0.04	9.71	9.67	-36.33	46.00	Average
11	* 17.410	26.33	9.95	36.28	-23.72	60.00	QP
12	* 17.410	17.99	9.95	27.94	-22.06	50.00	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-03
Factor	CE_ENV216-N (Filter ON)	Temp. / Humidity	25.5°C / 48%
Polarity	Neutral	Site / Test Engineer	SR2 / Jay
Test Mode	BLE_TX_1Mbps_CH19	Test Voltage	By Notebook PC



No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	0.150	31.95	9.62	41.57	-24.43	66.00	QP
2	0.150	12.69	9.62	22.31	-33.69	56.00	Average
3	0.213	24.36	9.61	33.97	-29.11	63.09	QP
4	0.213	5.64	9.61	15.26	-37.83	53.09	Average
5	0.519	15.46	9.63	25.09	-30.91	56.00	QP
6	0.519	10.15	9.63	19.78	-26.22	46.00	Average
7	1.495	11.59	9.68	21.27	-34.73	56.00	QP
8	1.495	6.52	9.68	16.20	-29.80	46.00	Average
9	2.940	5.10	9.71	14.81	-41.19	56.00	QP
10	2.940	2.61	9.71	12.32	-33.68	46.00	Average
11	* 15.651	26.48	9.98	36.46	-23.54	60.00	QP
12	* 15.651	20.75	9.98	30.73	-19.27	50.00	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).

5.2 峰值傳導輸出功率

5.2.1 量測方法

待測物之天線埠經由適當之衰減直接連至頻譜分析儀RF輸入端，設定頻譜分析儀之解析度頻寬大於6dB發射頻寬或使用峰值功率表。除使用上述測量方式外，並得使用以最大傳導輸出功率作為測量方式。

5.2.2 限制要求


操作於2400-2483.5 MHz之跳頻或數位調變的發射器材與5725-5850 MHz之跳頻發射器材：1W(含)以下，當跳頻系統符合國家通訊傳播委員會低功率射頻器材技術規範之第4.10.1.6(1)(A)(a)節，其限制值為0.125 W(含)以下。

若用於非固定式點對點操作時，若其發射天線之方向性增益超過6dBi，應依所超過之dB數等量降低峰值輸出功率。如用於固定式點對點(註)操作時，應符合下列情形之一：

(1)操作於2400-2483.5兆赫(MHz)者，其發射天線之方向性增益超過6dBi，應於每超過3dB降低1dB之峰值輸出功率。

(2) 操作於5725-5850兆赫(MHz)者，其發射天線之方向性增益超過6dBi，不需降低峰值輸出功率。

5.2.3 測試架構圖




5.2.4 峰值傳導輸出功率測試結果

待測物名稱	TRUE WIRELESS EARPHONES	測試日期	2021/7/3
待測物型號	AONIC FREE	溫度 / 濕度	23°C / 55%
測試場地 / 測試工程師	SR2 / Eric		


Test Mode	Channel No.	Frequency (MHz)	Peak Power (dBm)	Limit (dBm)
LE(1Mbps)	00	2402	10.546	< 30
LE(1Mbps)	19	2440	10.468	< 30
LE(1Mbps)	39	2480	10.475	< 30
LE(2Mbps)	00	2402	10.663	< 30
LE(2Mbps)	19	2440	10.519	< 30
LE(2Mbps)	39	2480	10.469	< 30

備 註： 此量測值已含線材損耗(Cable Loss=1dB)。


CH00 (2402MHz) LE(1Mbps)




CH19 (2440MHz) LE(1Mbps)




CH78 (2480MHz) LE(1Mbps)




CH00 (2402MHz) LE(2Mbps)



CH19 (2440MHz) LE(2Mbps)



CH78 (2480MHz) LE(2Mbps)



5.3 天線之要求

5.3.1 限制要求

依據國家通訊傳播委員會低功率射頻器材技術規範之第4.10.1.4節規定，天線之規格可不受下述規定之限制。

低功率射頻器材之發射機或收發信機所使用之天線，應為全固定、半固定式或以獨特之耦合(unique coupling)方式連接機體。製造者可設計供使用者因損壞而替換之天線，但不得設計或使用原認證以外之天線或可供引接各類電纜之標準天線插座或電氣連接頭，如：BNC、F type、N type、M type、UG type、RCA、SMA、SMB...等及其他各類工業或通訊標準接頭。

5.3.2 天線樣式

此其天線為 Monopole Antenna Type，(檢附天線規格書)

Antenna List

No.	Brand	Part No.	Peak Gain
1	SHURE	31AC20900C02	-0.82dBi

5.4 帶外發射限制

5.4.1 量測方法

待測物之天線埠經由適當之衰減直接連至頻譜分析儀 RF 輸入端：


- (1) 頻率掃描範圍足以檢測頻帶內的發射波峰位準以及由受測物產生之最低頻率到第 10 次諧波的所有混附發射，通常需要分幾段以涵蓋全部頻率範圍。
- (2) 解析頻寬為 100 kHz，視訊頻寬不小於解析頻寬。
- (3) 掃描時間為自動，檢波功能為峰值，訊號軌跡為最大保留(Max Hold)。
- (4) 將標記設定於任何欲紀錄之波峰上，所顯示之位準值必須符合指定之限制值。

5.4.2 限制要求

使用頻帶範圍外之任意 100 千赫 (kHz)內，發射器所產生的射頻功率相較於使用頻帶範圍中包含最高所需功率之 100 千赫 (kHz)內的射頻功率，衰減值限制如下：


- (1) 輸出功率以低功率射頻器材技術規範附件二之峰值輸出功率方式量測者，至少須衰減 20 dB，可使用射頻傳導或輻射方式測量。
- (2) 輸出功率以數位調變技術系統之最大傳導輸出功率量測方式者，至少須衰減 30 dB。
- (3) 若落於禁用頻段之輻射發射，應符合低功率射頻器材技術規範第 3.6 節之規定。

5.4.3 測試架構圖




5.4.4 帶外輻射測試結果


CH00 (2402MHz) LE(1Mbps)




CH00 (2402MHz) LE(1Mbps)




CH00 (2402MHz) LE(1Mbps)




CH00 (2402MHz) LE(1Mbps)




CH19 (2440MHz) LE(1Mbps)




CH19 (2440MHz) LE(1Mbps)




CH19 (2440MHz) LE(1Mbps)




CH19 (2440MHz) LE(1Mbps)




CH39 (2480MHz) LE(1Mbps)




CH39 (2480MHz) LE(1Mbps)




CH39 (2480MHz) LE(1Mbps)




CH39 (2480MHz) LE(1Mbps)




CH00 (2402MHz) LE(2Mbps)




CH00 (2402MHz) LE(2Mbps)




CH00 (2402MHz) LE(2Mbps)




CH00 (2402MHz) LE(2Mbps)




CH19 (2440MHz) LE(2Mbps)




CH19 (2440MHz) LE(2Mbps)




CH19 (2440MHz) LE(2Mbps)




CH19 (2440MHz) LE(2Mbps)




CH39 (2480MHz) LE(2Mbps)




CH39 (2480MHz) LE(2Mbps)



CH39 (2480MHz) LE(2Mbps)



CH39 (2480MHz) LE(2Mbps)



5.5 輻射電場強度

5.5.1 量測方法

待測物置於非導體桌面（落地型產品置於地上），受測物使用交流電源時，將其與任何配件設備之電源線連接至位於旋轉桌的交流電源。受測物使用電池時，測試時應裝置新電池或充電完全的電池。受測物與配件設備之電源線無須束綁，桌面上受測設備的所有電源線由桌子的後緣垂下沿旋轉桌表面接至交流插座。落地型設備的交流電源線可以方便的型態走線。桌面可 360 度旋轉，接收天線置於距待測物 3m 距離，高度可在 1 至 4 公尺間變動，以量測待測物之最大輻射電場強度，接收天線並應於水平及垂直極化方向各量測一次。（待測物擺設方式根據 ANSI C63.10-2013 版本，待測物放置桌中心，1G 以下擺設高度為 80cm/1G 以上擺設高度為 150cm）

- (1) 任一頻率小於或等於 1000 MHz 之訊號,使用 CISPR 準峰值檢波器
- (2) 任一頻率大於 1000 MHz 之訊號，使用平均值檢波器測量，當規定之發射限制值為平均值時(含 1000 MHz 以下)，受測訊號藉由峰值檢波器(RBW:1MHz,VBW:3MHz)所測量之峰值，亦須符合峰值發射限制值，其峰值發射限制值為最大容許平均值加 20 dB。

備註：若為手持式或穿戴式之裝置，需對其三個正交軸的方位評估測試，並記錄最差的數值。

5.5.2 限制要求


其電場強度不得超過下表之限值，且其不必要之發射皆不得大於主波發射強度。各頻段重疊處，以較嚴格之限制值為準。

頻率(f) (MHz)	電場強度 (微伏特/公尺, $\mu\text{V/m}$)	測距 (公尺)
$0.009 \leq f \leq 0.490$	$2400/f(\text{kHz})$	300
$0.490 < f \leq 1.705$	$24000/f(\text{kHz})$	30
$1.705 < f < 30$	30	30
$30 \leq f \leq 88$	100	3
$88 < f \leq 216$	150	3
$216 < f \leq 960$	200	3
$960 < f$	500	3


上表規定之電場強度，發射頻率在 9 kHz~90 kHz、110 kHz~490 kHz 及 1000MHz 以上者，其量測應以平均值檢波器為基準，且須符合低功率射頻器材技術規範第 6.14.節之規定；其他發射頻率，應以 CISPR 準峰值(quasi-peak) 檢波器測量；非以上表所指定之距離測量時，應符合第 6.5 節之規定，而輻射發射之量測頻率範圍須符合低功率射頻器材技術規範第 6.12 節之規定。

5.5.3 測試架構圖


Under 30MHz Test Setup




Under 1GHz Test Setup



1GHz ~ 18GHz Test Setup:




18GHz ~25GHz Test Setup:



5.5.4 輻射電場強度測試結果

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-07
Factor	VULB 9162	Temp. / Humidity	26°C /62%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	BT_TX_DH5_CH 39	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	49.220	0.05	22.01	22.06	-17.94	40.00	100	255	QP
2	105.190	0.44	18.94	19.38	-24.12	43.50	100	340	QP
3	184.520	5.53	18.07	23.60	-19.90	43.50	100	165	QP
4	213.200	10.31	18.93	29.24	-14.26	43.50	100	80	QP
5	249.060	4.80	20.51	25.31	-20.69	46.00	100	115	QP
6	* 731.450	2.69	29.82	32.50	-13.50	46.00	100	190	QP

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-07
Factor	VULB 9162	Temp. / Humidity	26°C /62%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	BT_TX_DH5_CH 39	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	37.110	0.16	20.05	20.22	-19.78	40.00	100	60	QP
2	48.570	0.50	21.98	22.48	-17.52	40.00	100	220	QP
3	98.960	1.42	18.94	20.36	-23.14	43.50	100	140	QP
4	214.480	7.58	18.98	26.57	-16.93	43.50	100	330	QP
5	437.360	1.89	24.68	26.57	-19.43	46.00	100	280	QP
6	* 730.190	1.47	29.80	31.27	-14.73	46.00	100	110	QP

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-07
Factor	VULB 9162	Temp. / Humidity	26°C /62%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	BT_RX_DH5_CH 39	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	49.270	-0.42	22.01	21.60	-18.40	40.00	100	255	QP
2	105.630	2.40	18.92	21.32	-22.18	43.50	100	340	QP
3	184.980	3.69	18.14	21.83	-21.67	43.50	100	165	QP
4	* 213.470	12.07	18.94	31.01	-12.49	43.50	100	80	QP
5	249.660	5.64	20.53	26.17	-19.83	46.00	100	115	QP
6	731.250	0.91	29.81	30.72	-15.28	46.00	100	190	QP

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-07
Factor	VULB 9162	Temp. / Humidity	26°C /62%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	BT_RX_DH5_CH 39	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	37.580	1.93	20.22	22.15	-17.85	40.00	100	60	QP
2	48.720	1.21	21.99	23.19	-16.81	40.00	100	220	QP
3	98.390	1.08	18.81	19.89	-23.61	43.50	100	140	QP
4	* 214.440	8.24	18.98	27.22	-16.28	43.50	100	330	QP
5	437.100	3.83	24.68	28.50	-17.50	46.00	100	280	QP
6	730.080	-0.38	29.80	29.41	-16.59	46.00	100	110	QP

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-07
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	26°C /62%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	BLE_TX_1Mbps_CH 0	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4804.000	41.89	3.60	45.49	-28.51	74.00	150	360	Peak
2	* 7206.000	42.50	11.71	54.22	-19.78	74.00	150	360	Peak
3	9608.000	32.30	15.90	48.20	-25.80	74.00	150	360	Peak

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- No2 is not in restricted band, its limit is 20dBc/30dBc of the fundamental emission level(already evaluated in Section 5.4) or LP0002 Section 3.6 which is higher.(Here, we are using stringent limits:74dBuV/m.)
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-07
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	26°C /62%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	BLE_TX_1Mbps_CH 0	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4804.000	39.03	3.60	42.63	-31.37	74.00	150	360	Peak
2	* 7206.000	38.40	11.71	50.12	-23.88	74.00	150	360	Peak
3	9608.000	31.01	15.90	46.91	-27.09	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-07
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	26°C /62%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	BLE_TX_1Mbps_CH 19	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4880.000	39.32	3.73	43.06	-30.94	74.00	150	360	Peak
2	* 7320.000	40.99	12.22	53.20	-20.80	74.00	150	360	Peak
3	9760.000	31.75	16.16	47.91	-26.09	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-07
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	26°C /62%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	BLE_TX_1Mbps_CH 19	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4880.000	37.46	3.73	41.19	-32.81	74.00	150	360	Peak
2	* 7320.000	36.94	12.22	49.15	-24.85	74.00	150	360	Peak
3	9760.000	31.56	16.16	47.72	-26.28	74.00	150	360	Peak

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-07
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	26°C /62%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	BLE_TX_1Mbps_CH 39	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4960.000	40.28	3.88	44.16	-29.84	74.00	150	360	Peak
2	* 7440.000	37.44	12.75	50.19	-23.81	74.00	150	360	Peak
3	9920.000	32.43	16.43	48.86	-25.14	74.00	150	360	Peak

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-07
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	26°C /62%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	BLE_TX_1Mbps_CH 39	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4960.000	38.48	3.88	42.36	-31.64	74.00	150	360	Peak
2	7440.000	35.37	12.75	48.12	-25.88	74.00	150	360	Peak
3	* 9920.000	32.31	16.43	48.73	-25.27	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-07
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	26°C /62%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	BLE_TX_2Mbps_CH 0	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4804.000	40.40	3.60	44.00	-30.00	74.00	150	360	Peak
2	* 7206.000	41.04	11.71	52.75	-21.25	74.00	150	360	Peak
3	9608.000	31.34	15.90	47.24	-26.76	74.00	150	360	Peak

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-07
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	26°C /62%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	BLE_TX_2Mbps_CH 0	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4804.000	37.13	3.60	40.73	-33.27	74.00	150	360	Peak
2	* 7206.000	37.64	11.71	49.35	-24.65	74.00	150	360	Peak
3	9608.000	29.67	15.90	45.57	-28.43	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-07
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	26°C /62%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	BLE_TX_2Mbps_CH 19	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4880.000	37.52	3.73	41.26	-32.74	74.00	150	360	Peak
2	* 7320.000	39.82	12.22	52.03	-21.97	74.00	150	360	Peak
3	9760.000	31.09	16.16	47.25	-26.75	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-07
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	26°C /62%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	BLE_TX_2Mbps_CH 19	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4880.000	34.68	3.73	38.42	-35.58	74.00	150	360	Peak
2	7320.000	32.40	12.22	44.62	-29.38	74.00	150	360	Peak
3	* 9960.000	32.41	16.49	48.91	-25.09	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-07
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	26°C /62%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	BLE_TX_2Mbps_CH 39	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4960.000	36.81	3.88	40.68	-33.32	74.00	150	360	Peak
2	7440.000	34.87	12.75	47.62	-26.38	74.00	150	360	Peak
3	* 9920.000	31.46	16.43	47.88	-26.12	74.00	150	360	Peak

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-07
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	26°C /62%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	BLE_TX_2Mbps_CH 39	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4960.000	39.57	3.88	43.45	-30.55	74.00	150	360	Peak
2	7440.000	33.80	12.75	46.55	-27.45	74.00	150	360	Peak
3	* 9920.000	32.58	16.43	49.00	-25.00	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-07
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	26°C /62%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	BLE_RX_1Mbps_CH 19	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	1159.906	57.10	-6.07	51.03	-22.97	74.00	150	360	Peak
2	* 1599.250	56.16	-4.57	51.59	-22.41	74.00	150	360	Peak
3	1993.969	42.22	-3.54	38.68	-35.32	74.00	150	360	Peak
4	2399.844	40.61	-2.00	38.61	-35.39	74.00	150	360	Peak
5	2720.188	41.21	-1.67	39.54	-34.46	74.00	150	360	Peak
6	2986.875	45.72	-1.73	44.00	-30.00	74.00	150	360	Peak

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-07
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	26°C /62%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	BLE_RX_1Mbps_CH 19	Test Voltage	By Notebook PC



No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	1159.906	52.91	-6.07	46.84	-27.16	74.00	150	360	Peak
2	* 1599.781	55.04	-4.57	50.48	-23.52	74.00	150	360	Peak
3	1998.750	42.01	-3.52	38.48	-35.52	74.00	150	360	Peak
4	2391.875	49.54	-2.03	47.51	-26.49	74.00	150	360	Peak
5	2591.625	44.32	-1.64	42.68	-31.32	74.00	150	360	Peak
6	3648.281	38.33	0.11	38.44	-35.56	74.00	150	360	Peak

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

5.6 頻帶邊緣

5.6.1 量測方法

待測物置於非導體桌面（落地型產品置於地上），受測物使用交流電源時，將其與任何配件設備之電源線連接至位於旋轉桌的交流電源。受測物使用電池時，測試時應裝置新電池或充電完全的電池。受測物與配件設備之電源線無須束綁，桌面上受測設備的所有電源線由桌子的後緣垂下沿旋轉桌表面接至交流插座。落地型設備的交流電源線可以方便的型態走線。桌面可360度旋轉，接收天線置於距待測物3m距離，高度可在1至4公尺間變動，以量測待測物之最大輻射電場強度，接收天線並應於水平及垂直極化方向各量測一次。（待測物擺設方式根據 ANSI C63.10-2013版，待測物放置桌中心，1G以下擺設高度為80cm/1G以上擺設高度為150cm）

- (1) 任一頻率小於或等於1000 MHz 之訊號,使用CISPR準峰值檢波器
- (2) 任一頻率大於1000 MHz 之訊號，使用平均值檢波器測量，當規定之發射限制值為平均值時(含1000 MHz 以下)，受測訊號藉由峰值檢波器(RBW:1MHz,VBW:3MHz)所測量之峰值，亦須符合峰值發射限制值，其峰值發射限制值為最大容許平均值加20 dB。

備註：若為手持式或穿戴式之裝置，需對其三個正交軸的方位評估測試，並記錄最差的數值。


5.6.2 限制要求

除低功率射頻器材技術規範另有規定外，任何低功率射頻器材之主波皆不得使用下表所列各頻段之頻率低功率射頻器材落於下表所列頻帶內之混附發射，其電場強度必須符合低功率射頻器材技術規範之第3.6節限制規定


頻 率 (MHz)	頻 率 (MHz)	頻 率 (MHz)	頻 率 (MHz)	頻 率 (MHz)
0.090~0.110	25.500~25.700	703.00~748.00	2310.0~2390.0	13250~13400
0.490~0.510	37.475~38.275	758.00~803.00	2483.5~2900.0	14470~14500
2.172~2.198	73.500~75.400	825.00~915.00	3260.0~3267.0	15350~16200
3.013~3.033	108.00~138.00	930.00~1240.0	3332.0~3339.0	17700~21400
4.115~4.198	149.90~150.05	1300.0~1427.0	3345.8~3358.0	22010~23120
5.670~5.690	156.70~156.90	1435.0~1626.5	3500.0~4400.0	23600~24000
6.200~6.300	162.01~167.17	1660.0~1785.0	4500.0~5250.0	31200~31800
8.230~8.400	167.72~173.20	1805.0~1880.0	5350.0~5460.0	36430~36500
12.265~12.600	240.00~285.00	1885.0~1900.0	7250.0~7750.0	38600 以上
13.340~13.430	322.00~335.40	1905.0~1985.0	8025.0~8500.0	
14.965~15.020	399.90~410.00	2010.0~2025.0	9000.0~9200.0	
16.700~16.755	485.00~510.00	2110.0~2170.0	9300.0~9500.0	
19.965~20.020	608.00~614.00	2200.0~2300.0	10600~12700	

5.6.3 測試架構圖

1GHz ~ 18GHz Test Setup:




18GHz ~ 25GHz Test Setup:



5.6.4 頻帶邊緣測試結果

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-05
Factor	BBHA 9120D	Temp. / Humidity	26°C /62%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	BLE_TX_1Mbps_CH 0	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2319.300	45.37	-2.31	43.06	-30.94	74.00	140	250	Peak
2	* 2390.000	47.95	-2.04	45.91	-28.09	74.00	140	250	Peak
3	2402.100	92.91	-1.99	90.92	N/A	N/A	140	250	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-05
Factor	BBHA 9120D	Temp. / Humidity	26°C /62%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	BLE_TX_1Mbps_CH 0	Test Voltage	By Notebook PC




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	2320.800	43.52	-2.30	41.22	-32.78	74.00	100	65	Peak
2		2390.000	42.40	-2.04	40.36	-33.64	74.00	100	65	Peak
3		2401.800	89.81	-1.99	87.82	N/A	N/A	100	65	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-05
Factor	BBHA 9120D	Temp. / Humidity	26°C /62%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	BLE_TX_1Mbps_CH 39	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2479.725	88.90	-1.70	87.20	N/A	N/A	135	250	Peak
2	2483.500	42.19	-1.68	40.50	-33.50	74.00	135	250	Peak
3	* 2488.275	43.30	-1.66	41.64	-32.36	74.00	135	250	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-05
Factor	BBHA 9120D	Temp. / Humidity	26°C /62%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	BLE_TX_1Mbps_CH 39	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2480.000	86.95	-1.70	85.25	N/A	N/A	150	5	Peak
2	2483.500	40.73	-1.68	39.05	-34.95	74.00	150	5	Peak
3	* 2484.625	42.41	-1.68	40.74	-33.26	74.00	150	5	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-05
Factor	BBHA 9120D	Temp. / Humidity	26°C /62%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	BLE_TX_2Mbps_CH 0	Test Voltage	By Notebook PC




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	2381.200	43.04	-2.07	40.97	-33.03	74.00	100	65	Peak
2		2390.000	41.30	-2.04	39.26	-34.74	74.00	100	65	Peak
3		2401.500	89.96	-1.99	87.96	N/A	N/A	100	65	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-05
Factor	BBHA 9120D	Temp. / Humidity	26°C /62%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	BLE_TX_2Mbps_CH 0	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2378.400	45.16	-2.08	43.08	-30.92	74.00	140	250	Peak
2	* 2390.000	46.32	-2.04	44.28	-29.72	74.00	140	250	Peak
3	2401.500	92.63	-1.99	90.64	N/A	N/A	140	250	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-05
Factor	BBHA 9120D	Temp. / Humidity	26°C /62%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	BLE_TX_2Mbps_CH 39	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2479.475	89.14	-1.70	87.44	N/A	N/A	135	250	Peak
2	* 2483.500	46.59	-1.68	44.91	-29.09	74.00	135	250	Peak
3	2484.800	43.00	-1.68	41.32	-32.68	74.00	135	250	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	TRUE WIRELESS EARPHONES	Date of Test	2021-07-05
Factor	BBHA 9120D	Temp. / Humidity	26°C /62%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	BLE_TX_2Mbps_CH 39	Test Voltage	By Notebook PC



No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2479.450	86.97	-1.70	85.27	N/A	N/A	150	5	Peak
2	* 2483.500	45.93	-1.68	44.25	-29.75	74.00	150	5	Peak
3	2486.750	42.67	-1.67	41.00	-33.00	74.00	150	5	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

5.7. 占用頻寬

5.7.1 量測方法


待測物之天線埠經由適當之衰減直接連至頻譜分析儀RF輸入端，頻譜分析儀之設定,參考如下:

- (1) Set RBW = 100 kHz
- (2) VBW $\geq 3 \times$ RBW
- (3) Detector = Peak
- (4) Trace mode = max hold
- (5) Sweep = auto couple

5.7.2 限制要求

6dB頻寬至少應有500kHz。


5.7.3 測試架構圖




5.7.4 占用頻寬測試結果

Test Mode	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Result
LE (1Mbps)	00	2420	0.7204	≥ 0.5	Pass
LE (1Mbps)	19	2440	0.7147	≥ 0.5	Pass
LE (1Mbps)	39	2480	0.7061	≥ 0.5	Pass
LE (2Mbps)	00	2420	1.2160	≥ 0.5	Pass
LE (2Mbps)	19	2440	1.1830	≥ 0.5	Pass
LE (2Mbps)	39	2480	1.2070	≥ 0.5	Pass


CH00 (2402MHz) LE(1Mbps)



CH19 (2440MHz) LE(1Mbps)



CH78 (2480MHz) LE(1Mbps)




CH00 (2402MHz) LE(2Mbps)



CH19 (2440MHz) LE(2Mbps)



CH78 (2480MHz) LE(2Mbps)



5.8. 功率頻譜密度

5.8.1 量測方法

將發射機之天線埠經由適當之衰減直接連至測試儀器。找出發射峰值並擴展於通帶內，設定解析頻寬為3 kHz，視訊頻寬大於解析頻寬，掃描時間為頻率掃描範圍除以3 kHz。所測得之峰值位準必須應小於或等於8 dBm。

若受測裝置之頻譜線間隔小於3 kHz，測量時應將解析頻寬降低以使頻譜線間隔大於3kHz，所測得之數據再藉加總3 kHz 頻帶內所有個別頻譜線之功率(即標準化至3 kHz)以決定是否符合規定。

5.8.2 限制要求


在使用頻率範圍之任意3千赫(kHz)頻寬內，由發射機傳導至天線之峰值發射電功率密度在任意期間內，皆不得大於8dBm。

若用於非固定式點對點操作時，若其發射天線之方向性增益超過6dBi，應依所超過之dB數等量降低峰值輸出功率。如用於固定式點對點(註)操作時，應符合下列情形之一：

(1)操作於2400-2483.5兆赫(MHz)者，其發射天線之方向性增益超過6dBi，應於每超過3dB降低1dB之峰值輸出功率。

(2) 操作於5725-5850兆赫(MHz)者，其發射天線之方向性增益超過6dBi，不需降低峰值輸出功率。


5.8.3 測試架構圖




5.8.4 功率頻譜密度測試結果

Test Mode	Channel No.	Frequency (MHz)	PSD Result (dBm / 3kHz)	Limit (dBm / 3kHz)	Result
LE (1Mbps)	00	2420	-4.679	≤ 8	Pass
LE (1Mbps)	19	2440	-4.556	≤ 8	Pass
LE (1Mbps)	39	2480	-4.633	≤ 8	Pass
LE (2Mbps)	00	2420	-7.500	≤ 8	Pass
LE (2Mbps)	19	2440	-7.586	≤ 8	Pass
LE (2Mbps)	39	2480	-7.691	≤ 8	Pass


CH00 (2402MHz) LE(1Mbps)



CH19 (2440MHz) LE(1Mbps)




CH78 (2480MHz) LE(1Mbps)




CH00 (2402MHz) LE(2Mbps)



CH19 (2440MHz) LE(2Mbps)



CH78 (2480MHz) LE(2Mbps)



The End