TEST REPORT

Test item description:	Hub
Trademark(s):	Klik
Model/Type reference:	Hub-RF-PA
Applicant's name:	Bizzabo Ltd.
Address:	1 Walter Mozes St., Tel-Aviv, Israel, 6789923
Manufacturer:	Inspi Technology Co., Ltd.
Address:	Room 703/726, HuaFeng Yu'An Business Building, District 45 of Ban'An, Shenzhen, China
Prepared By:	Shenzhen CTB Testing Technology Co., Ltd.
Address:	1&2/F., Building A, No.26, Xinhe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China
Sample Received Date:	Apr. 22, 2026
Sample tested Date:	Apr. 22, 2026 to Apr. 29, 2026
Issue Date:	Apr. 29, 2026
Report No.:	CTB26042205101RF01
Test Standards	MIC Public Notice 88:2004, annex 1 and annex 43 Ordinance Article 2 paragraph 1 item (19)
Test Results	PASS
Remark:	This is 2.4G radio test report.

Compiled by:	Reviewed by:	Approved by:
Kai Chen	Martin Feng	
Kai Chen	Martin Feng	Bin Mei / Director

Note: If there is any objection to the inspection results in this report, please submit a written report to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. The tested sample(s) and the sample information are provided by the applicant. The authenticity, accuracy, and completeness of the provided information are the sole responsibility of the applicant. Without written approval of Shenzhen CTB Testing Technology Co., Ltd. this report can't be reproduced except in full. The result decision rules of our laboratory are based solely on the direct comparison between the actual measured values of test results and the standard limits, without considering the measurement uncertainty."★" indicates the testing items were fulfilled by subcontracted lab. "※" indicates the items are not in CNAS accreditation scope.

Table of Contents Page

1 TEST SUMMARY 4

1 VERSION 4

1.2 TEST DESCRIPTION 5

1.3 MEASUREMENT UNCERTAINTY 6

2 GENERAL INFORMATION 7

2.1 GENERAL DESCRIPTION OF EUT 7

2.2 DESCRIPTION OF TEST MODES 8

2.3 ENVIRONMENTAL CONDITIONS 9

2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED 10

2.5 DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE) 11

2.6 MEASUREMENT EQUIPMENT LIST 12

3 TEST CONDITIONS AND RESULTS 14

3.1 FREQUENCY ERROR 14

3.1.1 Limit 14

3.1.2 Test configuration 14

3.1.3 Test procedure 14

3.1.4 Test results 15

3.2 ANTENNA OUTPUT POWER AND OUTPUT POWER TOLERANCE 17

3.2.1 Limit 17

3.2.2 Test configuration 17

3.2.3 Test procedure 17

3.2.4 Test results 18

3.3 OCCUPIED BANDWIDTH AND SPREADING BANDWIDTH 20

3.3.1 Limit 20

3.3.2 Test configuration 20

3.3.3 Test procedure 20

3.3.4 Test results 21

3.4 UNWANTED EMISSION STRENGTH 23

3.4.1 Limit 23

3.4.2 Test configuration 23

3.4.3 Test procedure 23

3.4.4 Test results 24

3.5 SECONDARY RADIATED EMISSION STRENGTH 28

3.5.1 Limit 28

3.5.2 Test configuration 28

3.5.3 Test procedure ····· 28
3.5.4 Test results ····· 28
3.6 TRANSMISSION ANTENNA GAIN (EIRP ANTENNA POWER) MEASUREMENT ····· 32
3.6.1 Limit ····· 32
3.6.2 Test Procedure ····· 32
3.6.3 Test results ····· 32
3.7 CONSTRUCTION PROTECTION METHOD ····· 33
3.7.1 Requirement ····· 33
3.7.2 Confirmation method ····· 33
3.7.3 The photos of construction protection ····· 33
3.8 INTERFERENCE PREVENTION FUNCTION ····· 34
3.8.1 Limit ····· 34
3.8.2 Measuring ID code software ····· 34
3.8.3 Test setup ····· 34
3.8.4 Test procedure ····· 34
3.8.5 Test result ····· 34
4 TEST SETUP PHOTOS OF EUT ····· 35

1 TEST SUMMARY

1VERSION

Report No.	Issue Date	Description	Approved
CTB26042205101RF01	Apr. 29, 2026	Original	Valid

1.2 Test description

Part	Rule Section	Description	Result
4.1	3	Frequency Error	Complies
4.2	4	Occupied Bandwidth (99%) and Spread-spectrum (90%)	Complies
4.3	5	Unwanted Emission Intensity	Complies
4.4	6	Antenna Power Error	Complies
4.5	7	Limitation of Collateral Emission of Receiver	Complies
4.6	8	Transmission Antenna Gain(EIRP Antenna Power)	Complies
4.7	9	Transmission Radiation Angle Width (3dB Beam width)	N/A
4.8	10	Radio Interference Prevention Capability	Complies
4.9	Note 1	Carrier Sense Capability	N/A
4.10	Note 2	Construction Protection Confirmation	Complies

Note:

1. “N/A” denotes test is not applicable in this Report.
2. “Note 1” is MIC Notice No.88 Appendix No.43.
3. “Note 2” is MIC Ordinance Regulating Radio Equipment Section 4.17 of Article 49.20.

1.3 Measurement uncertainty

The reported uncertainty of measurement **y ±U**，where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2**，providing a level of confidence of approximately **95** %。

Item	Uncertainty
Occupancy bandwidth	54.3kHz
Conducted output power Above 1G	0.9dB
Conducted output power below 1G	0.9dB
Power Spectral Density , Conduction	0.9dB
Conduction spurious emissions	2.0dB
Out of band emission	2.0dB
3m camber Radiated spurious emission(30MHz-1GHz)	4.6dB
3m chamber Radiated spurious emission(1GHz-18GHz)	5.1dB
3m chamber Radiated spurious emission(18GHz-40GHz)	3.4dB
Frequency Error	54.3Hz
Adjacent channel power below 1G	2.6dB
Adjacent channel power Above 1G	2.8dB
humidity uncertainty	5.5%
Temperature uncertainty	0.63℃
frequency	1×10^{-7}

2 GENERAL INFORMATION

2.1 General description of EUT

Model/Type reference:	Hub-RF-PA
Model Description:	N/A
Hardware Version:	V5.3
Software Version:	CSR V1.4.1 AVR V1.0
Operation Frequency:	2402-2480MHz
Max. RF output power:	2mW
Type of Modulation:	GFSK
Antenna installation:	External antenna
Antenna Gain:	3.8dBi
Ratings:	DC 5V, 1A Battery DC 3.7V

Note: For more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.2 Description of test modes

The EUT has been tested under typical operating condition. The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing.

CH	Frequency (MHz)	CH	Frequency (MHz)	CH	Frequency (MHz)
1	2402 MHz	2	2426MHz	3	2480 MHz

Note: Test performed at the lowest/middle/highest frequencies selected in the list above for EUT supported while working on specified mode.

Pretest Mode	Description
Transmitting mode	Low channel: 2402MHz
	Middle channel: 2426MHz
	High channel: 2480MHz
Receiver mode	Low channel: 2402MHz

2.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Supply Voltage			
	supply power V	Rated module power V	Tolerance (%)
Normal	3.7	3.3	
+10%	4.07	3.3	0
-10%	3.33	3.3	0
Others			
Temperature (°C)	20-25		
Relative humidity	54 %.		
ATM Pressure:	1010 mbar		
Note 1: When the input voltage is reduced or increased by 10%, the regulator voltage changes of less than 1%. So the following test items are conducted in the normal voltage.			

2.4 Block diagram showing the configuration of system tested

Transmitting mode

2.5 Description of support units (conducted mode)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Test item description	Trademark(s)	Model/Type reference	Note
1	Hub	Klik	Hub-RF-PA	EUT

Note:

1. The support equipment was authorized by Declaration of Confirmation.
2. For detachable type I/O cable should be specified the length in cm in『Length』column.
3. “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

2.6 Measurement equipment list

No.	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Calibrated until
1	Spectrum Analyzer	Agilent	N9020A	MY52090073	A.14.16	2026/6/27
2	Power Sensor	Agilent	U2021XA	MY56120032	/	2026/6/27
3	Power Sensor	Agilent	U2021XA	MY56120034	/	2026/6/27
4	Communication test set	R&S	CMW500	108058	V3.5.80	2026/6/27
5	Spectrum Analyzer	KEYSIGHT	N9020A	MY51289897	A.14.16	2026/6/27
6	Signal Generator	Agilent	N5181A	MY50140365	A.01.60	2026/6/27
7	Vector signal generator	Agilent	N5182A	MY47420195	A.01.87	2026/6/27
8	Communication test set	Agilent	E5515C	MY50102567	B.19.07 (E1962B)	2026/6/27
9	2.4 GHz Filter	Shenxiang	MSF2400-2483.5MS-1154	20181015001	/	2026/6/29
10	5 GHz Filter	Shenxiang	MSF5150-5850MS-1155	20181015001	/	2026/6/29
11	Filter	Xingbo	XBLBQ-DZA120	190821-1-1	/	2026/6/29
12	BT&WI-FI Automatic test software	Micowave	MTS8310	Ver. 2.0.0.0	/	/
13	Rohde & Schwarz SFU Broadcast Test System	R&S	SFU	101017	/	2026/6/27
14	Temperature humidity chamber	Hongjing	TH-80CH	DG-15174	/	2026/6/27
15	234G Automatic test software	Micowave	MTS8200	Ver. 2.0.0.0	/	/
16	966 chamber	C.R.T.	966	/	/	2027/6/21
17	Receiver	R&S	ESPI	100362	RF_ATTEN_7 (104489/003)	2026/6/27
18	Amplifier	HP	8447E	2945A02747	/	2026/6/27

19	Amplifier	Agilent	8449B	3008A01838	/	2026/6/27
20	TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	00869	/	2026/6/27
21	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA9120D	01911	/	2026/6/27
22	EMI test software	Fala	EZ-EMC	FA-03A2 RE	/	/
23	Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-224	/	2026/6/27
24	loop antenna	ZHINAN	ZN30900A	GTS534	/	/
25	40G Horn antenna	A/H/System	SAS-574	588	/	2026/6/27
26	Amplifier	AEROFLEX	Aeroflex	097	/	2026/6/27
27	Power Meter	KEYSIGHT	N1912AP	N/A	A.05.00	2026/6/27
28	DC power supply	Agilent	E3640A	MY53050046	/	2026/6/27

Remark: Calibration institution "GRG METROLOGY & TEST GROUP Co., LTD."

Remark: Calibration based on Article 24-2, paragraph 4 of the Radio Act method c.

3 TEST CONDITIONS AND RESULTS

3.1 Frequency error

3.1.1 Limit

Item	Limits
Frequency Error	+/-50ppm

3.1.2 Test configuration



3.1.3 Test procedure

The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram as TEST CONFIGURATION shows.

EUT Condition: non-modulation

Spectrum Condition:

Frequency: test frequency

Span: 2000 kHz

RBW: 10 kHz

VBW: 10 kHz

Sweep time: Auto

Detector mode: Positive peak

Indication mode: max hold

3.1.4 Test results

Test voltage (V)	Frequency (MHz)	Read (MHz)	Deviation (MHz)	Tolerance (ppm)	Limit (ppm)	Result
Normal Voltage	2402	2402.016	0.016	6.661	+/-50.00	Pass
	2426	2426.016	0.016	6.595		
	2480	2480.017	0.017	6.855		

Note: Below test graph is the worst data.

Normal Voltage



2402MHz



2426MHz



2480MHz

3.2 Antenna output power and output power tolerance

3.2.1 Limit

Item	Limits
Antenna Power Density	≦3mW/MHz (FH form 2427 - 2470.75MHz) ≦10mW/MHz (OFDM, DSfrOM-O2P400~2483.5MHz) ≦10mW (Other from2400~2483.5MHz)
Antenna Power Error	+20% (Base on manufacturer declare antenna power density)

3.2.2 Test configuration



3.2.3 Test procedure

Step 1:

Connect the UUT to the spectrum analyzer as TEST CONFIGURATION and use the following settings:

- Centre Frequency: The centre frequency of the channel under test.
- RBW: 1 MHz
- VBW: 1 MHz
- Span: Wide enough to cover the complete power envelope of the signal of the UUT.
- Detector: Peak
- Trace Mode: Max Hold

Step 2:

When the trace is complete, find the peak value of the power envelope and record the frequency.

Step 3:

Make the following changes to the settings of the spectrum analyzer:

- Centre Frequency: Equal to the frequency recorded in step 2.
- Span: 0 MHz
- RBW: 1 MHz
- VBW: 1 MHz
- Detector: RMS
- Trace Mode: Max Hold

3.2.4 Test results

Test voltage	Channel (MHz)	Average burst power(dBm)	Output power (mW)	Limit (mW)	Rated output power (mW)	Tolerance (%)	Limit	Result
Normal Voltage	2402	1.192	1.316	10	2	-34.208	20%	Pass
	2426	1.380	1.374	10	2	-31.298		
	2480	0.826	1.209	10	2	-39.526		

Test condition:	Normal Voltage	Test graph



2402MHz



2426MHz



2480MHz

3.3 Occupied bandwidth and spreading bandwidth

3.3.1 Limit

Item	Limits
Occupied Bandwidth:	FH≤83.5 MHz; OFDM≤40MHz, DS≤26 MHz; Others≤26 MHz

3.3.2 Test configuration



3.3.3 Test procedure

1. Setting of SA is following as fellow:

   RBW: 300 kHz

   VBW: 300 kHz

   Sweep time: Auto

   Sweep Mode: Continuous sweep

   Detect mode: Positive peak

   Trace mode: Max hold
2. EUT have transmitted the maximum modulation signal and fixed channelize. SA set to 99% of occupied bandwidth to measure occupied bandwidth.
3. EUT have transmitted the maximum modulation signal and fixed channelize. SA set to 90% of occupied bandwidth to measure spread bandwidth.
4. Spread Factor=Spread Bandwidth/modulation rate. The modulation rate: MR=1.375Mbps for 2.4g

3.3.4 Test results

Test voltage (V)	Channel (MHz)	Occupy 99% Bandwidth (MHz)	Limit (MHz)	Result
Normal Voltage	2402	1.0443	<26	Pass
	2426	1.0480		
	2480	1.0501		

Normal Voltage: 99% Bandwidth



2402MHz



2426MHz



2480MHz

Test voltage (V)	Channel (MHz)	Spread 90% Bandwidth(MHz)	Spread Factor	Spread Bandwidth Limit (MHz)	Spread Factor Limit	Result
Normal Voltage	2402	0.6733	N/A	>0.5	N/A	Pass
	2426	0.6772				
	2480	0.6754				

Note: N/A means not applicable to this modulation type.

Normal Voltage: 90% Bandwidth



2402MHz



2426MHz



2480MHz

3.4 Unwanted emission strength

3.4.1 Limit

Item	Limits
TX Spurious Emission	≤2.5 μW/MHz(30MHz≤f≤1000MHz)
	≤2.5 μW/MHz (1000MHz<f≤2387MHz)
	≤25 μW/MHz (2387MHz<f≤2400MHz)
	≤25 μW/MHz (2483.5MHz≤f<2496.5MHz)
	≤2.5 μW/MHz (2496.5MHz≤f<12500MHz)

3.4.2 Test configuration



3.4.3 Test procedure

The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram as TEST CONFIGURATION shows.

EUT Condition: modulation

Spectrum Condition:

Frequency: 30MHz-12.5GHz

RBW: 100 kHz (30MHz-1GHz), 1MHz (1GHz-12.5GHz)

VBW: 100 kHz (30MHz-1GHz), 1MHz (1GHz-12.5GHz)

Sweep time: Auto

Detector mode: Positive peak

Indication mode: max hold

3.4.4 Test results

Test Channel	Test freq. range	Emission Frequency (MHz)	Test result (dBm/MHz)	Test result (uW/MHz)	limits (uW/MHz)	Result
Low	30MHz≤f≤1000MHz	992.24	-53.15	0.048	2.5	PASS
	1000MHz＜f≤2387MHz	2357.87	-41.78	0.066	2.5	PASS
	2387MHz＜f≤2400MHz	2399.97	-30.29	0.935	25	PASS
	2483.5MHz≤f＜2496.5MHz	2489.91	-43.06	0.049	25	PASS
	2496.5MHz≤f＜12750MHz	5100.89	-40.51	0.089	2.5	PASS
Middle	30MHz≤f≤1000MHz	865.17	-53.92	0.004	2.5	PASS
	1000MHz＜f≤2387MHz	2219.17	-43.1	0.049	2.5	PASS
	2387MHz＜f≤2400MHz	2392.02	-41.83	0.066	25	PASS
	2483.5MHz≤f＜2496.5MHz	2485.41	-42.96	0.051	25	PASS
	2496.5MHz≤f＜12750MHz	5736.61	-40.38	0.092	2.5	PASS
High	30MHz≤f≤1000MHz	897.18	-54.21	0.004	2.5	PASS
	1000MHz＜f≤2387MHz	2288.52	-42.12	0.061	2.5	PASS
	2387MHz＜f≤2400MHz	2390.98	-43.08	0.049	25	PASS
	2483.5MHz≤f＜2496.5MHz	2483.63	-40.21	0.095	25	PASS
	2496.5MHz≤f＜12750MHz	4598.47	-40.5	0.089	2.5	PASS

Test channel：2402MHz



30MHz~1GHz



1GHz~2.387GHz



2.387GHz~2.4 GHz



2.4835GHz~2.4965GHz



2.4965GHz~12.5GHz

Test channel：2426MHz



30MHz~1GHz



1GHz~2.387GHz



2.387GHz~2.4 GHz



2.4835GHz~2.4965GHz



2.4965GHz~12.5GHz

Test channel：2480MHz



30MHz~1GHz



1GHz~2.387GHz



2.387GHz~2.4 GHz



2.4835GHz~2.4965GHz



2.4965GHz~12.5GHz

3.5 Secondary radiated emission strength

3.5.1 Limit

Item	Limits
RX Spurious Emission:	≤4nW (f<1GHz)
	≤20nW (1GHz≤f)

3.5.2 Test configuration



3.5.3 Test procedure

The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram as TEST CONFIGURATION shows.

EUT Condition: modulation

Spectrum Condition:

Frequency: 30MHz-12.75GHz

RBW: 100 KHz (30MHz-1GHz), 1MHz (1GHz-12.75GHz)

VBW: 100 KHz (30MHz-1GHz), 1MHz (1GHz-12.75GHz)

Sweep time: Auto

Detector mode: Positive peak

Indication mode: max hold

3.5.4 Test results

Test channel	Test freq. range	Emission Frequency (MHz)	Test result dBm	Test result nW	Limit nW	Result
L	30MHz≤f≤1000MHz	907.85	-73.96	0.040	4	PASS
	1000MHz＜f≤12750MHz	5100.75	-59.25	1.189	20	PASS

30MHz~1GHz



1GHz~12.75GHz



Test channel	Test freq. range	Emission Frequency (MHz)	Test result dBm	Test result nW	Limit nW	Result
M	30MHz≤f≤1000MHz	772.05	-72.38	0.058	4	PASS
	1000MHz＜f≤12750MHz	2703.75	-61	0.794	20	PASS

30MHz~1GHz



1GHz~12.75GHz



Test channel	Test freq. range	Emission Frequency (MHz)	Test result dBm	Test result nW	Limit nW	Result
H	30MHz≤f≤1000MHz	910.76	-73.29	0.047	4	PASS
	1000MHz＜f≤12750MHz	4607.25	-60.25	0.944	20	PASS

30MHz~1GHz



1GHz~12.75GHz



3.6 Transmission Antenna Gain(EIRP Antenna Power) Measurement

3.6.1 Limit

Ltem	Limits
EIRP Power Density	≤12.14dBm/MHz(OFDM.DS from 2400-2483.5MHz ≤12.14dBm(Other from 2400-2483.5MHz)
Remark: This test item will not be applied to Antenna gain is lower than 2.14dBi.	

3.6.2 Test Procedure

1. Set EUT ad measuring antenna at the same height and roughly facing aech other.
2. Move the measuring antenna height up and down within ± 50cm of EUT height and swing it to find the maximum output of the measuring antenna. The output level at the spectrum analyzer is read sa “E”.
3. Remove the EUT from the turn table and put the replacing antenna facing to measuring antenna at same height. Set the standard signal generator (SSG) at same frequency and transmit on then receive the signal.
4. Swing the replacing antenna give a maximum receiving level.
5. Move the measuring antenna height up and down within ± 50cm of replacing antenna height and swing it to find the maximum receiving level.
6. Set SSG output power at Pt to give the equivalent output level of “E” or caluate Pt with SSG output which gives the nearest of “E” and difference (± 1dB).Record the Pt.
7. Calculate EIRP by the formula below EIRP = Gt – L + Pt

   Gt: gain of replacing antenna (dBi)

   L: feeder loss between SSG and replacing antenna

   Pt: Output power of the SSG
8. If the antenna for the EUT has circular polarization. Sum of V-field and H-field will be result if measuring antenna is linear polarization.

3.6.3 Test results

Test voltage	Test modulation	Output power (dBm/MHz)	Gain (dBi)	EIRP (dBm/MHz)	Result
Normal Voltage	GFSK	1.192	3.8	4.992	Pass
		1.38	3.8	5.18	
		0.826	3.8	4.626	

3.7 Construction protection method

3.7.1 Requirement

The high-frequency section and modulation section of the radio equipment except for the antenna system shall not be capable of being opened easily

3.7.2 Confirmation method

☐	Sealed with special screws.
☐	Plastic chassis is being welded using ultrasonic wavs.
☐	Chassis is glued using a special adhesive.
☐	Metal covers are spot-fused.
☐	Cover is specially interlocked.
☐	RF and Modulation components are covered with shielding case and this shielding case is soldered.
☐	Shield case is welded ant RF and modulations parts, and ID-ROM is welded using BGA Method.
☐	Shield case is welded ant RF and modulations parts, and ID-ROM is glued at its lead with a special adhesive.
☐	Shield case is welded ant RF and modulations parts, and ID-ROM is glued with a non-transparent laminating agent.
☒	Other: All RF and modulation section packet in one IC, and IC is welded using BGA Method, and RF module is welded on the main board, end-User can't open it easily.

3.7.3 The photos of construction protection

The red circle is welding point.



3.8 Interference prevention function

3.8.1 Limit

Item	Limits
Identification code	≧48 bits

3.8.2 Measuring ID code software

Item	Limits
MAC IP List	MAC Scan

3.8.3Test setup



3.8.4 Test procedure

1. In the case that the EUT has the function of automatically transmitting the identification code:
   a. Transmit the predetermined identification codes form EUT.
   b. Check the transmitted identification codes with the demodulator.
2. In the case of receiving the identification code:
   a. Transmit the predetermined identification codes form the counterpart.
   b. Check if communication is normal.
   c. Transmit the signals other than predetermined ID codes form the counterpart.
   d. check if the EUT stops the transmission, or if it displays that identification codes are different from the predetermined ones.

3.8.5 Test result

PASS

Bluetooth Device Address: 2222C88A0249

4 TEST SETUP PHOTOS OF EUT



※※※※※ **END OF REPORT** ※※※※※