

EUROFINS ELECTRICAL TESTING SERVICE (SHENZHEN) CO., LTD.

RADIO TEST - REPORT

Japan Compliance Test Report

Test Report Number: EFGX26010506-IE-03-E01

Test Report No.: EFGX26010506-IE-03-E01

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.

Room 20 of 2/F., 1/F., Building 2, Spring Block & Room 102, Building 8, Autumn Block, Meishenghuigu Innovation Park, No.83, Dabao Road, Bao'an District, Shenzhen, Guangdong, China. Telephone: +86-755-82911867, Fax : +86-755-82910749

Page 1 of 27

Content

1	General Information	3
1.1	Notes	3
1.2	Testing laboratory	4
1.3	Details of approval holder	4
1.4	Details of Manufacturer	4
1.5	Application details	5
1.6	Test item	5
1.7	Standards	6
2	Technical test	7
2.1	Summary of test results	7
2.2	Test environment	7
2.3	Measurement uncertainty	7
2.4	Test mode	7
2.5	Test equipment utilized	8
2.6	Auxiliary Equipment Used during Test:	8
2.7	Test software information:	8
2.8	Customized Configurations	8
2.9	Test Environments	8
2.10	Test results	9
3	Technical Requirement	10
3.1	Antenna Power and E.I.R.P	10
3.2	Tolerances for Antenna Power	12
3.3	Frequency Tolerance	14
3.4	Dwell Time	16
3.5	Occupied Frequency Bandwidth	18
3.6	Spread Bandwidth and Process Gain	20
3.7	Transmitter Spurious Emissions (Conducted) (For transmitter)	22
3.8	Secondary Radiated Emissions (Conducted) (For receiver)	25
3.9	Interference prevention function	27

1 General Information

1.1 Notes

The results of this test report relate exclusively to the item tested as specified in chapter "Description of test item" and are not transferable to any other test items.

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd. is not responsible for any generalisations and conclusions drawn from this report. Any modification of the test item can lead to invalidity of test results and this test report may therefore be not applicable to the modified test item.

The test report may only be reproduced or published in full. Reproducing or publishing extracts of the report requires the prior written approval of the Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.

This document is subject to the General Terms and Conditions and the Testing and Certification System of Eurofins Electrical Testing Service (Shenzhen) Co., Ltd., available on request or accessible at www.eurofins.com.

Operator:

2026-03-16

Bruce Zheng / Project Engineer



Date

Eurofins-Lab.


Name / Title

Signature

Technical responsibility for area of testing:

2026-03-16

Albert Xu / Lab Manager



Date

Eurofins-Lab.

Name / Title

Signature

1.2 Testing laboratory

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.

Room 20 of 2/F., 1/F., Building 2, Spring Block & Room 102, Building 8, Autumn Block,

Meishenghuigu Innovation Park, No.83, Dabao Road, Bao'an District, Shenzhen, Guangdong, China

Telephone : +86-755-82911867

Fax : +86-755-82910749

The Laboratory has passed the Accreditation by the American Association for Laboratory Accreditation (A2LA). The Accreditation number is 5376.01.

The Laboratory has been listed by industry Canada to perform electromagnetic emission measurements, The CAB identifier is CN0088.

1.3 Details of approval holder

Name : PEANUTS CLUB CO., LTD

Address : 2-1-33 MIKURIYAMINAMI, HIGASHIOSAKA, OSAKA,
JAPAN

Telephone : N/A

Fax : N/A

1.4 Details of Manufacturer

Name : Shenzhen Bogoodwill industrial co., Limited.

Address : 302, Building L, No. 17 Wan'an Road, Ma'anshan Community, Shajing Street, Bao'an District, Shenzhen, Guangdong Province, China 518104

Telephone : N/A

Fax : N/A

1.5 Application details

Date of receipt of application : 2026-01-26
Date of receipt of test item : 2026-01-26
Date of test : 2026-01-26 to 2026-03-16
Date of issue : 2026-03-16

1.6 Test item

Product type : Wireless Earphone
Model name : Star beat
Brand : N/A
Serial number : N/A
Sample ID : 260127-20-003, 260127-20-004
Ratings : DC 3.7V
Test voltage : DC 3.7V
Additional information : ./.

RadioTechnical data

Operating Frequency : Bluetooth BR+EDR:2402 MHz- 2480 MHz
Radio Tech. : Classic Bluetooth
Frequency channel : 79Ch
Modulation : GFSK, $\pi/4$ DQPSK, 8DPSK
Antenna type : Internal antenna
Antenna gain : 2.7dBi

The above sample(s) and sample information was/were submitted and identified on behalf of the applicant.
Eurofins assures objectivity and impartiality of the test, and fulfills the obligation of confidentiality for applicant's commercial information and technical documents.

1.7 Standards

Standards	
Article 2 paragraph 1 item (19)	Low power data communications system in the 2.4GHz band
ARIB STD-T66 V3.7, 2014-10	SECOND GENERATION LOW POWER DATA COMMUNICATION SYSTEM/ WIRELESS LAN SYSTEM

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed. ☒

Or

The deviations as specified were ascertained in the course of the tests performed. ☐

2.2 Test environment

Temperature : 20 ... 25°C
Relative humidity content : 30 ... 60%
Air pressure : 100 ... 101kPa

2.3 Measurement uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

System Measurement Uncertainty	
Test Items	Extended Uncertainty
Uncertainty for Conducted RF test	RF Power Conducted: 1.16Db Frequency test involved: 1.05×10 ⁻⁷ or 1%

2.4 Test mode

The EUT was set at continuously transmitting (CH0, CH39, CH78, Hopping) and receiving mode (CH0, CH39, CH78) during the test.

EUT test voltage requirement:

The RF unit is supplied by DC power. The fluctuation of input voltage to the circuit of RF unit of test equipment is under ±1%, when input voltage from DC 3.7V to the test equipment is fluctuated by ±10%, So, the DC 3.7V is chosen in the test report.

The measurement result of the voltage fluctuation at RF circuit when DC 3.7V +/- 10%.

DC Input	DC 2.7V
3.33V	2.7V
3.7V	2.7V
4.07V	2.7V

2.5 Test equipment utilized

EQUIPMENT ID	EQUIPMENT NAME	MODEL NO.	SN NO.	CAL. DUE DATE
23-2-13-12	Signal Analyzer	N9010B-544	MY57471523	2026-03-26
23-2-10-43	Switch and Control Unit	ERIT-E-JS0806-2	/.	2026-03-26
23-2-10-44	DC power supply	E3642A	MY58386620	2026-03-26
23-2-10-50	Temperature & Humidity Meter	COS-03	582951	2026-03-26

All calibration reports are from CCIC (Shenzhen) Metrology & Testing Service Co.,Ltd.

2.6 Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.	S/N
Laptop	LENOVO	TP00096A	PF-1QH0LV

2.7 Test software information:

Test Software Version	BT TOOL		
Modulation	Setting TX Power	TX Pattern	Packet Type
GFSK	Default	Pn9	DH5
$\pi/4$ DQPSK	Default	Pn9	2DH5
8DPSK	Default	Pn9	3DH5

2.8 Customized Configurations

EUT Conf.	Signal Description	Operating Frequency	Duty Cycle
DH5	GFSK	CH0: 2402 CH39: 2441 CH78: 2480	70.60
2DH5	$\pi/4$ DQPSK	CH0: 2402 CH39: 2441 CH78: 2480	70.60
3DH5	8DPSK	CH0: 2402 CH39: 2441 CH78: 2480	70.60

2.9 Test Environments

Enviroment Parameter	Temperature	Voltage	Relative Humidity
101.5Kpa	25.2℃	3.7Vdc	56.3%

2.10 Test results

☒ 1st test

☐ test after modification

☐ production test

Conformance requirement according to Article 2 paragraph 1 item (19) and ARIB STD-T66 Version 3.7/2014-10		Result	Test site
Essential parameter	Corresponding technical requirements		
Transmitter requirements	3.2 (2) Antenna Power	PASS	Site 1
	3.2 (3) Tolerances for Antenna Power	PASS	Site 1
	3.2 (4) Frequency Tolerance	PASS	Site 1
	3.2 (5) Transmission Rate	Note 2	N/A
	3.2 (7) Occupied Frequency Bandwidth	PASS	Site 1
	3.2 (8) Spread Bandwidth	PASS	Site 1
	3.2 (9) Process Gain	PASS	Site 1
	3.2 (10) Number of Carriers	Note 3	N/A
	3.2 (11) Dwell Time	PASS	Site 1
	3.2 (6) Spurious Emissions	PASS	Site 1
Receiver requirements	3.5 (1) Secondary Radiated Emissions	PASS	Site 1
Controlling equipment	3.4.1 (1) Interference prevention function	PASS	Site 1
	3.4.2 Channel connection procedure	Note 4	N/A

Note 1: Measurement taken is within the measurement uncertainty of measurement system.

Note 2: Not Applicable, No signal transmission rate is regulated.

Note 3: Not Applicable, the test item only applicable to device with OFDM system.

Note 4: Not Applicable, Not particularly regulated.

Note 5: Test method: MIC Notice No.88 Appendix No.43


3 Technical Requirement

3.1 Antenna Power and E.I.R.P

3.1.1 Test Method

1. Connect EUT test port to RMS power sensor.
2. Set the EUT to transmit maximum output power at 2.4GHz.
3. Then set the EUT to transmit DH5, 2DH5, 3DH5 Hopping mode and measure the conducted output power separately.
4. Repeat above procedures until all frequencies measured were complete.

3.1.2 Test Setup:



3.1.3 Limit (ARIB STD-T66, Clause 3.2 (2)-a)

- a. The antenna power of a transmitting equipment (with a frequency band of 2,427 – 2,470.75 MHz, for spread spectrum systems using FH systems, hybrid systems of DS and FH, or hybrid systems of FH and OFDM) shall be such that the mean power within a bandwidth of 1 MHz is 3 mW or less in the case of modulation using a standard coding test signal with the same transmission rate as that of the modulation signal.
- b. The antenna power of a transmitting equipment using a spread spectrum system other than any of those in “a” and the OFDM system shall be such that the mean power within a bandwidth of 1 MHz is 10 mW or less in the case of modulation using a standard coding test signal with the same transmission rate as that of the modulation signal.

3.1.4 Test result

Earphone L part

Antenna Power										
Test Condition	TestMode	Antenna	Freq(M Hz)	Result (dBm)	Result (mW)	Burst ratio	90% BW (MHz)	Result (mW /MHz)	Limit (mW /MHz)	Ver-dict
NTNV	DH5	Ant1	Hop	-3.11	0.4887	0.7060	72.019	0.009	≤3	PASS
	2DH5	Ant1	Hop	-4.85	0.3273	0.7060	72.015	0.006	≤3	PASS
	3DH5	Ant1	Hop	-5.01	0.3155	0.7060	72.014	0.006	≤3	PASS

EIRP							
Test Condition	TestMode	Antenna	Freq (MHz)	Power (dBm/MHz)	EIRP (dBm/MHz)	Limit (dBm/MHz)	Ver-dict
NTNV	DH5	Ant1	Hop	-20.457	-17.757	≤6.91	PASS
	2DH5	Ant1	Hop	-22.218	-19.518	≤6.91	PASS
	3DH5	Ant1	Hop	-22.218	-19.518	≤6.91	PASS

Earphone R part

Antenna Power										
Test Condition	TestMode	Antenna	Freq(M Hz)	Result (dBm)	Result (mW)	Burst ratio	90% BW (MHz)	Result (mW /MHz)	Limit (mW /MHz)	Ver-dict
NTNV	DH5	Ant1	Hop	-3.14	0.4853	0.7060	72.000	0.009	≤3	PASS
	2DH5	Ant1	Hop	-4.88	0.3251	0.7060	72.054	0.006	≤3	PASS
	3DH5	Ant1	Hop	-5.02	0.3148	0.7060	72.309	0.006	≤3	PASS

EIRP							
Test Condition	TestMode	Antenna	Freq (MHz)	Power (dBm/MHz)	EIRP (dBm/MHz)	Limit (dBm/MHz)	Ver-dict
NTNV	DH5	Ant1	Hop	-20.457	-17.757	≤6.91	PASS
	2DH5	Ant1	Hop	-22.218	-19.518	≤6.91	PASS
	3DH5	Ant1	Hop	-22.218	-19.518	≤6.91	PASS

Remark:Antenna Power=Average burst power (mW) / burst ratio / spreading bandwidth

EIRP(dBm/MHz)=Antenna power(dBm/MHz)+gain(dBi)


3.2 Tolerances for Antenna Power

3.2.1 Test Method

1. Connect EUT test port to RMS power sensor.
2. Set the EUT to transmit maximum output power at 2.4GHz.
3. Then set the EUT to transmit DH5, 2DH5, 3DH5 Hopping mode and measure the conducted output power separately.
4. Repeat above procedures until all frequencies measured were complete.

3.2.2 Test Setup:

The Bluetooth component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



3.2.3 Limit (ARIB STD-T66, Clause 3.2 (3))

Upper limits of the tolerance for antenna power shall be 20%, respectively. Note that they represent the tolerance for the maximum rated antenna power and that no upper and lower limits of the tolerance are regulated in the case of antenna power reduction for communications reasons.

3.2.4 Test result

Modulation type	Output Power (mW/MHz)	Declared Output Power (mW/MHz)	Tolerances (%)	Limit
GFSK	0.009	0.1	-82	+20%
$\pi/4$ DQPSK	0.006	0.1	-88	+20%
8DPSK	0.006	0.1	-88	+20%

Note: Deviation = (Output power – Declared Output Power) / Declared Output Power * 100%

3.2.5 Result

The equipment met the requirement of this clause.


3.3 Frequency Tolerance

3.3.1 Test Method:

1. Connect EUT test port to spectrum analyzer.
2. Set the EUT to transmit maximum output power at 2.4GHz.
3. Then set the EUT to transmit at Highest, Middle, and Lowest frequency and measure the conducted output power separately.
4. RBW=10KHz, VBW=10KHz, Sweep = auto, Detector function = peak, Trace = max hold
5. Repeat above procedures until all frequencies measured were complete.

3.3.2 Test Setup:

The Bluetooth component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



3.3.3 Limit (ARIB STD-T66, Clause 3.2 (4))

Tolerance of frequency: $\pm 50 \times 10^{-6}$.

3.3.4 Test Result

Earphone L part

Test Condition	Antenna	Freq(MHz)	Measurement Frequency(MHz)	Result[ppm]	Limit[ppm]	Verdict
NTNV	Ant1	2402	2402.027	11.24063	±50	PASS
		2441	2441.024	9.83204	±50	PASS
		2480	2480.024	9.67742	±50	PASS

Earphone R part

Test Condition	Antenna	Freq(MHz)	Measurement Frequency(MHz)	Result[ppm]	Limit[ppm]	Verdict
NTNV	Ant1	2402	2402.024	9.99167	±50	PASS
		2441	2441.024	9.83204	±50	PASS
		2480	2480.027	10.88710	±50	PASS

Note: Frequency Tolerance (ppm) = [Measurement Frequency – Center Frequency] / Center Frequency*10⁶

Test Result: Pass

Please refer to the appendix A for test plotsThe equipment met the requirement of this clause.


3.4 Dwell Time

3.4.1 Test Method:

1. Connect EUT test port to spectrum analyzer.
2. Set the EUT to transmit maximum output power at 2.4GHz.
3. Then set the EUT to transmit at DH5, 2DH5 with hopping mode separately.
4. Set RBW=1MHz , VBW $\geq$ RBW.
5. Set Sweep = Single.
6. Repeat above procedures until all frequencies measured were complete.

3.4.2 Test Setup:

The Bluetooth component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



3.4.3 Limit (ARIB STD-T66, Clause 3.2 (11))

Frequency dwell time (time during which radio waves continue to be emitted at a specified frequency) of a transmitting equipment using the FH system shall be 0.4 seconds or less.

3.4.4 Test Result

The Dwell Time = Burst Width * Total Hops. The detailed calculations are showed as follows:
The observation time for dwell time calculation: 0.4 [s] * hopping number = 0.4 [s] * 79 = 31.6 [s];

The burst width, which is directly measured, refers to the duration on one channel hop.

The maximum number of hopping channels in 31.6s for

DH5=1600 / 6 / 79 *31.6=106.67

Test Result (Packet DH5, 2DH5 the worse result was reported to show compliance):

Earphone L part

Type	Packet	Pulse Time (ms)	Number of chips	Accumulated Dwell time (ms)	Limit (ms)
GFSK	DH5	2.91	106.67	310.4097	400
$\pi/4$ DQPSK	2DH5	2.91	106.67	310.4097	400
8DPSK	3DH5	2.92	106.67	311.4764	400

Earphone R part

Type	Packet	Pulse Time (ms)	Number of chips	Accumulated Dwell time (ms)	Limit (ms)
GFSK	DH5	2.91	106.67	310.4097	400
$\pi/4$ DQPSK	2DH5	2.91	106.67	310.4097	400
8DPSK	3DH5	2.92	106.67	311.4764	400

Test Result: Pass

Please refer to the appendix G for test plots
The equipment met the requirement of this clause.


3.5 Occupied Frequency Bandwidth

3.5.1 Test Method:

7. Connect EUT test port to spectrum analyzer.
8. Set the EUT to transmit maximum output power at 2.4GHz.
9. Then set the EUT to transmit at Highest, Middle, and Lowest frequency separately.
10. Set Occupied bandwidth 99%
11. Set RBW=1MHz , VBW $\geq$ RBW.
12. Set Sweep = auto.
13. Set Detector function = peak.
14. Allow the trace to stabilize.
15. Repeat above procedures until all frequencies measured were complete.

3.5.2 Test Setup:

The Bluetooth component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



3.5.3 Limit (ARIB STD-T66, Clause 3.2 (7))

Permissible value for occupied bandwidth using the FH system, a hybrid system combining DS and FH systems, or a hybrid system combining FH and OFDM systems shall be 83.5 MHz or less, while necessary bandwidth (minimum occupied bandwidth sufficient to ensure information transmission of required quality at a required transmission rate for the system used under specified conditions for a given emission type) using a system other than any of the above shall be 26 MHz or less.

3.5.4 Test Result

Earphone L part

Type	Channel (MHz)	Result (MHz)	Limit (MHz)
GFSK	2402 - 2480	78.887	<83.5MHz
$\pi/4$ DQPSK	2402 - 2480	79.007	<83.5MHz
8DPSK	2402 - 2480	78.923	<83.5MHz

Earphone R part

Type	Channel (MHz)	Result (MHz)	Limit (MHz)
GFSK	2402 - 2480	78.882	<83.5MHz
$\pi/4$ DQPSK	2402 - 2480	78.914	<83.5MHz
8DPSK	2402 - 2480	78.946	<83.5MHz

Test Result: Pass

Please refer to the appendix C for test plots
The equipment met the requirement of this clause.


3.6 Spread Bandwidth and Process Gain

3.6.1 Test Method:

1. Connect EUT test port to spectrum analyzer.
2. Set the EUT to transmit maximum output power at 2.4GHz.
3. Then set the EUT to transmit at Highest, Middle, and Lowest frequency separately.
4. Set Occupied bandwidth 90%
5. Set analyzer center frequency to channel center frequency.
6. Detector = peak.
7. Sweep time = auto couple.
8. Trace mode = max hold.
9. Allow trace to fully stabilize.
10. Repeat above procedures until all frequencies measured were complete.

3.6.2 Test Setup:

The Bluetooth component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



3.6.3 Limit (ARIB STD-T66, Clause 3.2 (8))

In spread spectrum systems, spread bandwidth (which refers to a frequency bandwidth with an upper limit and lower limit such that each of the mean powers radiated above the upper frequency limit and below the lower frequency limit is equal to 5 % of the total mean power radiated; this also applies hereafter) shall be 500 kHz or more

3.6.4 Test Result

Earphone L part

Type	Channel (MHz)	Spread Bandwidth (MHz)	Limit (MHz)	Spread Factor	Spread Factor Limit
GFSK	2402 - 2480	72.019	≥ 0.5	72.019	>5
$\pi/4$ DQPSK	2402 - 2480	72.015	≥ 0.5	72.015	>5
8DPSK	2402 - 2480	72.014	≥ 0.5	72.014	>5

Earphone R part

Type	Channel (MHz)	Spread Bandwidth (MHz)	Limit (MHz)	Spread Factor	Spread Factor Limit
GFSK	2402 - 2480	72.000	≥ 0.5	72.000	>5
$\pi/4$ DQPSK	2402 - 2480	72.054	≥ 0.5	72.054	>5
8DPSK	2402 - 2480	72.309	≥ 0.5	72.309	>5

Note: Spread Factor=Spread Bandwidth/Modulation rate.
The modulation rate: MR=1Mbps (Declared by Manufacturer)

Test Result: Pass

Please refer to the appendix D for test plots
The equipment met the requirement of this clause.


3.7 Transmitter Spurious Emissions (Conducted) (For transmitter)

Test Method:

1. Connect EUT test port to spectrum analyzer.
2. Set the EUT to transmit maximum output power at 2.4GHz.
3. Then set the EUT to transmit at Highest, Middle, and Lowest frequency separately.
4. Set Frequency range and limit: $2,387\text{MHz} \leq f \leq 2,400\text{MHz}$ and $2,483.5\text{MHz} < f \leq 2,496.5\text{MHz}$ 25 μW or less b. $2,387\text{MHz} > f$ and $2,496.5\text{MHz} < f$ 2.5 μW or less
5. Set RBW $\geq 100\text{KHz}$ for testing below 1GHz, 1MHz for testing above 1GHz, VBW $\geq$ RBW.
6. Set Sweep = auto.
7. Set Detector function = peak.
8. Allow the trace to stabilize.
9. Repeat above procedures until all frequencies measured were complete.

Test Setup:

The Bluetooth component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



3.7.1 Limit (ARIB STD-T66, Clause 3.2 (6))

Permissible mean power of spurious emission of each frequency supplied to a feeder, that is, mean power of spurious emission in the 1 MHz bandwidth at frequency f other than frequency band used shall be as follows: a. $2,387\text{MHz} \leq f \leq 2,400\text{MHz}$ and $2,483.5\text{MHz} < f \leq 2,496.5\text{MHz}$ 25 μW or less b. $2,387\text{MHz} > f$ and $2,496.5\text{MHz} < f$ 2.5 μW or less

3.7.2 Test Result

Earphone L part

Test Condition	Test Mode	Antenna	Freq(M Hz)	Freq.Range [MHz]	Freq. [MHz]	Result [dBm]	Limit [dBm]	Result [μW]	Limit [μW]	Verdict
NTNV	DH5	Ant1	2402	30~1000	839.22	-47.86	≤-26	0.01637	≤2.5	PASS
				1000~2387	2133.87	-46.62	≤-26	0.02178	≤2.5	PASS
				2387~2400	2399.95	-35.15	≤-16	0.30549	≤25	PASS
				2483.5~2496.5	2485.72	-36.09	≤-16	0.24604	≤25	PASS
				2496.5~13000	4804.12	-30.00	≤-26	1.00000	≤2.5	PASS
			2441	30~1000	861.53	-47.46	≤-26	0.01795	≤2.5	PASS
				1000~2387	2367.24	-46.29	≤-26	0.02350	≤2.5	PASS
				2387~2400	2398.90	-36.80	≤-16	0.20893	≤25	PASS
				2483.5~2496.5	2496.20	-36.46	≤-16	0.22594	≤25	PASS
				2496.5~13000	4882.37	-31.38	≤-26	0.72778	≤2.5	PASS
			2480	30~1000	887.48	-49.07	≤-26	0.01239	≤2.5	PASS
				1000~2387	2249.34	-45.99	≤-26	0.02518	≤2.5	PASS
				2387~2400	2397.11	-37.12	≤-16	0.19409	≤25	PASS
				2483.5~2496.5	2486.28	-36.22	≤-16	0.23878	≤25	PASS
				2496.5~13000	4960.10	-29.58	≤-26	1.10154	≤2.5	PASS
	2DH5	Ant1	2402	30~1000	999.52	-48.67	≤-26	0.01358	≤2.5	PASS
				1000~2387	2128.67	-46.88	≤-26	0.02051	≤2.5	PASS
				2387~2400	2399.92	-33.37	≤-16	0.46026	≤25	PASS
				2483.5~2496.5	2493.39	-36.18	≤-16	0.24099	≤25	PASS
				2496.5~13000	4803.59	-30.41	≤-26	0.90991	≤2.5	PASS
			2441	30~1000	859.11	-48.62	≤-26	0.01374	≤2.5	PASS
				1000~2387	2260.44	-46.71	≤-26	0.02133	≤2.5	PASS
				2387~2400	2387.91	-37.01	≤-16	0.19907	≤25	PASS
				2483.5~2496.5	2486.87	-36.50	≤-16	0.22387	≤25	PASS
				2496.5~13000	4882.37	-31.79	≤-26	0.66222	≤2.5	PASS
			2480	30~1000	878.02	-48.27	≤-26	0.01489	≤2.5	PASS
				1000~2387	2317.30	-46.99	≤-26	0.02000	≤2.5	PASS
				2387~2400	2391.45	-36.99	≤-16	0.19999	≤25	PASS
				2483.5~2496.5	2485.59	-36.65	≤-16	0.21627	≤25	PASS
				2496.5~13000	4960.10	-29.32	≤-26	1.16950	≤2.5	PASS
	3DH5	Ant1	2402	30~1000	858.38	-49.05	≤-26	0.01245	≤2.5	PASS
				1000~2387	2175.14	-46.53	≤-26	0.02223	≤2.5	PASS
				2387~2400	2400.00	-33.48	≤-16	0.44875	≤25	PASS
				2483.5~2496.5	2488.90	-36.57	≤-16	0.22029	≤25	PASS
				2496.5~13000	4804.12	-29.10	≤-26	1.23027	≤2.5	PASS
			2441	30~1000	880.69	-48.52	≤-26	0.01406	≤2.5	PASS
				1000~2387	2313.14	-46.84	≤-26	0.02070	≤2.5	PASS
				2387~2400	2397.39	-36.80	≤-16	0.20893	≤25	PASS
				2483.5~2496.5	2485.97	-36.00	≤-16	0.25119	≤25	PASS
				2496.5~13000	4881.84	-32.16	≤-26	0.60814	≤2.5	PASS
			2480	30~1000	939.86	-48.65	≤-26	0.01365	≤2.5	PASS
				1000~2387	2164.73	-46.76	≤-26	0.02109	≤2.5	PASS
				2387~2400	2391.24	-37.02	≤-16	0.19861	≤25	PASS
				2483.5~2496.5	2493.00	-36.44	≤-16	0.22699	≤25	PASS
				2496.5~13000	4960.10	-30.52	≤-26	0.88716	≤2.5	PASS

Earphone R part

Test Condition	Test Mode	Antenna	Freq(M Hz)	Freq.Range [MHz]	Freq. [MHz]	Result [dBm]	Limit [dBm]	Result [μW]	Limit [μW]	Verdict
NTNV	DH5	Ant1	2402	30~1000	881.90	-48.72	≤-26	0.01343	≤2.5	PASS
				1000~2387	2375.90	-46.52	≤-26	0.02228	≤2.5	PASS
				2387~2400	2399.79	-34.39	≤-16	0.36392	≤25	PASS
				2483.5~2496.5	2486.36	-36.29	≤-16	0.23496	≤25	PASS
				2496.5~13000	4804.64	-29.72	≤-26	1.06660	≤2.5	PASS
			2441	30~1000	679.17	-48.82	≤-26	0.01312	≤2.5	PASS
				1000~2387	2312.10	-46.66	≤-26	0.02158	≤2.5	PASS
				2387~2400	2387.09	-36.90	≤-16	0.20417	≤25	PASS
				2483.5~2496.5	2487.34	-36.43	≤-16	0.22751	≤25	PASS
				2496.5~13000	4881.84	-32.28	≤-26	0.59156	≤2.5	PASS
			2480	30~1000	895.24	-47.79	≤-26	0.01663	≤2.5	PASS
				1000~2387	2279.51	-46.86	≤-26	0.02061	≤2.5	PASS
				2387~2400	2394.74	-37.28	≤-16	0.18707	≤25	PASS
				2483.5~2496.5	2490.12	-36.29	≤-16	0.23496	≤25	PASS
				2496.5~13000	4960.10	-30.24	≤-26	0.94624	≤2.5	PASS
	2DH5	Ant1	2402	30~1000	805.27	-48.94	≤-26	0.01276	≤2.5	PASS
				1000~2387	2374.86	-46.38	≤-26	0.02301	≤2.5	PASS
				2387~2400	2399.99	-32.89	≤-16	0.51404	≤25	PASS
				2483.5~2496.5	2493.45	-36.22	≤-16	0.23878	≤25	PASS
				2496.5~13000	4804.12	-29.12	≤-26	1.22462	≤2.5	PASS
			2441	30~1000	875.11	-48.39	≤-26	0.01449	≤2.5	PASS
				1000~2387	2373.82	-46.82	≤-26	0.02080	≤2.5	PASS
				2387~2400	2387.27	-36.96	≤-16	0.20137	≤25	PASS
				2483.5~2496.5	2487.86	-36.62	≤-16	0.21777	≤25	PASS
				2496.5~13000	4881.84	-31.60	≤-26	0.69183	≤2.5	PASS
			2480	30~1000	821.76	-48.29	≤-26	0.01483	≤2.5	PASS
				1000~2387	2357.53	-46.40	≤-26	0.02291	≤2.5	PASS
				2387~2400	2387.16	-37.40	≤-16	0.18197	≤25	PASS
				2483.5~2496.5	2484.50	-36.35	≤-16	0.23174	≤25	PASS
				2496.5~13000	4960.62	-30.16	≤-26	0.96383	≤2.5	PASS
	3DH5	Ant1	2402	30~1000	767.93	-48.56	≤-26	0.01393	≤2.5	PASS
				1000~2387	2356.14	-46.13	≤-26	0.02438	≤2.5	PASS
				2387~2400	2399.99	-33.26	≤-16	0.47206	≤25	PASS
				2483.5~2496.5	2487.32	-35.78	≤-16	0.26424	≤25	PASS
				2496.5~13000	4804.12	-29.66	≤-26	1.08143	≤2.5	PASS
			2441	30~1000	909.79	-48.39	≤-26	0.01449	≤2.5	PASS
				1000~2387	2299.27	-46.73	≤-26	0.02123	≤2.5	PASS
				2387~2400	2395.19	-36.87	≤-16	0.20559	≤25	PASS
				2483.5~2496.5	2487.15	-36.38	≤-16	0.23014	≤25	PASS
				2496.5~13000	4881.84	-32.04	≤-26	0.62517	≤2.5	PASS
			2480	30~1000	928.22	-48.65	≤-26	0.01365	≤2.5	PASS
				1000~2387	2242.06	-47.28	≤-26	0.01871	≤2.5	PASS
				2387~2400	2390.22	-37.22	≤-16	0.18967	≤25	PASS
				2483.5~2496.5	2485.44	-36.79	≤-16	0.20941	≤25	PASS
				2496.5~13000	4960.10	-29.56	≤-26	1.10662	≤2.5	PASS

3.7.3 Result

Please refer to the appendix E for test plots
The equipment met the requirement of this clause.

3.8 Secondary Radiated Emissions (Conducted) (For receiver)


Test Method:

The test method was referred to the subclause 11.13.3.4 of ANSI C63.10-2013.

1. Connect EUT test port to spectrum analyzer.
2. Set the EUT to transmit maximum output power at 2.4GHz.
3. Then set the EUT to transmit at Highest, Middle, and Lowest frequency separately.
4. Set Frequency range and limit: 30MHz - 1 GHz and 20 nW or 1 GHz – 13GHz
5. Set RBW $\geq$ 100KHz for testing below 1GHz, 1MHz for testing above 1GHz, VBW $\geq$ RBW.
6. Set Sweep = auto.
7. Set Detector function = peak.
8. Allow the trace to stabilize.
9. Repeat above procedures until all frequencies measured were complete.

Test Setup:

The Bluetooth component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



3.8.1 Limit (ARIB STD-T66, Clause 3.5 (1))

The limit on secondary emissions radiated from the receiving equipment within which the function of other radio equipment will not be impaired shall be, in terms of the power of a dummy antenna circuit that has the same electrical constant as the receiving antenna, 4 nW or less at a frequency below 1 GHz and 20 nW or less at a frequency of 1 GHz or higher as measured using the circuit.

3.8.2 Test Result

Earphone L part

Test Condition	Test Mode	Antenna	Freq(M Hz)	Freq.Range [MHz]	Freq. [MHz]	Result [dBm]	Limit [dBm]	Result [nW]	Limit [nW]	Verdict
NTNV	DH5	Ant1	2402	30~1000	32.91	-60.61	≤-54	0.86896	≤4	PASS
				1000~12500	3770.93	-64.80	≤-47	0.33113	≤20	PASS
			2441	30~1000	798.73	-69.89	≤-54	0.10257	≤4	PASS
				1000~12500	3827.28	-64.78	≤-47	0.33266	≤20	PASS
			2480	30~1000	860.81	-70.23	≤-54	0.09484	≤4	PASS
				1000~12500	3812.33	-63.49	≤-47	0.44771	≤20	PASS
	2DH5	Ant1	2402	30~1000	921.43	-70.32	≤-54	0.09290	≤4	PASS
				1000~12500	1719.90	-60.96	≤-47	0.80168	≤20	PASS
			2441	30~1000	891.85	-69.96	≤-54	0.10093	≤4	PASS
				1000~12500	3738.15	-64.90	≤-47	0.32359	≤20	PASS
			2480	30~1000	831.22	-70.70	≤-54	0.08511	≤4	PASS
				1000~12500	3796.23	-64.07	≤-47	0.39174	≤20	PASS
	3DH5	Ant1	2402	30~1000	875.84	-70.34	≤-54	0.09247	≤4	PASS
				1000~12500	3779.55	-64.57	≤-47	0.34914	≤20	PASS
			2441	30~1000	963.14	-70.25	≤-54	0.09441	≤4	PASS
				1000~12500	3774.38	-64.19	≤-47	0.38107	≤20	PASS
			2480	30~1000	857.90	-70.05	≤-54	0.09886	≤4	PASS
				1000~12500	3733.55	-64.69	≤-47	0.33963	≤20	PASS

Earphone R part

Test Condition	Test Mode	Antenna	Freq(M Hz)	Freq.Range [MHz]	Freq. [MHz]	Result [dBm]	Limit [dBm]	Result [nW]	Limit [nW]	Verdict
NTNV	DH5	Ant1	2402	30~1000	992.24	-69.56	≤-54	0.11066	≤4	PASS
				1000~12500	3814.63	-64.76	≤-47	0.33420	≤20	PASS
			2441	30~1000	990.30	-70.09	≤-54	0.09795	≤4	PASS
				1000~12500	3737.58	-64.58	≤-47	0.34834	≤20	PASS
			2480	30~1000	991.27	-70.38	≤-54	0.09162	≤4	PASS
				1000~12500	3773.80	-63.26	≤-47	0.47206	≤20	PASS
	2DH5	Ant1	2402	30~1000	713.37	-70.11	≤-54	0.09750	≤4	PASS
				1000~12500	3805.43	-64.20	≤-47	0.38019	≤20	PASS
			2441	30~1000	905.91	-69.63	≤-54	0.10889	≤4	PASS
				1000~12500	3757.70	-64.74	≤-47	0.33574	≤20	PASS
			2480	30~1000	888.94	-70.13	≤-54	0.09705	≤4	PASS
				1000~12500	3771.50	-64.15	≤-47	0.38459	≤20	PASS
	3DH5	Ant1	2402	30~1000	934.53	-69.95	≤-54	0.10116	≤4	PASS
				1000~12500	3739.88	-64.68	≤-47	0.34041	≤20	PASS
			2441	30~1000	890.88	-70.59	≤-54	0.08730	≤4	PASS
				1000~12500	3827.85	-64.35	≤-47	0.36728	≤20	PASS
			2480	30~1000	867.11	-70.39	≤-54	0.09141	≤4	PASS
				1000~12500	3868.68	-65.25	≤-47	0.29854	≤20	PASS

3.8.3 Result

Please refer to the appendix F for test plots
The equipment met the requirement of this clause.

3.9 Interference prevention function

3.9.1 Limit

Item	Limits
Identification Code	≥48 bits

Measuring ID code Software
MAC IP List: MAC Scan

3.9.2 Test Procedure

1. In the case that the EUT has the function of automatically transmitting the identification code: a. Transmit the predetermined identification codes form EUT. b. Check the transmitted identification codes with the demodulator.
2. In the case of receiving the identification code: a. Transmit the predetermined identification codes form the counterpart. b . Check if communication is normal. c. Transmit the signals other than predetermined ID codes form the counterpart. d. check if the EUT stops the transmission, or if it displays that identification codes are different from the predetermined ones.

3.9.3 Conditions of Equipment under Test

Required normal mode of the applicable equipment (EUT)

3.9.4 TEST RESULTS

The radio equipment has an identification code. A verification of this code is done before a communication channel is established

MAC Address: 90B0EA482751

The equipment meet the requirement of this clause.

End