

低功率射頻電機技術規範測試報告

報告編號

RT180323D03

申請者

台灣威騰電子股份有限公司

產品名稱

iXpand Wireless Charger

型號

SDIZ90N

製造廠商

Western Digital Technologies, Inc. , USA

商標或廠牌

SANDISK

該產品樣品試驗
依據之試驗標準

國家通訊傳播委員會低功率射頻電機技術規範
107 年 1 月 10 日修訂

試驗結果

合格

香港商立德國際商品試驗有限公司桃園分公司
日期 107 年 12 月 20 日

報告簽署人簽章:



目 錄

報告發行紀錄	4
1 低功率射頻電機量測記錄表	6
2 一般敘述	7
2.1 待測設備	7
2.2 輔助測試之週邊設備描述	10
2.3 測試架構圖	10
3 適用規範	11
3.1 規範要求	11
3.2 限制使用之頻帶	15
4 帶外發射之量測	16
4.1 適用標準	16
4.2 量測方法	16
4.3 量測儀器	17
4.4 測試配置	18
4.5 場強度之計算	19
4.6 量測結果	20
4.6.1 發射諧波	20
4.6.2 接收諧波	44
4.6.3 其它不必要之訊號	46
4.7 量測結果判定	47
4.8 配置照片	47
5 電源線傳導干擾之量測	48
5.1 適用標準	48
5.2 量測方法	48
5.3 量測儀器	48
5.4 測試配置	49
5.5 干擾值之計算	49
5.6 量測結果	50
5.7 量測結果判定	51
5.8 配置照片	51
6 6 dB 頻寬之要求	52
6.1 適用標準	52
6.2 量測方法	52
6.3 量測儀器	52
6.4 測試配置	52
6.5 量測結果	53
6.6 量測結果判定	54
7 傳導輸出功率之量測	55
7.1 適用標準	55
7.2 量測方法	55
7.3 量測儀器	55
7.4 測試配置	55
7.5 量測結果	56
7.6 量測結果判定	56
8 功率頻譜密度之量測	57

8.1	適用標準	57
8.2	量測方法	57
8.3	量測儀器	57
8.4	測試配置	57
8.5	量測結果	58
8.6	量測結果判定	59
9	檢測實驗室基本資料	60

報告發行紀錄

Issue No.	Description	Date Issued
RT180323D03	Original release.	107 年 12 月 20 日

證 明 書


發行日期：107 年 12 月 20 日


產 品 名 稱：iXpand Wireless Charger
商 標：SANDISK
型 號：SDIZ90N
申 請 者：台灣威騰電子股份有限公司
量 測 規 範：低功率射頻電機技術規範 LP0002
ANSI C63.10-2013

香港商立德國際商品試驗有限公司桃園分公司在此證明上述待測設備樣品一組(型號：SDIZ90N)，收件日期 107 年 3 月 23 日，於 107 年 11 月 22 日至 107 年 12 月 3 日，已在本公司的標準測試場地完成量測。報告中所描述之測試結果和待測設備的架構組合，均根據樣品實際的量測情況作詳實的記錄。

立德桃園分公司依“低功率射頻電機技術規範”、“低功率電波輻射性電機管理辦法”及“電信管制射頻器材審驗辦法”製作測試結果報告。

特 此 證 明 ！

報告製作者：  , 日期： 107 年 12 月 20 日
鄭 幸 如 / 高級專員

審 核 者：  , 日期： 107 年 12 月 20 日
賴 正 軒 / 技術副理

香港商立德國際商品試驗有限公司桃園分公司

實驗室地址：新北市林口區嘉寶里 14 鄰 47-2 號

此份報告不得摘錄複製，除全份複製外，需經實驗室書面同意。



1 低功率射頻電機量測記錄表

申請廠商： 台灣威騰電子股份有限公司
申請廠商地址： 臺北市松山區敦化北路 205 號 14 樓 1402 室
製造廠商： Western Digital Technologies, Inc. , USA
廠牌： SANDISK
產品名稱： iXpand Wireless Charger
型號： SDIZ90N
量測單位名稱： 香港商立德國際商品試驗有限公司桃園分公司 林口實驗室
量測單位地址： 新北市林口區嘉寶里 14 鄰 47-2 號
量測單位認可編號： TAF 2021 (9kHz~40GHz)
量測規範： 低功率射頻電機技術規範 LP0002
ANSI C63.10-2013
KDB 558074
KDB 662911

WLAN 2.4GHz 頻段概要

項次	量測項目	規 範	量測結果判定
1	帶外發射	低功率射頻電機技術規範 3.10.1.5 節	合格
2	電源線傳導干擾	低功率射頻電機技術規範 2.3 節	合格
4	6 dB 頻寬	低功率射頻電機技術規範 3.10.1.6 節	合格
5	峰值傳導輸出功率	低功率射頻電機技術規範 3.10.1.2 節	合格
6	功率頻譜密度	低功率射頻電機技術規範 3.10.1.6 節	合格

2 一般敘述

2.1 待測設備

產品名稱：	iXpand Wireless Charger
型號：	SDIZ90N
額定電源：	12Vdc from adapter
調變方式：	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
調變技術：	DSSS, OFDM
傳輸速率：	802.11b: 11.0/ 5.5/ 2.0/ 1.0Mbps 802.11g: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps 802.11n: up to 300Mbps
載波頻率：	2412 ~ 2462MHz
頻道數：	802.11b, 802.11g, 802.11n (20MHz): 11 802.11n (40MHz): 7
發射功率(電場強度)：	28.26 dBm
天線種類：	見註
電源線類別：	見註
信號線類別：	N/A
配件：	N/A

註 1: 此待測物之技術的種類為2Tx /2Rx之組合。

Modulation Mode	Tx Function
802.11b	1TX
802.11g	1TX
802.11n (20MHz)	2TX
802.11n (40MHz)	2TX

註 2: 此待測設備搭配測試的天線，其資料如下：

No	Antenna Type	Connector	Gain(dBi)
1	Printed	N/A	1.79
2	Printed	N/A	2.12

*The maximum antenna gain is chosen for final test.

註 3: 此待測設備搭配使用之電源供應器規格如下：

Brand	Ktec
Model	KSA-18F-120150D5
Input Power	100-240Vac 50/60Hz 0.5A
Output Power	12Vdc 1.5A
Power Cord	AC 2-Pin Non-shielded DC cable (1.8m)

註 4: 此報告中，場強輻射量測經過評估後及電源線傳導干擾量測以下列測試模式進行最終量測。

量測項目	發射	接收
1GHz 以上量測	802.11b: Ch 1, 6, 11 802.11g: Ch 1, 6, 11 802.11n (20MHz): Ch 1, 6, 11 802.11n (40MHz): Ch 3, 6, 9	802.11n (20MHz): Ch 6
其它不必要之訊號	802.11n (20MHz): Ch 6	
電源線傳導干擾量測	802.11n (20MHz): Ch 6	

註 5: 此報告中傳輸模式，場強輻射量測及電源線傳導干擾量測之外的測試項目，以DSSS調變技術和OFDM調變技術分別進行測試並記錄最終量測結果於報告中。

註 6: Duty cycle of test signal.

2.4GHz頻段

If duty cycle of test signal is $\geq 98\%$, duty factor is not required.


If duty cycle of test signal is $< 98\%$, duty factor shall be considered.

802.11b: Duty cycle of test signal is 99%

802.11g: Duty cycle = $1.41/1.505 = 0.937$, Duty factor = $10 * \log(1/0.937) = 0.28$

802.11n (20MHz): Duty cycle = $1.32/1.495 = 0.883$, Duty factor = $10 * \log(1/0.883) = 0.54$

802.11n (40MHz): Duty cycle = $0.66/0.756 = 0.873$, Duty factor = $10 * \log(1/0.873) = 0.59$



此裝置各頻道的中心頻率如下：

2.4 GHz 頻段：

802.11b, 802.11g, 802.11n (20MHz):

頻道	對應頻率 (MHz)	頻道	對應頻率 (MHz)
01	2412	07	2442
02	2417	08	2447
03	2422	09	2452
04	2427	10	2457
05	2432	11	2462
06	2437		

802.11n (40MHz):

頻道	對應頻率 (MHz)	頻道	對應頻率 (MHz)
03	2422	07	2442
04	2427	08	2447
05	2432	09	2452
06	2437		

詳細之規格請參考使用說明書，產品的照片請參照 BV 報告編號:180323D03。

2.2 輔助測試之週邊設備描述

待測設備於受測時均接上其所屬的配件或一般用途之相關設備；下列輔助設備或配件測試中所使用的配備，以形成一個代表待測物實際運作的受測系統。


ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	LOAD	N/A	N/A	N/A	N/A	Provided by Lab

Note: All power cords of the above support units are non-shielded (1.8m).

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	DC cable	1	1.8	N	0	Supplied by client
2.	USB cable	1	1.0	Y	0	Provided by Lab

Note: The core(s) is(are) originally attached to the cable(s)

2.3 測試架構圖



3 適用規範

3.1 規範要求

(1) 傳導之規定

依據國家通訊傳播委員會低功率射頻電機技術規範之 2.3 節，電源傳導干擾之限制要求如下：

頻率(MHz)	傳導限制值 (dBUV)	
	準峰值(Quasi-peak)	平均值(Average)
0.15-0.5	66-56(註)	56-46(註)
0.5-5	56	46
5-30	60	50

(註)：隨頻率之對數遞減。

(2) 帶外發射之規定

(I) 操作於 2.4000~2.4835 GHz band:

依據國家通訊傳播委員會低功率射頻電機技術規範 3.10.1.5 節之要求，操作頻帶範圍外之任意 100 kHz 內，發射機所產生的射頻功率相較於使用頻帶範圍中包含最高所需功率之 100 kHz 內的射頻功率，其衰減值限制如下：(1) 輸出功率以附件二之峰值輸出功率方式測量者，至少須衰減 20 dB，可使用射頻傳導或輻射方式測量。(2) 輸出功率以 3.10.1.2(1)(C)之最大傳導輸出功率測量方式者，至少須衰減 30 dB。

(II) 操作於 5.15 GHz~5.35 GHz 及 5.470 GHz ~5.725 GHz 頻段：

依據國家通訊傳播委員會低功率射頻電機技術規範 4.7.4.1 節之要求，帶外發射之有效等向輻射功率(EIRP) ≤ -27 dBm/MHz。

(III) 操作於 5.725 GHz~5.850 GHz 頻段：

依據國家通訊傳播委員會低功率射頻電機技術規範 4.7.4.2 節之要求，所有頻帶邊緣向外 5 MHz 內頻率之發射，有效等向輻射功率(EIRP) ≤ 27 dBm/MHz~15.6 dBm/MHz (以線性法計算對應之限制值)；所有頻帶邊緣向外 5 MHz~25 MHz，有效等向輻射功率 35(EIRP) ≤ 15.6 dBm/MHz~10 dBm/MHz (以線性法計算對應之限制值)；所有頻帶邊緣外 25 MHz~75 MHz，有效等向輻射功率(EIRP) ≤ 10 dBm/MHz~-27 dBm/MHz(以線性法計算對應之限制值)；所有頻帶邊緣外 ≥ 75 MHz 的頻率之發射，有效等向輻射功率(EIRP) ≤ -27 dBm/MHz；有關遮罩限制值詳圖 1。

在 5.725 GHz~5.850 GHz 頻段操作且天線增益大於 10dBi 之設備於 106 年 3 月 2 日前得適用 3.10.1.5 帶外發射限制；在 5.725 GHz~5.850 GHz 頻段操作且天線增益小於等於 10dBi 之設備於 107 年 3 月 2 日前得適用 3.10.1.5 帶外發射限制規定。




圖 1

在 1 GHz 以下不必要之發射，應符合 2.8 之規定。此外，落於 2.7 禁用頻段之輻射發射，應符合 2.8 之規定。

頻率(MHz)	電場強度(微伏特/公尺, uV/m)	測距(公尺)
0.009 - 0.490(含)	2,400/f(kHz)	300
0.490 (不含) - 1.705 (含)	24,000/f(kHz)	30
1.705(不含) - 30 (不含)	30	30
30 (含) - 88 (含)	100	3
88 (不含)- 216 (含)	150	3
216 (不含)- 960 (含)	200	3
960 (不含)以上	500	3

(3)天線之規定

天線規格不受第 2.2 節規定之限制。

(4)天線增益之要求

低功率發射機，依據國家通訊傳播委員會低功率射頻電機技術規範 3.10.1.3 節及 4.7.3 節之規定如下：

(I) 操作於 2400 MHz~2483.5 MHz 頻段：

- (A) 進行固定式點對點操作時，其發射天線之方向性增益超過6 dBi，每超過3 dBi，最大傳導輸出功率限制值應降低1 dB。
- (B) 天線以多向波束發射方式(含同時發射或循序發射)將訊號導向多個接收機或接收機群組時，應符合下列規定：
 - (a) 非同時發射多向波束者，所有載波或頻道傳輸至所有天線陣列或陣列群之總和傳導輸出功率應符合 3.10.1.2 之功率限制值。如天線/天線陣列群之方向性增益超過6 dBi，每超過3 dBi，總和傳導輸出功率限制值應降低1 dB。方向性增益值應計算如下：
 - (i) 方向性增益值= 10log(天線陣列之單元數目)+各單元中最高之方向性增益值。
 - (ii) 天線陣列間之遮蔽效應或波束干涉損失能充分佐證時，方向性增益得低於(i)計算數值。
 - (b) 同時發射多向波束於相同或不同頻道者，其每一波束功率應符合(a)之功率限制值。如發射波束有重疊現象，功率應降低，以確保總和傳導輸出功率符合(a)之限制值。同時發射的所有波束總和傳導輸出功率不大於(a) 總和傳導輸出功率限制值加8 dB。方向性增益值計算同(a)。
 - (c) 發射機之天線具備單向波束功能者，應符合(1)(A)及(3)後段之規定。

除(A)及(B)外，使用超過6 dBi 方向增益之發射天線時，應依超過6 dBi 天線方向增益的dBi 總量，等量減少最大傳導輸出功率限制值。

(II) 操作於 5.15 GHz~5.25 GHz 頻段：

- (A) 供戶外操作使用：使用超過6 dBi 方向增益之發射天線時，應依超過6 dBi 天線方向增益的dBi 總量，等量減少最大傳導輸出功率及最大功率頻譜密度。在水平面仰角超過30 度時，其最大EIRP 應小於或等於21 dBm。
- (B) 供室內操作使用：使用超過6 dBi 方向增益之發射天線時，應依超過6 dBi 天線方向增益的dBi 總量，等量減少最大傳導輸出功率及最大功率頻譜密度。
- (C) 供固定式點對點操作使用：使用超過23 dBi方向增益之指向性天線時，應依超過23 dBi天線方向增益的dBi 總量，等量減少最大傳導輸出功率及最大功率頻譜密度。固定式點對點操作，不包括點對多點系統、全方向性應用及多台共站發射機傳送相同資訊。
- (D) 供用戶端裝置(Client Device)操作使用：使用超過6 dBi 方向增益之發射天線時，應依超過6 dBi 天線方向增益的dBi 總量，等量減少最大傳導輸出功率及最大功率頻譜密度。

(III) 操作於 5.25 GHz~5.35 GHz 與 5.470 GHz ~5.725 GHz 頻段：

使用超過 6 dBi 方向增益之發射天線時，應依超過 6 dBi 天線方向增益的 dBi 總量，等量減少最大傳導輸出功率及最大功率頻譜密度。

(IV) 操作於 5.725 GHz~5.850 GHz 頻段：

- (A) 供固定式點對點操作時，使用方向增益超過6 dBi 之發射天線，可不需對應減少發射器之傳導輸出功

率限制值。

(B) 除(A)外，使用超過6 dBi 方向增益之發射天線時，應依超過6 dBi 天線方向增益的dBi 總量，等量減少最大傳導輸出功率及最大功率頻譜密度。

(5) 6dB 頻寬之要求

(I) 操作於 2400 MHz~2483.5 MHz 頻段：

對使用數位調變技術(digital modulation techniques)系統之低功率發射機，依據國家通訊傳播委員會低功率射頻電機技術規範 3.10.1.6 節之規定，6dB 頻寬至少應有 500kHz。

(II) 操作於 5.725 GHz~5.850 GHz 頻段：

依據國家通訊傳播委員會低功率射頻電機技術規範 4.7.5 節之規定，其 6dB 頻寬至少應有 500kHz。

(6) 傳導輸出功率之要求

(I) 操作於 2.4000~2.4835 GHz band:

依據國家通訊傳播委員會低功率射頻電機技術規範 3.10.1.2 節之規定：

數位調變技術系統：1 W(含)以下。

(II) 操作於 5.15 GHz~5.25 GHz 頻段：

依據國家通訊傳播委員會低功率射頻電機技術規範 4.7.3.1 節之要求：

(A) 供戶外操作使用/供室內操作使用/供固定式點對點操作使用：最大傳導輸出功率應小於或等於1 W。

(B) 供用戶端裝置(Client Device)操作使用：最大傳導輸出功率應小於或等於250 mW。

(III) 操作於 5.25 GHz~5.35 GHz 及 5.470 GHz ~5.725 GHz 頻段：

依據國家通訊傳播委員會低功率射頻電機技術規範4.7.3.2節之規定，最大傳導輸出功率應小於或等於250 mW或11dBm+10log B (B是26 dB發射頻寬，單位MHz)之較小者。

(IV) 操作於 5.725 GHz~5.850 GHz 頻段：

依據國家通訊傳播委員會低功率射頻電機技術規範 4.7.3.3 節之規定，最大傳導輸出功率應小於或等於 1 W。

(7) 功率頻譜密度之要求

(I) 操作於 2.4000~2.4835 GHz band:

依據國家通訊傳播委員會低功率射頻電機技術規範 3.10.1.6 節之規定，在使用頻率範圍之任一 3 kHz 頻寬內，由發射機傳導至天線之功率頻譜密度在任意傳輸期間內，皆小於或等於 8 毫分貝(dBm)，且應依 3.10.1.3 之方式降低功率頻譜密度限制值。

(II) 操作於 5.15 GHz~5.25 GHz 頻段：

依據國家通訊傳播委員會低功率射頻電機技術規範 4.7.3.1 節之要求：

(A) 供戶外操作使用/供室內操作使用/供固定式點對點操作使用：在任何1 MHz 頻帶中最大功率頻譜密度應小於或等於17 dBm。

(B) 供用戶端裝置(Client Device)操作使用：在任何1 MHz 頻帶中最大功率頻譜密度應小於或等於11 dBm。

(III) 操作於 5.25 GHz~5.35 GHz 及 5.470 GHz ~5.725 GHz 頻段：

依據國家通訊傳播委員會低功率射頻電機技術規範4.7.3.2節之規定，最大功率頻譜密度在任何1 MHz 頻帶中應小於或等於11 dBm。

(IV) 操作於5.725 GHz~5.850 GHz頻段：

依據國家通訊傳播委員會低功率射頻電機技術規範 4.7.3.3 節之規定，在任何 500 kHz 頻帶中最大功率頻譜密度應小於或等於 30 dBm。

(8) 發射功率控制(TPC)及動態頻率選擇(DFS)之要求

依據國家通訊傳播委員會低功率射頻電機技術規範4.7.7.1及4.7.7.2節之規定。

發射功率控制(TPC)：操作於5.25 GHz~5.35 GHz 與5.470 GHz~5.725 GHz 頻段的設備，應具備發射功率控制功能。設備必須至少具有6 dB低於平均EIRP 30 dBm的能力。EIRP 低於500 mW 之系統不須具備TPC 功能。

動態頻率選擇(DFS)：操作於5.25 GHz~5.35 GHz與5.470 GHz~5.725 GHz頻段之設備應具備動態頻率選擇雷達偵測功能並啟動之，以完整偵測使用頻帶內之雷達訊號，避免與雷達系統同頻道操作。相關規定如下：

(1) 最低動態頻率選擇的偵測門檻

- (A) 最大EIRP 為200 mW~1 W之設備，其最低動態頻率選擇的偵測門檻值為-64dBm。
- (B) 最大EIRP 低於200 mW，且功率頻譜密度小於10 dBm/MHz 之設備，其最低動態頻率選擇的偵測門檻值為-62 dBm。
- (C) 最大EIRP 低於200 mW，且功率頻譜密度大於或等於10 dBm/MHz 之設備，其最低動態頻率選擇的偵測門檻值為-64 dBm。
- (D) 此偵測門檻值為1 微秒內之平均接收功率，並以0 dBi 天線為參考基準。頻道初始設定得由系統隨機選取或使用者手動選取。

(2) 操作模式：動態頻率選擇之規定適用於以下之操作模式：

- (A) 頻道可用性檢查時間之規定，適用於主控運作模式。
- (B) 頻道移動時間之規定，適用於主控及受控運作模式。

(3) 頻道可用性檢查時間：設備必須檢查其可在某一頻道上起始傳送之前是否有雷達系統已經操作在該頻道上，以及何時其必須移動到另一新的頻道，在60 秒內若沒有偵測到功率位準大過上述之干擾門檻值的雷達訊號時，設備才可開始使用該頻道。

(4) 頻道移動時間：在偵測到雷達的存在後，所有在該操作頻道上的所有傳輸須在10秒內停止，在偵測到雷達訊號後，該期間內的傳輸應維持最多200 毫秒的正常通訊。另外，間歇性的管理與控制訊號可在剩餘的時間中傳送，以便撤離該操作頻道。

(5) 不可佔用期間：某一頻道已被頻道可用性檢查或"服務中"監視顯示含有雷達系統，至少須有30 分鐘的不可佔用期間。不可佔用期間起始於偵測到雷達系統的當時。

(9)無線資訊傳輸設備必須擁有安全功能之要求：

依據國家通訊傳播委員會低功率射頻電機技術規範4.7.7.3節之規定，無線資訊傳輸設備必須擁有安全功能，以保護未經授權之一方更改軟體。製造商應提出符合本節規定之相關證明文件或符合性聲明。

(10) 依據國家通訊傳播委員會低功率射頻電機技術規範4.7.7.4 節之規定，製造商必須在操作於 U-NII 頻段上之數位調變系統中提供安全功能，使第三方團體無法重寫程式，使其操作於非經認證之設定。該軟體必須避免發射機操作於非經認證之頻率、輸出功率、調變形式或其他射頻參數。製造商可使用私有網路，只有經授權的用戶能下載軟體、進行軟體式電子簽章或硬體式的韌體更新，新的軟體可以被合法的載入到設備中，同時又能符合上述事項，並於應用程式中描述設備授權的方法。

(11) 依據國家通訊傳播委員會低功率射頻電機技術規範4.7.7.5 節之規定，製造商必須確保 DFS 功能無法被無線資訊傳輸設備之操作者取消。

(12)電波暴露量之評估

依據國家通訊傳播委員會低功率射頻電機技術規範 5.20.2 節之規定，若受測物於正常操作模式下，其發射機距離人體 20 公分以上者，可測試最大暴露允許值(Maximum Permissible Exposure, MPE)以證明其符合電波暴露量之要求。

限制值如下：

(1) 職業性/可控制之暴露

頻率範圍 (MHz)	電場強度 (V/m)	磁場強度 (A/m)	功率密度 (mW/cm ²)	平均時間 (minutes)
0.3 - 3.0	614	1.63	*100	6
3 - 30	1842/f	4.89/f	*900/f ²	6
30 - 300	61.4	0.163	1.0	6
300 - 1,500	---	---	f/300	6
1,500 - 100,000	---	---	5.0	6

註 1：標記*表平面波等效功率密度。

註 2：f 表測試頻率，單位：MHz。

(2) 一般人/不可控制之暴露

頻率範圍 (MHz)	電場強度 (V/m)	磁場強度 (A/m)	功率密度 (mW/cm ²)	平均時間 (minutes)
0.3 - 3.0	614	1.63	*100	30
3 - 30	1842/f	4.89/f	*180/f ²	30
30 - 300	27.5	0.073	1.0	30
300 - 1,500	---	---	f/1500	30
1,500 - 100,000	---	---	1.0	30

註 1：標記*表平面波等效功率密度。

註 2：f 表測試頻率，單位：MHz。

3.2 限制使用之頻帶

除本規範另有規定外，任何低功率射頻電機之主波皆不得使用下表所列各頻段之頻率；低功率射頻電機落於下表所列頻段之混附發射，其電場強度必須符合 2.8 之限制規定。

頻率(兆赫)	頻率(兆赫)	頻率(兆赫)
0.090~0.110	240.00~285.00	3332.0~3339.0
0.490~0.510	322.00~335.40	3345.8~3358.0
2.172~2.198	399.90~410.00	3500.0~4400.0
3.013~3.033	485.00~510.00	4500.0~5250.0
4.115~4.198	608.00~614.00	5350.0~5460.0
5.670~5.690	703.00~748.00	7250.0~7750.0
6.200~6.300	758.00~803.00	8025.0~8500.0
8.230~8.400	825.00~915.00	9000.0~9200.0
12.265~12.600	930.00~1240.0	9300.0~9500.0
13.340~13.430	1300.0~1427.0	10600~12700
14.965~15.020	1435.0~1626.5	13250~13400
16.700~16.755	1660.0~1785.0	14470~14500
19.965~20.020	1805.0~1880.0	15350~16200
25.500~25.700	1885.0~1900.0	17700~21400
37.475~38.275	1905.0~1985.0	22010~23120
73.500~75.400	2010.0~2025.0	23600~24000
108.00~138.00	2110.0~2170.0	31200~31800
149.90~150.05	2200.0~2300.0	36430~36500
156.70~156.90	2310.0~2390.0	38600 以上
162.01~167.17	2483.5~2900.0	
167.72~173.20	3260.0~3267.0	

4 帶外發射之量測

4.1 適用標準

請見本報告 3.1 節第 2 項(I)的規定。

4.2 量測方法

量測頻率 9kHz ~ 30MHz :

將待測物置於0.8米高的非金屬桌面，使其操作在工作狀態。接收天線置於3米外離地1米的高度。測試桌面要360度旋轉，另外接收天線也要分別設置為Open軸性(Loop antenna面向EUT)與Close軸性(Loop antenna與EUT垂直)與 ground-parallel軸性(Loop antenna面向地板) 作量測，以找出最大的輻射電場強度。

量測頻率 30MHz 以上:

在電波暗室，將待測物置於 0.8 米高的非金屬桌面，使其操作在工作狀態。接收天線置於 3 米距離。桌面要 360 度旋轉，另外接收天線從離地 1 米至 4 米升降變化，以找出最大的輻射電場強度，接收天線分別置於水平、垂直極化各執行測試一次。

備註: 對於 1GHz 以上場強輻射的測試，待測物則置於1.5米高的非金屬桌面

4.3 量測儀器


DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
HP Preamplifier	8447D	2432A03504	Feb. 21, 2018	Feb. 20, 2019
HP Preamplifier	8449B	3008A01201	Feb. 22, 2018	Feb. 21, 2019
MITEQ Preamplifier	AMF-6F-260400-33-8P	892164	Feb. 21, 2018	Feb. 20, 2019
Agilent TEST RECEIVER	N9038A	MY51210129	Feb. 6, 2018	Feb. 5, 2019
Schwarzbeck Antenna	VULB 9168	139	Nov. 29, 2017	Nov. 28, 2018
			Nov. 26, 2018	Nov. 25, 2019
Schwarzbeck Antenna	VHBA 9123	480	May 19, 2017	May 18, 2019
Schwarzbeck Horn Antenna	BBHA-9170	212	Dec. 1, 2017	Nov. 30, 2018
			Nov. 25, 2018	Nov. 24, 2019
Schwarzbeck Horn Antenna	BBHA 9120-D1	D130	Dec. 1, 2017	Nov. 30, 2018
			Nov. 25, 2018	Nov. 24, 2019
ADT. Turn Table	TT100	0306	NA	NA
ADT. Tower	AT100	0306	NA	NA
Software	Radiated_V7.6.15.9.5	NA	NA	NA
SUHNER RF cable With 4dB PAD	SF102	Cable-CH6-01	Aug. 13, 2018	Aug. 12, 2019
SUHNER RF cable With 3/4dB PAD	SF102	Cable-CH8-3.6m	Aug. 13, 2018	Aug. 12, 2019
KEYSIGHT MIMO Powermeasurement Test set	U2021XA	U2021XA-001	Jun. 4, 2018	Jun. 3, 2019
KEYSIGHT Spectrum Analyzer	N9030A	MY54490260	Aug. 3, 2018	Aug. 2, 2019
Loop Antenna EMCI	LPA600	270	Aug. 11, 2017	Aug. 10, 2019
EMCO Horn Antenna	3115	00028257	Nov. 30, 2017	Nov. 29, 2018
			Nov. 25, 2018	Nov. 24, 2019
Highpass filter Wainwright Instruments	WHK 3.1/18G-10SS	SN 8	NA	NA

- NOTE:** 1. The calibration interval of the above test instruments is 12/24 months. And the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
3. The test was performed in Chamber No. 6.
4. The Industry Canada Reference No. IC 7450E-6.
5. The following table is for the measurement uncertainty, which is calculated as per the document CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.


MEASUREMENT	FREQUENCY	UNCERTAINTY
Radiated emissions	9kHz ~ 30MHz	±2.38 dB
	30MHz ~ 1GHz	±5.54 dB
	Above 1GHz	±5.48 dB

4.4 測試配置


<Frequency Range 9kHz ~ 30MHz>



<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



4.5 場強度之計算

場強之計算公式如下：

結果值 Emission level (dBuV/m)=機器讀值 Raw Value (dBuV) +校正因子 Correction Factor (dB/m)

餘裕度 Margin(dB)= 結果值 Emission level (dBuV/m)-限制值 Limit value (dBuV/m)

量測結果請見下頁。

4.6 量測結果

4.6.1 發射諧波


802.11b

操作模式：	發射	調變技術：	DSSS
基本波頻率：	CH 1：2412 MHz	測試儀器：	(PK) RB=1MHz, VB=3MHz (AV) RB=1MHz, VB=10Hz
量測場地溫度：	20°C	量測場地濕度：	70%RH
測試日期：	107 年 11 月 22 日	測試者：	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	54.94 PK	74.00	-19.06	1.49 H	118	56.44	-1.50
2	2390.00	41.38 AV	54.00	-12.62	1.49 H	118	42.88	-1.50
3	*2412.00	105.74 PK			1.49 H	118	107.36	-1.62
4	*2412.00	102.23 AV			1.49 H	118	103.85	-1.62
5	4824.00	53.53 PK	74.00	-20.47	2.00 H	78	48.74	4.79
6	4824.00	47.95 AV	54.00	-6.05	2.00 H	78	43.16	4.79
7	#7236.00	-	-	-	-	-	-	-
8	#9648.00	-	-	-	-	-	-	-
9	12060.00	-	-	-	-	-	-	-
10	14472.00	-	-	-	-	-	-	-
11	#16884.00	-	-	-	-	-	-	-
12	19296.00	-	-	-	-	-	-	-
13	#21708.00	-	-	-	-	-	-	-
14	#24120.00	-	-	-	-	-	-	-

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency (主頻).
6. " # ": The radiated frequency is out of the restricted band.
7. " - ": The emission levels were too low to be detected.
8. The blank is not available, the limit of fundamental frequency was restricted at the output power.




操作模式：	發射	調變技術：	DSSS
基本波頻率：	CH 1：2412 MHz	測試儀器：	(PK) RB=1MHz, VB=3MHz (AV) RB=1MHz, VB=10Hz
量測場地溫度：	20℃	量測場地濕度：	70%RH
測試日期：	107 年 11 月 22 日	測試者：	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	53.86 PK	74.00	-20.14	3.48 V	115	55.36	-1.50
2	2390.00	39.16 AV	54.00	-14.84	3.48 V	115	40.66	-1.50
3	*2412.00	100.94 PK			3.48 V	115	102.56	-1.62
4	*2412.00	98.13 AV			3.48 V	115	99.75	-1.62
5	4824.00	50.52 PK	74.00	-23.48	3.01 V	302	45.73	4.79
6	4824.00	46.63 AV	54.00	-7.37	3.01 V	302	41.84	4.79
7	#7236.00	-	-	-	-	-	-	-
8	#9648.00	-	-	-	-	-	-	-
9	12060.00	-	-	-	-	-	-	-
10	14472.00	-	-	-	-	-	-	-
11	#16884.00	-	-	-	-	-	-	-
12	19296.00	-	-	-	-	-	-	-
13	#21708.00	-	-	-	-	-	-	-
14	#24120.00	-	-	-	-	-	-	-

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency (主頻).
6. " # ": The radiated frequency is out of the restricted band.
7. " - ": The emission levels were too low to be detected.
8. The blank is not available, the limit of fundamental frequency was restricted at the output power.




操作模式：	發射	調變技術：	DSSS
基本波頻率：	CH 6：2437 MHz	測試儀器：	(PK) RB=1MHz, VB=3MHz (AV) RB=1MHz, VB=10Hz
量測場地溫度：	20°C	量測場地濕度：	70%RH
測試日期：	107 年 11 月 22 日	測試者：	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	106.19 PK			1.47 H	118	107.93	-1.74
2	*2437.00	102.54 AV			1.47 H	118	104.28	-1.74
3	4874.00	52.14 PK	74.00	-21.86	3.21 H	78	47.27	4.87
4	4874.00	48.35 AV	54.00	-5.65	3.21 H	78	43.48	4.87
5	7311.00	-	-	-	-	-	-	-
6	#9748.00	-	-	-	-	-	-	-
7	12185.00	-	-	-	-	-	-	-
8	#14622.00	-	-	-	-	-	-	-
9	#17059.00	-	-	-	-	-	-	-
10	19496.00	-	-	-	-	-	-	-
11	#21933.00	-	-	-	-	-	-	-
12	#24370.00	-	-	-	-	-	-	-

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency (主頻).
6. " # ": The radiated frequency is out of the restricted band.
7. " - ": The emission levels were too low to be detected.
8. The blank is not available, the limit of fundamental frequency was restricted at the output power.




操作模式：	發射	調變技術：	DSSS
基本波頻率：	CH 6：2437 MHz	測試儀器：	(PK) RB=1MHz, VB=3MHz (AV) RB=1MHz, VB=10Hz
量測場地溫度：	20℃	量測場地濕度：	70%RH
測試日期：	107 年 11 月 22 日	測試者：	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	101.09 PK			2.25 V	347	102.83	-1.74
2	*2437.00	97.66 AV			2.25 V	347	99.40	-1.74
3	4874.00	50.08 PK	74.00	-23.92	1.52 V	101	45.21	4.87
4	4874.00	46.01 AV	54.00	-7.99	1.52 V	101	41.14	4.87
5	7311.00	-	-	-	-	-	-	-
6	#9748.00	-	-	-	-	-	-	-
7	12185.00	-	-	-	-	-	-	-
8	#14622.00	-	-	-	-	-	-	-
9	#17059.00	-	-	-	-	-	-	-
10	19496.00	-	-	-	-	-	-	-
11	#21933.00	-	-	-	-	-	-	-
12	#24370.00	-	-	-	-	-	-	-

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency (主頻).
6. " # ": The radiated frequency is out of the restricted band.
7. " - ": The emission levels were too low to be detected.
8. The blank is not available, the limit of fundamental frequency was restricted at the output power.




操作模式：	發射	調變技術：	DSSS
基本波頻率：	CH 11：2462 MHz	測試儀器：	(PK) RB=1MHz, VB=3MHz (AV) RB=1MHz, VB=10Hz
量測場地溫度：	20°C	量測場地濕度：	70%RH
測試日期：	107 年 11 月 22 日	測試者：	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	108.31 PK			1.46 H	118	109.93	-1.62
2	*2462.00	102.04 AV			1.46 H	118	103.66	-1.62
3	2483.50	55.27 PK	74.00	-18.73	1.46 H	118	56.59	-1.32
4	2483.50	42.54 AV	54.00	-11.46	1.46 H	118	43.86	-1.32
5	4924.00	51.85 PK	74.00	-22.15	2.07 H	76	47.05	4.80
6	4924.00	48.49 AV	54.00	-5.51	2.07 H	76	43.69	4.80
7	7386.00	-	-	-	-	-	-	-
8	#9848.00	-	-	-	-	-	-	-
9	12310.00	-	-	-	-	-	-	-
10	#14772.00	-	-	-	-	-	-	-
11	#17234.00	-	-	-	-	-	-	-
12	19696.00	-	-	-	-	-	-	-
13	22158.00	-	-	-	-	-	-	-
14	#24620.00	-	-	-	-	-	-	-

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency (主頻).
6. " # ": The radiated frequency is out of the restricted band.
7. " - ": The emission levels were too low to be detected.
8. The blank is not available, the limit of fundamental frequency was restricted at the output power.




操作模式：	發射	調變技術：	DSSS
基本波頻率：	CH 11：2462 MHz	測試儀器：	(PK) RB=1MHz, VB=3MHz (AV) RB=1MHz, VB=10Hz
量測場地溫度：	20℃	量測場地濕度：	70%RH
測試日期：	107 年 11 月 22 日	測試者：	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	102.26 PK			2.29 V	350	103.88	-1.62
2	*2462.00	98.90 AV			2.29 V	350	100.52	-1.62
3	2483.50	53.84 PK	74.00	-20.16	2.29 V	350	55.16	-1.32
4	2483.50	40.31 AV	54.00	-13.69	2.29 V	350	41.63	-1.32
5	4924.00	49.98 PK	74.00	-24.02	1.58 V	112	45.18	4.80
6	4924.00	46.43 AV	54.00	-7.57	1.58 V	112	41.63	4.80
7	7386.00	-	-	-	-	-	-	-
8	#9848.00	-	-	-	-	-	-	-
9	12310.00	-	-	-	-	-	-	-
10	#14772.00	-	-	-	-	-	-	-
11	#17234.00	-	-	-	-	-	-	-
12	19696.00	-	-	-	-	-	-	-
13	22158.00	-	-	-	-	-	-	-
14	#24620.00	-	-	-	-	-	-	-

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency (主頻).
6. " # ": The radiated frequency is out of the restricted band.
7. " - ": The emission levels were too low to be detected.
8. The blank is not available, the limit of fundamental frequency was restricted at the output power.



802.11g


操作模式：	發射	調變技術：	OFDM
基本波頻率：	CH 1：2412 MHz	測試儀器：	(PK) RB=1MHz, VB=3MHz (AV) RB=1MHz, VB=750Hz
量測場地溫度：	20℃	量測場地濕度：	70%RH
測試日期：	107 年 11 月 22 日	測試者：	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	67.02 PK	74.00	-6.98	1.50 H	118	68.52	-1.50
2	2390.00	49.94 AV	54.00	-4.06	1.50 H	118	51.44	-1.50
3	*2412.00	106.54 PK			1.50 H	118	108.16	-1.62
4	*2412.00	97.64 AV			1.50 H	118	99.26	-1.62
5	4824.00	47.14 PK	74.00	-26.86	1.50 H	120	42.35	4.79
6	4824.00	33.28 AV	54.00	-20.72	1.50 H	120	28.49	4.79
7	#7236.00	-	-	-	-	-	-	-
8	#9648.00	-	-	-	-	-	-	-
9	12060.00	-	-	-	-	-	-	-
10	14472.00	-	-	-	-	-	-	-
11	#16884.00	-	-	-	-	-	-	-
12	19296.00	-	-	-	-	-	-	-
13	#21708.00	-	-	-	-	-	-	-
14	#24120.00	-	-	-	-	-	-	-

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency (主頻).
6. " # ": The radiated frequency is out of the restricted band.
7. " - ": The emission levels were too low to be detected.
8. The blank is not available, the limit of fundamental frequency was restricted at the output power.




操作模式：	發射	調變技術：	OFDM
基本波頻率：	CH 1：2412 MHz	測試儀器：	(PK) RB=1MHz, VB=3MHz (AV) RB=1MHz, VB=750Hz
量測場地溫度：	20°C	量測場地濕度：	70%RH
測試日期：	107 年 11 月 22 日	測試者：	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	66.03 PK	74.00	-7.97	2.54 V	170	67.53	-1.50
2	2390.00	48.27 AV	54.00	-5.73	2.54 V	170	49.77	-1.50
3	*2412.00	104.96 PK			2.54 V	170	106.58	-1.62
4	*2412.00	96.02 AV			2.54 V	170	97.64	-1.62
5	4824.00	47.99 PK	74.00	-26.01	1.51 V	101	43.20	4.79
6	4824.00	34.83 AV	54.00	-19.17	1.51 V	101	30.04	4.79
7	#7236.00	-	-	-	-	-	-	-
8	#9648.00	-	-	-	-	-	-	-
9	12060.00	-	-	-	-	-	-	-
10	14472.00	-	-	-	-	-	-	-
11	#16884.00	-	-	-	-	-	-	-
12	19296.00	-	-	-	-	-	-	-
13	#21708.00	-	-	-	-	-	-	-
14	#24120.00	-	-	-	-	-	-	-

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency (主頻).
6. " # ": The radiated frequency is out of the restricted band.
7. " - ": The emission levels were too low to be detected.
8. The blank is not available, the limit of fundamental frequency was restricted at the output power.




操作模式：	發射	調變技術：	OFDM
基本波頻率：	CH 6：2437 MHz	測試儀器：	(PK) RB=1MHz, VB=3MHz (AV) RB=1MHz, VB=750Hz
量測場地溫度：	20°C	量測場地濕度：	70%RH
測試日期：	107 年 11 月 22 日	測試者：	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	107.57 PK			1.49 H	117	109.31	-1.74
2	*2437.00	98.49 AV			1.49 H	117	100.23	-1.74
3	4874.00	47.51 PK	74.00	-26.49	1.52 H	123	42.64	4.87
4	4874.00	33.55 AV	54.00	-20.45	1.52 H	123	28.68	4.87
5	7311.00	-	-	-	-	-	-	-
6	#9748.00	-	-	-	-	-	-	-
7	12185.00	-	-	-	-	-	-	-
8	#14622.00	-	-	-	-	-	-	-
9	#17059.00	-	-	-	-	-	-	-
10	19496.00	-	-	-	-	-	-	-
11	#21933.00	-	-	-	-	-	-	-
12	#24370.00	-	-	-	-	-	-	-

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency (主頻).
6. " # ": The radiated frequency is out of the restricted band.
7. " - ": The emission levels were too low to be detected.
8. The blank is not available, the limit of fundamental frequency was restricted at the output power.




操作模式：	發射	調變技術：	OFDM
基本波頻率：	CH 6：2437 MHz	測試儀器：	(PK) RB=1MHz, VB=3MHz (AV) RB=1MHz, VB=750Hz
量測場地溫度：	20°C	量測場地濕度：	70%RH
測試日期：	107 年 11 月 22 日	測試者：	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	105.28 PK			2.49 V	181	107.02	-1.74
2	*2437.00	95.39 AV			2.49 V	181	97.13	-1.74
3	4874.00	48.43 PK	74.00	-25.57	1.48 V	111	43.56	4.87
4	4874.00	35.05 AV	54.00	-18.95	1.48 V	111	30.18	4.87
5	7311.00	-	-	-	-	-	-	-
6	#9748.00	-	-	-	-	-	-	-
7	12185.00	-	-	-	-	-	-	-
8	#14622.00	-	-	-	-	-	-	-
9	#17059.00	-	-	-	-	-	-	-
10	19496.00	-	-	-	-	-	-	-
11	#21933.00	-	-	-	-	-	-	-
12	#24370.00	-	-	-	-	-	-	-

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency (主頻).
6. " # ": The radiated frequency is out of the restricted band.
7. " - ": The emission levels were too low to be detected.
8. The blank is not available, the limit of fundamental frequency was restricted at the output power.




操作模式：	發射	調變技術：	OFDM
基本波頻率：	CH 11：2462 MHz	測試儀器：	(PK) RB=1MHz, VB=3MHz (AV) RB=1MHz, VB=750Hz
量測場地溫度：	20℃	量測場地濕度：	70%RH
測試日期：	107 年 11 月 22 日	測試者：	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	106.52 PK			1.47 H	113	108.14	-1.62
2	*2462.00	97.09 AV			1.47 H	113	98.71	-1.62
3	2483.50	69.99 PK	74.00	-4.01	1.46 H	113	71.31	-1.32
4	2483.50	49.95 AV	54.00	-4.05	1.46 H	113	51.27	-1.32
5	4924.00	46.18 PK	74.00	-27.82	1.53 H	104	41.38	4.80
6	4924.00	32.24 AV	54.00	-21.76	1.53 H	104	27.44	4.80
7	7386.00	-	-	-	-	-	-	-
8	#9848.00	-	-	-	-	-	-	-
9	12310.00	-	-	-	-	-	-	-
10	#14772.00	-	-	-	-	-	-	-
11	#17234.00	-	-	-	-	-	-	-
12	19696.00	-	-	-	-	-	-	-
13	22158.00	-	-	-	-	-	-	-
14	#24620.00	-	-	-	-	-	-	-

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency (主頻).
6. " # ": The radiated frequency is out of the restricted band.
7. " - ": The emission levels were too low to be detected.
8. The blank is not available, the limit of fundamental frequency was restricted at the output power.




操作模式：	發射	調變技術：	OFDM
基本波頻率：	CH 11：2462 MHz	測試儀器：	(PK) RB=1MHz, VB=3MHz (AV) RB=1MHz, VB=750Hz
量測場地溫度：	20℃	量測場地濕度：	70%RH
測試日期：	107 年 11 月 22 日	測試者：	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	103.86 PK			2.52 V	181	105.48	-1.62
2	*2462.00	93.64 AV			2.52 V	181	95.26	-1.62
3	2483.50	69.70 PK	74.00	-4.30	2.52 V	181	71.02	-1.32
4	2483.50	49.34 AV	54.00	-4.66	2.52 V	181	50.66	-1.32
5	4924.00	47.57 PK	74.00	-26.43	1.55 V	128	42.77	4.80
6	4924.00	34.33 AV	54.00	-19.67	1.55 V	128	29.53	4.80
7	7386.00	-	-	-	-	-	-	-
8	#9848.00	-	-	-	-	-	-	-
9	12310.00	-	-	-	-	-	-	-
10	#14772.00	-	-	-	-	-	-	-
11	#17234.00	-	-	-	-	-	-	-
12	19696.00	-	-	-	-	-	-	-
13	22158.00	-	-	-	-	-	-	-
14	#24620.00	-	-	-	-	-	-	-

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency (主頻).
6. " # ": The radiated frequency is out of the restricted band.
7. " - ": The emission levels were too low to be detected.
8. The blank is not available, the limit of fundamental frequency was restricted at the output power.



802.11n (20MHz)


操作模式：	發射	調變技術：	OFDM
基本波頻率：	CH 1：2412 MHz	測試儀器：	(PK) RB=1MHz, VB=3MHz (AV) RB=1MHz, VB=820Hz
量測場地溫度：	20℃	量測場地濕度：	70%RH
測試日期：	107 年 11 月 22 日	測試者：	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	69.86 PK	74.00	-4.14	1.48 H	121	71.36	-1.50
2	2390.00	47.45 AV	54.00	-6.55	1.48 H	121	48.95	-1.50
3	*2412.00	109.77 PK			1.48 H	121	111.39	-1.62
4	*2412.00	99.38 AV			1.48 H	121	101.00	-1.62
5	4824.00	44.95 PK	74.00	-29.05	1.58 H	147	40.16	4.79
6	4824.00	33.01 AV	54.00	-20.99	1.58 H	147	28.22	4.79
7	#7236.00	-	-	-	-	-	-	-
8	#9648.00	-	-	-	-	-	-	-
9	12060.00	-	-	-	-	-	-	-
10	14472.00	-	-	-	-	-	-	-
11	#16884.00	-	-	-	-	-	-	-
12	19296.00	-	-	-	-	-	-	-
13	#21708.00	-	-	-	-	-	-	-
14	#24120.00	-	-	-	-	-	-	-

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency (主頻).
6. " # ": The radiated frequency is out of the restricted band.
7. " - ": The emission levels were too low to be detected.
8. The blank is not available, the limit of fundamental frequency was restricted at the output power.




操作模式：	發射	調變技術：	OFDM
基本波頻率：	CH 1：2412 MHz	測試儀器：	(PK) RB=1MHz, VB=3MHz (AV) RB=1MHz, VB=820Hz
量測場地溫度：	20℃	量測場地濕度：	70%RH
測試日期：	107 年 11 月 22 日	測試者：	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	69.52 PK	74.00	-4.48	2.56 V	192	71.02	-1.50
2	2390.00	46.72 AV	54.00	-7.28	2.56 V	192	48.22	-1.50
3	*2412.00	106.22 PK			2.56 V	192	107.84	-1.62
4	*2412.00	95.00 AV			2.56 V	192	96.62	-1.62
5	4824.00	44.56 PK	74.00	-29.44	1.57 V	241	39.77	4.79
6	4824.00	32.04 AV	54.00	-21.96	1.57 V	241	27.25	4.79
7	#7236.00	-	-	-	-	-	-	-
8	#9648.00	-	-	-	-	-	-	-
9	12060.00	-	-	-	-	-	-	-
10	14472.00	-	-	-	-	-	-	-
11	#16884.00	-	-	-	-	-	-	-
12	19296.00	-	-	-	-	-	-	-
13	#21708.00	-	-	-	-	-	-	-
14	#24120.00	-	-	-	-	-	-	-

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency (主頻).
6. " # ": The radiated frequency is out of the restricted band.
7. " - ": The emission levels were too low to be detected.
8. The blank is not available, the limit of fundamental frequency was restricted at the output power.




操作模式：	發射	調變技術：	OFDM
基本波頻率：	CH 6：2437 MHz	測試儀器：	(PK) RB=1MHz, VB=3MHz (AV) RB=1MHz, VB=820Hz
量測場地溫度：	20°C	量測場地濕度：	70%RH
測試日期：	107 年 11 月 23 日	測試者：	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	110.45 PK			1.47 H	118	112.19	-1.74
2	*2437.00	100.07 AV			1.47 H	118	101.81	-1.74
3	4874.00	46.09 PK	74.00	-27.91	1.69 H	102	41.22	4.87
4	4874.00	34.25 AV	54.00	-19.75	1.69 H	102	29.38	4.87
5	7311.00	-	-	-	-	-	-	-
6	#9748.00	-	-	-	-	-	-	-
7	12185.00	-	-	-	-	-	-	-
8	#14622.00	-	-	-	-	-	-	-
9	#17059.00	-	-	-	-	-	-	-
10	19496.00	-	-	-	-	-	-	-
11	#21933.00	-	-	-	-	-	-	-
12	#24370.00	-	-	-	-	-	-	-

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency (主頻).
6. " # ": The radiated frequency is out of the restricted band.
7. " - ": The emission levels were too low to be detected.
8. The blank is not available, the limit of fundamental frequency was restricted at the output power.




操作模式：	發射	調變技術：	OFDM
基本波頻率：	CH 6：2437 MHz	測試儀器：	(PK) RB=1MHz, VB=3MHz (AV) RB=1MHz, VB=820Hz
量測場地溫度：	20°C	量測場地濕度：	70%RH
測試日期：	107 年 11 月 23 日	測試者：	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	106.14 PK			2.58 V	178	107.88	-1.74
2	*2437.00	96.22 AV			2.58 V	178	97.96	-1.74
3	4874.00	45.05 PK	74.00	-28.95	1.55 V	233	40.18	4.87
4	4874.00	33.23 AV	54.00	-20.77	1.55 V	233	28.36	4.87
5	7311.00	-	-	-	-	-	-	-
6	#9748.00	-	-	-	-	-	-	-
7	12185.00	-	-	-	-	-	-	-
8	#14622.00	-	-	-	-	-	-	-
9	#17059.00	-	-	-	-	-	-	-
10	19496.00	-	-	-	-	-	-	-
11	#21933.00	-	-	-	-	-	-	-
12	#24370.00	-	-	-	-	-	-	-

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency (主頻).
6. " # ": The radiated frequency is out of the restricted band.
7. " - ": The emission levels were too low to be detected.
8. The blank is not available, the limit of fundamental frequency was restricted at the output power.




操作模式：	發射	調變技術：	OFDM
基本波頻率：	CH 11：2462 MHz	測試儀器：	(PK) RB=1MHz, VB=3MHz (AV) RB=1MHz, VB=820Hz
量測場地溫度：	20℃	量測場地濕度：	70%RH
測試日期：	107 年 11 月 23 日	測試者：	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	108.27 PK			1.46 H	119	109.89	-1.62
2	*2462.00	97.99 AV			1.46 H	119	99.61	-1.62
3	2483.50	69.91 PK	74.00	-4.09	1.46 H	119	71.23	-1.32
4	2483.50	45.60 AV	54.00	-8.40	1.46 H	119	46.92	-1.32
5	4924.00	44.97 PK	74.00	-29.03	1.61 H	144	40.17	4.80
6	4924.00	32.79 AV	54.00	-21.21	1.61 H	144	27.99	4.80
7	7386.00	-	-	-	-	-	-	-
8	#9848.00	-	-	-	-	-	-	-
9	12310.00	-	-	-	-	-	-	-
10	#14772.00	-	-	-	-	-	-	-
11	#17234.00	-	-	-	-	-	-	-
12	19696.00	-	-	-	-	-	-	-
13	22158.00	-	-	-	-	-	-	-
14	#24620.00	-	-	-	-	-	-	-

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency (主頻).
6. " # ": The radiated frequency is out of the restricted band.
7. " - ": The emission levels were too low to be detected.
8. The blank is not available, the limit of fundamental frequency was restricted at the output power.




操作模式：	發射	調變技術：	OFDM
基本波頻率：	CH 11：2462 MHz	測試儀器：	(PK) RB=1MHz, VB=3MHz (AV) RB=1MHz, VB=820Hz
量測場地溫度：	20℃	量測場地濕度：	70%RH
測試日期：	107 年 11 月 23 日	測試者：	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	106.22 PK			2.58 V	149	107.84	-1.62
2	*2462.00	93.74 AV			2.58 V	149	95.36	-1.62
3	2483.50	68.73 PK	74.00	-5.27	2.58 V	149	70.05	-1.32
4	2483.50	45.04 AV	54.00	-8.96	2.58 V	149	46.36	-1.32
5	4924.00	44.13 PK	74.00	-29.87	1.52 V	269	39.33	4.80
6	4924.00	31.39 AV	54.00	-22.61	1.52 V	269	26.59	4.80
7	7386.00	-	-	-	-	-	-	-
8	#9848.00	-	-	-	-	-	-	-
9	12310.00	-	-	-	-	-	-	-
10	#14772.00	-	-	-	-	-	-	-
11	#17234.00	-	-	-	-	-	-	-
12	19696.00	-	-	-	-	-	-	-
13	22158.00	-	-	-	-	-	-	-
14	#24620.00	-	-	-	-	-	-	-

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency (主頻).
6. " # ": The radiated frequency is out of the restricted band.
7. " - ": The emission levels were too low to be detected.
8. The blank is not available, the limit of fundamental frequency was restricted at the output power.



802.11n (40MHz)


操作模式：	發射	調變技術：	OFDM
基本波頻率：	CH 3：2422 MHz	測試儀器：	(PK) RB=1MHz, VB=3MHz (AV) RB=1MHz, VB=1.6kHz
量測場地溫度：	20°C	量測場地濕度：	70%RH
測試日期：	107 年 11 月 23 日	測試者：	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	67.95 PK	74.00	-6.05	1.50 H	117	69.45	-1.50
2	2390.00	49.90 AV	54.00	-4.10	1.50 H	117	51.40	-1.50
3	*2422.00	105.46 PK			1.50 H	117	107.13	-1.67
4	*2422.00	94.86 AV			1.50 H	117	96.53	-1.67
5	4844.00	45.04 PK	74.00	-28.96	1.58 H	120	40.17	4.87
6	4844.00	32.31 AV	54.00	-21.69	1.58 H	120	27.44	4.87
7	7266.00	-	-	-	-	-	-	-
8	#9688.00	-	-	-	-	-	-	-
9	12110.00	-	-	-	-	-	-	-
10	#14532.00	-	-	-	-	-	-	-
11	#16954.00	-	-	-	-	-	-	-
12	19376.00	-	-	-	-	-	-	-
13	#21798.00	-	-	-	-	-	-	-
14	#24220.00	-	-	-	-	-	-	-

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency (主頻).
6. " # ": The radiated frequency is out of the restricted band.
7. " - ": The emission levels were too low to be detected.
8. The blank is not available, the limit of fundamental frequency was restricted at the output power.




操作模式：	發射	調變技術：	OFDM
基本波頻率：	CH 3：2422 MHz	測試儀器：	(PK) RB=1MHz, VB=3MHz (AV) RB=1MHz, VB=1.6kHz
量測場地溫度：	20℃	量測場地濕度：	70%RH
測試日期：	107 年 11 月 23 日	測試者：	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	63.60 PK	74.00	-10.40	2.53 V	187	65.10	-1.50
2	2390.00	48.76 AV	54.00	-5.24	2.53 V	187	50.26	-1.50
3	*2422.00	99.47 PK			2.53 V	187	101.14	-1.67
4	*2422.00	89.21 AV			2.53 V	187	90.88	-1.67
5	4844.00	44.20 PK	74.00	-29.80	1.57 V	149	39.33	4.87
6	4844.00	31.71 AV	54.00	-22.29	1.57 V	149	26.84	4.87
7	7266.00	-	-	-	-	-	-	-
8	#9688.00	-	-	-	-	-	-	-
9	12110.00	-	-	-	-	-	-	-
10	#14532.00	-	-	-	-	-	-	-
11	#16954.00	-	-	-	-	-	-	-
12	19376.00	-	-	-	-	-	-	-
13	#21798.00	-	-	-	-	-	-	-
14	#24220.00	-	-	-	-	-	-	-

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency (主頻).
6. " # ": The radiated frequency is out of the restricted band.
7. " - ": The emission levels were too low to be detected.
8. The blank is not available, the limit of fundamental frequency was restricted at the output power.




操作模式：	發射	調變技術：	OFDM
基本波頻率：	CH 6：2437 MHz	測試儀器：	(PK) RB=1MHz, VB=3MHz (AV) RB=1MHz, VB=1.6kHz
量測場地溫度：	20℃	量測場地濕度：	70%RH
測試日期：	107 年 11 月 23 日	測試者：	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	67.45 PK	74.00	-6.55	1.47 H	121	68.95	-1.50
2	2390.00	49.96 AV	54.00	-4.04	1.47 H	121	51.46	-1.50
3	*2437.00	107.47 PK			1.47 H	121	109.21	-1.74
4	*2437.00	96.51 AV			1.47 H	121	98.25	-1.74
5	2483.50	61.25 PK	74.00	-12.75	1.47 H	121	62.57	-1.32
6	2483.50	44.52 AV	54.00	-9.48	1.47 H	121	45.84	-1.32
7	4874.00	45.42 PK	74.00	-28.58	1.55 H	113	40.55	4.87
8	4874.00	32.56 AV	54.00	-21.44	1.55 H	113	27.69	4.87
9	7311.00	-	-	-	-	-	-	-
10	#9748.00	-	-	-	-	-	-	-
11	12185.00	-	-	-	-	-	-	-
12	#14622.00	-	-	-	-	-	-	-
13	#17059.00	-	-	-	-	-	-	-
14	19496.00	-	-	-	-	-	-	-
15	#21933.00	-	-	-	-	-	-	-
16	#24370.00	-	-	-	-	-	-	-

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency (主頻).
6. " # ": The radiated frequency is out of the restricted band.
7. " - ": The emission levels were too low to be detected.
8. The blank is not available, the limit of fundamental frequency was restricted at the output power.




操作模式：	發射	調變技術：	OFDM
基本波頻率：	CH 6：2437 MHz	測試儀器：	(PK) RB=1MHz, VB=3MHz (AV) RB=1MHz, VB=1.6kHz
量測場地溫度：	20℃	量測場地濕度：	70%RH
測試日期：	107 年 11 月 23 日	測試者：	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	62.69 PK	74.00	-11.31	2.59 V	189	64.19	-1.50
2	2390.00	46.76 AV	54.00	-7.24	2.59 V	189	48.26	-1.50
3	*2437.00	103.04 PK			2.59 V	189	104.78	-1.74
4	*2437.00	91.92 AV			2.59 V	189	93.66	-1.74
5	2483.50	56.90 PK	74.00	-17.10	2.59 V	189	58.22	-1.32
6	2483.50	40.04 AV	54.00	-13.96	2.59 V	189	41.36	-1.32
7	4874.00	44.56 PK	74.00	-29.44	1.53 V	263	39.69	4.87
8	4874.00	30.89 AV	54.00	-23.11	1.53 V	263	26.02	4.87
9	7311.00	-	-	-	-	-	-	-
10	#9748.00	-	-	-	-	-	-	-
11	12185.00	-	-	-	-	-	-	-
12	#14622.00	-	-	-	-	-	-	-
13	#17059.00	-	-	-	-	-	-	-
14	19496.00	-	-	-	-	-	-	-
15	#21933.00	-	-	-	-	-	-	-
16	#24370.00	-	-	-	-	-	-	-

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency (主頻).
6. " # ": The radiated frequency is out of the restricted band.
7. " - ": The emission levels were too low to be detected.
8. The blank is not available, the limit of fundamental frequency was restricted at the output power.




操作模式：	發射	調變技術：	OFDM
基本波頻率：	CH 9：2452 MHz	測試儀器：	(PK) RB=1MHz, VB=3MHz (AV) RB=1MHz, VB=1.6kHz
量測場地溫度：	20℃	量測場地濕度：	70%RH
測試日期：	107 年 11 月 23 日	測試者：	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	106.23 PK			1.47 H	118	108.00	-1.77
2	*2452.00	95.85 AV			1.47 H	118	97.62	-1.77
3	2483.50	68.59 PK	74.00	-5.41	1.47 H	118	69.91	-1.32
4	2483.50	49.80 AV	54.00	-4.20	1.47 H	118	51.12	-1.32
5	4904.00	44.96 PK	74.00	-29.04	1.52 H	126	40.11	4.85
6	4904.00	31.70 AV	54.00	-22.30	1.52 H	126	26.85	4.85
7	7356.00	-	-	-	-	-	-	-
8	#9808.00	-	-	-	-	-	-	-
9	12260.00	-	-	-	-	-	-	-
10	#14712.00	-	-	-	-	-	-	-
11	#17164.00	-	-	-	-	-	-	-
12	19616.00	-	-	-	-	-	-	-
13	22068.00	-	-	-	-	-	-	-
14	#24520.00	-	-	-	-	-	-	-

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency (主頻).
6. " # ": The radiated frequency is out of the restricted band.
7. " - ": The emission levels were too low to be detected.
8. The blank is not available, the limit of fundamental frequency was restricted at the output power.




操作模式：	發射	調變技術：	OFDM
基本波頻率：	CH 9：2452 MHz	測試儀器：	(PK) RB=1MHz, VB=3MHz (AV) RB=1MHz, VB=1.6kHz
量測場地溫度：	20℃	量測場地濕度：	70%RH
測試日期：	107 年 11 月 23 日	測試者：	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	100.39 PK			2.55 V	188	102.16	-1.77
2	*2452.00	90.64 AV			2.55 V	188	92.41	-1.77
3	2483.50	66.93 PK	74.00	-7.07	2.55 V	188	68.25	-1.32
4	2483.50	48.79 AV	54.00	-5.21	2.55 V	188	50.11	-1.32
5	4904.00	44.10 PK	74.00	-29.90	1.58 V	178	39.25	4.85
6	4904.00	30.27 AV	54.00	-23.73	1.58 V	178	25.42	4.85
7	7356.00	-	-	-	-	-	-	-
8	#9808.00	-	-	-	-	-	-	-
9	12260.00	-	-	-	-	-	-	-
10	#14712.00	-	-	-	-	-	-	-
11	#17164.00	-	-	-	-	-	-	-
12	19616.00	-	-	-	-	-	-	-
13	22068.00	-	-	-	-	-	-	-
14	#24520.00	-	-	-	-	-	-	-

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency (主頻).
6. " # ": The radiated frequency is out of the restricted band.
7. " - ": The emission levels were too low to be detected.
8. The blank is not available, the limit of fundamental frequency was restricted at the output power.



4.6.2 接收諧波


802.11n (20MHz)

操 作 模 式 :	接收		
基 本 波 頻 率 :	CH 6 : 2437 MHz	測 試 儀 器 :	(PK) RB=1MHz, VB=3MHz (AV) RB=1MHz, VB=820Hz
量測場地溫度 :	20°C	量測場地濕度 :	70%RH
測 試 日 期 :	107 年 11 月 29 日	測 試 者 :	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	4874.00	44.52 PK	74.00	-29.48	1.85 H	264	39.65	4.87
2	4874.00	31.98 AV	54.00	-22.02	1.85 H	264	27.11	4.87

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value




操作模式：	接收		
基本波頻率：	CH 6：2437 MHz	測試儀器：	(PK) RB=1MHz, VB=3MHz (AV) RB=1MHz, VB=820Hz
量測場地溫度：	20°C	量測場地濕度：	70%RH
測試日期：	107 年 11 月 29 日	測試者：	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	4874.00	43.14 PK	74.00	-30.86	1.81 V	102	38.27	4.87
2	4874.00	31.43 AV	54.00	-22.57	1.81 V	102	26.56	4.87

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value



4.6.3 其它不必要之訊號


802.11n (20MHz)

操作模式：	發射接收	調變技術：	OFDM
基本波頻率：	CH 6：2437 MHz	測試儀器：	(QP) RB=120kHz
量測場地溫度：	26℃	量測場地濕度：	76%RH
測試日期：	107 年 11 月 29 日	測試者：	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	73.21	25.26 QP	40.00	-14.74	2.18 H	269	34.95	-9.69
2	148.00	26.13 QP	43.50	-17.37	1.84 H	267	33.15	-7.02
3	201.84	22.68 QP	43.50	-20.82	1.79 H	274	32.44	-9.76
4	281.47	27.40 QP	46.00	-18.60	2.25 H	248	33.09	-5.69
5	323.13	30.39 QP	46.00	-15.61	1.98 H	234	34.99	-4.60
6	366.88	29.69 QP	46.00	-16.31	2.66 H	165	33.63	-3.94
7	530.67	27.87 QP	46.00	-18.13	1.06 H	106	28.68	-0.81

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
4. Margin value = Emission Level – Limit value
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz.




操作模式：	發射接收	調變技術：	OFDM
基本波頻率：	CH 6：2437 MHz	測試儀器：	(QP) RB=120kHz
量測場地溫度：	26°C	量測場地濕度：	76%RH
測試日期：	107 年 11 月 29 日	測試者：	吳宗霖

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	65.26	33.25 QP	40.00	-6.75	1.64 V	0	41.43	-8.18
2	167.93	25.89 QP	43.50	-17.61	2.36 V	13	33.10	-7.21
3	320.76	29.28 QP	46.00	-16.72	1.88 V	203	33.92	-4.64
4	388.27	27.95 QP	46.00	-18.05	1.74 V	310	31.41	-3.46
5	534.30	27.87 QP	46.00	-18.13	2.05 V	196	28.67	-0.80
6	627.81	29.42 QP	46.00	-16.58	2.22 V	146	27.86	1.56

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
4. Margin value = Emission Level – Limit value
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz.



4.7 量測結果判定

依據測試數據結果，符合低功率射頻電機技術規範之要求。

4.8 配置照片

請參閱附件(測試設置照片)

5 電源線傳導干擾之量測

5.1 適用標準

請見本報告 3.1 節第 1 項的規定。

5.2 量測方法

將待測物置於 0.8 米高的非金屬桌面，使其操作在工作狀態，待測物電源線接至電源線阻抗穩定網路上，從測試接收機記錄頻率由 0.15MHz 至 30MHz 之間之電源線傳導放射強度。


5.3 量測儀器

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
ROHDE & SCHWARZ TEST RECEIVER	ESR3	102414	Feb. 7, 2018	Feb. 6, 2019
ROHDE & SCHWARZ Artificial Mains Network (for EUT)	ENV216	101197	May 23, 2018	May 22, 2019
LISN With Adapter (for EUT)	AD10	C10Ada-002	May 23, 2018	May 22, 2019
ROHDE & SCHWARZ Artificial Mains Network (for peripherals)	38215	9504-2359	Jul. 26, 2018	Jul. 25, 2019
SCHWARZBECK Artificial Mains Network (For EUT)	NNLK8129	8129229	May 3, 2018	May 2, 2019
Software	Cond_V7.3.7.4	NA	NA	NA
RF cable (JYBAO) With 10dB PAD	5D-FB	Cable-C10.01	Feb. 14, 2018	Feb. 13, 2019
SUHNTER Terminator (For ROHDE & SCHWARZ LISN)	65BNC-5001	E1-011484	May 8, 2018	May 7, 2019
ROHDE & SCHWARZ Artificial Mains Network (For TV EUT)	ESH3-Z5	100220	Nov. 21, 2018	Nov. 20, 2019
LISN With Adapter (for TV EUT)	100220	N/A	Nov. 21, 2018	Nov. 20, 2019

- Notes: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. 10.
3. The following table is for the measurement uncertainty, which is calculated as per the document CISPR 16-4. This uncertainty represents an expanded uncert

Measurement	Uncertainty
Conducted emissions	± 2.79

5.4 測試配置



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

5.5 干擾值之計算

餘裕度 Margin(dB)= 結果值 Emission level (dBuV)-限制值 Limit value (dBuV)

電源傳導干擾電壓之計算公式如下

結果值 Emission level (dBuV)=校正因子 Correction Factor (dB)+儀器讀值 Reading value (dBuV)

其中校正因子 Correction Factor (dB)為：

饋線損失+電源阻抗模擬網路損失

5.6 量測結果


802.11n (20MHz)

操作模式	發射	測試日期	107 年 11 月 29 日
基本波頻率：	CH 6：2437 MHz	量測場地溫度	25°C
調變技術	OFDM	量測場地濕度	75%RH
測試者	張君煌		

		6 dB Bandwidth: 9kHz				PHASE: LINE (L)			
輻射頻率	校正因子	儀器讀值		結果值		限制值		餘裕度	
[MHz]	[dB]	[dB (uV)]		[dB (uV)]		[dB (uV)]		[dB]	
		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.15000	9.68	26.77	8.48	36.45	18.16	66.00	56.00	-29.55	-37.84
0.30640	9.73	22.82	2.95	32.55	12.68	60.07	50.07	-27.52	-37.39
0.49017	9.78	23.53	10.22	33.31	20.00	56.16	46.16	-22.85	-26.16
0.66422	9.80	24.86	20.22	34.66	30.02	56.00	46.00	-21.34	-15.98
0.94556	9.85	16.25	2.25	26.10	12.10	56.00	46.00	-29.90	-33.90
2.29469	9.99	17.53	4.51	27.52	14.50	56.00	46.00	-28.48	-31.50
11.34202	10.24	19.24	1.88	29.48	12.12	60.00	50.00	-30.52	-37.88

NOTE:

- 1.Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2.The emission levels of other frequencies were very low against the limit.
- 3.Margin value = Emission level - Limit value
- 4.Correction factor = Insertion loss + Cable loss
- 5.Emission Level = Correction Factor + Reading Value.




操作模式	發射	測試日期	107 年 11 月 29 日
基本波頻率：	CH 6 : 2437 MHz	量測場地溫度	25°C
調變技術	OFDM	量測場地濕度	75%RH
測試者	張君煌		

		6 dB Bandwidth: 9kHz				PHASE: NEUTRAL (N)			
輻射頻率	校正因子	儀器讀值		結果值		限制值		餘裕度	
[MHz]	[dB]	[dB (uV)]		[dB (uV)]		[dB (uV)]		[dB]	
		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.15000	9.69	27.43	8.44	37.12	18.13	66.00	56.00	-28.88	-37.87
0.21621	9.73	21.86	5.87	31.59	15.60	62.96	52.96	-31.37	-37.36
0.69839	9.84	25.21	14.19	35.05	24.03	56.00	46.00	-20.95	-21.97
1.93497	9.98	4.24	1.91	14.22	11.89	56.00	46.00	-41.78	-34.11
4.21059	10.07	4.73	3.78	14.80	13.85	56.00	46.00	-41.20	-32.15
14.73981	10.31	2.77	2.76	13.08	13.07	60.00	50.00	-46.92	-36.93

NOTE:

- 1.Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2.The emission levels of other frequencies were very low against the limit.
- 3.Margin value = Emission level - Limit value
- 4.Correction factor = Insertion loss + Cable loss
- 5.Emission Level = Correction Factor + Reading Value.



5.7 量測結果判定

依據測試數據結果，符合低功率射頻電機技術規範之要求。

5.8 配置照片

請參閱附件(測試設置照片)

6 6 dB 頻寬之要求

6.1 適用標準

請見本報告 3.1 節第 5 項(I)的規定。

6.2 量測方法

- 將待測物輸出經由衰減器接到頻譜分析儀上。
- 設定待測物處於連續發射狀態。
- 計算最大輸出功率峰值減 6dB 的最大頻率範圍。


6.3 量測儀器

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration	Due Date Of Calibration
ROHDE & SCHWARZ Spectrum Analyzer	FSV40	101042	Sep. 27, 2018	Sep. 26, 2019

NOTE:

- The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
- The measurement uncertainty is 207Hz, which is calculated as per the document ETSI TR 100 028. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

6.4 測試配置



6.5 量測結果

操作模式	發射	測試日期	107 年 12 月 3 日
量測場地溫度	25°C	量測場地濕度	76%RH
測試者	李澤洋		

802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	10.05	0.5	PASS
6	2437	10.05	0.5	PASS
11	2462	9.13	0.5	PASS

802.11g

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	16.34	0.5	PASS
6	2437	16.01	0.5	PASS
11	2462	16.35	0.5	PASS

802.11n (20MHz)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
1	2412	16.57	16.34	0.5	Pass
6	2437	16.35	16.35	0.5	Pass
11	2462	16.56	16.68	0.5	Pass

802.11n (40MHz)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
3	2422	36.34	36.34	0.5	Pass
6	2437	36.34	36.34	0.5	Pass
9	2452	36.09	36.09	0.5	Pass

Spectrum Plot of Worst Value


802.11b / CH11




802.11g / CH6



802.11n (20MHz) / Chain 1 : CH1



802.11n (40MHz) / Chain 0 : CH9



6.6 量測結果判定

依據測試數據結果，符合低功率射頻電機技術規範之要求。

7 傳導輸出功率之量測

7.1 適用標準

請見本報告 3.1 節第 6 項(I)及 4 項(I)的規定。

7.2 量測方法

- 將待測物輸出經由衰減器接到功率計上。
- 設定待測物處於連續發射狀態。
- 計算其最大輸出功率。


7.3 量測儀器

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration	Due Date Of Calibration
Anritsu Power Sensor	MA2411B	0738404	Apr. 26, 2018	Apr. 25, 2019
Anritsu Power Meter	ML2495A	0842014	Apr. 26, 2018	Apr. 25, 2019

NOTE:

- The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
- The measurement uncertainty is 1.393dB, which is calculated as per the document ETSI TR 100 028. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.
- Measurement Bandwidth of ML2495A is 65MHz greater than 6dB bandwidth of emission.

7.4 測試配置



7.5 量測結果

操作模式	發射	測試日期	107 年 12 月 3 日
量測場地溫度	25°C	量測場地濕度	76%RH
測試者	李澤洋		

802.11b

Chan.	Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
1	2412	130.918	21.17	30	Pass
6	2437	132.434	21.22	30	Pass
11	2462	133.352	21.25	30	Pass

802.11g

Chan.	Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
1	2412	252.93	24.03	30	Pass
6	2437	287.078	24.58	30	Pass
11	2462	247.172	23.93	30	Pass

802.11n (20MHz)

Chan.	Freq. (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	23.73	24.34	507.692	27.06	30	Pass
6	2437	24.48	25.90	669.588	28.26	30	Pass
11	2462	23.33	23.07	418.046	26.21	30	Pass

802.11n (40MHz)

Chan.	Freq. (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
3	2422	22.56	22.95	377.544	25.77	30	Pass
6	2437	24.26	24.78	567.294	27.54	30	Pass
9	2452	23.11	23.22	414.538	26.18	30	Pass

7.6 量測結果判定

依據測試數據結果，符合低功率射頻電機技術規範之要求。

8 功率頻譜密度之量測

8.1 適用標準

請見本報告 3.1 節第 7 項(I)的規定。

8.2 量測方法

- 將待測物之天線埠連接至測試儀器。
- 設定解析頻寬為 3 kHz，視訊頻寬為 10kHz，掃描時間設為自動，直至掃描信號穩定。
- 使用峰值功能鍵,並找到最大的峰值準位。


8.3 量測儀器

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration	Due Date Of Calibration
ROHDE & SCHWARZ Spectrum Analyzer	FSV40	101042	Sep. 27, 2018	Sep. 26, 2019

NOTE:

- The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
- The measurement uncertainty is 0.9dB, which is calculated as per the document ETSI TR 100 028. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

8.4 測試配置



8.5 量測結果

操作模式	發射	測試日期	107 年 12 月 3 日
量測場地溫度	25°C	量測場地濕度	76%RH
測試者	李澤洋		

802.11b

Channel	Freq. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
1	2412	-6.54	8	Pass
6	2437	-5.06	8	Pass
11	2462	-4.12	8	Pass

802.11g

Channel	Freq. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
1	2412	-8.77	8	Pass
6	2437	-7.47	8	Pass
11	2462	-8.58	8	Pass

802.11n (20MHz)

TX chain	Channel	Freq. (MHz)	PSD (dBm/3kHz)	10 log (N=2) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	1	2412	-9.84	3.01	-6.83	8	Pass
	6	2437	-6.43	3.01	-3.42	8	Pass
	11	2462	-11.14	3.01	-8.13	8	Pass
1	1	2412	-10.04	3.01	-7.03	8	Pass
	6	2437	-6.90	3.01	-3.89	8	Pass
	11	2462	-11.23	3.01	-8.22	8	Pass

NOTE: Directional gain = 2.12dBi + 10log(2) = 5.13dBi < 6dBi, so the power spectral density limit doesn't reduce.


802.11n (40MHz)

TX chain	Channel	Freq. (MHz)	PSD (dBm/3kHz)	10 log (N=2) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	3	2422	-16.50	3.01	-13.49	8	Pass
	6	2437	-13.26	3.01	-10.25	8	Pass
	9	2452	-13.93	3.01	-10.92	8	Pass
1	3	2422	-15.74	3.01	-12.73	8	Pass
	6	2437	-13.47	3.01	-10.46	8	Pass
	9	2452	-14.23	3.01	-11.22	8	Pass


NOTE: Directional gain = 2.12dBi + 10log(2) = 5.13dBi < 6dBi, so the power spectral density limit doesn't reduce.

Spectrum Plot of Worst Value


802.11b / CH11




802.11g / CH6



802.11n (20MHz) / Chain 0 : CH6



802.11n (40MHz) / Chain 0 : CH6



8.6 量測結果判定

依據測試數據結果，符合低功率射頻電機技術規範之要求。

9 檢測實驗室基本資料

立德國際商品試驗有限公司桃園分公司提供產業界最佳的檢測以及諮詢服務。
本公司為 ISO/IEC 17025 認可實驗室。

如您有任何問題或建議，請與下列實驗室聯絡：

林口 EMC / RF 實驗室：

Tel: 886-2-26052180

Fax: 886-2-26051924

新竹 EMC / RF 及通訊實驗室：

Tel: 886-3-6668565

Fax: 886-3-6668323

華亞 EMC / RF / Safety 實驗室：

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

您也可以在我们的网站内找到各實驗室的地圖。

---END---