

MAXIMUM PERMISSIBLE EXPOSURE

Standard Applicable

According to FCC Part1.1310: Radiofrequency radiation exposure limits. The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency radiation as specified in 1.1307(b) LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range	Electric field strength	Magnetic field strength	Power density	Averaging time
(MHz)	(V/m)	(A/m)	(mW/cm ²)	(minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1	30

F = Frequency in MHz

Calculations

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

The limit of **P_d** is 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the **P_d** at 20 mm is meet the limit of MPE.

Result (Worse case mode)

測試日期: Mar 12, 2019

環境溫度 : 25°C

環境濕度 : 59%

Radio Technology	Operation Frequency (MHz)	Distance (mm)	Maximu Output Power with Antenna Gain (mW)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2.4 GHz	2462	20	134.59	0.0268	1

The **P_d** at 20 mm distance calculated from the Friis transmission formula is mush smaller than the limit requirement 1 mW/cm² or 10W/m².

The **Installation Manual** instructs the user to install the device such that it has a separation of at least 20 mm from persons to comply with the FCC's requirements. This separation of 20 mm more than meets the FCC's and Industry Canada RF exposure requirements.

Simultaneous Evaluation:

All MPE evaluations are less than 1, which confirm the device comply the MPE limit.